

ภาคผนวกที่ 8

รายงานผลการวิเคราะห์คุณภาพน้ำ
ประจำเดือน กรกฎาคม-ธันวาคม 2567
บ่อกักเก็บน้ำด้านหน้าท่าเทียบเรือ



ANALYSIS REPORT

CUSTOMER NAME : SIAM CHEMICALS PUBLIC COMPANY
ADDRESS : 196 MOO 1 SUK SAWAT ROAD PAK KHLONG BANG PLA KOT PHRA SAMUT CHEDI SAMUT PRAKAN 10290
CONTACT INFORMATION : TEL : 06 2374 2691 e-mail : safetyofficer@siamchemicals.co.th
SAMPLING SOURCE : SIAM CHEMICALS PUBLIC COMPANY
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : JULY 12, 2024
SAMPLING TIME : 09:30 HOUR
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW ว-145-ค-0027
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM ว-145-จ-0114

RECEIVED DATE : JULY 12, 2024
ANALYTICAL DATE : JULY 12-18, 2024
ISSUE DATE : JULY 24, 2024
REPORT NO. : 2024-U067184
WORK NO. : 2023-010570
ANALYSIS NO. : T24AP845-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT
			บอกเกินมาตรฐาน หาเทียบหรือ T24AP845-0003		
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.3 (32°C)	5.5-9.0	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	5-DAY BOD TEST, MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	7.0	≤ 20	2.0
CHEMICAL OXYGEN DEMAND ^a	mg/L	CLOSED REFLUX, COLOURIMETRIC METHOD (SM: PART 5220 D)	41.7	≤ 120	25.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	16.4	≤ 50	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	DRIED AT 180 °C (SM: PART 2540 C)	2,007	≤ 3,000	25
OIL AND GREASE ^c	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	ND	≤ 5	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : INDUSTRIAL EFFLUENT STANDARDS, NOTIFICATION OF THE MINISTRY OF INDUSTRY, B.E. 2560,
PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 134, PART 153 D, DATED JUNE 7, 2017.

ND : NOT DETECTED.

Piyapat S.

(MRS PIYAPAT SUTTAMANUTWONG)
LABORATORY SUPERVISOR
ว-145-ค-0004



ANALYSIS REPORT

CUSTOMER NAME : SIAM CHEMICALS PUBLIC COMPANY
ADDRESS : 196 MOO 1 SUK SAWAT ROAD PAK KHLONG BANG PLA KOT PHRA SAMUT CHEDI SAMUT PRAKAN 10290
CONTACT INFORMATION : TEL : 06 2374 2691 e-mail : safetyofficer@siamchemicals.co.th
SAMPLING SOURCE : SIAM CHEMICALS PUBLIC COMPANY
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : AUGUST 16, 2024
SAMPLING TIME : 13:10 HOUR
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW จ-145-ค-0027
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM จ-145-จ-0114

RECEIVED DATE : AUGUST 16, 2024
ANALYTICAL DATE : AUGUST 16-23, 2024
ISSUE DATE : AUGUST 27, 2024
REPORT NO. : 2024-U078127
WORK NO. : 2023-010570
ANALYSIS NO. : T24AS597-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT
			ผลกักเก็บน้ำด้านหน้า ท่าเทียบเรือ T24AS597-0003		
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.2 (32°C)	5.5-9.0	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	5-DAY BOD TEST, MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	< 2.0	≤ 20	2.0
CHEMICAL OXYGEN DEMAND ^a	mg/L	CLOSED REFLUX, COLOURIMETRIC METHOD (SM: PART 5220 D)	27.2	≤ 120	25.0
TOTAL SUSPENDED SOLIDS ^c	mg/L	DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	ND	≤ 50	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	DRIED AT 180 °C (SM: PART 2540 C)	913	≤ 3,000	25
OIL AND GREASE ^c	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	ND	≤ 5	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/CLEAR BROWN		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : INDUSTRIAL EFFLUENT STANDARDS, NOTIFICATION OF THE MINISTRY OF INDUSTRY, B.E. 2560,
PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 134, PART 153 D, DATED JUNE 7, 2017.

ND : NOT DETECTED.

Piyapat S.

(MRS PIYAPAT SUTTAMANUTWONG)
LABORATORY SUPERVISOR
จ-145-ค-0004



ANALYSIS REPORT

CUSTOMER NAME : SIAM CHEMICALS PUBLIC COMPANY
ADDRESS : 196 MOO 1 SUK SAWAT ROAD PAK KHLONG BANG PLA KOT PHRA SAMUT CHEDI SAMUT PRAKAN 10290
CONTACT INFORMATION : TEL : 06 2374 2691 e-mail : safetyofficer@siamchemicals.co.th
SAMPLING SOURCE : SIAM CHEMICALS PUBLIC COMPANY
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : SEPTEMBER 13, 2024
SAMPLING TIME : 11:20 HOUR
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW ๖-145-๓-0027
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM ๖-145-๖-0114

RECEIVED DATE : SEPTEMBER 13, 2024
ANALYTICAL DATE : SEPTEMBER 13-19, 2024
ISSUE DATE : SEPTEMBER 25, 2024
REPORT NO. : 2024-U088983
WORK NO. : 2023-010570
ANALYSIS NO. : T24AV226-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT
			บอกเกินมาตรฐาน ค่าเทียบเรือ T24AV226-0003		
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H* B AND 1060 B	7.3 (32.3°C)	5.5-9.0	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	5-DAY BOD TEST, MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	4.0	≤ 20	2.0
CHEMICAL OXYGEN DEMAND ^a	mg/L	CLOSED REFLUX, COLOURIMETRIC METHOD (SM: PART 5220 D)	29.4	≤ 120	25.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	8.0	≤ 50	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	DRIED AT 180 °C (SM: PART 2540 C)	944	≤ 3,000	25
OIL AND GREASE ^c	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	ND	≤ 5	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : INDUSTRIAL EFFLUENT STANDARDS, NOTIFICATION OF THE MINISTRY OF INDUSTRY, B.E. 2560, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 134, PART 153 D, DATED JUNE 7, 2017.

ND : NOT DETECTED.

Piyapat S.

(MRS PIYAPAT SUTTAMANUTWONG)
 LABORATORY SUPERVISOR
 ๖-145-๓-0004



ANALYSIS REPORT

CUSTOMER NAME : SIAM CHEMICALS PUBLIC COMPANY
ADDRESS : 196 MOO 1 SUK SAWAT ROAD PAK KHLONG BANG PLA KOT PHRA SAMUT CHEDI SAMUT PRAKAN 10290
CONTACT INFORMATION : TEL : 06 2374 2691 e-mail : safetyofficer@siamchemicals.co.th
SAMPLING SOURCE : SIAM CHEMICALS PUBLIC COMPANY
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : OCTOBER 8, 2024
SAMPLING TIME : 13:10 HOUR
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW ๖-145-๙-0027
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM ๖-145-๙-0114

RECEIVED DATE : OCTOBER 8, 2024
ANALYTICAL DATE : OCTOBER 8-16, 2024
ISSUE DATE : OCTOBER 18, 2024
REPORT NO. : 2024-U097775
WORK NO. : 2023-010570
ANALYSIS NO. : T24AX634-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT
			ผลกักเก็บน้ำด้านหน้า ท่าเทียบเรือ T24AX634-0003		
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.4 (32.3°C)	5.5-9.0	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	5-DAY BOD TEST, MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O ₂ G)	< 2.0	≤ 20	2.0
CHEMICAL OXYGEN DEMAND ^c	mg/L	CLOSED REFLUX, COLOURIMETRIC METHOD (SM: PART 5220 D)	ND	≤ 120	25.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	20.1	≤ 50	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	DRIED AT 180 °C (SM: PART 2540 C)	625	≤ 3,000	25
OIL AND GREASE ^c	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	ND	≤ 5	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : INDUSTRIAL EFFLUENT STANDARDS, NOTIFICATION OF THE MINISTRY OF INDUSTRY, B.E. 2560,
PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 134, PART 153 D, DATED JUNE 7, 2017.

ND : NOT DETECTED.

Piyapat S.

(MRS PIYAPAT SUTTAMANUTWONG)
LABORATORY SUPERVISOR
๖-145-๙-0004



ANALYSIS REPORT

CUSTOMER NAME : SIAM CHEMICALS PUBLIC COMPANY
ADDRESS : 196 MOO 1 SUK SAWAT ROAD PAK KHLONG BANG PLA KOT PHRA SAMUT CHEDI SAMUT PRAKAN 10290
CONTACT INFORMATION : TEL : 06 2374 2691 e-mail : safetyofficer@siamchemicals.co.th
SAMPLING SOURCE : SIAM CHEMICALS PUBLIC COMPANY
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : NOVEMBER 11, 2024
SAMPLING TIME : 10:30 HOUR
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW ว-145-ค-0027
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM ว-145-จ-0114

RECEIVED DATE : NOVEMBER 11, 2024
ANALYTICAL DATE : NOVEMBER 11-19, 2024
ISSUE DATE : NOVEMBER 22, 2024
REPORT NO. : 2024-U109286
WORK NO. : 2023-010570
ANALYSIS NO. : T24BA427-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	LIMIT OF QUANTITATION (LOQ)
			ปกติไม่เกินค่า ตามหน้าทำเทียบหรือ T24BA427-0003		
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.5 (30.2°C)	5.5-9.0	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	5-DAY BOD TEST, MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	3.0	≤ 20	2.0
CHEMICAL OXYGEN DEMAND ^c	mg/L	CLOSED REFLUX, COLOURIMETRIC METHOD (SM: PART 5220 D)	< 25.0	≤ 120	25.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	5.8	≤ 50	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	DRIED AT 180 °C (SM: PART 2540 C)	496	≤ 3,000	25
OIL AND GREASE ^c	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 5	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : INDUSTRIAL EFFLUENT STANDARDS, NOTIFICATION OF THE MINISTRY OF INDUSTRY, B.E. 2560,
 PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 134, PART 153 D, DATED JUNE 7, 2017.

Piyapat S.

(MRS PIYAPAT SUTTAMANUTWONG)
 LABORATORY SUPERVISOR
 ว-145-ค-0004



ANALYSIS REPORT

CUSTOMER NAME : SIAM CHEMICALS PUBLIC COMPANY
ADDRESS : 196 MOO 1 SUK SAWAT ROAD PAK KHLONG BANG PLA KOT PHRA SAMUT CHEDI SAMUT PRAKAN 10290
CONTACT INFORMATION : TEL : 06 2374 2691 e-mail : safetyofficer@siamchemicals.co.th
SAMPLING SOURCE : SIAM CHEMICALS PUBLIC COMPANY
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : DECEMBER 9, 2024
SAMPLING TIME : 12:45 HOUR
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW จ-145-ก-0027
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM จ-145-ก-0114

RECEIVED DATE : DECEMBER 9, 2024
ANALYTICAL DATE : DECEMBER 9-19, 2024
ISSUE DATE : DECEMBER 24, 2024
REPORT NO. : 2024-U120128
WORK NO. : 2023-010570
ANALYSIS NO. : T24BC949-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	LIMIT OF QUANTITATION (LOQ)
			ปกติเก็บน้ำ ด้านหน้าท่าเทียบเรือ T24BC949-0003		
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.7 (29.7°C)	5.5-9.0	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	5-DAY BOD TEST, MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	2.0	≤ 20	2.0
CHEMICAL OXYGEN DEMAND ^c	mg/L	CLOSED REFLUX, TITRIMETRIC METHOD (SM: PART 5220 C)	53.9	≤ 120	40.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	24.0	≤ 50	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	DRIED AT 180 °C (SM: PART 2540 C)	5,062	≤ 3,000	25
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 5	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : INDUSTRIAL EFFLUENT STANDARDS, NOTIFICATION OF THE MINISTRY OF INDUSTRY, B.E. 2560,
PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 134, PART 153 D, DATED JUNE 7, 2017.

Piyapat S.

(MRS PIYAPAT SUTTAMANUTWONG)
LABORATORY SUPERVISOR
จ-145-ก-0004

