

ภาคผนวก

ภาคผนวก ก หนังสือที่เกี่ยวข้อง

- ภาคผนวก ก-1 หนังสือแจ้งผลการพิจารณารายงานการประเมินผลกระทบสิ่งแวดล้อม เลขที่ ทส. 1009.5/2775 ลงวันที่ 14 มีนาคม พ.ศ. 2557 และมาตรการป้องกันและแก้ไขผลกระทบสิ่งแวดล้อมและมาตรการติดตามตรวจสอบผลกระทบสิ่งแวดล้อม
- ภาคผนวก ก-2 หนังสือรับเปลี่ยนชื่อโครงการ
- ภาคผนวก ก-3 หนังสือรับรองบริษัท สิงห์ เอสเตท จำกัด (มหาชน)
- ภาคผนวก ก-4 หนังสือรับรองการก่อสร้าง (อ.6)

ภาคผนวก ข ภาพประกอบผลการปฏิบัติตามมาตรการ

ภาคผนวก ค เอกสารประกอบผลการปฏิบัติตามมาตรการ

- ภาคผนวก ค-1 แผนผังบริเวณโครงการและสภาพแวดล้อมโดยรอบ
- ภาคผนวก ค-2 แผนผังพื้นที่สีเขียว
- ภาคผนวก ค-3 แผนการดูแลรักษา/ทำความสะอาดภายในโครงการ
- ภาคผนวก ค-4 แผนผังตำแหน่งจุดรวมพล
- ภาคผนวก ค-5 แผนผังระบบบำบัดน้ำเสีย
- ภาคผนวก ค-6 แผนบำรุงรักษาเชิงป้องกันของการดูแลระบบสาธารณูปโภคและระบบสุขาภิบาล
- ภาคผนวก ค-7 เอกสารการตรวจสอบระบบไฟฟ้า ประจำปี 2568
- ภาคผนวก ค-8 บันทึกการทำความสะอาดเครื่องปรับอากาศของพื้นที่ส่วนกลาง
- ภาคผนวก ค-9 บันทึกการทำความสะอาดถังเก็บน้ำใช้
- ภาคผนวก ค-10 บันทึกการทำความสะอาดห่อฝังเย็น
- ภาคผนวก ค-11 บันทึกการตรวจสอบระบบจ่ายน้ำประปา
- ภาคผนวก ค-12 สถิติและข้อมูลการทำงานของระบบบำบัดน้ำเสีย (ทส. 1/ทส. 2)
- ภาคผนวก ค-13 บันทึกการตรวจสอบระบบป้องกันและเตือนอัคคีภัย
- ภาคผนวก ค-14 เอกสารรายงาน การอบรม/ซ้อมดับเพลิง
- ภาคผนวก ค-15 บันทึกการตรวจสอบระบบเส้นท่อประปา
- ภาคผนวก ค-16 บันทึกการตรวจสอบการตรวจสอบปริมาณตะกอน
- ภาคผนวก ค-17 สำเนาใบเสร็จค่าธรรมเนียมการให้บริการสูบน้ำตะกอน
- ภาคผนวก ค-18 สัญญาว่าจ้างบริษัททำความสะอาด
- ภาคผนวก ค-19 กฎ ข้อบังคับ บริษัท สิงห์ เอสเตท จำกัด (มหาชน)

ภาคผนวก

ภาคผนวก ง ผลการตรวจวิเคราะห์คุณภาพสิ่งแวดล้อม

ภาคผนวก ง-1 ผลการตรวจวิเคราะห์คุณภาพน้ำทิ้ง

ภาคผนวก ง-2 ผลการตรวจวิเคราะห์คุณภาพน้ำจากระบบปรับอากาศ

ภาคผนวก จ มาตรฐานที่เกี่ยวข้อง

ภาคผนวก จ-1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด ประกาศในราชกิจจานุเบกษา เล่ม 122 ตอนที่ 125 ง วันที่ 29 ธันวาคม พ.ศ. 2548

ภาคผนวก จ-2 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด พ.ศ. 2567 ประกาศในราชกิจจานุเบกษา เล่ม 141 ตอนพิเศษ 233 ง วันที่ 27 สิงหาคม พ.ศ. 2567

ภาคผนวก จ-3 ประกาศการประปานครหลวง เรื่อง เกณฑ์กำหนดคุณภาพน้ำประปานครหลวง
ประกาศ ณ วันที่ 11 ตุลาคม พ.ศ. 2565

ภาคผนวก ฉ เอกสารสอบเทียบเครื่องมือ

ภาคผนวก ช หนังสืออนุญาตขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

ภาคผนวก ง
ผลการตรวจวิเคราะห์คุณภาพสิ่งแวดล้อม

ภาคผนวก ง-1
ผลการตรวจวิเคราะห์คุณภาพน้ำทิ้ง

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : WASTEWATER
SAMPLING DATE : JULY 31, 2025
SAMPLING TIME : 1/
SAMPLING METHOD : GRAB
SAMPLING BY : MR SITTHIPOL PROMPOCHENBOON
ANALYZED BY : MISS ARIYA THARAROM

RECEIVED DATE : JULY 31, 2025
ANALYTICAL DATE : JULY 31 - AUGUST 6, 2025
ISSUE DATE : AUGUST 8, 2025
REPORT NO. : 2025-U071497
WORK NO. : 2025-000402
ANALYSIS NO. : T25AQ650-0002 - T25AQ650-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 09:20 HOUR 1/ T25AQ650-0002	2 09:10 HOUR 1/ T25AQ650-0003			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	6.9 (29.8°C)	6.6 (30.7°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	65.2	33.4	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	14.9	47.9	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	307	362	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	< 0.50	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	55.2	16.8	≤ 35	1.5	5.0



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 09:20 HOUR 1/ T25AQ650-0002	2 09:10 HOUR 1/ T25AQ650-0003			
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	4	< 3	≤ 20	-	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN	YELLOW/TURBID BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

RESULT 1 : คุณภาพน้ำทิ้ง : จุดที่ 1 น้ำเข้าระบบ

RESULT 2 : คุณภาพน้ำทิ้ง : จุดที่ 2 น้ำออกจากระบบ

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : WASTEWATER
SAMPLING DATE : AUGUST 29, 2025
SAMPLING TIME : 1/
SAMPLING METHOD : GRAB
SAMPLING BY : MR SITTHIPOL PROMPOCHENBOON
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : AUGUST 29, 2025
ANALYTICAL DATE : AUGUST 29 - SEPTEMBER 8, 2025
ISSUE DATE : SEPTEMBER 8, 2025
REPORT NO. : 2025-U080725
WORK NO. : 2025-000402
ANALYSIS NO. : T25AS980-0002 - T25AS980-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 14:30 HOUR 1/ T25AS980-0002	2 14:20 HOUR 1/ T25AS980-0003			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.3 (28.7°C)	6.6 (29.3°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	39.8	81.8	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	11.0	58.3	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	289	396	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	0.4	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	1.0	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	65.5	17.7	≤ 35	1.5	5.0



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 14:30 HOUR 1/ T25AS980-0002	2 14:20 HOUR 1/ T25AS980-0003			
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	3	< 3	≤ 20	-	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN	YELLOW/TURBID BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

RESULT 1 : คุณภาพน้ำทิ้ง : จุดที่ 1 น้ำเข้าระบบ

RESULT 2 : คุณภาพน้ำทิ้ง : จุดที่ 2 น้ำออกจากระบบ

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : WASTEWATER
SAMPLING DATE : SEPTEMBER 29, 2025
SAMPLING TIME : 1/
SAMPLING METHOD : GRAB
SAMPLING BY : MR RONNAYUT PRATHUMKET
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : SEPTEMBER 29, 2025
ANALYTICAL DATE : SEPTEMBER 29 - OCTOBER 4, 2025
ISSUE DATE : OCTOBER 7, 2025
REPORT NO. : 2025-U090910
WORK NO. : 2025-000402
ANALYSIS NO. : T25AV853-0002 - T25AV853-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 12:30 HOUR 1/ T25AV853-0002	2 12:45 HOUR 1/ T25AV853-0003			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.4 (29.8°C)	7.5 (30.9°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	132	81.2	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	47.8	30.2	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	302	311	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ₂ F)	2.9	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^d	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	72.9	57.0	≤ 35	1.5	5.0



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 12:30 HOUR 1/ T25AV853-0002	2 12:45 HOUR 1/ T25AV853-0003			
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	5	< 3	≤ 20	-	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN	YELLOW/TURBID BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

RESULT 1 : คุณภาพน้ำทิ้ง : จุดที่ 1 น้ำเข้าระบบ

RESULT 2 : คุณภาพน้ำทิ้ง : จุดที่ 2 น้ำออกจากระบบ

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME	: SINGHA ESTATE PUBLIC COMPANY LIMITED	RECEIVED DATE	: OCTOBER 30, 2025
ADDRESS	: 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110	ANALYTICAL DATE	: OCTOBER 30 - NOVEMBER 5, 2025
CONTACT INFORMATION	: TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th	ISSUE DATE	: NOVEMBER 7, 2025
SAMPLING SOURCE	: S-METRO	REPORT NO.	: 2025-U101439
SAMPLE TYPE	: WASTEWATER	WORK NO.	: 2025-000402
SAMPLING DATE	: OCTOBER 30, 2025	ANALYSIS NO.	: T25AY465-0002 - T25AY465-0003
SAMPLING TIME	: 1/		
SAMPLING METHOD	: GRAB		
SAMPLING BY	: MR SITTHIPOL PROMPOCHENBOON		
ANALYZED BY	: MISS NAPAPORN KHUNNOKKHUM		

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 10:00 HOUR 1/ T25AY465-0002	2 09:50 HOUR 1/ T25AY465-0003			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.5 (28.8°C)	6.8 (29.6°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	141	25.1	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	34.2	49.9	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	390	410	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	0.1	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	2.5	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	96.3	17.5	≤ 35	1.5	5.0



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 10:00 HOUR 1/ T25AY465-0002	2 09:50 HOUR 1/ T25AY465-0003			
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	7	< 3	≤ 20	-	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN	YELLOW/TURBID BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

RESULT 1 : คุณภาพน้ำทิ้ง : จุดที่ 1 น้ำเข้าระบบ

RESULT 2 : คุณภาพน้ำทิ้ง : จุดที่ 2 น้ำออกจากระบบ

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : WASTEWATER
SAMPLING DATE : NOVEMBER 27, 2025
SAMPLING TIME : 1/
SAMPLING METHOD : GRAB
SAMPLING BY : MR SITTHIPOL PROMPOCHENBOON
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : NOVEMBER 28, 2025
ANALYTICAL DATE : NOVEMBER 28 - DECEMBER 3, 2025
ISSUE DATE : DECEMBER 4, 2025
REPORT NO. : 2025-U110800
WORK NO. : 2025-000402
ANALYSIS NO. : T25BA919-0002 - T25BA919-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 11:05 HOUR 1/ T25BA919-0002	2 11:00 HOUR 1/ T25BA919-0003			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.8 (26.7°C)	7.5 (24.8°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	130	40.7	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	512	217	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	311	276	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ₂ F)	1.7	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	93.0	37.2	≤ 35	1.5	5.0



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 11:05 HOUR 1/ T25BA919-0002	2 11:00 HOUR 1/ T25BA919-0003			
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	4	< 3	≤ 20	-	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID BROWN	YELLOW/TURBID BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

RESULT 1 : คุณภาพน้ำทิ้ง : จุดที่ 1 น้ำเข้าระบบ

RESULT 2 : คุณภาพน้ำทิ้ง : จุดที่ 2 น้ำออกจากระบบ

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : WASTEWATER
SAMPLING DATE : DECEMBER 24, 2025
SAMPLING TIME : 1/
SAMPLING METHOD : GRAB
SAMPLING BY : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : DECEMBER 24, 2025
ANALYTICAL DATE : DECEMBER 24, 2025 - JANUARY 7, 2026
ISSUE DATE : JANUARY 7, 2026
REPORT NO. : 2026-U001233
WORK NO. : 2025-000402
ANALYSIS NO. : T25BD192-0002 - T25BD192-0003

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 10:50 HOUR 1/ T25BD192-0002	2 10:40 HOUR 1/ T25BD192-0003			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.6 (27.6°C)	7.4 (28.4°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	103	10.7	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	81.3	7.1	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	345	252	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	0.8	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	0.59	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE TP WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	87.8	22.7	≤ 35	1.5	5.0

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			1 10:50 HOUR 1/ T25BD192-0002	2 10:40 HOUR 1/ T25BD192-0003			
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM. PART 5520 B)	5	3	≤ 20	-	3
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			GREY/TURBID GREY	YELLOW/CLEAR BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

RESULT 1 : คุณภาพน้ำทิ้ง : จุดที่ 1 น้ำเข้าระบบ

RESULT 2 : คุณภาพน้ำทิ้ง : จุดที่ 2 น้ำออกจากระบบ

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ภาคผนวก ง-2
ผลการตรวจวิเคราะห์คุณภาพน้ำจากระบบปรับอากาศ

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
MEASURING DATE : JULY 31, 2025
MEASURING TIME : 09:30 HOUR
SAMPLING METHOD : GRAB
MEASURED BY : MR SITTHIPOL PROMPOCHENBOON

RECEIVED DATE : -
ANALYTICAL DATE : -
ISSUE DATE : AUGUST 11, 2025
REPORT NO. : 2025-U071496
WORK NO. : 2025-000402
ANALYSIS NO. : T25AQ650-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			น้ำจากระบบปรับอากาศ T25AQ650-0001	
RESIDUAL CHLORINE	mg/L Cl ₂	MODIFIED DPD COLOURIMETRIC METHOD (AT SITE)	ND	0.1
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID WHITE	

ND : NOT DETECTED.



(MR THEERAWAT CHOMMING)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
MEASURING DATE : AUGUST 29, 2025
MEASURING TIME : 14:40 HOUR
SAMPLING METHOD : GRAB
MEASURED BY : MR SITTHIPOL PROMPOCHENBOON

RECEIVED DATE : -
ANALYTICAL DATE : -
ISSUE DATE : SEPTEMBER 9, 2025
REPORT NO. : 2025-U080722
WORK NO. : 2025-000402
ANALYSIS NO. : T25AS980-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			นำจากระบบปรับอากาศ T25AS980-0001	
RESIDUAL CHLORINE	mg/L Cl ₂	MODIFIED DPD COLOURIMETRIC METHOD (AT SITE)	ND	0.1
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID WHITE	

ND : NOT DETECTED.

(MR THEERAWAT CHOMMING)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
MEASURING DATE : SEPTEMBER 29, 2025
MEASURING TIME : 12:25 HOUR
SAMPLING METHOD : GRAB
MEASURED BY : MR RONNAYUT PRATHUMKET

RECEIVED DATE : -
ANALYTICAL DATE : -
ISSUE DATE : OCTOBER 7, 2025
REPORT NO. : 2025-U090909
WORK NO. : 2025-000402
ANALYSIS NO. : T25AV853-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			น้ำจากระบบปรับอากาศ T25AV853-0001	
RESIDUAL CHLORINE	mg/L Cl ₂	MODIFIED DPD COLOURIMETRIC METHOD (AT SITE)	ND	0.1
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			COLOURLESS/CLEAR -	

ND : NOT DETECTED.

(MR THEERAWAT CHOMMING)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
MEASURING DATE : OCTOBER 30, 2025
MEASURING TIME : 10:10 HOUR
SAMPLING METHOD : GRAB
MEASURED BY : MR SITTHIPOL PROMPOCHENBOON

RECEIVED DATE : -
ANALYTICAL DATE : -
ISSUE DATE : NOVEMBER 10, 2025
REPORT NO. : 2025-U101438
WORK NO. : 2025-000402
ANALYSIS NO. : T25AY465-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			นำจากระบบรับอากาศ T25AY465-0001	
RESIDUAL CHLORINE	mg/L Cl ₂	MODIFIED DPD COLOURIMETRIC METHOD (AT SITE)	ND	0.1
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/TURBID WHITE	

ND : NOT DETECTED.



(MR THEERAWAT CHOMMING)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
SAMPLING DATE : NOVEMBER 17, 2025
SAMPLING TIME : 15:15 HOUR
SAMPLING METHOD * : GRAB AND STERILE TECHNIQUE
SAMPLING BY * : MR SUKSAN BOONLEANG
ANALYZED BY : MISS BUSSAKORN MAJAI

RECEIVED DATE : NOVEMBER 17, 2025
ANALYTICAL DATE : NOVEMBER 17 - DECEMBER 1, 2025
ISSUE DATE : DECEMBER 4, 2025
REPORT NO. : 2025-U110895
WORK NO. : 2025-000402
ANALYSIS NO. : T25AZ978-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			น้ำจากระบบปรับอากาศ : จุดที่ 1 (น้ำในถาด) T25AZ978-0001	
MICROBIOLOGY				
Legionella spp.	CFU/L	ISO 11731:2017-05 (E)	NOT DETECTED	100
SAMPLE CONDITION				
WATER'S COLOUR/TURBID			YELLOW/CLEAR	
SEDIMENT			-	

THE LABORATORY HAS BEEN ACCEPTED AS AN ACCREDITED LABORATORY COMPLYING WITH THE ISO/IEC 17025.

* : TEST METHOD ARE NOT COVERED COMPLYING WITH THE ISO/IEC 17025, VERIFIED BY OWN LABORATORY QUALITY SYSTEM.

(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
SAMPLING DATE : NOVEMBER 17, 2025
SAMPLING TIME : 15:20 HOUR
SAMPLING METHOD * : GRAB AND STERILE TECHNIQUE
SAMPLING BY * : MR SUKSAN BOONLEANG
ANALYZED BY : MISS BUSSAKORN MAJAI

RECEIVED DATE : NOVEMBER 17, 2025
ANALYTICAL DATE : NOVEMBER 17 - DECEMBER 1, 2025
ISSUE DATE : DECEMBER 4, 2025
REPORT NO. : 2025-U110896
WORK NO. : 2025-000402
ANALYSIS NO. : T25AZ978-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			น้ำจากระบบปรับอากาศ : จุดที่ 2 (น้ำเดิมเข้าระบบ) T25AZ978-0002	
MICROBIOLOGY				
Legionella spp.	CFU/L	ISO 11731:2017-05 (E)	NOT DETECTED	100
SAMPLE CONDITION				
WATER'S COLOUR/TURBID			YELLOW/CLEAR	
SEDIMENT			BROWN	

THE LABORATORY HAS BEEN ACCEPTED AS AN ACCREDITED LABORATORY COMPLYING WITH THE ISO/IEC 17025.

* : TEST METHOD ARE NOT COVERED COMPLYING WITH THE ISO/IEC 17025, VERIFIED BY OWN LABORATORY QUALITY SYSTEM.

[REDACTED SIGNATURE]

(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
MEASURING DATE : NOVEMBER 27, 2025
MEASURING TIME : 11:10 HOUR
SAMPLING METHOD : GRAB
MEASURED BY : MR SITTHIPOL PROMPOCHENBOON

RECEIVED DATE : -
ANALYTICAL DATE : -
ISSUE DATE : DECEMBER 11, 2025
REPORT NO. : 2025-U110799
WORK NO. : 2025-000402
ANALYSIS NO. : T25BA919-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			น้ำจากระบบปรับอากาศ T25BA919-0001	
RESIDUAL CHLORINE	mg/L Cl ₂	MODIFIED DPD COLOURIMETRIC METHOD (AT SITE)	ND	0.1
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/CLEAR	

ND : NOT DETECTED.



(MR THEERAWAT CHOMMING)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : SINGHA ESTATE PUBLIC COMPANY LIMITED
ADDRESS : 725 METROPOLIS SUKHUMVIT ROAD KHLONG TAN NUEA WATTHANA BANGKOK 10110
CONTACT INFORMATION : TEL : 081 939 8493 e-mail : sopit.p@singhaestate.co.th
SAMPLING SOURCE : S-METRO
SAMPLE TYPE : COOLING WATER
MEASURING DATE : DECEMBER 24, 2025
MEASURING TIME : 10:55 HOUR
SAMPLING METHOD : GRAB
MEASURED BY : MR WEERAYUT MOKKAEW

RECEIVED DATE : -
ANALYTICAL DATE : -
ISSUE DATE : JANUARY 9, 2026
REPORT NO. : 2026-U001232
WORK NO. : 2025-000402
ANALYSIS NO. : T258D192-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			น้ำจากระบบปรับอากาศ T258D192-0001	
RESIDUAL CHLORINE	mg/L Cl ₂	MODIFIED DPD COLOURIMETRIC METHOD (AT SITE)	ND	0.1
SAMPLE CONDITION WATER'S COLOUR/TURBID SEDIMENT			YELLOW/CLEAR	

ND : NOT DETECTED.

(MR THEERAWAT CHOMMING)
LABORATORY SUPERVISOR



ภาคผนวก จ
มาตรฐานที่เกี่ยวข้อง

ภาคผนวก จ-1
ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม
เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้ง
จากอาคารบางประเภทและบางขนาด
ประกาศในราชกิจจานุเบกษา เล่ม 122 ตอนที่ 125 ง
วันที่ 29 ธันวาคม พ.ศ. 2548

ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานความคุ้มครองระยะบายน้ำทิ้ง

จากอาคารบางประเภทและบางขนาด

โดยที่ได้มีการปฏิบัติประจวบราชการ โดยให้มีการจัดตั้งกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อมขึ้นมา และให้อำนาจของกระทรวงวิทยาศาสตร์ เทคโนโลยีและสิ่งแวดล้อม ในส่วนที่เกี่ยวข้องกับพระราชบัญญัติส่งเสริมและรักษาคุณภาพสิ่งแวดล้อมแห่งชาติ พ.ศ. ๒๕๓๕ ไปเป็นของกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม ประกอบกับการสมควรให้คณะกรรมการควบคุมมลพิษเป็นผู้พิจารณาเห็นชอบกับวิธีการตรวจหาค่ามาตรฐานการระบายน้ำทิ้ง นอกเหนือจากวิธีการที่กำหนดไว้ในกรมควบคุมมลพิษ จึงสมควรแก้ไขปรับปรุงประกาศกระทรวงวิทยาศาสตร์ เทคโนโลยีและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานความคุ้มครองระยะบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด

อาศัยอำนาจตามความในมาตรา ๕๕ แห่งพระราชบัญญัติส่งเสริมและรักษาคุณภาพสิ่งแวดล้อมแห่งชาติ พ.ศ. ๒๕๓๕ แก้ไขโดยมาตรา ๑๑๔ แห่งพระราชกฤษฎีกาแก้ไขบทบัญญัติให้สอดคล้องกับการโอนอำนาจหน้าที่ของส่วนราชการ ให้เป็นไปตามพระราชบัญญัติปรับปรุงกระทรวง ทบวง กรม พ.ศ. ๒๕๔๕ พ.ศ. ๒๕๔๕ อันเป็นพระราชบัญญัติที่มีบทบัญญัติบางประการเกี่ยวกับการจัดตั้งและการจัดสภาพของบุคคล ซึ่งมาตรา ๒๕ ประกอบกับมาตรา ๑๕ มาตรา ๔๘ มาตรา ๕๐ และมาตรา ๕๑ ของรัฐธรรมนูญแห่งราชอาณาจักรไทยบัญญัติให้กระทำได้ โดยอาศัยอำนาจตามบทบัญญัติแห่งกฎหมาย รัฐมนตรีว่าการกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม โดยคำแนะนำของคณะกรรมการควบคุมมลพิษ และโดยความเห็นชอบของคณะกรรมการสิ่งแวดล้อมแห่งชาติ จึงออกประกาศไว้ ดังต่อไปนี้

ข้อ ๑ ให้ยกเลิกประกาศกระทรวงวิทยาศาสตร์ เทคโนโลยีและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานความคุ้มครองระยะบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด ลงวันที่ ๑๐ มกราคม พ.ศ. ๒๕๓๗

ข้อ ๒ ในประกาศนี้

“อาคาร” หมายความว่า อาคารที่ก่อสร้างขึ้น ไม่ว่าจะมียลักษณะเป็นอาคารหลังเดียว หรือเป็นกลุ่มของอาคารซึ่งตั้งอยู่ภายในพื้นที่ซึ่งเป็นบริเวณเดียวกัน และไม่ว่าจะมีที่ระบายน้ำที่เดียว หรือมีหลายท่อ ที่เชื่อมติดต่อกันระหว่างอาคารหรือไม่ก็ตาม ซึ่งได้แก่

- (๑) อาคารชุด ตามกฎหมายว่าด้วยอาคารชุด
- (๒) โรงแรม ตามกฎหมายว่าด้วยโรงแรม

(๓) หอพัก ตามกฎหมายว่าด้วยหอพัก

(๔) สถานบริการประเภทสถานอาบน้ำ นวดหรืออบตัว ซึ่งมีผู้ให้บริการแก่ลูกค้า ตามกฎหมายว่าด้วยสถานบริการ

(๕) โรงพยาบาลของทางราชการหรือสถานพยาบาล ตามกฎหมายว่าด้วยสถานพยาบาล

(๖) อาคารโรงเรียนเอกชน ตามกฎหมายว่าด้วยโรงเรียนเอกชน โรงเรียนของทางราชการ อาคารสถาบันอุดมศึกษาของเอกชน ตามกฎหมายว่าด้วยสถาบันอุดมศึกษาของเอกชนและสถาบันอุดมศึกษาของทางราชการ

(๗) อาคารที่ทำการของทางราชการ รัฐวิสาหกิจ หรือองค์การระหว่างประเทศและของเอกชน

(๘) อาคารของศูนย์การค้าหรือห้างสรรพสินค้า

(๙) ตลาด ตามกฎหมายว่าด้วยการค้าสาธารณะสุข แต่ไม่รวมถึง ท่าเทียบเรือประมง สะพานปลา หรือกิจการแพปลา

(๑๐) กัดอาคารหรือรั้นอาคาร

“น้ำทิ้ง” หมายความว่า น้ำเสียที่ผ่านระบบบำบัดน้ำเสียแล้วจนเป็นไปตามมาตรฐานควบคุมการระบายน้ำทิ้งตามที่กำหนดไว้ในประกาศนี้

ข้อ ๓ ให้แบ่งประเภทของอาคารตามข้อ ๒ ออกเป็น ๕ ประเภท คือ

- (๑) อาคารประเภท ก.
- (๒) อาคารประเภท ข.
- (๓) อาคารประเภท ค.
- (๔) อาคารประเภท ง.
- (๕) อาคารประเภท จ.

ข้อ ๔ อาคารประเภท ก. หมายความว่า อาคารดังต่อไปนี้

(๑) อาคารชุดที่มีจำนวนห้องสำหรับใช้เป็นที่อยู่อาศัยรวมกันทุกชั้นของอาคาร หรือกลุ่มของอาคารตั้งแต่ ๕๐๐ ห้องขึ้นไป

(๒) โรงแรมที่มีจำนวนห้องสำหรับใช้เป็นที่พำนักรวมกันทุกชั้นของอาคาร หรือกลุ่มของอาคารตั้งแต่ ๒๐๐ ห้องขึ้นไป

(๓) โรงพยาบาลของทางราชการ รัฐวิสาหกิจหรือสถานพยาบาล ตามกฎหมายว่าด้วยสถานพยาบาล ที่มีเตียงสำหรับผู้ป่วยไว้ค้างคืนรวมกันทุกชั้นของอาคารหรือกลุ่มของอาคารตั้งแต่ ๓๐ เตียงขึ้นไป

(๔) อาคารโรงเรียนเอกชน โรงเรียนของทางราชการ สถาบันอุดมศึกษาของเอกชน หรือสถาบันอุดมศึกษาของทางราชการที่มีพื้นที่ใช้สอยร่วมกันทุกชั้นของอาคารหรือกลุ่มของอาคารตั้งแต่ ๒๕,๐๐๐ ตารางเมตรขึ้นไป]

(๕) อาคารที่ทำการของทางราชการ รัฐวิสาหกิจ องค์การระหว่างประเทศ หรือของเอกชน

(๖) อาคารของศูนย์การทหารอากาศหรือหังสรรพสินค้าตามพื้นที่ใช้สอยรวมกันทุกชั้นของอาคารหรือ

(๓) ตลอดจนพบว่า ใช้สอรวมกันมากขึ้นของอาคารหรือกลุ่มของอาคารตั้งแต่ ๒,๕๐๐ ตารางเมตรขึ้นไป

ตั้งแต่ ๒๕๐๐ ตรงมาจนถึงปี
(๘) กิตติาคารหรือร้านอาหารที่มีพื้นที่ให้บริการร่วมกันทุก軒ของอาคารหรือกลุ่มของอาคาร

ข้อ ๕ อัตราเงินเฟ้อ หมายถึง ความเปลี่ยนแปลงของระดับราคาของสินค้าและบริการต่าง ๆ ในระยะเวลาหนึ่ง โดยทั่วไปแล้ว อัตราเงินเฟ้อจะวัดโดยใช้ดัชนีราคาของสินค้าและบริการที่สำคัญ ๆ ในประเทศ

(๑) อธิการบดีมีอำนาจหรือสิทธิ์เบ็ดเสร็จในการบริหารงานของอาคาร หรือกลุ่มของอาคาร ดังแต่ ๑๐๐ ห้องนอน แต่ไม่ถึง ๕๐๐ ห้องนอน^{๔๕}

(๒) โรงพยาบาลจิตเวชขอนแก่นราชนครินทร์ หรือกลุ่มของอาคาร

(๓) หอพักมีจำนวนห้องสำหรับเพื่อผู้สมัครงานเองอาคาร หรือกลุ่มของอาคาร

(๔) สถานบริการที่พึงพิ^๕ที่^๖ใช้สอยร่วมกันทุกชั้นของอาคาร หรือกลุ่มของอาคารตั้งแต่ ๕,๐๐๐ ตารางเมตรขึ้นไป

(๕) โรงพยาบาลของกระทรวงการ รัฐวิสาหกิจ หรือสถานพยาบาล ตามกฎหมายว่าด้วยสถานพยาบาล
ที่มีเตียงสำหรับผู้ป่วยไว้ค้างคืนรวมกันทุกแห่งของอาคารตั้งแต่ ๑๐ เตียง แต่ไม่ถึง
๑๐๐ เตียง

(๖) อาคารโรงเรียนเอกชน โรงเรียนอุดมศึกษาของเอกชน หรือสถาบันอุดมศึกษาของทางราชการ สถาบันอุดมศึกษาหรือกลุ่มของอาคารดังกล่าวใช้สอยร่วมกันทุกชั้นของอาคารหรือกลุ่มของอาคารตั้งแต่ ๕,๐๐๐ ตารางเมตร แต่ไม่ถึง ๒๕,๐๐๐ ตารางเมตร

(๗) อาคารที่ทำการของทางราชการ รัฐวิสาหกิจ องค์การระหว่างประเทศ หรือของเอกชน ที่พื้นที่ที่ได้รับสอยรวมกันทุกชั้นของอาคารหรือกลุ่มของอาคารตั้งแต่ ๑๐,๐๐๐ ตารางเมตร แต่ไม่ถึง ๕๕,๐๐๐ ตารางเมตร

(๘) ๑. ๒. ๓. ๔. ๕. ๖. ๗. ๘. ๙. ๑๐. ๑๑. ๑๒. ๑๓. ๑๔. ๑๕. ๑๖. ๑๗. ๑๘. ๑๙. ๒๐. ๒๑. ๒๒. ๒๓. ๒๔. ๒๕. ๒๖. ๒๗. ๒๘. ๒๙. ๓๐. ๓๑. ๓๒. ๓๓. ๓๔. ๓๕. ๓๖. ๓๗. ๓๘. ๓๙. ๔๐. ๔๑. ๔๒. ๔๓. ๔๔. ๔๕. ๔๖. ๔๗. ๔๘. ๔๙. ๕๐. ๕๑. ๕๒. ๕๓. ๕๔. ๕๕. ๕๖. ๕๗. ๕๘. ๕๙. ๖๐. ๖๑. ๖๒. ๖๓. ๖๔. ๖๕. ๖๖. ๖๗. ๖๘. ๖๙. ๗๐. ๗๑. ๗๒. ๗๓. ๗๔. ๗๕. ๗๖. ๗๗. ๗๘. ๗๙. ๘๐. ๘๑. ๘๒. ๘๓. ๘๔. ๘๕. ๘๖. ๘๗. ๘๘. ๘๙. ๙๐. ๙๑. ๙๒. ๙๓. ๙๔. ๙๕. ๙๖. ๙๗. ๙๘. ๙๙. ๑๐๐.

(๕) ผลคดีแพ่งทางอาชญากรรมเกี่ยวกับความผิดของอาชญากรที่ ๑,๕๐๐ ตารางเมตร

(๑๐) ภัตตาหารหรือ^{๔๓}อาหาร^{๔๔}ที่^{๔๕}ให้บริการ^{๔๖}ร่วมกัน^{๔๗}ของอาคาร^{๔๘}หรือกลุ่มของอาคาร^{๔๙}ตั้งแต่ ๕๐๐ ตารางเมตร แต่ไม่ถึง ๑,๕๐๐ ตารางเมตร

ข้อ ๖ อาคารประเภท จ. หมายความว่า อาคารดังต่อไปนี้

(๑) อาคารชุดที่มีจำนวนห้องตั้งแต่ห้าสิบขึ้นไปที่มีผู้อาศัยร่วมกันทุกชั้นของอาคาร หรือกลุ่มของอาคาร
ไปถึง ๑๐๐ ห้องนอน

(๒) โรงพยาบาลจำนวน^๗แห่งสำหรับ^๘ใช้เป็น^๙ห้องพรีมาร^{๑๐}กับ^{๑๑}ทุกชั้นของอาคาร หรือ^{๑๒}กลุ่มของอาคาร

๗.๔๘ ๖๐ ห้อง

(๓) พหุพจน์จำนวนหนึ่งสำหรับ^๗ เพื่อเข้าสู่ระบบ^๘ ของอาคาร หรือกลุ่มของอาคาร

(๔) สถาบันบริการพัฒนา^{๕๔} ให้สื่อรวมกันทางวิชาการ^{๕๕} หรือกลุ่มของการตั้งแต่ ๑,๐๐๐ ตารางเมตร^{๕๖} แต่ไม่ถึง ๕,๐๐๐ ตารางเมตร^{๕๗}

(๕) อาคารที่ทำการของทางราชการ รัฐวิสาหกิจ องค์การระหว่างประเทศ หรือของเอกชน ที่มณฑลให้ใช้สอยร่วมกันทุกชั้นของอาคารหรือกลุ่มของอาคารตั้งแต่ ๕,๐๐๐ ตารางเมตรขึ้นไป แต่ไม่เกิน ๑๐,๐๐๐ ตารางเมตร

(๖) ตลาดที่มีพื้นที่ใช้สอยรวมกันทุก軒ของอาคารหรือกลุ่มของอาคารตั้งแต่ ๑,๐๐๐ ตารางเมตร

(๓) กัดเคี้ยวหรือรับประทานเพนแทท ๕๐๐ มิลลิกรัม หรืออีกนึ่งของอาคาร

ข้อ ๗ อาคารประเภท ง. หมายความว่า อาคารดังต่อไปนี้

- (๓) ซัลไฟด์ ต้องมีค่าไม่เกิน ๓.๐ มิลลิกรัมต่อลิตร
- (๔) ค่าทีเคเอ็น ต้องมีค่าไม่เกิน ๔๐ มิลลิกรัมต่อลิตร

ข้อ ๑๒ มาตรฐานควบคุมการระบายน้ำทิ้งจากอาคาร ประเภท ง. ต้องเป็นไปตามข้อ ๕ เว้นแต่

- (๑) บีโอดี ต้องมีค่าไม่เกิน ๕๐ มิลลิกรัมต่อลิตร
- (๒) สารแขวนลอย ต้องมีค่าไม่เกิน ๕๐ มิลลิกรัมต่อลิตร
- (๓) ซัลไฟด์ ต้องมีค่าไม่เกิน ๔.๐ มิลลิกรัมต่อลิตร
- (๔) ค่าทีเคเอ็น ต้องมีค่าไม่เกิน ๔๐ มิลลิกรัมต่อลิตร
- ข้อ ๑๓ มาตรฐานควบคุมการระบายน้ำทิ้งจากอาคาร ประเภท จ. ต้องมีค่าดังต่อไปนี้

- (๑) ความเป็นกรดและด่างต้องมีค่าระหว่าง ๕-๙
- (๒) บีโอดี ต้องมีค่าไม่เกิน ๒๐๐ มิลลิกรัมต่อลิตร
- (๓) สารแขวนลอย ต้องมีค่าไม่เกิน ๖๐ มิลลิกรัมต่อลิตร
- (๔) น้ำมันและไขมัน ต้องมีค่าไม่เกิน ๑๐๐ มิลลิกรัมต่อลิตร

ข้อ ๑๔ การตรวจสอบมาตรฐานการระบายน้ำทิ้งจากอาคาร ให้ใช้วิธีการดังต่อไปนี้

(๑) การตรวจสอบค่าความเป็นกรดและด่างให้กระทำโดยใช้เครื่องวัดความเป็นกรดและด่างของน้ำ (PH Meter)

(๒) การตรวจสอบค่าบีโอดีให้กระทำโดยใช้วิธีการอะไซด์โมดิฟิเคชัน (Azide Modification) ที่อุณหภูมิ ๒๐ องศาเซลเซียส เป็นเวลา ๕ วัน ติดต่อกันหรือวิธีการอื่นที่คณะกรรมการควบคุมมลพิษให้ความเห็นชอบ

(๓) การตรวจสอบค่าสารแขวนลอยให้กระทำโดยใช้วิธีการกรองผ่านกระดาษกรองใยแก้ว (Glass Fibre Filter Disc)

- (๔) การตรวจสอบค่าซัลไฟด์ให้กระทำโดยใช้วิธีการไตเตรท (Titrate)
- (๕) การตรวจสอบค่าสารที่ละลายได้ทั้งหมดให้กระทำโดยใช้วิธีการหยดแห้งระหว่างอุณหภูมิ ๑๐๓ องศาเซลเซียส ถึงอุณหภูมิ ๑๐๕ องศาเซลเซียส ในเวลา ๑ ชั่วโมง
- (๖) การตรวจสอบค่าตะกอนหนักให้กระทำโดยใช้วิธีการกรวยอิมฮอฟฟ์ (Imhoff cone) ขนาดบรรจุ ๑,๐๐๐ ลูกบาศก์เซนติเมตร ในเวลา ๑ ชั่วโมง

(๑) หอพักที่มีจำนวนห้องสำหรับใช้เป็นที่อยู่อาศัยรวมกันทุกชั้นของอาคาร หรือกลุ่มของอาคาร ตั้งแต่ ๑๐ ห้อง แต่ไม่ถึง ๕๐ ห้อง

(๒) ตลาดที่มีพื้นที่ใช้สอยรวมกันทุกชั้นของอาคาร หรือกลุ่มของอาคารตั้งแต่ ๕๐๐ ตารางเมตร แต่ไม่ถึง ๑,๐๐๐ ตารางเมตร

(๓)ภัตตาคารหรือร้านอาหารที่มีพื้นที่ให้บริการรวมกันทุกชั้นของอาคาร หรือกลุ่มของอาคาร ตั้งแต่ ๑๐๐ ตารางเมตร แต่ไม่ถึง ๒๕๐ ตารางเมตร

ข้อ ๘ อาคารประเภท จ. หมายความว่า ภัตตาคารหรือร้านอาหารที่มีพื้นที่ให้บริการรวมกันทุกชั้นไม่ถึง ๑๐๐ ตารางเมตร

ข้อ ๙ มาตรฐานควบคุมการระบายน้ำทิ้งจากอาคาร ประเภท ก. ต้องมีค่าดังต่อไปนี้

- (๑) ความเป็นกรดและด่าง (PH) ต้องมีค่าระหว่าง ๕-๙
- (๒) บีโอดี (BOD) ต้องมีค่าไม่เกิน ๒๐ มิลลิกรัมต่อลิตร
- (๓) สารแขวนลอย (Suspended Solids) ต้องมีค่าไม่เกิน ๓๐ มิลลิกรัมต่อลิตร
- (๔) ซัลไฟด์ (Sulfide) ต้องมีค่าไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร
- (๕) สารที่ละลายได้ทั้งหมด (Total Dissolved Solids) ต้องมีค่าเพิ่มขึ้นจากปริมาณสารละลายในน้ำใช้ตามปกติไม่เกิน ๕๐๐ มิลลิกรัมต่อลิตร

- (๖) ตะกอนหนัก (Settleable Solids) ต้องมีค่าไม่เกิน ๐.๕ มิลลิกรัมต่อลิตร
- (๗) น้ำมันและไขมัน (Fat Oil and Grease) ต้องมีค่าไม่เกิน ๒๐ มิลลิกรัมต่อลิตร
- (๘) ทีเคเอ็น (TKN) ต้องมีค่าไม่เกิน ๓๕ มิลลิกรัมต่อลิตร
- ข้อ ๑๐ มาตรฐานควบคุมการระบายน้ำทิ้งจากอาคาร ประเภท ข. ต้องเป็นไปตามข้อ ๕ เว้นแต่

(๑) บีโอดี ต้องมีค่าไม่เกิน ๓๐ มิลลิกรัมต่อลิตร

(๒) สารแขวนลอย ต้องมีค่าไม่เกิน ๔๐ มิลลิกรัมต่อลิตร

ข้อ ๑๑ มาตรฐานควบคุมการระบายน้ำทิ้งจากอาคาร ประเภท ค. ต้องเป็นไปตามข้อ ๕ เว้นแต่

- (๑) บีโอดี ต้องมีค่าไม่เกิน ๔๐ มิลลิกรัมต่อลิตร
- (๒) สารแขวนลอย ต้องมีค่าไม่เกิน ๕๐ มิลลิกรัมต่อลิตร

- น้ำหนักรองน้ำมันและไขมัน
- (๗) การตรวจสอบค่าน้ำมันและไขมัน ให้กระทำโดยใช้วิธีการสกัดด้วยตัวทำละลาย แล้วแยกหาน้ำมันจากน้ำมันและไขมัน
- (๘) การตรวจสอบค่าที่เคเอ็นให้กระทำโดยใช้วิธีการเจลด้าห์ล (Kjeldahl)
- ข้อ ๑๕ การคิดคำนวณพื้นที่ใช้สอย จำนวนอาคารและจำนวนห้องของอาคาร หรือกลุ่มของอาคาร ให้เป็นไปตามวิธีการที่คณะกรรมการควบคุมมลพิษกำหนด โดยประกาศในราชกิจจานุเบกษา
- ข้อ ๑๖ วิธีการเก็บตัวอย่างน้ำ ความถี่ และระยะเวลาในการเก็บตัวอย่างน้ำ ให้เป็นไปตามที่คณะกรรมการควบคุมมลพิษกำหนด โดยประกาศในราชกิจจานุเบกษา
- ข้อ ๑๗ ประกาศนี้ให้ใช้บังคับตั้งแต่วันถัดจากวันประกาศในราชกิจจานุเบกษาเป็นต้นไป

ประกาศ ณ วันที่ ๗ พฤศจิกายน พ.ศ. ๒๕๔๘

ยงยุทธ ดิยะไพรัช

รัฐมนตรีว่าการกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

ภาคผนวก จ-2

ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม
เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้ง
จากอาคารบางประเภทและบางขนาด พ.ศ. 2567
ประกาศในราชกิจจานุเบกษา เล่ม 141 ตอนพิเศษ 233 ง
วันที่ 27 สิงหาคม พ.ศ. 2567

ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด

พ.ศ. ๒๕๖๗

โดยที่เป็นการสมควรปรับปรุงการกำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคาร ให้เหมาะสมตามความก้าวหน้าในทางวิทยาศาสตร์ เทคโนโลยี และความเปลี่ยนแปลงทางเศรษฐกิจ สังคม ของประเทศ และให้สอดคล้องกับสภาพการณ์ปัจจุบัน

อาศัยอำนาจตามความในมาตรา ๕๕ แห่งพระราชบัญญัติส่งเสริมและรักษาคุณภาพสิ่งแวดล้อมแห่งชาติ พ.ศ. ๒๕๓๕ รัฐมนตรีว่าการกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม จึงได้มีคำสั่งและคำแนะนำของคณะกรรมการควบคุมมลพิษ และโดยความเห็นชอบของคณะกรรมการสิ่งแวดล้อมแห่งชาติ จึงออกประกาศไว้ ดังต่อไปนี้

ข้อ ๑ ให้ยกเลิกประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด ฉบับลงวันที่ ๗ พฤศจิกายน พ.ศ. ๒๕๔๘

ข้อ ๒ ในประกาศนี้

“อาคาร” หมายความว่า อาคารที่ก่อสร้างขึ้น ไม่ว่าจะมีลักษณะเป็นอาคารหลังเดียวหรือเป็นกลุ่มของอาคารตั้งอยู่ภายในพื้นที่ซึ่งเป็นบริเวณเดียวกัน และไม่ว่าจะมีระยะบายน้ำเพื่อเดียวหรือมีหลายท่อที่เชื่อมติดต่อกันระหว่างอาคารหรือไม่ก็ตาม

“น้ำทิ้ง” หมายความว่า น้ำที่เกิดจากกิจกรรมของอาคารที่ระบายหรือจะระบายลงสู่แหล่งน้ำสาธารณะหรือออกสู่สิ่งแวดล้อม

ข้อ ๓ ให้แปลอาคาร ออกเป็น ๓ ชนิด คือ

ชนิดที่ ๑ อาคารอยู่อาศัย หมายถึง อาคารที่มีวัตถุประสงค์ให้เป็นที่พักอาศัยของบุคคล ทั้งการอยู่อาศัยถาวรหรือชั่วคราว ได้แก่

(๑) อาคารชุด ตามกฎหมายว่าด้วยอาคารชุด

(๒) หอพัก ตามกฎหมายว่าด้วยหอพัก

(๓) หอพัก ห้องเช่า ห้องแบ่งเช่า หรือกิจการอื่นในทำนองเดียวกันตามกฎหมายว่าด้วยสาธารณูปโภค

(๔) สถานรับเลี้ยงเด็ก ตามกฎหมายว่าด้วยคุ้มครองเด็ก

(๕) สถานดูแลผู้สูงอายุหรือผู้พิการที่พึ่ง ตามกฎหมายว่าด้วยสถานประกอบการเพื่อสุขภาพ

(๖) ที่พักอาศัยสำหรับลูกจ้างประเภทกิจการก่อสร้าง ตามกฎหมายว่าด้วยการคุ้มครองแรงงาน

ชนิดที่ ๒ อาคารพาณิชย์ หมายถึง อาคารที่ใช้ประโยชน์ในการพาณิชย์กรรม หรือบริการธุรกิจ อย่างเดียวหรือหลายอย่าง ได้แก่

(๑) โรงแรม ตามกฎหมายว่าด้วยโรงแรม

- (๒) ศูนย์การค้าหรือห้างสรรพสินค้า
- (๓) ตลาด ตามกฎหมายว่าด้วยการสาธารณสุข
- (๔) สถานบริการประเภทสถานอาบน้ำ นวดหรืออบตัว ตามกฎหมายว่าด้วยสถานบริการ
- (๕) ภัตตาคารหรือร้านอาหาร
- (๖) อาคารที่ทำการของทางราชการ รัฐวิสาหกิจ หรือองค์การระหว่างประเทศและของเอกชน
- (๗) อาคารโรงเรียนเอกชน ตามกฎหมายว่าด้วยโรงเรียนเอกชน โรงเรียนของทางราชการ
- อาคารสถาบันอุดมศึกษาของเอกชน ตามกฎหมายว่าด้วยสถาบันอุดมศึกษาของเอกชนและสถาบันอุดมศึกษาของทางราชการ

ชนิดที่ ๓ อาคารสถานพยาบาล หมายถึง สถานพยาบาล ตามกฎหมายว่าด้วยสถานพยาบาล ประเภทที่รับผู้ป่วยไว้ค้างคืน

ข้อ ๔ ให้แบ่งขนาดของอาคาร ออกเป็น ๔ ประเภท ดังต่อไปนี้

ประเภทอาคาร	หน่วย	อาคารประเภท ก.	อาคารประเภท ข.	อาคารประเภท ค.	อาคารประเภท ง.
๑. อาคารอยู่อาศัย	อาคารชุด	ตั้งแต่ ๕๐๐ ขึ้นไป	ตั้งแต่ ๑๐๐ แต่ไม่ถึง ๕๐๐	ไม่ถึง ๑๐๐	-
	หอพัก	-	ตั้งแต่ ๒๕๐ ขึ้นไป	ตั้งแต่ ๕๐ แต่ไม่ถึง ๒๕๐	ไม่ถึง ๕๐
	หอพัก ห้องเช่า ห้องแบ่งเช่า หรือกิจการอื่นในทำนองเดียวกัน ตามกฎหมายว่าด้วยการสาธารณสุข	-	ตั้งแต่ ๒๕๐ ขึ้นไป	ตั้งแต่ ๕๐ แต่ไม่ถึง ๒๕๐	ไม่ถึง ๕๐
	สถานรับเลี้ยงเด็ก	-	-	-	ทุกขนาด
	สถานดูแลผู้สูงอายุหรือผู้พิการที่พึ่ง	-	-	-	ทุกขนาด
	ที่พักอาศัยสำหรับลูกจ้างประเภทกิจการก่อสร้าง	-	-	-	ทุกขนาด
๒. อาคารพาณิชย์					
โรงแรม	ห้อง	ตั้งแต่ ๒๐๐ ขึ้นไป	ตั้งแต่ ๖๐ แต่ไม่ถึง ๒๐๐	ไม่ถึง ๖๐	-
	สถานบริการประเภทสถานอาบน้ำ นวดหรืออบตัว	-	ตั้งแต่ ๕,๐๐๐ ขึ้นไป	ตั้งแต่ ๑,๐๐๐ แต่ไม่ถึง ๕,๐๐๐	ไม่ถึง ๑,๐๐๐
	โรงเรียนเอกชน	ตั้งแต่ ๒๕,๐๐๐ ขึ้นไป	ตั้งแต่ ๕,๐๐๐ แต่ไม่ถึง ๒๕,๐๐๐	-	ไม่ถึง ๕,๐๐๐
	ทางราชการ สถาบันอุดมศึกษาของเอกชนหรือสถาบันอุดมศึกษาของทางราชการ	-	-	-	-

ประเภทอาคาร	หน่วย	อาคาร ประเภท ก.	อาคาร ประเภท ข.	อาคาร ประเภท ค.	อาคาร ประเภท ง.
อาคารที่ทำการของทาง ราชการ รัฐวิสาหกิจ หรือ องค์การระหว่างประเทศและ ของเอกชน	อาคาร ราชการ	ตั้งแต่ ๕๕,๐๐๐ ขึ้นไป	ตั้งแต่ ๑๐,๐๐๐ แต่ไม่ถึง ๕๕,๐๐๐	ตั้งแต่ ๕,๐๐๐ แต่ไม่ถึง ๑๐,๐๐๐	ไม่ถึง ๕,๐๐๐
		ตั้งแต่ ๒๕,๐๐๐ ขึ้นไป	ตั้งแต่ ๕,๐๐๐ แต่ไม่ถึง ๒๕,๐๐๐	-	ไม่ถึง ๕,๐๐๐
ตลาด	ศูนย์การค้า หรือห้างสรรพสินค้า	ตั้งแต่ ๒,๕๐๐ ขึ้นไป	ตั้งแต่ ๑,๕๐๐ แต่ไม่ถึง ๒,๕๐๐	ตั้งแต่ ๑,๐๐๐ แต่ไม่ถึง ๑,๕๐๐	ไม่ถึง ๑,๐๐๐
		ตั้งแต่ ๒,๕๐๐ ขึ้นไป	ตั้งแต่ ๕๐๐ แต่ไม่ถึง ๒,๕๐๐	ตั้งแต่ ๒๕๐ แต่ไม่ถึง ๕๐๐	ไม่ถึง ๒๕๐
ภัตตาคารหรือร้านอาหาร	อาคาร สถานพยาบาล	ตั้งแต่ ๓๐ ขึ้นไป	ตั้งแต่ ๑๐ แต่ไม่ถึง ๓๐	-	ไม่ถึง ๑๐
		ตั้งแต่ ๓๐ ขึ้นไป	ตั้งแต่ ๑๐ แต่ไม่ถึง ๓๐	-	ไม่ถึง ๑๐

ข้อ ๕ กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารไว้ ดังต่อไปนี้

พารามิเตอร์	ค่ามาตรฐาน			
	อาคาร ประเภท ก.	อาคาร ประเภท ข.	อาคาร ประเภท ค.	อาคาร ประเภท ง.
๑. ความเป็นกรดและด่าง (pH)	๕.๕ - ๙.๐	๕.๕ - ๙.๐	๕.๕ - ๙.๐	๕.๕ - ๙.๐
๒. บีโอดี (Biochemical Oxygen Demand)	ไม่เกิน ๒๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๓๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๔๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๕๐ มิลลิกรัมต่อลิตร
	ไม่เกิน ๒๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๓๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๔๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๕๐ มิลลิกรัมต่อลิตร
๓. ของแข็งแขวนลอยทั้งหมด (Total Suspended Solids)	ไม่เกิน ๓๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๔๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๕๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๖๐ มิลลิกรัมต่อลิตร
๔. ของแข็งละลายน้ำทั้งหมด (Total Dissolved Solids)	ไม่เกิน ๑,๐๐๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑,๐๐๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑,๓๐๐ มิลลิกรัมต่อลิตร	-

พารามิเตอร์	ค่ามาตรฐาน			
	อาคาร ประเภท ก.	อาคาร ประเภท ข.	อาคาร ประเภท ค.	อาคาร ประเภท ง.
	สำหรับอาคารอยู่อาศัยและอาคารพาณิชย์	สำหรับอาคารอยู่อาศัยและอาคารพาณิชย์	สำหรับอาคารอยู่อาศัยและอาคารพาณิชย์	สำหรับอาคารอยู่อาศัยและอาคารพาณิชย์
	เพิ่มขึ้นจากปริมาณในน้ำใช้ปกติไม่เกิน ๑,๐๐๐	เพิ่มขึ้นจากปริมาณในน้ำใช้ปกติไม่เกิน ๑,๐๐๐	เพิ่มขึ้นจากปริมาณในน้ำใช้ปกติไม่เกิน ๑,๐๐๐	เพิ่มขึ้นจากปริมาณในน้ำใช้ปกติไม่เกิน ๑,๐๐๐
๕. ซัลไฟด์ (Sulfide)	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร
๖. ทิคเอ็น (Total Kjeldahl Nitrogen)	ไม่เกิน ๓๕ มิลลิกรัมต่อลิตร	ไม่เกิน ๓๕ มิลลิกรัมต่อลิตร	ไม่เกิน ๔๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๔๐ มิลลิกรัมต่อลิตร
๗. น้ำมันและไขมัน (Oil and Grease)	ไม่เกิน ๒๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๒๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๒๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๒๐ มิลลิกรัมต่อลิตร
๘. แบคทีเรียอุจจาระทั้งหมด (Total Coliform Bacteria) (สำหรับอาคารสถานพยาบาล)	ไม่เกิน ๕,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)	ไม่เกิน ๕,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)	ไม่เกิน ๕,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)	ไม่เกิน ๕,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)
๙. แบคทีเรียอุจจาระโคลิฟอร์ม (Fecal Coliform Bacteria) (สำหรับอาคารสถานพยาบาล)	ไม่เกิน ๑,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)	ไม่เกิน ๑,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)	ไม่เกิน ๑,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)	ไม่เกิน ๑,๐๐๐ (เอ็มทีเอ็นต่อ ๑๐๐ มิลลิตร)
๑๐. คลอรีนอิสระ (Free Chlorine) (สำหรับอาคารสถานพยาบาล)	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร	ไม่เกิน ๑.๐ มิลลิกรัมต่อลิตร

ข้อ ๖ การตรวจสอบมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารให้ใช้วิธีการ ดังต่อไปนี้

๖.๑ ความเป็นกรดและต่าง ให้ใช้เครื่องวัดความเป็นกรดและต่างของน้ำ (pH Meter) ที่มีความละเอียดไม่ต่ำกว่า ๐.๑ หน่วย

๖.๒ บีโอดี ให้ใช้วิธีบ่งตัวอย่างที่อุณหภูมิ ๒๐ องศาเซลเซียส เป็นเวลา ๕ วันติดกัน และหาค่าออกซิเจนละลายด้วยวิธีอะไซด์มอดิฟิเคชัน (Azide Modification) หรือวิธีเอ็มเบรนอิลีเกโทรด (Membrane Electrode) หรือวิธีออปติคคอลลีโพรบ (Optical Probe)

๖.๓ ของแข็งแขวนลอยทั้งหมด ให้ใช้วิธีกรองผ่านกระดาษกรองใยแก้ว (Glass Fiber Filter) และอบแห้งที่อุณหภูมิ ตั้งแต่ ๑๐๓ ถึง ๑๐๕ องศาเซลเซียส เป็นเวลาอย่างน้อย ๑ ชั่วโมง

๖.๔ ของแข็งละลายน้ำทั้งหมด ให้ใช้วิธีระเหยตัวอย่างที่กรองผ่านกระดาษกรองใยแก้ว (Glass Fiber Filter) และอบแห้งที่อุณหภูมิ ๑๘๐ องศาเซลเซียส เป็นเวลาอย่างน้อย ๑ ชั่วโมง

๖.๕ ซัลไฟด์ ให้ใช้วิธีไอโอดิเมทริก (Iodometric Method) หรือวิธีเมทิลีนบลู (Methylene Blue Method)

๖.๖ ทีเคเอ็น ให้ใช้วิธีเจลดาทัลด์ (Kjeldahl)

๖.๗ น้ำนัมและไขมัน ให้ใช้วิธีสกัดด้วยตัวทำละลายแล้นแยกหน้ำหน้ำกอนนั้นนัมและไขมัน

๖.๘ แบคทีเรียกลุ่มโคลิฟอร์มทั้งหมดและแบคทีเรียกลุ่มฟีคอลโคลิฟอร์ม ให้ใช้วิธีมัลติเทิล ทิวบ์ เฟอว์เมนเท็น เทคนิค (Multiple Tube Fermentation Technique)

๖.๙ คลอรีนอิสระ ให้ใช้วิธีไทเมทรต (Titrimetric method) หรือวิธีเทียบสี (Colorimetric method) หรือวิธีไอโอดิเมทริก อิลีเกโทรด (Iodometric Electrode Technique)

ข้อ ๗ การคิดคำนวณขนาดของอาคารตามข้อ ๔ ให้เป็นไปตามวิธีการที่คณะกรรมการควบคุมมลพิษกำหนด โดยประกาศในราชกิจจานุเบกษา

ข้อ ๘ การตรวจสอบค่ามาตรฐานน้ำทิ้งตามข้อ ๖ ต้องเป็นไปตามคู่มือวิเคราะห์น้ำและน้ำเสียของสมาคมวิศวกรรมสิ่งแวดล้อมแห่งประเทศไทย หรือ Standard Methods for the Examination of Water and Wastewater ซึ่ง American Public Health Association, American Water Works Association และ Water Environment Federation ของประเทศสหรัฐอเมริกากำหนดฉบับล่าสุด หรือตามที่ได้คณะกรรมการควบคุมมลพิษประกาศในราชกิจจานุเบกษา

ข้อ ๙ การเก็บตัวอย่างน้ำทิ้งเพื่อการตรวจสอบมาตรฐานควบคุมการระบายน้ำทิ้งตามข้อ ๕ ให้เป็น ดังต่อไปนี้

๙.๑ ให้เก็บเป็นจุดระบายน้ำทิ้งลงสู่แหล่งน้ำสาธารณะหรือออกสู่สิ่งแวดล้อมหรือจุดอื่นที่สามารถใช้เป็นตัวแทนของน้ำทิ้งที่ระบายนอกจากอาคาร ในกรณีมีการระบายทิ้งหลายจุดให้เก็บทุกจุด

๙.๒ วิธีการเก็บตัวอย่างน้ำทิ้ง ณ จุดเก็บตัวอย่างตามข้อ ๙.๑ ให้เก็บแบบจ้วง (Grab Sampling)

ข้อ ๑๐ ประกาศนี้ให้ใช้บังคับตั้งแต่วันถัดจากวันประกาศในราชกิจจานุเบกษาเป็นต้นไป

ประกาศ ณ วันที่ ๒๘ มิถุนายน พ.ศ. ๒๕๖๗
พลตำรวจเอก พัชรวาท วงษ์สุวรรณ
รัฐมนตรีว่าการกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

ภาคผนวก จ-3
ประกาศการประปานครหลวง
เรื่อง เกณฑ์กำหนดคุณภาพน้ำประปานครหลวง
ประกาศ ณ วันที่ 11 ตุลาคม พ.ศ. 2565



ประกาศการประปานครหลวง
เรื่อง เกณฑ์กำหนดคุณภาพน้ำประปาของการประปานครหลวง

โดยที่เห็นเป็นการสมควรปรับปรุงเกณฑ์กำหนดคุณภาพน้ำประปาของการประปานครหลวง เพื่อให้สอดคล้องกับเกณฑ์มาตรฐานคุณภาพน้ำดื่มที่เกี่ยวข้อง และได้มาตรฐานตามมาตรฐานสากล ตลอดจน อีกทั้งเป็นการสร้างความเชื่อมั่นให้กับประชาชนในการใช้น้ำประปาเพื่อการอุปโภคบริโภค

อาศัยอำนาจตามความในมาตรา ๓๑ และมาตรา ๓๒ แห่งพระราชบัญญัติการประปานครหลวง พ.ศ. ๒๕๑๐ ผู้ว่าการการประปานครหลวงจึงให้ยกเลิกประกาศการประปานครหลวง เรื่อง เกณฑ์กำหนดคุณภาพน้ำประปาของการประปานครหลวง ลงวันที่ ๒๘ มีนาคม พ.ศ. ๒๕๖๐ และกำหนด เกณฑ์กำหนดคุณภาพน้ำประปาของการประปานครหลวง ไว้ดังต่อไปนี้

ข้อ ๑ ในประกาศนี้

“น้ำประปา” หมายความว่า น้ำที่ผ่านกระบวนการทำให้สะอาดปราศจากเชื้อโรค แล้ว จำหน่ายให้ประชาชนได้บริโภค ซึ่งผลิตจากโรงงานผลิตน้ำของการประปานครหลวง

ข้อ ๒ คุณภาพน้ำประปาของการประปานครหลวงทั้ง ๖๔ รายการ ต้องมีคุณภาพไม่ต่ำกว่า เกณฑ์กำหนดคุณภาพน้ำประปาของการประปานครหลวงตามบัญชีแนบท้ายประกาศนี้

ข้อ ๓ การตรวจวิเคราะห์ วิธีการเก็บและรักษาคุณภาพน้ำประปาดมข้อ ๒ ให้เป็นไปตาม Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 23rd Edition, 2017 หรือให้ถือตามฉบับปรับปรุงล่าสุด

ข้อ ๔ กรณีที่ใช้วิธีวิเคราะห์นอกเหนือจากข้อ ๓ ให้อ้างอิงวิธีวิเคราะห์ที่เป็นมาตรฐานในระดับสากล หรือวิธีวิเคราะห์ที่เป็นที่ยอมรับทางวิชาการ

จึงประกาศให้ทราบโดยทั่วกัน

ประกาศ ณ วันที่ ๑๐ ตุลาคม พ.ศ. ๒๕๖๕

(นายมานิต ปานอม)

ผู้อำนวยการประปานครหลวง

เกณฑ์กำหนดคุณภาพน้ำประปาของการประปานครหลวง

1. คุณสมบัติทางจุลชีววิทยา (Biological quality)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
โคลิฟอร์มแบคทีเรีย (Coliform Bacteria)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
อี. โคไล (E. coli)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
จุลินทรีย์ทั้งหมัด (Heterotrophic Bacteria)	ซีเอฟยู/มิลลิลิตร (CFU/mL)	ไม่เกิน 500
คลอสทริเดียม เพอร์ฟริงเจนส์ (Clostridium perfringens)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
ลีสทีเรีย (Listeria spp.)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
ซูโดโมแนส แอโรซิโนซา (Pseudomonas aeruginosa)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
ซาลโมเนลลา (Salmonella spp.)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
ชิเกลลา (Shigella sp.)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
สแตฟีโลค็อกคัส ออเรียส (Staphylococcus aureus)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
วิบรียอ คอลเอร่า (Vibrio cholerae)	พบบ – ไม่พบต่อ 100 มิลลิลิตร	ไม่พบ
คริปโตสปอริเดียม (Cryptosporidium spp.)	พบบ – ไม่พบต่อ 20 ลิตร	ไม่พบ
ไกอาร์เดีย (Giardia spp.)	พบบ – ไม่พบต่อ 20 ลิตร	ไม่พบ
ไวรัสตับอักเสบเอ (Hepatitis A Virus)	พบบ – ไม่พบต่อ 20 ลิตร	ไม่พบ
โรต้าไวรัส (Rotavirus)	พบบ – ไม่พบต่อ 20 ลิตร	ไม่พบ
โพลิโอไวรัส (Poliovirus)	พบบ – ไม่พบต่อ 20 ลิตร	ไม่พบ

หมายเหตุ : CFU หมายถึง Colony forming unit เป็นหน่วยที่ได้จากวิธีตรวจนับปริมาณจุลินทรีย์ ซึ่งเจริญขึ้นมาบนผิวหน้าของอาหารเจริญจานเลี้ยงเชื้อ โดยเจริญและแบ่งตัวจนเป็นกลุ่มเรียกว่า โคลน (colony)

2. คุณสมบัติทางเคมี-ฟิสิกส์ (Physical and Chemical quality)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
สีปรากฏ (Apparent color) #	แพลตินัม-โคบอลต์ (Pt-Co)	ไม่เกิน 15
ความขุ่น (Turbidity) #	เอ็นทียู (NTU)	ไม่เกิน 1.0
รสและกลิ่น (Taste and Odor) #	-	ไม่เป็นที่น่ารังเกียจ
ค่าพีเอช (pH) #	-	6.5-8.5
ปริมาณมวลสารที่ละลายทั้งหมด (Total dissolved solids) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 1,000
คลอรีนอิสระคงเหลือ (Free Residual Chlorine)	มิลลิกรัมต่อลิตร (mg/L)	0.2-2.0
อะลูมิเนียม (Aluminium) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.2
พลวง (Antimony)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.02
สารหนู (Arsenic)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.01
แบเรียม (Barium)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 1.3
แคดเมียม (Cadmium)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.003
โครเมียม (Total Chromium)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.05
ทองแดง (Copper) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 1
เหล็ก (Iron) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.3
ตะกั่ว (Lead)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.01
แมงกานีส (Manganese)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.08
ปรอท (Inorganic Mercury)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.006
นิกเกิล (Nickel)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.07
เงิน (Silver)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.1
โซเดียม (Sodium) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 200

2. คุณสมบัติทางเคมี-ฟิสิกส์ (Physical and Chemical quality) (ต่อ)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
สังกะสี (Zinc) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 3
คลอไรด์ (Chloride) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 250
ฟลูออไรด์ (Fluoride)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.7
ซีลีเนียม (Selenium)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.04
ซัลเฟต (Sulfate) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 250
ความกระด้างทั้งหมด (Total Hardness) (คำนวณเป็นแคลเซียมคาร์บอเนต) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 300
แอมโมเนียไนโตรเจน (Ammonia Nitrogen) #	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 1.5
ไนเตรตคำนวณในรูปไนเตรต (Nitrate as NO ₃)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 50
ไนไตรต์คำนวณในรูปไนไตรต์ (Nitrite as NO ₂)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 3
ไซยาไนด์ (Cyanide)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.07
ไมโครซิสติน (Microcystin-Total)	มิลลิกรัมต่อลิตร (mg/L)	ไม่เกิน 0.001

หมายเหตุ : 1. # หมายถึง รายการที่ไม่ลดความแม่นยำมาใช้
2. Pt-Co คือ Platinum-Cobalt Unit
3. NTU คือ Nephelometric Turbidity Unit

3. กลุ่มสารกำจัดศัตรูพืชและสัตว์ (Pesticides)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
อะทราซีน (Atrazine)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 2
คาร์โบฟูเร็น (Carbofuran)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 7
คลอไพริฟอส (Chlorpyrifos)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 30
ดีดีที (DDT)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 1
กรด (2,4-ไดคลอโรฟีนอกซี) อะซิติก ((2,4-dichlorophenoxy) acetic acid)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 30
ไกลิฟอสเฟต (glyphosate) และกรดอะมิโนเมทิลฟอสโฟนิก (AMPA)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 900
พาราควอต (Paraquat)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 10

4. กลุ่มสารอินทรีย์ระเหยง่าย (Volatile Organic Compounds : VOCs)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
เบนซีน (Benzene)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 10
คาร์บอนเตตระคลอไรด์ (Carbon tetrachloride)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 4
1,2-ไดคลอโรอีเทน (1,2-Dichloroethane)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 30
เอทิลเบนซีน (Ethylbenzene)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 300
สไตรีน (Styrene)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 20
เตตราคลอโรอีเทน (Tetrachloroethene)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 100
1,1,1-ไตรคลอโรอีเทน (1,1,1-Trichloroethane)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 2,000
โทลูอีน (Toluene)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 700
ไตรคลอโรอีเทน (Trichloroethene)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 8

5. กลุ่มสารไตรฮาโลมีเทน (Trihalomethanes : THMs)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
โบรมิโนไดคลอโรมีเทน (Bromodichloromethane : CHBrCl ₂ ; BDCM)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 60
โบรมิโนฟอร์ม (Bromoform : CHBr ₃)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 100
คลอโรฟอร์ม (Chloroform : CHCl ₃)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 300
ไดโบรมิโนไดคลอโรมีเทน (Dibromodichloromethane : CHBr ₂ Cl; DBCM)	ไมโครกรัมต่อลิตร (µg/L)	ไม่เกิน 100
ผลรวมอัตราส่วนสารไตรฮาโลมีเทน (THMs : Sum of ratio)	-	ไม่เกิน 1

6. กลุ่มกัมมันตรังสี (Radioactive)

รายการ (Parameter)	หน่วย (Unit)	เกณฑ์กำหนด (Specification)
ความเข้มรังสีแอลฟา (Gross alpha activity)	เบ็กเคอเรลต่อลิตร (Bq/L)	ไม่เกิน 0.5
ความเข้มรังสีเบตา (Gross beta activity)	เบ็กเคอเรลต่อลิตร (Bq/L)	ไม่เกิน 1

ภาคผนวก จ
เอกสารสอบเทียบเครื่องมือ

List of Instruments Certification for Water Quality Analysis

No.	Instrument/Equipment	Parameter	Manufacturer	Model/Serial No.	Calibrator	Certification No.	Date of Calibration	Due date of Calibration	Remark
Water									
1	pH Meter	pH	Horiba	LAQUA-PH210 HA9A0006	Technology Promotion Association (Thailand-Japan)	25CH606	27 May 25	26 May 26	-



TECHNOLOGY PROMOTION ASSOCIATION (THAILAND-JAPAN)
CORPORATE SERVICES 3: EQUIPMENT CALIBRATION AND TESTING SERVICES
534/4 PATTANAKARN ROAD SOI 18, SUANLUANG, SUWANLUANG BANGKOK 10250
TEL 0-2717-3000-29 FAX 0-2718-9484



Certificate of Calibration

Cert.No.: 25CH608
Page: 1 of 3

Equipment : pH Meter
Manufacturer : Horiba
Model : LAQUA-PH210
Serial No. : HA0A0006
ID No. : UAE.EFM.006/2563(EFM.pH.06/03)
Condition As-Received:
Received Date : 26 May 2025
Calibration Date : 27 May 2025
Reference : 2505-0796WSC-1
Submitted by : United Analyst and Engineering Consultant Co.,Ltd.
3 Soi Udomsuk 41, Sukhumvit Road,
Bangchak, Phrakhanong, Bangkok 10260

Ambient Temperature : $(25 \pm 2.5) ^\circ\text{C}$
Relative Humidity : $(50 \pm 15) \%$
Calibration Procedure : In - house method :
- CP-CH5 by direct measurement with DC voltage standard and direct measurement with certified reference material (CRM)
- CP-CH8 by comparison with temperature standard

Calibrated by : Warakorn Lemgagrakul

Approved by : 
Approved Signatory

() Chalrit Waenwanjua
() Ponpan Paiporn
(✓) Sathip Meangmal

Issue Date : 28 May 2025

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written approval of the head of Corporate Services 3 : Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม



Cert.No.: 25CH606
Page: 2 of 3

Condition of this calibration result

1. Reference Standard Instrument

Instrument

Serial No.	ID No.	Cert. No.	Due Date
54030049	130RC118	24E2759	25 Aug 2025
4982054	110RC044	24I757	14 July 2025

- This measurement result is traceable to SI through Technology Promotion Association (Thailand - Japan)

2. Certified Reference Materials : The measurement results are traceable to SI through Hach Lange GmbH Ltd.,

Deutsche Akkreditierungsstelle, Accredited No.D-RM-45184-01-00

: The measurement results are traceable to SI through CPA chem Ltd.,

Deutsche Akkreditierungsstelle, Accredited No.D-RM-15184-01-00

Buffer Solution	Manufacturer	Lot No.	Exp. date
pH 4.007	CPA chem	1066665	18 Jan 2027
pH 7.000	Hach Lange GmbH	C03232	02 Dec 2026
pH 10.010	CPA chem	1066669	18 Jan 2028

3. This certificate is valid only to the item calibrated on date and place of calibration.

Calibration Results

Function : mV Measurement

Performing standard curve by Document Process Calibrator at pH (4,7,7.10)

Unit Under Calibration	Nominal Value	Standard Voltage Input		Actual Reading		Uncertainty of Measurement (mV)	Coverage factor k
		pH	mV	mV	pH		
pH Meter S/N: HA0A0006	4.00	4.00	177.48	177.5	4.01	0.058	2.00
	7.00	7.00	0.00	0.0	7.00	0.058	2.00
	10.00	10.00	-177.48	-177.4	10.01	0.058	2.00

เอกสารไม่ควบคุม



Cert.No.: 25CH608
Page.: 3 of 3

Calibration Results

Function : pH Measurement

Performing three buffers standard curve by using buffer nominal pH (4.7)(7.10)

Unit Under Calibration	Standard pH Buffer Solution	Actual pH Reading	Actual mV Reading (mV)	Uncertainty of pH Measurement ($\pm$)	Coverage factor k
pH Electrode S/N.: Q82M0159	4.007	4.01	181.7	0.0071	2.00
	7.000	7.00	6.4	0.0085	2.00
	7.000	7.00	6.5	0.0082	2.00
	10.010	10.00	-188.7	0.0085	2.00

Function : Temperature Measurement

(*) Without adjustment

This equipment was connected with Temperature Probe;

- Model : 9652-10D
- Serial No. : Q82M0159
- Dimension of probe
 - Length : 103 mm.
 - Diameter : 16 mm.
 - Immersion Depth : 80 mm.

Calibration Point (°C)	Standard Temperature (°C)	UUC* Reading (°C)	Error (°C)	Uncertainty of measurement ($\pm$ °C)	Coverage factor k
15.0	15.002	15.0	-0.002	0.13	2.00
30.0	30.003	30.0	-0.003	0.13	2.00
45.0	45.003	45.0	-0.003	0.13	2.00

Remark - UUC* = Unit Under Calibration

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor k , providing a level of confidence of approximately 95 %.

-000-

เอกสารไม่ควบคุม

List of Instrument Certificates for Environmental Quality Analysis

No.	Instrument/Equipment	Parameter	Manufacturer	Model/Serial No.	Calibrator	Certification No.	Date of Calibration	Due date of Calibration*
1	Analytical Balance	FAT OIL AND GREASE	Mettler Toledo	AB204-S/FACT / 1129361010	United Analyst and Engineering Consultant Co., Ltd.	250422 1 BL002 25	23/4/2025	22/4/2026
2	Analytical Balance	TOTAL DISSOLVED SOLIDS	Mettler Toledo	XSR205DU / C210685394	National Food Institute,Ministry of Industry, Thailand	2502226-002-01	20/3/2025	19/3/2026
3	Analytical Balance	TOTAL SUSPENDED SOLIDS	Mettler Toledo	XSR205DU / C009071872	National Food Institute,Ministry of Industry, Thailand	2502226-001-01	20/3/2025	19/3/2026
4	BOD Incubator	BIOCHEMICAL OXYGEN DEMAND	ARCO	UC4-1320 / 1021	Technology Promotion Association (Thailand-Japan)	24TM1002	7/7/2025	6/7/2026
5	BOD Incubator	BIOCHEMICAL OXYGEN DEMAND	ARCO	UC4-1320 / 1021	Technology Promotion Association (Thailand-Japan)	25TM1001	7/7/2025	6/7/2026
6	DO Meter	BIOCHEMICAL OXYGEN DEMAND	YSI	5100 / 11B 101863	Technology Promotion Association (Thailand-Japan)	25TW29	17/2/2025	16/2/2026
7	Digestion Units	TOTAL KJELDAHL NITROGEN	Foss Tecator	2520 Auto / 91794469	National Food Institute Ministry of Industry, Thailand	2501440-001-01	27/1/2025	26/1/2026
8	Hot Air Oven	TOTAL SUSPENDED SOLIDS	Memmert	UF55 / B216.1666	National Food Institute, Ministry of Industry, Thailand	2500116-001-01	8/10/2024	7/10/2025
9	Hot Air Oven	TOTAL DISSOLVED SOLIDS TOTAL SUSPENDED SOLIDS	Memmert	UF55 / B212.0411	Technology Promotion Association (Thailand-Japan)	25TM579	19/3/2025	18/3/2026
10	Incubator	LEGIONELLA SP.	Memmert	IPP260 / V616.0066	National Food Institute, Ministry of Industry, Thailand	2502229-002-01	19/3/2025	18/3/2026
11	Kjeltec System Distilling Unit	TOTAL KJELDAHL NITROGEN	Foss Tecator (Labtec)	KT200 / 91790524	FOSS South East Asia	13319	27/1/2025	26/1/2026
12	Kjeltec Distillation Unit	TOTAL KJELDAHL NITROGEN	FOSS	Kjeltec 8100 / 91889052	FOSS South East Asia	13854	24/2/2025	23/2/2026
13	pH Meter	pH	Horiba	LAQUA-PH210 / HA9M0047	technology promotion association (thailand-japan	25CH354	20/3/2025	19/3/2026
14	pH Meter	pH	Horiba	LAQUA-PH210 / HAOC0025	technology promotion association (thailand-japan	25CH261	26/2/2025	25/2/2026
15	pH Meter	pH	YSI Environmental	pH 100A / JC03354	Technology Promotion Association (Thailand-Japan)	24CH1379	6/11/2024	5/11/2025

Due Date of Calibration* : Based on the annual calibration plan. At least 1 time per year.

Certificate of Calibration

Certificate No.: 250422-1-BL002-25

Code No.: BL002-25

Page: 1 of 3

Customer Name: United Analyst and Engineering Consultant Co., Ltd.
Address: 3 Soi Udomsuk 41, Sukhumvit Rd., Bang Chak, Phra Khanong, Bangkok 10260

Equipment: Electronic Balance
Manufacturer: Mettler Toledo
Model: AB204-S/FACT
Serial No.: 1129361010
Asset No.: UAE.WAS.002/2552

Building: N/A **Floor:** 1 **Room:** 107

Received Date: April 22, 2025

Date of Calibration: April 23, 2025

Calibration Conditions: Temperature 22.8 °C to 23.4 °C
Humidity 54.8 % to 68.9 %
Pressure 756.6 mmHg to 758.2 mmHg

Calibrated by: Sakkarin Srirahang

Approved by: Suwit Chotnok

Signature:

Issued Date: April 25, 2025

Note: 1) The Uncertainties are for a confidence probability of approximately 95%

2) This Certificate is valid only to the item calibrated on date and place of calibration.

3) This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation Scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the units of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the United Analyst and Engineering Consultant Co., Ltd. (UAE)

เอกสารไม่ควบคุม

Certificate No.: 250422-1-BL002-25

Code No.: BL002-25

Page: 2 of 3

Equipment: Electronic Balance **Manufacturer:** Mettler Toledo
Model: AB204-S/FACT **Readability:** 0.0001 g
Serial No.: 1129361010 **ID No.:** UAE.WAS.002/2552
Max. Capacity: 220 g
Calibration Date: April 23, 2025
Condition As-Received: In Condition

Condition of Equipment:

Condition of This Result of Calibration:

1. Calibration Method: This instrument was calibrated by method UAE.CP.CAL.009 In-House Method based on UKAS Lab 14: 2022

2. Reference Standards:

Reference Standard:	Model	Serial No.	Calibrated By	Certificate No.	Traceability	Due Date
Standard Weight Class E2 (DML)	1 mg to 1 kg	8749109122	AMARC	25-009359	Mettler-Toledo	21-Jan-27
Standard Weight Class F1 (DML)	1 mg to 200 g	11119512	AMARC	24-013840	Mettler-Toledo	04-Feb-26
Instrument	Model	Serial No.	Calibrated By	Certificate No.	Traceability	Due Date
Thermo-Hygro-Baro Meter	MH-B-38250	AK-46457	SLCCSS	SG-H-00997/67	Success Gateway	21-Nov-25
Thermo-Hygro-Baro Meter	MH-B-38250	AK-46457	TPA	25PT95	TPA	25-Feb-26

3. This certification is traceable to SI Unit

4. This certification was certified only for the instrument we calibrated

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Through the reference standard laboratory of AMARC 25-009359 Calibration 0152

Calibration Result:

1. Repeatability of Reading:

Nominal Value (g)	Standard Deviation of Reading (g)
200*	0.00045

2. Eccentric or off-center loading

A mass of 100 g was placed and moved to various position on pan

The balance reading obtained is given in the table.



1 (g)	2 (g)	3 (g)	4 (g)	5 (g)	Maximum Difference (g)
100.0000	99.9996	99.9997	100.0003	100.0005	0.0005

เอกสารไม่ควบคุม

Certificate No.: 250422-1-BL002-25

Code No.: BL002-25

Page: 3 of 3

Equipment: Electronic Balance **Manufacturer:** Mettler Toledo
Model: AB204-S/FACT **Readability:** 0.0001 g
Serial No.: 1129361010 **ID No.:** UAE.WAS.002/2552
Max. Capacity: 220 g
Calibration Date: April 23, 2025

Calibration Result: (Continued)

Calibration Range: 0 - 200 g

Calibration Adjustment: Internal Calibration

3. Error of Indication from nominal or conventional mass value:

Nominal Value (g)	Reference Value (g)	Indication (g)	Correction (g)	Uncertainty (± mg)	Coverage Factor k
Unload	0.0000000	0.0000	0.0000	0.10	2.05
0.01	0.0100025	0.0099	0.0001	0.10	2.05
0.05	0.0500056	0.0500	0.0000	0.10	2.05
0.1	0.1000012	0.0999	0.0001	0.10	2.05
0.5	0.5000133	0.5000	0.0000	0.10	2.05
1	1.0000105	1.0000	0.0000	0.10	2.05
10	10.000010	10.0000	0.0000	0.11	2.04
40	40.000076	40.0000	0.0000	0.14	2.00
50	50.000056	50.0000	0.0001	0.13	2.00
80	80.000107	80.0000	0.0001	0.18	2.00
100	100.000109	99.9999	0.0002	0.17	2.00
120	120.00015	119.9999	0.0003	0.21	2.00
150	150.000165	149.9998	0.0003	0.24	2.00
160	160.000175	159.9997	0.0005	0.26	2.00
200	200.000129	199.9998	0.0004	0.30	2.00

4. Effect of Tare test:

Tare Load (g)	Test Load (g)	Indication (g)	Correction (g)
100	20.000041	19.9999	0.0001
	40.000076	39.9998	0.0002
	60.000066	59.9997	0.0003
	80.000107	79.9999	0.0002
	100.000168	100.0004	-0.0003

Remark:

The report uncertainty of measurement was based on standard uncertainty multiplied by coverage factor k, providing

เอกสารไม่ควบคุม

o--o-End-o--o

Calibration Certificate

Certificate No.: 2502226-002-01
Client name: UNITED ANALYST AND ENGINEERING CONSULTANT CO.,LTD.
Address: 3 Soi Udomsuk 41, Sukhumvit Road,
Bangchack, Prakhonong, Bangkok 10260

Page 1 of 4

Equipment: Electronic Balance

Manufacturer: METTLER TOLEDO

Model: XSR2050U

Serial No.: C210685394

ID No.: UAE.WAO.010/2565

Order No.: 2502226

Operation No.: 2502226-002

Date of Receipt: 19 March 2025

Date of Calibration: 20 March 2025

Calibrated by Mr.Yothin Charoensuk
Scientist

Approved by [Signature]

(Mr.Pheraphet Tuanjit)
Manager, Division of Calibration Laboratory

Date of Issue: 25 March 2025

Responsible for the Technical Management Team

The uncertainties are for a confidence probability of approximately 95%

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation Scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the units of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the National Food Institute.

FCS-012 Revision: 01 Date: 20-04-65

ศูนย์บริการห้องปฏิบัติการอุตสาหกรรมอาหาร (National Food Institute) เลขสารไม่ควบคุม
20000 Soi 36, Anin Aree Road, Bang Yi Khan Sukhumvit, Bang Phli District, Bangkok 10700, Thailand
Tel: +66(0) 2422 8688 Fax: +66(0) 2422 8545



Calibration Report

Certificate No.: 2502226-002-01
Equipment: Electronic Balance
Model: XSR2050U
Serial No.: C210685394
Capacity: 82 g / 220 g
Manufacturer: METTLER TOLEDO
Resolution: 0.00001 g / 0.0001 g
ID No.: UAE.WAO.010/2565

Page 2 of 4

Date of Calibration: 20 March 2025

Environment Condition: Ambient Temperature: 21.2 ± 0.6 °C Relative Humidity: 48 ± 3.5 %

Place of Calibration: 208 Balance Room, UNITED ANALYST AND ENGINEERING CONSULTANT CO.,LTD.

Condition of Equipment: Good Condition

Condition of This Results of Calibration:

1. Calibration Method: NFI Method W-MA-001 In-House Method based on UKAS Lab 14 : 2019

2. Reference Standards:

Reference Standard	Model	Serial No.	Calibrated By	Certificate No.	Due Date
Standard Weight Class E2	1mg to 200g	850567572	TCS	H2491005	19 April 2025
Instrument	Model	Serial No.	Calibrated By	Certificate No.	Due Date
Thermo-Hygro Meter	608-H1	NFI.BTH 017/23	Quality Reborn	QR25-0542	10 February 2026

3. This certification is traceable to SI UNIT

4. This Certificate was certified only for the instrument we calibrated.

5. This result of calibration was found accurate as shown on date and place of calibration only.

Calibration Results:


1. Repeatability of Reading:

Nominal Value (g)	Standard Deviation of Reading (g)
40	0.0000042
80	0.0000042
100	0.0000000
200	0.0000000

2. Off-Center Error:

A mass of 100 g was placed and moved to various position on pan.

The balance reading obtained is given in the table:



1	2	3	4	5	6	(Maximum Difference)
(g)	(g)	(g)	(g)	(g)	(g)	(g)
100.0001	100.0001	100.0001	100.0001	100.0001	100.0001	0.0000

FCS-012 Revision: 01 Date: 20-04-65

ศูนย์บริการห้องปฏิบัติการอุตสาหกรรมอาหาร (National Food Institute) เลขสารไม่ควบคุม
20000 Soi 36, Anin Aree Road, Bang Yi Khan Sukhumvit, Bang Phli District, Bangkok 10700, Thailand
Tel: +66(0) 2422 8688 Fax: +66(0) 2422 8545



Calibration Report

Certificate No.: 2502226-002-01
Equipment: Electronic Balance
Model: XSR2050U
Serial No.: C210685394
Capacity: 82 g / 220 g
Manufacturer: METTLER TOLEDO
Resolution: 0.00001 g / 0.0001 g
ID No.: UAE.WAO.010/2565

Page 3 of 4

Date of Calibration: 20 March 2025

Calibration Results: (Continued)

Calibration Range: 0-80 g

Calibration Adjustment: Internal Calibration

3. Departure from Nominal Value: (Range: 0 - 82 g ; Resolution: 0.00001 g)

Nominal Value (g)	Standard Value (g)	Average Reading (g)	Correction (g)	Uncertainty (± g)	Coverage Factor K
Unload	0.00000	0.00000	0.00000	0.0000007	2.00
0.001	0.001003	0.00100	0.00000	0.0000090	2.00
0.005	0.005002	0.00501	-0.00001	0.0000092	2.00
0.01	0.010003	0.01002	-0.00002	0.0000089	2.00
0.05	0.049996	0.05001	-0.00001	0.0000096	2.00
0.1	0.100011	0.10002	-0.00001	0.000011	2.00
0.5	0.500016	0.50004	-0.00002	0.000014	2.00
1	1.000033	1.00005	-0.00002	0.000016	2.00
2	2.000073	2.00006	-0.00004	0.000017	2.00
5	5.000015	5.00006	-0.00005	0.000020	2.00
10	10.000009	10.00005	-0.00004	0.000026	2.00
20	20.000030	20.00007	-0.00004	0.000032	2.00
30	30.000039	30.00009	-0.00005	0.000050	2.00
50	50.000028	50.00008	-0.00005	0.000068	2.00
80	80.000067	80.00013	-0.00006	0.00011	2.00

FCS-012 Revision: 01 Date: 20-04-65

ศูนย์บริการห้องปฏิบัติการอุตสาหกรรมอาหาร (National Food Institute) เลขสารไม่ควบคุม
20000 Soi 36, Anin Aree Road, Bang Yi Khan Sukhumvit, Bang Phli District, Bangkok 10700, Thailand
Tel: +66(0) 2422 8688 Fax: +66(0) 2422 8545



Calibration Report

Certificate No.: 2502226-002-01
Equipment: Electronic Balance
Model: XSR2050U
Serial No.: C210685394
Capacity: 82 g / 220 g
Manufacturer: METTLER TOLEDO
Resolution: 0.00001 g / 0.0001 g
ID No.: UAE.WAO.010/2565

Page 4 of 4

Date of Calibration: 20 March 2025

Calibration Results: (Continued)

Calibration Range: >80-200 g

Calibration Adjustment: Internal Calibration

3. Departure from Nominal Value: (Range: >80 - 200 g ; Resolution: 0.00001 g)

Nominal Value (g)	Standard Value (g)	Average Reading (g)	Correction (g)	Uncertainty (± g)	Coverage Factor K
90	90.00010	90.0002	-0.0001	0.00015	2.00
100	100.00006	100.0001	0.0000	0.00016	2.00
110	110.00007	110.0002	-0.0001	0.00017	2.00
120	120.00009	120.0002	-0.0001	0.00018	2.00
130	130.00010	130.0002	-0.0001	0.00019	2.00
140	140.00013	140.0002	-0.0001	0.00019	2.00
150	150.00009	150.0002	-0.0001	0.00021	2.00
160	160.00016	160.0002	-0.0001	0.00022	2.00
170	170.00012	170.0002	-0.0001	0.00023	2.00
200	200.00013	200.0002	-0.0001	0.00028	2.00

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor K, providing a level of confidence of approximately 95 %.

***** End *****

FCS-012 Revision: 01 Date: 20-04-65

ศูนย์บริการห้องปฏิบัติการอุตสาหกรรมอาหาร (National Food Institute) เลขสารไม่ควบคุม
20000 Soi 36, Anin Aree Road, Bang Yi Khan Sukhumvit, Bang Phli District, Bangkok 10700, Thailand
Tel: +66(0) 2422 8688 Fax: +66(0) 2422 8545





Certificate of Calibration

Cert. No.: 25TM1002
Page : 1 of 3

Equipment : BOD Incubator
Manufacturer : ARCO
Model : UC4-1320
Serial No. :
ID No. : UAE.WAO.002/2550
Submitted by : United Analyst and Engineering Consultant Co.,Ltd.
3 Sol Udomsuk 41, Sukhumvit Road,
Bangchak, Phrakhanong,
Bangkok 10260
Location : Lab Floor 2
Received Order : 07 July 2025
Calibration Date : 07 July 2025
Ambient Temperature : (26 ± 10) °C
Relative Humidity : (50 ± 30) %
AC Line Voltage : (220 ± 22) V
Calibrated by : Man Pattanapongpaiboon
Approved by :
() Chakrit Waewwanjua
() Suwit Imjai
(✓) Kunchit Promprat

Issue Date : 17 July 2025

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written
Approval of the head of Corporate Services 3: Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม



Equipment : BOD Incubator
Condition As-Received : Used Item
Reference : 2507-0146OC-3
Procedure Used :-

Cert. No.: 25TM1002
Page : 2 of 3

Calibration were conducted using calibration procedure CP-OT02 based on TLAS G-20 according to direct measurement method with Data Acquisition which connected with Resistance Temperature Detector (RTD).
The temperature scale used was based on ITS-90.

Condition of this result of calibration

1. Reference standard instrument-

Instrument	Serial No.	Cert. No.	Traceable	Due Date
1.) Data Acquisition	MY59003411	24LM192	TPA	24 Dec 2025

2. This certificate is valid only to the item calibrated on date and place of calibration.

3. This measurement result is traceable to the International System of Unit maintained through :


Remark : TPA : Technology Promotion Association (Thailand - Japan)

Result of Calibration :- (*) Without Adjustment

Function of UUC* : Temperature Source

Fresh air setting : Not Available

Environment during calibration		
	Beginning	Finished
Temp. (°C)	28	28
REL.Humid. (%)	57	58
AC Supply (Volt)	225	226



Probe Installation Details :

a = 10 cm
b = 10 cm
c = 10 cm

Dimension of Chamber :

D = 0.62 m
W = 1.2 m
H = 1.2 m
Capacity = 0.89 m³

Position :	Ref. Std. ID No.:
1	25-20RTD-2/1
2	25-20RTD-2/2
3	25-20RTD-2/3
4	20RTD-2/4
5	20RTD-2/5
6	20RTD-2/6
7	20RTD-2/7
8	20RTD-2/8
9 (ref.)	20RTD-2/9

เอกสารไม่ควบคุม



Equipment : BOD Incubator
Condition As-Received : Used Item
Reference : 2507-0146OC-3
Result of Calibration :- (*) Without Adjustment
Function of UUC* : Temperature Source
Fresh air setting : Not Available

Cert. No.: 25TM1002
Page : 3 of 3

Calibration Point (°C)	UUC* Setting (°C)	UUC* Reading (°C)	Temperature stability (± °C)	Temperature uniformity (°C)	Overall Variation (°C)	Coverage Factor k
20.0	20.0	19.8	0.48	0.46	1.2	2

Calibration Point (°C)	Measured Temperature (°C)									Uncertainty (± °C)
	1	2	3	4	5	6	7	8	9 (ref.)	
20.0	20.226	20.266	20.121	19.807	19.971	20.055	19.872	19.853	19.925	0.72

Average* : The average of 30 values in each position.

Temperature stability : One-half of the greatest maximum difference of measured temperature at any one sensor.

Temperature uniformity : The maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time or at as close an observation time as possible to determine the temperature pattern or homogeneity within the chamber under steady-state conditions.

Overall Variation : The Difference of the maximum and minimum measured temperatures throughout observation.

UUC* : Unit Under Calibration

Note : The reported uncertainty of measurement was included stability and excluded uniformity .

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor k, providing a level of confidence of approximately 95 %.

-000-

เอกสารไม่ควบคุม



Certificate of Calibration

Cert. No.: 25TM1001
Page : 1 of 3

Equipment : BOD Incubator
Manufacturer : ARCO
Model : UC4-1320
Serial No. : -
ID No. : UAE.WAO.018/2559
Submitted by : United Analyst and Engineering Consultant Co.,Ltd.
3 Soi Udomsuk 41, Sukhumvit Road,
Bangchak, Phrakhanong,
Bangkok 10260
Location : Lab Floor 2
Received Order : 07 July 2025
Calibration Date : 07 July 2025
Ambient Temperature : (26 ± 10) °C
Relative Humidity : (50 ± 30) %
AC Line Voltage : (220 ± 22) V
Calibrated by : Man Pattanapongpaiboon
Approved by : [Signature]
() Chakrit Waewwanjua
() Suwit Imjai
(✓) Kunchit Promprat

Issue Date : 17 July 2025

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written
Approval of the head of Corporate Services 3: Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม



Equipment : BOD Incubator
Condition As-Received : Used Item
Reference : 2507-0148OC-2
Procedure Used :-

Cert. No.: 25TM1001
Page : 2 of 3

Calibration were conducted using calibration procedure CP-OT02 based on TLAS G-20 according to direct measurement method with Data Acquisition which connected with Resistance Temperature Detector (RTD).
The temperature scale used was based on ITS-90.

Condition of this result of calibration

1. Reference standard instrument:-

Instrument	Serial No.	Cert. No.	Traceable	Due Date
1) Data Acquisition	MY59003411	24LM192	TPA	24 Dec 2025

2. This certificate is valid only to the item calibrated on date and place of calibration.

3. This measurement result is traceable to the International System of Unit maintained through :


Remark : TPA : Technology Promotion Association (Thailand - Japan)

Result of Calibration :- (*) Without Adjustment

Function of UUC* : Temperature Source

Fresh air setting : Not Available

Environment during calibration		
	Beginning	Finished
Temp. (°C)	28	28
REL.Humid. (%)	54	57
AC Supply (Volt)	224	226



Probe Installation Details :

a = 10 cm
b = 10 cm
c = 10 cm

Dimension of Chamber :

D = 0.62 m
W = 1.2 m
H = 1.2 m
Capacity = 0.89 m³

Position :	Ref. Std. ID No.:
1	25-20RTD-2/1
2	25-20RTD-2/2
3	25-20RTD-2/3
4	20RTD-2/4
5	20RTD-2/5
6	20RTD-2/6
7	20RTD-2/7
8	20RTD-2/8
9 (ref.)	20RTD-2/9

เอกสารไม่ควบคุม



Equipment : BOD Incubator
Condition As-Received : Used Item
Reference : 2507-0148OC-2
Result of Calibration :- (*) Without Adjustment
Function of UUC* : Temperature Source
Fresh air setting : Not Available

Cert. No.: 25TM1001
Page : 3 of 3

Calibration Point (°C)	UUC* Setting (°C)	UUC* Reading (°C)	Temperature stability (± °C)	Temperature uniformity (°C)	Overall Variation (°C)	Coverage Factor k
20.0	20.0	19.9	0.18	0.60	0.63	2

Calibration Point (°C)	Measured Temperature (°C)									Uncertainty (± °C)
	1	2	3	4	5	6	7	8	9 (ref.)	
20.0	20.202	19.900	20.390	20.077	20.111	20.044	20.275	20.173	19.835	0.38

Average* : The average of 30 values in each position.

Temperature stability : One-half of the greatest maximum difference of measured temperature at any one sensor.

Temperature uniformity : The maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time or at as close an observation time as possible to determine the temperature pattern or homogeneity within the chamber under steady-state conditions.

Overall Variation : The Difference of the maximum and minimum measured temperatures throughout observation.

UUC* : Unit Under Calibration

Note : The reported uncertainty of measurement was included stability and excluded uniformity .

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor *k*, providing a level of confidence of approximately 95 %.

-000-

เอกสารไม่ควบคุม

Calibration Certificate

Certificate No.: 2500116-001-01
Client name: UNITED ANALYST AND ENGINEERING CONSULTANT CO.,LTD.
Address: 3 Soi Udomsuk 41, Sukhumvit Road,
Bangchack, Prakhonong, Bangkok 10260

Page 1 of 3

Equipment: CHAMBER (Hot Air Oven)

Manufacturer: MEMMERT

Model: UF55

Serial No.: B216.1666

ID No.: UAE.WAO.027/2559

Order No.: 2500116

Operation No.: 2500116-001

Date of Receipt: 8 October 2024

Date of Calibration: 8 October 2024

Calibrated by Mr.Yothin Charoensuk **Approved by** (Mr.Pheraphat Tuanjit)
Scientist Manager, Division of Calibration Laboratory
Date of Issue: 15 October 2024 Responsible for the Technical Management Team

The uncertainties are for a confidence probability of approximately 95 %.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the units of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the National Food Institute.

F-CS-009 Revision: 01 Date: 20-04-65

2500116-001-01: 30.3 ± 1.0 °C, 55 ± 1.0 %, 230 ± 3.0 Volt
2500116-001-01: 30.3 ± 1.0 °C, 55 ± 1.0 %, 230 ± 3.0 Volt
Tel: +662-0462-8888 Fax: +662-0462-8889

เอกสารไม่ควบคุม



Calibration Report

Certificate No.: 2500116-001-01
Equipment: CHAMBER (Hot Air Oven)
Model: UF55 **Serial No.:** B216.1666
Resolution: 0.1 °C **ID No.:** UAE.WAO.027/2559
Manufacturer: MEMMERT

Date of Calibration: 8 October 2024

Page 2 of 3

Location: Laboratory, UNITED ANALYST AND ENGINEERING CONSULTANT CO.,LTD.

Environment Condition:
Ambient Temperature (30.3 ± 1.0) °C
Relative Humidity (55 ± 1.0) %
Line Voltage (230 ± 3.0) Volt

Condition of this results of Calibration:

- This instrument was calibrated by insert 9 standard thermometer into its chamber and calibration according to W-TE-014 Based on TLAS G-20-1/02-08 (E): Guidelines for Calibration and Checks of Temperature Controlled Enclosures.
- The temperature scale used was based on ITS - 90.
- All data show below were final values and the initial data may be obtained upon request.
- Reference Standard Instrument :

Instrument	Model	Serial No./ID No.	Certificate No.	Due Date	Through
Digital Thermometer with sensor	34972A	MYS7003188	TE 670486-01	8 June 2025	NATIONAL FOOD INSTITUTE
	RTD	CH201-209; RTD4201-209			

- This certificate is traceable to International System of Units (SI Units).
- This certificate was certified only for the instrument we calibrated.
- This result of calibration was found accurate as shown on date and place of calibration only.
- Condition of Calibrated item : Good

UUC Description :
Time of Record : 1 Hour 9 Minute At 104.0, 140.0 and 180.0 °C
Fresh air Damper : ☐ Open Position ☐ ☒ Close Fan 40%
Not Available

- Result of Calibration : ☒ Without adjustment ☐ After adjustment

F-CS-012 Revision: 01 Date: 20-04-65

2500116-001-01: 30.3 ± 1.0 °C, 55 ± 1.0 %, 230 ± 3.0 Volt
2500116-001-01: 30.3 ± 1.0 °C, 55 ± 1.0 %, 230 ± 3.0 Volt
Tel: +662-0462-8888 Fax: +662-0462-8889

เอกสารไม่ควบคุม



Calibration Report

Certificate No.: 2500116-001-01
Equipment: CHAMBER (Hot Air Oven)
Model: UF55 **Serial No.:** B216.1666
Resolution: 0.1 °C **ID No.:** UAE.WAO.027/2559
Manufacturer: MEMMERT

Date of Calibration: 8 October 2024

Page 3 of 3

Calibration point: 104.0, 140.0 and 180.0 °C

Calibration Condition	Temperature (°C)	Relative Humidity (%)	Line Voltage (Volt)
MIN	29.3	54	227.0
MAX	31.2	56	232.0

Table 1 : Reporting of Temperature

Calibration point (°C)	Measured Temperature (°C) @ Sensor No. (Sensor No.9 is REF)									Uncertainty ± (°C)
	# 1	# 2	# 3	# 4	# 5	# 6	# 7	# 8	# 9	
104.0	103.89	103.66	103.88	103.89	104.40	103.98	103.70	104.10	104.15	0.53
140.0	139.85	139.53	139.87	139.88	140.67	140.00	139.60	140.25	140.23	0.73
180.0	179.63	179.22	179.71	179.76	181.03	180.06	179.41	180.87	180.39	0.90

Table 2 : Reporting of Characterization Result

UUC* Setting (°C)	UUC* Reading (°C)			Stability ± (°C)	Uniformity (°C)	Overall Variation (°C)
	MIN	MAX	Average			
104.0	104.0	104.0	104.0	0.15	0.49	0.88
140.0	140.0	140.0	140.0	0.13	0.71	1.2
180.0	180.0	180.0	180.0	0.13	1.2	1.9

Note The quoted uncertainty include " Stability " and " Loading effect (20% of Temp Uniformity) "

UUC* = Unit Under Calibration

Stability = One-half of the greatest maximum difference of measured temperatures at any one sensors, for at least half an hour after reaching steady state.

Uniformity = The maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.

Overall Variation = The difference of the maximum and minimum measured temperatures throughout observation time.

The report uncertainty of measurement was based on standard uncertainty multiplied by coverage factor k= 2, providing a level of confidence of approximately 95 %.

***** End *****

F-CS-012 Revision: 01 Date: 20-04-65

2500116-001-01: 30.3 ± 1.0 °C, 55 ± 1.0 %, 230 ± 3.0 Volt
2500116-001-01: 30.3 ± 1.0 °C, 55 ± 1.0 %, 230 ± 3.0 Volt
Tel: +662-0462-8888 Fax: +662-0462-8889

เอกสารไม่ควบคุม





Certificate of Calibration

Cert. No.: 25TM579
Page : 1 of 3

Equipment : Hot Air Oven
Manufacturer : Memmert
Model : UF 55
Serial No. : B212.0411
ID No. : UAE.WAO.005/2556
Submitted by : United Analyst and Engineering Consultant Co.,Ltd.
3 Soi Udomsuk 41, Sukhumvit Road,
Bangchak, Phrakhanong,
Bangkok 10250
Location : Lab Floor 2
Received Order : 19 March 2025
Calibration Date : 19 March 2025
Ambient Temperature : $(26 \pm 10) ^\circ\text{C}$
Relative Humidity : $(50 \pm 30) \%$
AC Line Voltage : $(220 \pm 22) \text{V}$
Calibrated by : Man Pattanapongpaiboon
Approved by :
() Chakrit Waewwanjua
() Suwit Imjai
(✓) Kunchit Promprat
Issue Date : 27 March 2025

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written
Approval of the head of Corporate Services 3 : Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม



Equipment : Hot Air Oven
Condition As-Received : Used Item
Reference : 2503-0437OC-3

Cert. No.: 25TM579
Page : 2 of 3

Procedure Used :-

Calibration were conducted using calibration procedure CP-OT02 based on TLAS G-20 according to direct measurement method with Data Acquisition which connected with Resistance Temperature Detector (RTD) and Thermocouple Type T.

The temperature scale used was based on ITS-90.

Condition of this result of calibration

1. Reference standard instrument:-

Instrument	Serial No.	Cert. No.	Traceable	Due Date
1) Data Acquisition	MY44073381	24LM73	TPA	18 May 2025

2. This certificate is valid only to the item calibrated on date and place of calibration.

3. This certification is traceable to the International System of Unit.

Remark : TPA : Technology Promotion Association (Thailand - Japan)


Result of Calibration :-

(*) Without Adjustment

Function of UUC* : Temperature Source

Fresh air setting : Close

Environment during calibration		
	Beginning	Finished
Temp. (°C)	27	28
REL Humid. (%)	49	55
AC Supply (Volt)	221	224



Probe Installation Details :

a = 5.0 cm
b = 5.0 cm
c = 5.0 cm

Dimension of Chamber :

D = 0.50 m
W = 0.80 m
H = 0.75 m
Capacity = 0.30 m³

Ref. Std. ID No.: @ Calibration Point		
Position :	(120,180) °C	(104) °C
1	23-01TC-01	1RTD-2/1
2	23-01TC-02	1RTD-2/2
3	23-01TC-03	22-01RTD-03
4	23-01TC-04	1RTD-2/4
5	23-01TC-05	1RTD-2/5
6	23-01TC-06	1RTD-2/6
7	23-01TC-07	23-01RTD-07
8	23-01TC-08	1RTD-2/8
9 (ref.)	23-01TC-09	23-01RTD-09

เอกสารไม่ควบคุม



Equipment : Hot Air Oven
Condition As-Received : Used Item
Reference : 2503-0437OC-3
Result of Calibration :- (*) Without Adjustment
Function of UUC* : Temperature Source
Fresh air setting : Close

Cert. No.: 25TM579
Page : 3 of 3

Calibration Point (°C)	UUC* Setting (°C)	UUC* Reading (°C)	Temperature stability (± °C)	Temperature uniformity (°C)	Overall Variation (°C)	Coverage Factor k
104.0	104.0	104.0	0.040	0.43	0.78	2
120.0	120.0	120.0	0.64	1.3	1.6	2
180.0	180.0	180.0	0.49	1.5	1.8	2

Calibration Point (°C)	Measured Temperature (°C)									Uncertainty (± °C)
	1	2	3	4	5	6	7	8	9 (ref.)	
104.0	104.335	104.135	104.363	104.317	103.649	103.738	104.179	104.229	104.025	0.42
120.0	119.575	119.366	119.807	119.905	118.994	119.194	119.888	119.994	120.064	1.1
180.0	180.286	179.510	180.401	180.551	179.281	179.463	180.196	180.451	180.374	1.2

Average* : The average of 30 values in each position.

Temperature stability : One-half of the greatest maximum difference of measured temperature at any one sensor.

Temperature uniformity : The maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time or at as close an observation time as possible to determine the temperature pattern or homogeneity within the chamber under steady-state conditions.

Overall Variation : The Difference of the maximum and minimum measured temperatures throughout observation.

UUC* : Unit Under Calibration

Note : The reported uncertainty of measurement was included stability and excluded uniformity .

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor k, providing a level of confidence of approximately 95 %.

-o0o-

เอกสารไม่ควบคุม

Calibration Certificate

Certificate No.: 2502229-002-01
Client name: UNITED ANALYST AND ENGINEERING CONSULTANT CO.,LTD.
Address: 3 Soi Udomsuk 41, Sukhumvit Road,
Bangchack, Prakhonong, Bangkok 10260

Page 1 of 3

Equipment: CHAMBER (Incubator)

Manufacturer: MEMMERT

Model: IPP260

Serial No.: V616.0066

ID No.: UAE.MIC.032/2559

Order No.: 2502229

Operation No.: 2502229-002

Date of Receipt: 19 March 2025

Date of Calibration: 19 March 2025

Calibrated by Mr.Yothin Charoensuk **Approved by** [Signature]
Scientist Manager, Division of Calibration Laboratory
Date of Issue: 25 March 2025 **Responsible for the Technical Management Team**

The uncertainties are for a confidence probability of approximately 95 %.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the units of measurement realized at the corresponding national standards laboratory. This certificate may be reproduced other than in full except with the prior written approval of the National Food Institute.

FCS-009 Revision: 01 Date: 20-04-65

เอกสารไม่ควบคุม

Calibration Report

Certificate No.: 2502229-002-01
Equipment: CHAMBER (Incubator)
Model: IPP260 **Serial No.:** V616.0066
Resolution: 0.1 °C **ID No.:** UAE.MIC.032/2559
Manufacturer: MEMMERT
Date of Calibration: 19 March 2025

Page 2 of 3

Location: 302, UNITED ANALYST AND ENGINEERING CONSULTANT CO.,LTD.
Environment Condition: Ambient Temperature (21.7 ± 1) °C
Relative Humidity (59 ± 1) %
Line Voltage (223 ± 3) Volt

Condition of this results of Calibration:

- This instrument was calibrated by insert 9 standard thermometer into its chamber and calibration according to W-TE-014 Based on TLAS G-20-1/02-08 (E): Guidelines for Calibration and Checks of Temperature Controlled Enclosures.
- The temperature scale used was based on ITS - 90.
- All data show below were final values and the initial data may be obtained upon request.
- Reference Standard Instrument :

Instrument	Model	Serial No./ID No.	Certificate No.	Due Date	Through
Digital Thermometer with sensor	34972A	MYS7003188	TE 670486-01	8 June 2025	NATIONAL FOOD INSTITUTE
	RTD	CH201-209; RTD4201-209			

- This certificate is traceable to International System of Units (SI Units).
- This certificate was certified only for the instrument we calibrated.
- This result of calibration was found accurate as shown on date and place of calibration only.
- Condition of Calibrated item : Good

UUC Description :
Time of Record 1 Hour 9 Minute At 25.0 and 36.0 °C
Fresh air Damper - Open Position -
Close Fan -
Not Available

7. Result of Calibration : ☒ Without adjustment ☐ After adjustment

FCS-612 Revision: 01 Date: 20-04-65

เอกสารไม่ควบคุม

Calibration Report

Certificate No.: 2502229-002-01
Equipment: CHAMBER (Incubator)
Model: IPP260 **Serial No.:** V616.0066
Resolution: 0.1 °C **ID No.:** UAE.MIC.032/2559
Manufacturer: MEMMERT

Date of Calibration: 19 March 2025

Calibration point: 25.0 and 36.0 °C

Calibration Condition	Temperature (°C)	Relative Humidity (%)	Line Voltage (Volt)
MIN	21.3	58	220.0
MAX	22.0	60	225.0

Table 1 : Reporting of Temperature

Calibration point (°C)	#1	#2	#3	#4	#5	#6	#7	#8	#9	Uncertainty ± (°C)
25.0	25.19	25.16	25.22	25.17	24.85	24.91	24.78	24.85	24.97	0.29
36.0	34.57	34.74	35.13	35.29	36.32	36.16	36.20	36.34	35.73	0.63

Table 2 : Reporting of Characterization Result

UUC* Setting (°C)	MIN	MAX	Average	Stability ± (°C)	Uniformity (°C)	Overall Variation (°C)
25.0	24.9	25.0	25.0	0.088	0.25	0.61
36.0	35.9	36.0	36.0	0.44	1.2	2.3

Note: The quoted uncertainty include " Stability " and " Loading effect (20% of Temp Uniformity) "
UUC* = Unit Under Calibration

Stability = One-half of the greatest maximum difference of measured temperatures at any one sensors, for at least half an hour after reaching steady state.

Uniformity = The maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.

Overall Variation = The difference of the maximum and minimum measured temperatures throughout observation time.

The report uncertainty of measurement was based on standard uncertainty multiplied by coverage factor k = 2, providing a level of confidence of approximately 95 %.

FCS-612 Revision: 01 Date: 20-04-65

เอกสารไม่ควบคุม

FOSS Customer Service Report

FOSS South East Asia
3388 Sirinrat Building, 25th - 26th Floor, Unit No. 3388/90,
Rama IV Road, Klongton, Klongtoey, Bangkok, Thailand 10110

Report No.: 13319

Date: Jun 27, 2025

Customer: UAE

Job No.: 11695

Address: Bangkok

Instrument: K1200

Serial: 9190524

Start	Travel To Customer (Hrs)	Labour (Hrs)	Travel From Customer (Hrs)
09:00	1	10:00	3
Finish	10:00	13:00	-

Application	Special	Standard
Distributor	Courtesy Visit	Installation
Digital Service	PMA Onboarding	Quote
Internal	Warranty	Repair
Investigate	Sales Support	Remote
		Health Check Visit

PMA Type	Smartcare	Smartcare Pro	Fosscore
	Smartcare Advance	Fosscore Pro	N/A

Details of Work / Test
- PM -
+ Visual Check
- No leak
- Check change on heater at main switch
- Check heater at main switch before use
+ Check PM kit
+ Function Check
- Power on/off
- Alarm
- Stirrer
- Condenser
- Water pump

Instrument Ready for Use ☒ OK ☐ Not OK*

Part No.	Batch	Description	Qty
10069465	11-06-2024	FOSS PM kit K1200 heater Analyzer/2100	1
10004617	09-09-2024	Heating element 800W	1
15630111	11-10-2022	Unit for K1200 kit + 2 PM	1

I confirm this report is accurate and complete
Signed FOSS [Signature] **Signed Customer** [Signature]
Name [Name] **Name** [Name]
Email: [Email] **Customer Contact:** [Contact]

*Remark:

เอกสารไม่ควบคุม

Date: 24 February 2025

Customer: UAE

Job No.: 11735

Address: Bangkok

Instrument: KT8100

Serial: 91887052

Start	Travel To Customer (Hrs)	Labour (Hrs)	Travel From Customer (Hrs)
Finish	07:00 07:00	09:00-12:00 13:00-14:00	15:00 17:00

Application	Special	Standard
Distributor	Courtesy Visit	Installation
Digital Service	PMA Onboarding	Quote
Internal	Warranty	Repair
Investigate	Sales Support	Remote
		Health Check Visit

PMA Type	Smartcare	☒	Smartcare Pro	☒	Fosscore	☒
	Smartcare Advance	☒	Fosscore Pro	☒	N/A	☒

Details of Work / Test
PM 12:00 - 12:30
- test before 0m
- Cleaning KT800 36 mmo replace
- washing Alkali 0.1M
- test operation
- Distillation 50 - 80 ml
- Distillation 5 min 150 - 170 ml
- Alkali 50 - 80 ml
- All pass

Instrument Ready for Use	OK	X	Not OK*
--------------------------	----	---	---------

Part No.	Batch	Description	Qty
60031810	06-01-2024	Foss PM 12:00 12:30 3.6 mmo	1

Signed FOSS	Signed Customer
Name	Name

Email: Customer Contact:

*Remark:

เอกสารไม่ควบคุม

Please scan QR code



Certificate of Calibration

Cert.No.: 25CH354
Page.: 1 of 3

Equipment : pH Meter
Manufacturer : Horiba
Model : LAQUA-PH210
Serial No. : HA9M0047
ID No. : UAE.EFM.005/2563 (EFM.pH.05/63)
Condition As-Received: Used Item
Received Date : 18 March 2025
Calibration Date : 20 March 2025
Reference : 2503-0612WSC-2
Submitted by : United Analyst and Engineering Consultant Co., Ltd.
3 Soi Udomsuk 41, Sukhumvit Road, Bangchak,
Phrakhanong, Bangkok 10260

Ambient Temperature : (25 ± 2.5) °C
Relative Humidity : (50 ± 15) %
Calibration Procedure : In - house method :
- CP-CH5 by direct measurement with DC voltage
standard and direct measurement with
certified reference material (CRM)
- CP-CH8 by comparison with temperature standard

Calibrated by : Uthen Kankawi

Approved by : Approved Signatory

() Chakrit Waewwanjua
() Ponpan Paipim
(✓) Salthip Meangmai

Issue Date : 20 March 2025

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written
Approval of the head of Corporate Services 3 : Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม

Cert.No.: 25CH354
Page.: 2 of 3

Condition of this calibration result

1. Reference Standard Instrument

Instrument	Serial No.	ID No.	Cert. No.	Due Date
1) Document Process Calibrator	43160066	130RC092	24E1320	22 Apr 2025
2) Ref. Standard Thermometer	4982054	110RC044	24I757	14 Jul 2025

- This Certification is traceable to SI Through Technology Promotion Association (Thailand - Japan)

2. Certified Reference Materials

:The measurement results are traceable to SI through Hach Lenge GmbH Ltd.,
Deutsche Akkreditierungsstelle, Accredited No.D-RM-15184-01-00
: The measurement results are traceable to SI through CPA chem Ltd.,
ANSI-ASQ National Accreditation Board, Accredited No. AR-1835

Buffer Solution	Manufacturer	Lot No.	Exp. date
pH 4.007	CPA chem	1066665	18 Jan 2027
pH 6.999	Hach Lenge GmbH	C03220	29 Oct 2026
pH 10.010	CPA chem	1066669	18 Jan 2026

3. This certificate is valid only to the item calibrated on date and place of calibration.

Calibration Results

Function : mV Measurement

Performing standard curve by Document Process Calibrator at pH (4.7)(7.10)

Unit Under Calibration	Nominal Value	Standard Voltage Input	Actual Reading	Uncertainty of Measurement	Coverage factor
	pH	mV	mV	(±mV)	k
pH Meter	4.00	177.48	177.7	0.058	2.00
S/N.: HA9M0047	7.00	0.00	0.3	0.058	2.00
	7.00	0.00	0.3	0.058	2.00
	10.00	-177.48	-176.8	0.058	2.00

Cert.No.: 25CH354
Page.: 3 of 3

Calibration Results

Function : pH Measurement

Performing three buffers standard curve by using buffer nominal pH (4.7)(7.10)

Unit Under Calibration	Standard pH Buffer Solution	Actual pH Reading	Actual mV Reading (mV)	Uncertainty of pH Measurement (±)	Coverage factor k
pH Electrode	4.007	4.01	168.5	0.011	2.13
S/N.: -	6.999	7.00	-5.9	0.012	2.09
	6.999	7.00	-6.1	0.011	2.07
	10.010	10.02	-176.7	0.010	2.00

Function : Temperature Measurement

(*) Without adjustment

This equipment was connected with Temperature Probe;

- Model :
- Serial No. :
Dimension of probe
- Length : 103 mm.
- Diameter : 16 mm.
- Immersion Depth : 90 mm.

Calibration Point (°C)	Standard Temperature (°C)	UUC* Reading (°C)	Error (°C)	Uncertainty of measurement (± °C)	Coverage factor k
15.0	15.005	15.0	-0.005	0.13	2.00
30.0	30.007	30.0	-0.007	0.13	2.00
45.0	44.995	44.9	-0.095	0.13	2.00

Remark : - UUC* = Unit Under Calibration

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor k, providing a level of confidence of approximately 95 %.

-000-

เอกสารไม่ควบคุม

เอกสารไม่ควบคุม



Certificate of Calibration

Cert.No.: 25CH261
Page.: 1 of 3

Equipment : pH Meter
Manufacturer : Horiba
Model : LAQUA-PH210
Serial No. : HAOC0025
ID No. : UAE.EFM.117/2563(EFM.pH.07/63)
Condition As-Received: Used Item
Received Date : 25 February 2025
Calibration Date : 26 to 28 February 2025
Reference : 2502-0783WSC-1
Submitted by : United Analyst and Engineering Consultant Co.,Ltd.
3 Soi Udomsuk 41, Sukhumvit Road,
Bangchak, Phrakhanong, Bangkok 10260

Ambient Temperature : (25 ± 2.5) °C
Relative Humidity : (50 ± 15) %
Calibration Procedure : In - house method :
- CP-CH5 by direct measurement with DC voltage
standard and direct measurement with
certified reference material (CRM)
- CP-CH8 by comparison with temperature standard

Calibrated by : Warakorn Lemgatrakul

Approved by : _____
Approved Signatory

() Chakrit Waewwanjua
() Ponpan Paipim
(✓) Sathip Meangmai

Issue Date : 28 February 2025

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written
Approval of the head of Corporate Services 3: Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม



Cert.No.: 25CH261
Page.: 2 of 3

Condition of this calibration result

1. Reference Standard Instrument

Instrument	Serial No.	ID No.	Cert. No.	Due Date
1)Document Process Calibrator	54030049	130RC116	24E2759	25 Aug 2025
2)Ref. Standard Thermometer	4982054	110RC044	24I757	14 July 2025

- This Certification is traceable to SI Through Technology Promotion Association (Thailand - Japan)

2. Certified Reference Materials :The measurement results are traceable to SI through Hach Lenge GmbH Ltd.,
Deutsche Akkreditierungsstelle, Accredited No.D-RM-15184-01-00
: The measurement results are traceable to SI through CPA chem Ltd.,
ANSI-ASQ National Accreditation Board, Accredited No. AR-1835

Buffer Solution	Manufacturer	Lot No.	Exp. date
pH 4.007	CPA chem	1066665	18 Jan 2027
pH 6.999	Hach Lenge GmbH	C03220	29 Oct 2026
pH 10.010	CPA chem	1066669	18 Jan 2026

3. This certificate is valid only to the item calibrated on date and place of calibration.

Calibration Results

Function : mV Measurement

Performing standard curve by Document Process Calibrator at pH (4.7)(7,10)

Unit Under Calibration	Nominal Value	Standard Voltage Input	Actual Reading		Uncertainty of Measurement (±mV)	Coverage factor k
	pH	mV	mV	pH		
pH Meter S/N.: HAOC0025	4.00	177.48	177.5	4.01	0.058	2.00
	7.00	0.00	0.0	7.02	0.058	2.00
	7.00	0.00	0.0	7.02	0.058	2.00
	10.00	-177.48	-177.5	10.01	0.058	2.00

เอกสารไม่ควบคุม



Cert.No.: 25CH261
Page.: 3 of 3

Calibration Results

Function : pH Measurement

Performing three buffers standard curve by using buffer nominal pH (4.7)(7,10)

Unit Under Calibration	Standard pH Buffer Solution	Actual pH Reading	Actual mV Reading (mV)	Uncertainty of pH Measurement (±)	Coverage factor k
pH Electrode S/N.: Q9AG0214	4.007	4.01	178.4	0.0071	2.00
	6.999	7.00	4.1	0.0092	2.00
	6.999	7.00	3.0	0.0095	2.00
	10.010	10.01	-169.8	0.0092	2.00

Function : Temperature Measurement

(*) Without adjustment

This equipment was connected with Temperature Probe;

- Model : 9652-10D
- Serial No. : Q9AG0214

Dimension of probe

- Length : 110 mm.
- Diameter : 16 mm.
- Immersion Depth : 80 mm.

Calibration Point (°C)	Standard Temperature (°C)	UUC* Reading (°C)	Error (°C)	Uncertainty of measurement (± °C)	Coverage factor k
15.0	15.002	15.0	-0.002	0.13	2.00
30.0	30.003	30.0	-0.003	0.13	2.00
45.0	45.002	44.9	-0.102	0.13	2.00

Remark : UUC* = Unit Under Calibration

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor k, providing a level of confidence of approximately 95 %.

-000-

เอกสารไม่ควบคุม



Certificate of Calibration

Cert.No.: 24CH1379
Page: 1 of 3

Equipment : pH Meter
Manufacturer : EcoSence
Model : pH100A
Serial No. : JC03354
ID No. : UAE.EFM.063/2562(ENV.pH03/62)
Condition As-Received: Used Item
Received Date : 05 November 2024
Calibration Date : 06 November 2024
Reference : 2411-0122WSC-1
Submitted by : United Analyst and Engineering Consultant Co.,Ltd.
3 Soi Udomsuk 41, Sukhumvit Road,
Bangchak, Phrakhanong, Bangkok 10260
Ambient Temperature : (25 ± 2.5) °C
Relative Humidity : (50 ± 15) %
Calibration Procedure : In - house method :
- CP-CH5 by direct measurement with DC voltage
standard and direct measurement with
certified reference material (CRM)
- CP-CH8 by comparison with temperature standard
Calibrated by : Warakorn Lemgagrakul
Approved by : _____
Approved Signatory
() Unnopphol Harachai
(✓) Ponpan Paipim
() Salthip Meangmai
Issue Date : 8 November 2024

The Uncertainties are for a confidence probability of approximately 95%

This certificate may not be reproduced other than in full, except with the prior written
Approval of the head of Corporate Services 3 : Equipment Calibration and Testing Services.

เอกสารไม่ควบคุม



Cert.No.: 24CH1379
Page: 2 of 3

Condition of this calibration result

1. Reference Standard Instrument

Instrument	Serial No.	ID No.	Cert. No.	Due Date
1)Document Process Calibrator	54030049	130RC116	24E2759	25 Aug 2025
2)Ref. Standard Thermometer	4982054	110RC044	24I757	14 July 2025

- This Certification is traceable to SI Through Technology Promotion Association (Thailand - Japan)

2. Certified Reference Materials

:The measurement results are traceable to SI through Hach Lenge GmbH Ltd.,
Deutsche Akkreditierungsstelle, Accredited No.D-RM-15184-01-00

Buffer Solution	Manufacturer	Lot No.	Exp. date
pH 4.008	CPA chem	1034203	27 Sep 2026
pH 6.999	Hach Lenge GmbH	C03145	28 Feb 2026
pH 10.010	CPA chem	1034205	27 Sep 2025

3. This certificate is valid only to the item calibrated on date and place of calibration.

Calibration Results

Function : mV Measurement

Performing standard curve by Document Process Calibrator at pH (4,7)(7,10)

Unit Under Calibration	Nominal Value	Standard Voltage Input	Actual Reading		Uncertainty of Measurement (±mV)	Coverage factor k
	pH	mV	mV	pH		
pH Meter S/N.: JC03354	4.00	177.48	177	4.01	0.58	2.00
	7.00	0.00	0	7.00	0.58	2.00
	7.00	0.00	0	7.00	0.58	2.00
	10.00	-177.48	-178	10.01	0.58	2.00

เอกสารไม่ควบคุม



Cert.No.: 24CH1379
Page: 3 of 3

Calibration Results

Function : pH Measurement

Performing three buffers standard curve by using buffer nominal pH (4,7)(7,10)

Unit Under Calibration	Standard pH Buffer Solution	Actual pH Reading	Actual mV Reading (mV)	Uncertainty of pH Measurement (±)	Coverage factor k
pH Electrode S/N.:240710SIA605377	4.008	4.01	173	0.0079	2.00
	6.999	7.00	-2	0.0092	2.00
	6.999	7.00	-2	0.0095	2.00
	10.010	10.01	-178	0.0092	2.00

Function : Temperature Measurement

(*) Without adjustment

This equipment was connected with Temperature Probe;

- Model : _____
- Serial No. : 240710SIA605377
Dimension of probe
- Length : 110 mm.
- Diameter : 12 mm.
- Immersion Depth : 100 mm.

Calibration Point (°C)	Standard Temperature (°C)	UUC* Reading (°C)	Error (°C)	Uncertainty of measurement (± °C)	Coverage factor k
15.0	15.003	14.9	-0.103	0.13	2.00
30.0	30.001	29.9	-0.101	0.13	2.00
45.0	45.003	44.8	-0.203	0.13	2.00

Remark : * UUC* = Unit Under Calibration

The reported uncertainty of measurement was based on a standard uncertainty multiplied by a coverage factor k, providing a level of confidence of approximately 95 %.

-o-o-

เอกสารไม่ควบคุม

ภาคผนวก ข

หนังสืออนุญาตขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

ที่ อก ๐๓๑๐(๑)/ ๕๓ ๐ ๒



กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๐๔ ตุลาคม ๒๕๖๔

เรื่อง ยกเลิกบุคลากรของห้องปฏิบัติการวิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และขอคืนสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๒๕ กันยายน ๒๕๖๓

ตามคำขอที่อ้างถึง บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด
ห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ๖-๑๔๕ สถานที่ตั้งเลขที่ ๓ ซอยอุดมสุข ๔๑ ถนนสุขุมวิท
แขวงบางจาก เขตพระโขนง กรุงเทพมหานคร ขอยกเลิกบุคลากร ความละเอียดแจ้งแล้ว นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้ออกเลิกเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน
จำนวน ๓ ราย ได้แก่

- | | |
|------------------------|----------------------------|
| ๑) นางสาวอารียา ทวามย์ | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๐๖๓ |
| ๒) นางสาวศรียพร ทองขาว | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๓๓ |
| ๓) นางสาวปวีณา แคนชนม | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๖๓ |

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นางสาวปัทมวรรณ คุณประเสริฐ)
ผู้อำนวยการทั่วไปและโฆษกสื่อสัมพันธ์โรงงาน
ปฏิบัติการตามหนังสือกรมโรงงานอุตสาหกรรม



ดำเนินการถูกต้อง

กองวิจัยและเฝ้าระวังมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๕๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๕๓๐ ๖๓๑๒ ต่อ ๒๑๑๓

ไปรษณีย์อิเล็กทรอนิกส์ sarabang@diw.mail.go.th



"อุตสาหกรรมก้าวไกล ประเทไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว"



ที่ อก ๐๓๑๐(๑)/ ๖๕ ๓



กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๒๕ สิงหาคม ๒๕๖๔

เรื่อง ยกเลิกบุคลากรของห้องปฏิบัติการวิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และขอคืนสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๗ สิงหาคม ๒๕๖๔

ตามคำขอที่อ้างถึง บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด
ห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ๖-๑๔๕ สถานที่ตั้งเลขที่ ๓ ซอยอุดมสุข ๔๑ ถนนสุขุมวิท
แขวงบางจาก เขตพระโขนง กรุงเทพมหานคร ขอยกเลิกบุคลากร ความละเอียดแจ้งแล้ว นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้ออกเลิกเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน
จำนวน ๕ ราย ได้แก่

- | | |
|---------------------------|----------------------------|
| ๑) นายคณิศร พงษ์ธิราบุพร | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๐๓ |
| ๒) นายธีรวัฒน์ ธรรมสุวรรณ | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๓๓ |
| ๓) นายอาทิตย์ ตากา | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๖๓ |
| ๔) นางสาวณชนก ปูนคำ | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๓๓ |
| ๕) นายวิระพงษ์ แสงทำนง | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๔๓ |

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายคิระ จันทร์เลิศ)
ผู้อำนวยการฝ่ายวิจัย ทรัพยากรธรรมชาติ
ผู้อำนวยการสำนักงานสิ่งแวดล้อมและเฝ้าระวังมลพิษโรงงาน
ปฏิบัติการตามหนังสือกรมโรงงานอุตสาหกรรม

กองวิจัยและเฝ้าระวังมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๕๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๕๓๐ ๖๓๑๒ ต่อ ๒๑๑๓

ไปรษณีย์อิเล็กทรอนิกส์ sarabang@diw.mail.go.th



"อุตสาหกรรมก้าวไกล ประเทไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว"



ดำเนินการถูกต้อง

ที่ อก ๐๓๑๐(๑)/ ๕๖ ๔ ๑



กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๐๗ กรกฎาคม ๒๕๖๔

เรื่อง เปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และขอคืนสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๙ พฤษภาคม ๒๕๖๔

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์
บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด จำนวน ๒ แผ่น

ตามหนังสือที่อ้างถึง บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด
ห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ๖-๑๔๕ สถานที่ตั้งเลขที่ ๓ ซอยอุดมสุข ๔๑ ถนนสุขุมวิท
แขวงบางจาก เขตพระโขนง กรุงเทพมหานคร ขอเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์
ความละเอียดแจ้งแล้ว นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว มีความเห็นดังนี้

๑. ให้ออกเลิกเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๓ ราย

- | | |
|-----------------------------|----------------------------|
| ๑) นายสุสันต์ พันสิงห์ | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๐๐๓ |
| ๒) นางสาวสุกิตรา เลื่อนเงิน | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๔๓ |
| ๓) นางสาวชนาภา ภิมาคม | ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๑๖๓ |

๒. ให้เพิ่มผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๓ ราย

นายสุสันต์ พันสิงห์ ทะเบียนเลขที่ ๖-๑๔๕-๖-๐๐๐๓

๓. ให้เพิ่มข้อข่ายสารมลพิษที่วิเคราะห์ในน้ำใต้ดิน อากาศเสีย และดิน ตามที่ส่งมาด้วย

อนึ่ง หนังสือฉบับนี้จะหมดอายุพร้อมหนังสือฉบับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

ในวันที่ ๒ กุมภาพันธ์ ๒๕๖๕

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายประจักษ์ สว่างพาศ)
ผู้อำนวยการฝ่ายวิจัย ทรัพยากรธรรมชาติ
ผู้อำนวยการสำนักงานสิ่งแวดล้อมและเฝ้าระวังมลพิษโรงงาน
ปฏิบัติการตามหนังสือกรมโรงงานอุตสาหกรรม

กองวิจัยและเฝ้าระวังมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๕๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๕๓๐ ๖๓๑๒ ต่อ ๒๑๑๓

ไปรษณีย์อิเล็กทรอนิกส์ sarabang@diw.mail.go.th



"อุตสาหกรรมก้าวไกล ประเทไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว"



ดำเนินการถูกต้อง

เอกสารแนบท้ายหนังสือเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

บริษัท ยูโนเด็ค แอนนาลิสต์ แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด เลขทะเบียน ๖-๑๔๕

ที่ อก ๐๓๑๐(๑)/ ๕๖ ๔ ๑ ลงวันที่ ๐๗ กรกฎาคม ๒๕๖๔

ขอข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๑๑ รายการ

น้ำใต้ดิน จำนวน ๔ รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Aluminum	Digestion, Inductively Coupled Plasma Method ⁽¹⁾
2	Copper	1) Digestion, Flame Atomic Absorption Spectrometric Method ⁽¹⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽¹⁾
3	Iron	1) Digestion, Flame Atomic Absorption Spectrometric Method ⁽¹⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽¹⁾
4	Molybdenum	Digestion, Inductively Coupled Plasma Method ⁽¹⁾

อากาศเสีย (ปล่องระบาย) จำนวน ๑ รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Oxides of Nitrogen	Absorption Sampling, Ion Chromatographic Method ⁽²⁾

ดิน จำนวน ๖ รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Aluminum	Digestion, Inductively Coupled Plasma Method ^(3,4)
2	Copper	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(3,4) 2) Digestion, Inductively Coupled Plasma Method ^(3,4)
3	Iron	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(3,4) 2) Digestion, Inductively Coupled Plasma Method ^(3,4)
4	Molybdenum	Digestion, Inductively Coupled Plasma Method ^(3,4)
5	pH	Electrometric Method ⁽⁵⁾
6	TPH (C ₅ -C ₆)	Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(6,7)

เอกสารอ้างอิง

1. APHA, AWWA, WEF. Standard Methods for the Examination of Water and Wastewater. 24th ed. Washington, DC: APHA, 2023.
2. United States Environmental Protection Agency. Standards of Performance for New Stationary Sources. 40 CFR 60. Appendix A, 2023.

3. United States...



ดำเนินการถูกต้อง

3. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Acid Digestion of Sediments, Sludges, and Soils. SW-846 Method 3050B, 1996.
4. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Volatile Organic Compounds in Various Sample Matrices Using Equilibrium Headspace Analysis. SW-846 Method 5021A, 2014.
5. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Inductively Coupled Plasma-Optical Emission Spectrometry. SW-846 Method 6010D, 2018.
6. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Flame Atomic Absorption Spectrophotometry. SW-846 Method 7000B, 2007.
7. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Volatile Organic Compounds by Gas Chromatography/Mass Spectrometry. SW-846 Method 8260D, 2018.
8. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Soil and Waste pH. SW-846 Method 9045D, 2004.



ดำเนินการถูกต้อง

กลุ่มมาตรฐานวิธีการวิเคราะห์และประเมินผลเชิงปฏิบัติการ กองโขนและสิ่งแวดล้อมจังหวัดกรม กรมโรงงานอุตสาหกรรม โทร. ๐ ๒๒๐๖ ๒๒๐๖-๕



ที่ อก ๐๓๓๐(๑)/ ๑ ๕ ๕ ๑

กรมโรงงานอุตสาหกรรม
ถนนพรหมรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๒๕ กุมภาพันธ์ ๒๕๖๕

เรื่อง ยกเลิกผลการตรวจห้องปฏิบัติการวิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท ยูนิค แอนาไลติก แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และขอคืนสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน ลงวันที่ ๑๕ กุมภาพันธ์ ๒๕๖๔

ตามคำขอที่อ้างถึง บริษัท ยูนิค แอนาไลติก แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด ห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ๖-๑๕๕ สถานที่ตั้งเลขที่ ๓ ซอยอุดมสุข ๕๓ ถนนสุขุมวิท แขวงบางจาก เขตพระโขนง กรุงเทพมหานคร ขอยกเลิกบุคลากร ความละเอียดแจ้งแล้ว นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้ยกเลิกเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๓ ราย ได้แก่

- | | |
|---------------------------|----------------------------|
| ๑) นายอภิสิทธิ์ ศรีคมทวี | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๕ |
| ๒) นางสาววันนิลา พรหมกวดำ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๖ |
| ๓) นายภูวศล เปรมภา | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๗ |

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายธรรมยศ อัคราภรณ์ ณ อุบลราชธานี)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมโรงงานอุตสาหกรรม

กองวิจัยและเฝ้าระวังมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและประเมินผลเชิงปฏิบัติการ

โทร. ๐ ๒๒๐๖ ๒๒๐๖ ต่อ ๒๒๐๖-๕
โทรสาร ๐ ๒๒๐๖ ๒๒๐๖ ต่อ ๒๒๐๖-๕
ไปรษณีย์อิเล็กทรอนิกส์ sarabak@dfw.mail.go.th



ดำเนินการถูกต้อง



"อุตสาหกรรมก้าวไกล ประเทไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว"



ที่ อก ๐๓๓๐(๑)/ ๑ ๐ ๘ ๘

กรมโรงงานอุตสาหกรรม
ถนนพรหมรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๑๗ กุมภาพันธ์ ๒๕๖๕

เรื่อง ต่ออายุหนังสือขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

เรียน กรรมการผู้จัดการ บริษัท ยูนิค แอนาไลติก แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และขอคืนสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน ลงวันที่ ๓ ธันวาคม ๒๕๖๔

- สิ่งที่ส่งมาด้วย ๑. รายชื่อผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๔๐ ราย
๒. รายชื่อเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๑๕๔ ราย
๓. ขอนำสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม

ตามคำขอที่อ้างถึง บริษัท ยูนิค แอนาไลติก แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด ขอต่ออายุหนังสือขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ๖-๑๕๕ สถานที่ตั้งเลขที่ ๓ ซอยอุดมสุข ๕๓ ถนนสุขุมวิท แขวงบางจาก เขตพระโขนง กรุงเทพมหานคร ต่อกรมโรงงานอุตสาหกรรม นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้บริษัท ยูนิค แอนาไลติก แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด ต่ออายุหนังสือขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน โดยมีเงื่อนไขดังนี้

- ก. ผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๔๐ ราย ตามสิ่งที่ส่งมาด้วย ๑
ข. เจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๑๕๔ ราย ตามสิ่งที่ส่งมาด้วย ๒
ค. ขอนำสารมลพิษที่ได้รับขึ้นทะเบียนไว้วิเคราะห์ในน้ำเสีย น้ำดิบดิน อากาศเสีย

สิ่งปลูกสร้างหรือวัตถุที่ไม่ใช่แล้ว และดิน ตามสิ่งที่ส่งมาด้วย ๓

หนังสือฉบับนี้จะหมดอายุในวันที่ ๒ กุมภาพันธ์ ๒๕๖๖ หากประสงค์จะต่ออายุหนังสือขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน ให้ยื่นคำขอต่ออายุหรือเอกสารประกอบคำขอต่อกรมโรงงานอุตสาหกรรมภายใน ๖๐ วัน ก่อนวันสิ้นสุดของหนังสือขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายธรรมยศ อัคราภรณ์ ณ อุบลราชธานี)

รองอธิบดี ปฏิบัติราชการแทน

อธิบดีกรมโรงงานอุตสาหกรรม



ดำเนินการถูกต้อง

กองวิจัยและเฝ้าระวังมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและประเมินผลเชิงปฏิบัติการ

โทร. ๐ ๒๒๐๖ ๒๒๐๖ ต่อ ๒๒๐๖-๕

โทรสาร ๐ ๒๒๐๖ ๒๒๐๖ ต่อ ๒๒๐๖-๕

ไปรษณีย์อิเล็กทรอนิกส์ sarabak@dfw.mail.go.th



"อุตสาหกรรมก้าวไกล ประเทไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว"



สิ่งที่ส่งมาด้วย ๑

เอกสารแนบท้ายหนังสือต่ออายุขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน
บริษัท ยูนิค แอนาไลติก แอนด์ เอ็นจิเนียริ่ง คอนซัลแตนท์ จำกัด เลขทะเบียน ๖-๑๕๕
ที่ อก ๐๓๓๐(๑)/ ๑ ๐ ๘ ๘ ลงวันที่ ๑๗ กุมภาพันธ์ ๒๕๖๕

ก. ผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๔๐ ราย

- | | |
|------------------------------------|----------------------------|
| ๑) นางสาวสุพรรณ ทวีศรีกุล | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๑ |
| ๒) นายณกร ธิมาภัส | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๒ |
| ๓) นางสาวนันทิศา บุญไชย | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๓ |
| ๔) นายปิยะพัชร สุทธิมงคล | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๔ |
| ๕) นางสาวณัฐวรรณ วิริยะชัย | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๕ |
| ๖) นายอนันต์ วัชรบุรุษชัย | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๖ |
| ๗) นางสาวอริวรรณ บุญลา | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๗ |
| ๘) นายสุวิทย์ จอดนอก | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๘ |
| ๙) นางสาวโศภิตา สมภรณ์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๐๙ |
| ๑๐) นางสาวบุษกร เลิศกาญจนา | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๐ |
| ๑๑) นางสาววิไลลักษณ์ ศรีสุข | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๑ |
| ๑๒) นายศิลา บรรจงเจริญ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๒ |
| ๑๓) นายปฏิกรณ์ วัฒนภา | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๓ |
| ๑๔) นายธีรวัฒน์ เขมิง | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๔ |
| ๑๕) นางสาวศิริพร ศรีประดิษฐ์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๕ |
| ๑๖) นางสาวสวดี วัชร | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๖ |
| ๑๗) นางสาวพรพรรณ อวาทย์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๗ |
| ๑๘) นายภูษิต พานิชเลิศคำ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๘ |
| ๑๙) นายอริวัฒน์ แสงสวัสดิ์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๑๙ |
| ๒๐) นายอภิรักษ์ ปะคะมินทร์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๐ |
| ๒๑) นางสาววิภากรีน ศรีสุกใสศิริโชค | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๑ |
| ๒๒) นางสาวจตุรจินทร์ ทำเลียด | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๒ |
| ๒๓) นางสาวสุวรรณา คงทอง | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๓ |
| ๒๔) นางสาววรรณา พัดทองชื่น | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๔ |
| ๒๕) นายวิรัช โมกแก้ว | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๕ |
| ๒๖) นายวิรัชพงศ์ เทพรัตน์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๖ |
| ๒๗) นายอนุศาสน์ สยดี | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๗ |
| ๒๘) นายทวีทรัพย์ เขียวศิริกุล | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๘ |
| ๒๙) นายสุวิทย์ อรุณจันทร์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๒๙ |
| ๓๐) นางสาวทัศนีย์ อ่อนคำ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๓๐ |
| ๓๑) นางพิมพ์พร กองสิน | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๓๑ |
| ๓๒) นายสุกฤษณ์ คุณอนากุล | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๓๒ |
| ๓๓) นางสาวศิริภาพร เหมอินทร์ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๓๓ |
| ๓๔) นางสาวนิตติ จำปาศ | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๓๔ |
| ๓๕) นางสาวพรนภา ธีระจินดา | ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๐๓๕ |

๓๖) นายนาเคนทร์...

๑๑๓) นางสาวปิตีญา

๑๑๑) นางสาวปัทมา พุฒิตอง	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๐
๑๑๔) นางสาวอติพร โพธิ์พันธ์	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๑
๑๑๕) นายอาทิตย์ ศาภา	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๒
๑๑๖) นางสาวบุษยาพร บุญถนอมศรี	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๓
๑๑๗) นางสาวพัชรพรรณ จันทิบุตร	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๔
๑๑๘) นางสาวนฤกร ใต้นากย	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๕
๑๑๙) นางสาวปวีณา แสนชนบ	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๖
๑๒๐) นางสาวนันทิดา พรมกวดำ	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๗
๑๒๑) นางสาวนงนุช ปุ่นคำ	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๘
๑๒๒) นางสาวปาริฉัตร ทองใจ	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๖๙
๑๒๓) นายธีรวัฒน์ จันละคร	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๐
๑๒๔) นางสาวกัญญา สิงห์แก้ว	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๑
๑๒๕) นางสาวอรวิมา มณีเมียร	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๒
๑๒๖) นายฐานันท์ อนุรา	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๓
๑๒๗) นางสาวชนัดดา วิชาคม	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๔
๑๒๘) นายธนสินทร์ ยาทะล้อม	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๕
๑๒๙) นายวีระพงษ์ แสงท้าว	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๖
๑๓๐) นางสาวปิยะณัฐยา สันภาพษ์	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๗
๑๓๑) นางสาวนภัสกร ศรีสถาน	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๘
๑๓๒) นางสาวจุฑิวัฑน์ โสแทน	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๗๙
๑๓๓) นายธีรวัฒน์ พรหมลา	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๐
๑๓๔) นายอภิสิทธิ์ บัณฑิตถาวร	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๑
๑๓๕) นายเนกัทธ เสงี่ยมบุตร	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๒
๑๓๖) นางสาวจิตาภา ฤาชา	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๓
๑๓๗) นางสาวสุเมธพรทิพย์ สังข์ทอง	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๔
๑๓๘) นางสาวจริยา บำบุญ	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๕
๑๓๙) นายภูวดล เปี่ยมา	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๖
๑๔๐) ว่าที่ร้อยตรีณัฐพร ประทุมเขตต์	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๗
๑๔๑) นายอนุสร พงษ์ไธสง	ทะเบียนเลขที่ ๖-๑๕๕-๖-๐๑๘๘

เอกสารแนบท้ายหนังสือตอบรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน
บริษัท ยูเน็ค แอนาไลติก แอนด์ เอ็นจิเนียริง คอนซัลแตนท์ จำกัด เลขทะเบียน ๖-๑๕๕-
ที่ ๐๑๓๐(๑) ๑๐๘๘ ลงวันที่ ๐๗ กุมภาพันธ์ ๒๕๖๕

ขอข่าวดำเนินการที่ขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๑๕๗ รายการ

ลำดับ	สารเคมี	วิธีวิเคราะห์
1	Aldrin	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
2	Arsenic	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
3	Barium	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
4	α-BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
5	β-BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
6	δ-BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
7	γ-BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
8	Biochemical Oxygen Demand	1) 5-Day BOD Test, Azide Modification Method ⁽⁴⁾ 2) 5-Day BOD Test, Membrane Electrode Method ⁽⁴⁾
9	Cadmium	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
10	Chemical Oxygen Demand	1) Closed Reflux, Titrimetric Method ⁽⁴⁾ 2) Closed Reflux, Colorimetric Method ⁽⁴⁾ 3) Open Reflux, Titrimetric Method ⁽⁴⁾
11	Chlordane	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
12	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
13	Color	ADMI Weighted-Ordinate Spectrophotometric Method ⁽⁴⁾
14	Copper	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
15	Cyanide	1) Distillation, Colorimetric Method ⁽⁴⁾ 2) Total Cyanide after Distillation, by Flow Injection Analysis Method ⁽⁴⁾
16	o,p'-DDT	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
17	4,4'-DDD	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
18	4,4'-DDE	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
19	4,4'-DDT	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
20	Dieldrin	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
21	Endosulfan I	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
22	Endosulfan II	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
23	Endosulfan sulfate	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
24	Endrin	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾

25 Endrin aldehyde...

ลำดับ	สารเคมี	วิธีวิเคราะห์
25	Endrin aldehyde	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
26	Formaldehyde	Distillation, Colorimetric Method ⁽⁴⁾
27	Free Chlorine	1) Iodometric Method ⁽⁴⁾ 2) DPD Ferrous Titrimetric Method ⁽⁴⁾
28	Heptachlor	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
29	Heptachlor Epoxide	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
30	Hexavalent Chromium	Colorimetric Method ⁽⁴⁾
31	Lead	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
32	Manganese	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
33	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ⁽⁴⁾
34	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
35	Nickel	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
36	Oil & Grease	1) Liquid-Liquid, Partition-Gravimetric Method ⁽⁴⁾ 2) Soxhlet Extraction Method ⁽⁴⁾
37	pH	Electrometric Method ⁽⁴⁾
38	Phenols	1) Distillation, Chloroform Extraction Method ⁽⁴⁾ 2) Distillation, Direct Photometric Method ⁽⁴⁾
39	Selenium	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
40	Sulfide	1) Iodometric Method ⁽⁴⁾ 2) Methylene Blue Method ⁽⁴⁾
41	Temperature	Laboratory and Field Methods ⁽⁴⁾
42	Total Dissolved Solids	Dried at 180 °C ⁽⁴⁾
43	Total Kjeldahl Nitrogen	Semi-Micro-Kjeldahl Method ⁽⁴⁾
44	Total Suspended Solids	Dried from 103 to 105 °C ⁽⁴⁾
45	Trivalent Chromium	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
46	Zinc	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾

ดำเนินการโดย

น้ำได้ขึ้น จำนวน 126 รายการ

ลำดับ	สารเคมี	วิธีวิเคราะห์
1	Acenaphthene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
2	Acetone	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
3	Aldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
4	Anthracene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
5	Antimony	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
6	Arsenic	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
7	Atrazine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
8	Barium	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
9	Benz(a)anthracene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
10	Benzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
11	Benzo(b)fluoranthene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
12	Benzo(k)fluoranthene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
13	Benzoic acid	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

14 Benzo(a)pyrene...

ลำดับ	สารเคมี	วิธีวิเคราะห์
14	Benzo(a)pyrene	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
15	Benzo(g,h,i)perylene	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
16	Beryllium	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
17	Bis(2-chloroethyl)ether	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
18	Bis(2-ethylhexyl)phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
19	Bromodichloromethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
20	Bromoform	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
21	Butanol	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
22	Butyl benzyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
23	Cadmium	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Electrothermal Atomic Absorption Spectrometric Method ⁽⁴⁾ 3) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
24	Carbazole	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
25	Carbon disulfide	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
26	Carbon tetrachloride	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
27	Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
28	p-Chloroaniline	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

29 Chlorobenzene...

ลำดับ	สารเคมี	วิธีวิเคราะห์
29	Chlorobenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
30	Chlorodibromomethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
31	Chloroform	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
32	2-Chlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
33	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
34	Chromium (III)	1) Digestion, Direct Air-Acetylene Flame Method; Colorimetric Method; Calculation ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method; Colorimetric Method; Calculation ⁽⁴⁾
35	Chromium (VI)	Colorimetric Method ⁽⁴⁾
36	Chrysene	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
37	Cyanide	Distillation, Colorimetric Method ⁽⁴⁾
38	2,4-D	Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾
39	DDD	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
40	DDE	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
41	DDT	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
42	Dibenz(a,h)anthracene	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

43 Di-n-butyl phthalate...

ลำดับ	สารเคมี	วิธีวิเคราะห์
43	Di-n-butyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
44	1,2-Dichlorobenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
45	1,3-Dichlorobenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
46	1,4-Dichlorobenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
47	3,3'-Dichlorobenzidine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
48	1,1-Dichloroethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
49	1,2-Dichloroethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
50	1,1-Dichloroethylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
51	cis-1,2-Dichloroethylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
52	trans-1,2-Dichloroethylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
53	2,4-Dichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
54	1,2-Dichloropropane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
55	1,3-Dichloropropane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
56	1,3-Dichloropropene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
57	Dieldrin	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
58	Diethyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
59	2,4-Dimethylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
60	2,4-Dinitrophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

61 2,4-Dinitrotoluene...

ลำดับ	สารเคมี	วิธีวิเคราะห์
61	2,4-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
62	2,6-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
63	Di-n-Octyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
64	Endosulfan	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
65	Endrin	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
66	Ethylbenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
67	Fluoranthene	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
68	Fluorene	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
69	Heptachlor	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
70	Heptachlor epoxide	1) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
71	Hexachlorobenzene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
72	Hexachloro-1,3-butadiene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
73	n-Hexane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

74 α-HCH...

ลำดับ	สารเคมี	วิธีวิเคราะห์
74	α -HCH	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
75	β -HCH	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
76	γ -HCH	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
77	Hexachlorocyclopentadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
78	Hexachloroethane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
79	Indeno(1,2,3-cd)pyrene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
80	Isophorone	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
81	Lead	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Electrothermal Atomic Absorption Spectrometric Method ⁽⁴⁾ 3) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
82	Manganese	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
83	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ⁽⁴⁾
84	Methanol	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
85	Methoxychlor	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
86	Methyl bromide	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

87 Methylene chloride...

ลำดับ	สารเคมี	วิธีวิเคราะห์
87	Methylene chloride	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
88	2-Methylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
89	2-Methylnaphthalene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
90	Methyl tert-butyl ether	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
91	Naphthalene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
92	Nickel	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
93	Nitrobenzene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
94	N-Nitrosodiphenylamine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
95	N-Nitrosodi-n-propylamine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
96	Polychlorinated Biphenyls - PCB 1016 - PCB 1221 - PCB 1232 - PCB 1242 - PCB 1248 - PCB 1254 - PCB 1260	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
97	Pentachlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
98	pH	Electrometric Method ⁽⁴⁾
99	Phenanthrene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

100 Phenol...

ลำดับ	สารเคมี	วิธีวิเคราะห์
100	Phenol	1) Distillation, Chloroform Extraction Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
101	Pyrene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
102	Selenium	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
103	Silver	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
104	Styrene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
105	1,1,2,2-Tetrachloroethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
106	Tetrachloroethylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
107	Toluene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
108	Toxaphene	1) Liquid-Liquid Extraction, Gas Chromatographic Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
109	TPH (C ₅ - C ₆)	1) Purge and Trap, Gas Chromatographic Method ^(1,2,21) 2) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(1,2,21)
110	TPH (C ₈ - C ₁₄)	Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(1,2,21)
111	TPH (C ₁₆ - C ₂₈)	Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(1,2,21)
112	1,2,4-Trichlorobenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
113	1,1,1-Trichloroethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
114	1,1,2-Trichloroethane	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
115	Trichloroethylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

116 2,4,5-Trichlorophenol...

ลำดับ	สารเคมี	วิธีวิเคราะห์
116	2,4,5-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
117	2,4,6-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
118	1,3,5-Trimethylbenzene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
119	Vanadium	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
120	Vinyl acetate	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
121	Vinyl chloride	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
122	m-Xylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
123	o-Xylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
124	p-Xylene	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
125	Xylene (Total)	Purge and Trap Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
126	Zinc	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾

ภาคที่สี่ (ต่อเนื่องจาก) จำนวน 25 รายการ

ลำดับ	สารเคมี	วิธีวิเคราะห์
1	Antimony	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
2	Arsenic	1) Isokinetic Sampling, Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽¹⁾ 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
3	Cadmium	1) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ⁽³⁾ 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
4	Carbon Monoxide	Instrumental Analyzer Method ⁽³⁾
5	Chlorine	Isokinetic Sampling, Ion Chromatographic Method ⁽³⁾
6	Chromium	1) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ⁽³⁾

Chromium (ต่อ)...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
6	Chromium (๖)	2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
7	Cobalt	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
8	Copper	1) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ⁽³⁾ 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
9	Cresol	Absorption Sampling, Gas Chromatographic Method ⁽³⁾
10	Dioxins/Furans	Isokinetic Sampling ⁽³⁾
11	Hydrogen Chloride	Isokinetic Sampling, Ion Chromatographic Method ⁽³⁾
12	Hydrogen Fluoride	Isokinetic Sampling, Ion Chromatographic Method ⁽³⁾
13	Hydrogen Sulfide	Absorption Sampling, Iodometric Method ⁽³⁾
14	Lead	1) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ⁽³⁾ 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
15	Manganese	1) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ⁽³⁾ 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
16	Mercury	Isokinetic Sampling, Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ⁽³⁾
17	Nickel	1) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ⁽³⁾ 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
18	Opacity	Ringelmann's Method ⁽¹⁾
19	Oxides of Nitrogen	1) Absorption Sampling, Phenoldisulfonic acid Method ⁽³⁾ 2) Instrumental Analyzer Method ⁽³⁾
20	Selenium	1) Isokinetic Sampling, Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^(3,14) 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
21	Sulfur Dioxide	1) Absorption Sampling, Barium-Thorin Titrimetric Method ⁽³⁾ 2) Instrumental Analyzer Method ⁽³⁾
22	Sulfuric Acid	Isokinetic Sampling, Barium-Thorin Titrimetric Method ⁽³⁾

23 Total Suspended Particulate...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
24	Total Suspended Particulate	Isokinetic Sampling, Gravimetric Method ⁽³⁾
25	Vanadium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ⁽³⁾
25	Xylene	1) Bag Sampling, Gas Chromatographic Method ⁽³⁾ 2) Adsorption Sampling, Gas Chromatographic Method ⁽³⁾

สิ่งปฏิกูลหรือวัสดุที่ไม่ได้เกิดจาก จำนวน 35 รายการ

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
2	Antimony	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 2) Digestion, Inductively Coupled Plasma Method ^(3,14)
3	Arsenic	1) Waste Extraction, Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^(3,14) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 3) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^(3,14) 4) Digestion, Inductively Coupled Plasma Method ^(3,14)
4	Barium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 2) Digestion, Inductively Coupled Plasma Method ^(3,14)
5	Beryllium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 2) Digestion, Inductively Coupled Plasma Method ^(3,14)
6	Cadmium	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method ^(3,14) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 3) Digestion, Flame Atomic Absorption Spectrometric Method ^(3,14) 4) Digestion, Inductively Coupled Plasma Method ^(3,14)
7	Chlordane	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)

8 Chromium...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
8	Chromium	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method ^(3,13) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 3) Digestion, Flame Atomic Absorption Spectrometric Method ^(3,13) 4) Digestion, Inductively Coupled Plasma Method ^(3,14)
9	Chromium (III)	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method; Waste Extraction, Colorimetric Method; Calculation ^(3,13,17) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method; Waste Extraction, Colorimetric Method; Calculation ^(3,13,17) 3) Digestion, Flame Atomic Absorption Spectrometric Method; Alkaline Digestion, Colorimetric Method; Calculation ^(3,13,17) 4) Digestion, Inductively Coupled Plasma Method; Alkaline Digestion, Colorimetric Method; Calculation ^(3,13,17)
10	Chromium (VI)	1) Waste Extraction, Colorimetric Method ^(3,17) 2) Alkaline Digestion, Colorimetric Method ^(3,17)
11	Cobalt	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 2) Digestion, Inductively Coupled Plasma Method ^(3,14)
12	Copper	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method ^(3,13) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 3) Digestion, Flame Atomic Absorption Spectrometric Method ^(3,13) 4) Digestion, Inductively Coupled Plasma Method ^(3,14)
13	2,4-D	1) Waste Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
14	DDD	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)

15 DDE...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
15	DOE	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
16	DDT	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
17	Dieldrin	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
18	Endrin	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
19	Heptachlor	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
20	Lead	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method ^(3,13) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 3) Digestion, Flame Atomic Absorption Spectrometric Method ^(3,13) 4) Digestion, Inductively Coupled Plasma Method ^(3,14)
21	Lindane	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^(3,23) 2) Ultrasonic Extraction, Gas Chromatographic Method ^(3,23)
22	Mercury	1) Waste Extraction, Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^(3,13) 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(3,14) 3) Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^(3,13) 4) Digestion, Inductively Coupled Plasma Method ^(3,14)

Mercury (IIa)...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
22	Mercury (คอป)	5) Thermal Decomposition Amalgamation and Atomic Absorption Spectrometric Method ⁽²⁾⁽³⁾
23	Methoxychlor	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾
24	Molybdenum	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽³⁾⁽⁴⁾⁽⁵⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
25	Nickel	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method ⁽³⁾⁽⁴⁾⁽⁵⁾ 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽³⁾⁽⁴⁾⁽⁵⁾ 3) Digestion, Flame Atomic Absorption Spectrometric Method ⁽⁷⁾⁽¹⁵⁾ 4) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
26	Polychlorinated Biphenyls - Aroclor 1016 - Aroclor 1221 - Aroclor 1232 - Aroclor 1242 - Aroclor 1248 - Aroclor 1254 - Aroclor 1260 - 2-Chlorobiphenyl - 2,3-Dichlorobiphenyl - 2,2',5'-Trichlorobiphenyl - 2,4',5'-Trichlorobiphenyl - 2,2',3,5'-Tetrachlorobiphenyl - 2,2',5,5'-Tetrachlorobiphenyl - 2,3',4,4'-Tetrachlorobiphenyl - 2,2',3,4,5'-Pentachlorobiphenyl - 2,2',4,5,5'-Pentachlorobiphenyl - 2,3,3',4,6'-Pentachlorobiphenyl	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽⁴⁾

Polychlorinated Biphenyls(คอป)...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
	Polychlorinated Biphenyls(คอป) - 2,2',3,4,4',5'-Hexachlorobiphenyl - 2,2',3,4,5,5'-Hexachlorobiphenyl - 2,2',3,5,5',6'-Hexachlorobiphenyl - 2,2',4,4',5,5'-Hexachlorobiphenyl - 2,2',3,3',4,4',5'-Heptachlorobiphenyl - 2,2',3,4,4',5,5'-Heptachlorobiphenyl - 2,2',3,4',5,5',6'-Heptachlorobiphenyl - 2,2',3,3',4,4',5,5',6'-Nonachlorobiphenyl	
27	Pentachlorophenol	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
28	pH	Electrometric Method ⁽³⁾⁽³⁾⁽⁵⁾
29	Selenium	1) Waste Extraction, Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽³⁾⁽⁴⁾⁽¹⁾ 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽³⁾⁽⁴⁾⁽¹⁾ 3) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁷⁾⁽²¹⁾ 4) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
30	Silver	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
31	Thallium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾

32 Toxaphene...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
32	Toxaphene	1) Waste Extraction, Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾
33	Trichloroethylene	1) Waste Extraction, Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽¹²⁾⁽²⁷⁾ 2) Waste Extraction, Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽¹²⁾⁽²⁷⁾ 3) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁷⁾ 4) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁷⁾
34	Vanadium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽³⁾⁽⁴⁾⁽⁵⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
35	Zinc	1) Waste Extraction, Digestion, Flame Atomic Absorption Spectrometric Method ⁽³⁾⁽⁴⁾⁽⁵⁾ 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ⁽³⁾⁽⁴⁾⁽⁵⁾ 3) Digestion, Flame Atomic Absorption Spectrometric Method ⁽⁷⁾⁽¹⁵⁾ 4) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾

ดิน จำนวน 125 รายการ

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
1	Acenaphthene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽⁵⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
2	Acetone	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁷⁾
3	Aldrin	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
4	Anthracene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾

Anthracene (คอป)...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
4	Anthracene (คอป)	2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
5	Antimony	Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
6	Arsenic	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁷⁾⁽¹⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
7	Atrazine	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
8	Barium	Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾
9	Benz(a)anthracene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
10	Benzene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁷⁾ 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ⁽¹¹⁾⁽²⁷⁾
11	Benzol(b)fluoranthene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
12	Benzol(k)fluoranthene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
13	Benzoic acid	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
14	Benzo(a)pyrene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
15	Benzo(g,h,i)perylene	1) Ultrasonic Extraction, Gas Chromatographic Method ⁽³⁾⁽²⁾⁽³⁾ 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽³⁾⁽²⁾⁽⁸⁾
16	Beryllium	Digestion, Inductively Coupled Plasma Method ⁽⁷⁾⁽¹⁴⁾

17 Bis(2-chloroethyl)ether...

ลำดับ	สารเคมี	วิธีวิเคราะห์
17	Bis(2-chloroethyl)ether	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
18	Bis(2-ethylhexyl)phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
19	Bromodichloromethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
20	Bromoform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
21	Butanol	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
22	Butyl benzyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
23	Cadmium	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(7,13) 2) Digestion, Inductively Coupled Plasma Method ^(7,14)
24	Carbazole	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
25	Carbon disulfide	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
26	Carbon tetrachloride	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
27	Chlordane	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
28	p-Chloroaniline	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
29	Chlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
30	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
31	Chloroform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
32	2-Chlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)

33 Chromium...

ลำดับ	สารเคมี	วิธีวิเคราะห์
33	Chromium	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(7,13) 2) Digestion, Inductively Coupled Plasma Method ^(7,14)
34	Chromium (III)	1) Digestion, Flame Atomic Absorption Spectrometric Method; Alkaline Digestion, Colorimetric Method; Calculation ^(7,8,15,17) 2) Digestion, Inductively Coupled Plasma Method; Alkaline Digestion, Colorimetric Method; Calculation ^(7,8,15,17)
35	Chromium (VI)	Alkaline Digestion, Colorimetric Method ^(8,17)
36	Chrysene	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
37	Cyanide	Extraction, Distillation, Colorimetric Method ^(9,30)
38	2,4-D	Ultrasonic Extraction, Gas Chromatographic Method ⁽²⁶⁾
39	DDD	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
40	DDE	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
41	DDT	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
42	Dibenz(a,h)anthracene	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
43	Di-n-butyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
44	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)

45 1,3-Dichlorobenzene...

ลำดับ	สารเคมี	วิธีวิเคราะห์
45	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
46	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
47	3,3'-Dichlorobenzidine	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
48	1,1-Dichloroethane	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
49	1,2-Dichloroethane	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
50	1,1-Dichloroethylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
51	cis-1,2-Dichloroethylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
52	trans-1,2-Dichloroethylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
53	2,4-Dichlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
54	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
55	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
56	1,3-Dichloropropene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
57	Dieldrin	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)

58 Diethyl phthalate...

ลำดับ	สารเคมี	วิธีวิเคราะห์
58	Diethyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
59	2,4-Dimethylphenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
60	2,4-Dinitrophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
61	2,4-Dinitrotoluene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
62	2,6-Dinitrotoluene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
63	Di-n-Octyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
64	Endosulfan	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
65	Endrin	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
66	Ethylbenzene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(11,27)
67	Fluoranthene	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
68	Fluorene	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
69	Heptachlor	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,26)
70	Heptachlor epoxide	1) Ultrasonic Extraction, Gas Chromatographic Method ^(10,26)

Heptachlor epoxide (ค่า)

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
70	Heptachlor epoxide (คเค)	2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
71	Hexachlorobenzene	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
72	Hexachloro-1,3-butadiene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
73	n-Hexane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
74	α-HCH	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
75	β-HCH	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
76	γ-HCH	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
77	Hexachlorocyclopentadiene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
78	Hexachloroethane	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
79	Indeno(1,2,3-cd)pyrene	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
80	Isophorone	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
81	Lead	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(7,15) 2) Digestion, Inductively Coupled Plasma Method ^(7,14)
82	Manganese	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(7,15) 2) Digestion, Inductively Coupled Plasma Method ^(7,14)

83 Mercury...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
83	Mercury	1) Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ⁽⁹⁾ 2) Thermal Decomposition Amalgamation and Atomic Absorption Spectrometric Method ⁽²⁸⁾
84	Methanol	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
85	Methoxychlor	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
86	Methyl bromide	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
87	Methylene chloride	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
88	2-Methylphenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
89	2-Methylnaphthalene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
90	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
91	Naphthalene	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
92	Nickel	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(7,15) 2) Digestion, Inductively Coupled Plasma Method ^(7,14)
93	Nitrobenzene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
94	N-Nitrosodiphenylamine	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
95	N-Nitrosodi-n-propylamine	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
96	Polychlorinated Biphenyls - Aroclor 1016	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)

Polychlorinated Biphenyls(คเค)...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
96	Polychlorinated Biphenyls(คเค) - Aroclor 1221 - Aroclor 1232 - Aroclor 1242 - Aroclor 1248 - Aroclor 1254 - Aroclor 1260 Polychlorinated Biphenyls - 2-Chlorobiphenyl - 2,3-Dichlorobiphenyl - 2,2',5'-Trichlorobiphenyl - 2,4',5'-Trichlorobiphenyl - 2,2',3,5'-Tetrachlorobiphenyl - 2,2',5,5'-Tetrachlorobiphenyl - 2,3',4,4'-Tetrachlorobiphenyl - 2,2',3,4,5'-Pentachlorobiphenyl - 2,2',4,5,5'-Pentachlorobiphenyl - 2,3,3',4',6'-Pentachlorobiphenyl - 2,2',3,4,4',5'-Hexachlorobiphenyl - 2,2',3,4,5,5'-Hexachlorobiphenyl - 2,2',3,5,5',6'-Hexachlorobiphenyl - 2,2',4,4',5,5'-Hexachlorobiphenyl - 2,2',3,3',4,4',5'-Heptachlorobiphenyl - 2,2',3,4,4',5,5'-Heptachlorobiphenyl - 2,2',3,4,4',5,5',6'-Heptachlorobiphenyl - 2,2',3,3',4,4',5,5',6'-Nonachlorobiphenyl	2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) Ultrasonic Extraction, Gas Chromatographic Method ^(10,24)

97 Pentachlorophenol...

ลำดับ	สารมลพิษ	วิธีวิเคราะห์
97	Pentachlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
98	Phenanthrene	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
99	Phenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
100	Pyrene	1) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28) 2) Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(10,28)
101	Selenium	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^(7,21) 2) Digestion, Inductively Coupled Plasma Method ^(7,14)
102	Silver	Digestion, Inductively Coupled Plasma Method ^(7,14)
103	Styrene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
104	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
105	Tetrachloroethylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
106	Toluene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
107	Toxaphene	Ultrasonic Extraction, Gas Chromatographic Method ^(10,23)
108	TPH (C ₅ -C ₆)	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
109	TPH (C ₇ -C ₁₀)	Ultrasonic Extraction, Gas Chromatographic Method ^(10,22)
110	TPH (C ₁₁ -C ₁₅)	Ultrasonic Extraction, Gas Chromatographic Method ^(10,22)

111 1,2,4-Trichlorobenzene...

ลำดับ	สารเคมี	วิธีวิเคราะห์
111	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
112	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
113	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
114	Trichloroethylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
115	2,4,5-Trichlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(16,28)
116	2,4,6-Trichlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(16,28)
117	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
118	Vanadium	Digestion, Inductively Coupled Plasma Method ^(13,28)
119	Vinyl acetate	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
120	Vinyl chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
121	m-Xylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
122	o-Xylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
123	p-Xylene	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)
124	Xylene (Total)	1) Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(13,27) 2) Equilibrium Headspace, Gas Chromatographic/Mass Spectrometric Method ^(13,27)

125 Zinc...

ลำดับ	สารเคมี	วิธีวิเคราะห์
125	Zinc	1) Digestion, Flame Atomic Absorption Spectrometric Method ^(7,19) 2) Digestion, Inductively Coupled Plasma Method ^(7,24)

เอกสารอ้างอิง

- กระทรวงอุตสาหกรรม. ประกาศกระทรวงอุตสาหกรรม, พ.ศ. 2549. เรื่อง กำหนดค่าปริมาณเคมีภัณฑ์ที่เจือปนในอากาศที่ระบายออกจากปล่องหรือท่อไอระเหยที่เชื่อมกับระบบเชื้อเพลิง. ราชกิจจานุเบกษา. 4 ธันวาคม 2549. เล่มที่ 123 ตอนพิเศษ 1254.
- สมาคมวิศวกรรมสิ่งแวดล้อมแห่งประเทศไทย. คู่มือวิเคราะห์น้ำเสีย. พิมพ์ครั้งที่ 4. กรุงเทพฯ: เจเนอรัลการพิมพ์, 2547.
- กระทรวงอุตสาหกรรม. ประกาศกระทรวงอุตสาหกรรม, พ.ศ. 2566. เรื่อง การจัดการสิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว. ราชกิจจานุเบกษา. 31 พฤษภาคม 2566. เล่มที่ 140 ตอนพิเศษ 126 ง.
- APHA, AWWA, WEF. Standard Methods for the Examination of Water and Wastewater. 24th ed. Washington, DC: APHA, 2023.
- United States Environmental Protection Agency. Standards of Performance for New Stationary Sources. 40 CFR 60. Appendix A, 2020.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. SW-846, 2014.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Acid Digestion of Sediments, Sludges, and Soils. SW-846 Method 3050B, 1996.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Alkaline Digestion for Hexavalent Chromium. SW-846 Method 3060A, 1996.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Separatory Funnel Liquid-Liquid Extraction. SW-846 Method 3510C, 1996.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Ultrasonic Extraction. SW-846 Method 3550C, 2007.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Volatile Organic Compounds in Various Sample Matrices Using Equilibrium Headspace Analysis. SW-846 Method 5030B, 2003.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Purge and Trap for Aqueous Samples. SW-846 Method 5030C, 2003.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Closed System Purge and Trap and Extraction for Volatile Organics in Soil and Waste Sample. SW-846 Method 5035A, 2000.
- United States...

- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Inductively Coupled Plasma-Optical Emission Spectrometry. SW-846 Method 6010D, 2014.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Flame Atomic Absorption Spectrophotometry. SW-846 Method 7000B, 2007.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Arsenic (Atomic Absorption, Gaseous Hydride). SW-846 Method 7061A, 1992.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Chromium, Hexavalent (Colorimetric). SW-846 Method 7196A, 1992.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Mercury in Liquid Waste (Manual Cold Vapor Technique). SW-846 Method 7470A, 1994.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Mercury in Solid or Semisolid Waste (Manual Cold-Vapor Technique). SW-846 Method 7471B, 1998.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Mercury in Solids and Solutions by Thermal Decomposition, Amalgamation, and Atomic Absorption Spectrophotometry. SW-846 Method 7473, 2007.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Selenium (Atomic Absorption, Borohydride Reduction). SW-846 Method 7742, 1994.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Nonhalogenated Organics Using GC/RID. SW-846 Method 8015D, 2003.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Organochlorine Pesticides by Gas Chromatography. SW-846 Method 8081B, 2007.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Polychlorinated Biphenyls (PCBs) by Gas Chromatography. SW-846 Method 8082A, 2007.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Organochlorine Pesticides by Gas Chromatography. SW-846 Method 8081B, 2007.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Chlorinated Herbicides by GC Using Methylation or Pentafluorobenzoylation Derivatization. SW-846 Method 8151A, 1996.
- United States...

- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Volatile Organic Compounds by Gas Chromatography/ Mass Spectrometry. SW-846 Method 8260D, 2018.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Semivolatile Organic Compounds by Gas Chromatography/Mass Spectrometry. SW-846 Method 8270E, 2018.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Cyanide Extraction Procedure for Solids and Oils. SW-846 Method 9013A, 2014.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Cyanide in Waters and Extracts using Titrimetric and Manual Spectrophotometric Procedures. SW-846 Method 9014, 2014.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. pH Electrometric Measurement. SW-846 Method 9040C, 2004.
- United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Soil and Waste pH. SW-846 Method 9045D, 2004.

