

รายงานผลการตรวจวัดคุณภาพอากาศในบรรยากาศโดยทั่วไป
โครงการ โรงแรม ไม้ขาว ดรีม (เปลี่ยนการใช้อาคาร)
กันยายน 2568

บริษัท เช้าเทิร์นไทยคอนซัลติ้ง จำกัด

Environment Research &
Technology Co., Ltd.



หนังสือรับรองการจัดทำรายงาน

10 ตุลาคม 2568

หนังสือฉบับนี้ให้ไว้รับรองว่า บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด เป็นผู้จัดทำ รายงานผลการตรวจวัดคุณภาพอากาศในบรรยากาศโดยทั่วไป โครงการ โรงแรม ไม้ขาว ดรีม (เปลี่ยนการใช้อาคาร) ดำเนินการตรวจวัดระหว่างวันที่ 16-17 กันยายน 2568 โดยมีเจ้าหน้าที่ผู้เข้าร่วมตรวจวัด และจัดทำรายงาน ดังนี้

ผู้เก็บตัวอย่าง

นายสิทธิพร วงษ์คำ


นายกฤษดา ราชพันธ์

ผู้วิเคราะห์

ห้องปฏิบัติการบริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

ผู้จัดทำรายงาน

นางสาวนนท์ทิยา การสมพรต



envi research
ENVIRONMENT RESEARCH & TECHNOLOGY CO., LTD.

(นางสาวปณิชา พรหมชัย)

ผู้จัดการฝ่ายจัดทำรายงาน

และติดตามตรวจสอบคุณภาพสิ่งแวดล้อม

รายงานผลการตรวจวัดคุณภาพอากาศในบรรยากาศโดยทั่วไป
โครงการ โรงแรม ไม้ขาว ตรัง (เปลี่ยนการใช้อาคาร)
บริษัท เช่าเทิร์นไทยคอนสตรัคติ้ง จำกัด
กันยายน 2568

บริษัท เช่าเทิร์นไทยคอนสตรัคติ้ง จำกัด ได้มอบหมายให้บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด เป็นผู้ดำเนินการเก็บตัวอย่างและตรวจวิเคราะห์คุณภาพอากาศในบรรยากาศโดยทั่วไป โครงการ โรงแรม ไม้ขาว ตรัง (เปลี่ยนการใช้อาคาร) ตั้งอยู่ที่เลขที่ 151/34 หมู่ที่ 4 ซอยไม้ขาว 8 ตำบลไม้ขาว อำเภอถลาง จังหวัดภูเก็ต เพื่อเป็นข้อมูลในการประเมินผลกระทบสิ่งแวดล้อม ตลอดจนหาแนวทางการปฏิบัติเพื่อลดผลกระทบที่อาจเกิดขึ้นต่อสิ่งแวดล้อมและสาธารณสุขต่อไป ดำเนินการตรวจวัดระหว่างวันที่ 16-17 กันยายน 2568 มีรายละเอียดดังนี้

1. วัตถุประสงค์

1.1 เพื่อให้ได้ข้อมูลคุณภาพอากาศในบรรยากาศโดยทั่วไป เพื่อเปรียบเทียบกับมาตรฐานตามที่ราชการกำหนด และมาตรฐานตามหลักวิชาการอื่นๆ ที่เกี่ยวข้อง

1.2 เพื่อจัดทำรายงานผลการตรวจวัดคุณภาพอากาศในบรรยากาศโดยทั่วไป นำเสนอต่อเจ้าหน้าที่ผู้รับผิดชอบของโครงการ เพื่อใช้ในการศึกษาตามวัตถุประสงค์ของโครงการต่อไป

2. ขอบเขตการดำเนินการ

ดำเนินการตรวจวิเคราะห์คุณภาพอากาศในบรรยากาศโดยทั่วไป โดยมีตำแหน่งตรวจวัดตลอดจนดัชนีที่ทำการตรวจวิเคราะห์ ดังแสดงในตารางที่ 1

ตารางที่ 1

ขอบเขตการดำเนินงานตรวจวัดคุณภาพสิ่งแวดล้อม

รายการตรวจวัด	ดัชนีที่วิเคราะห์	วันที่ตรวจวัด
คุณภาพอากาศในบรรยากาศโดยทั่วไป จำนวน 1 สถานี (บริเวณพื้นที่โครงการ)	Total Suspended Particulate, Particulate Size Less Than 10 Micron	16-17 ก.ย. 68

3. วิธีการเก็บตัวอย่างและวิเคราะห์คุณภาพสิ่งแวดล้อม

การตรวจวัดและวิเคราะห์ได้ดำเนินการตามวิธีที่กำหนดไว้ในมาตรฐานตามที่ราชการกำหนดและมาตรฐานสากลที่ได้รับการยอมรับกันโดยทั่วไป สรุปวิธีเก็บตัวอย่างและวิเคราะห์ได้ดังตารางที่ 2

ตารางที่ 2
วิธีการเก็บตัวอย่างและวิเคราะห์คุณภาพสิ่งแวดล้อม

ดัชนีที่ตรวจวัด	วิธีการตรวจวัด / วิเคราะห์	รายละเอียดการตรวจวัด / วิเคราะห์
Ambient Air Quality - Total Suspended Particulate	High-Volume Air Sampler; Gravimetric Method	เก็บตัวอย่างอากาศโดยใช้วิธี High-Volume Air Sampler ดูดอากาศผ่านกระดาษกรองชนิดใยแก้ว (Glass Fiber Filter) ขนาด 8x10 นิ้ว อัตราการไหลประมาณ 40-60 ลูกบาศก์ฟุตต่อนาที เป็นเวลา 24 ชั่วโมง และนำไปวิเคราะห์ในห้องปฏิบัติการด้วยวิธี Gravimetric มีหน่วยเป็น mg/m ³
- Particulate Size Less Than 10 Micron	PM10 Size Selective, High-Volume Air Sampler; Gravimetric Method	เก็บตัวอย่างอากาศโดยใช้วิธี PM10 Size Selective, Hi-Volume ดูดอากาศผ่านกระดาษกรองชนิดใยหิน (Quartz Fiber Filter) ขนาด 8x10 นิ้ว อัตราการไหลประมาณ 40 ลูกบาศก์ฟุตต่อนาที เป็นเวลา 24 ชั่วโมง และนำไปวิเคราะห์ในห้องปฏิบัติการด้วยวิธี Gravimetric มีหน่วยเป็น mg/m ³

4. ผลและสรุปผลการตรวจวัด

ผลการตรวจวัดฝุ่นละอองรวมหรือฝุ่นละอองขนาดเล็กไม่เกิน 100 ไมครอน (Total Suspended Particulate) และ ฝุ่นละอองขนาดเล็กไม่เกิน 10 ไมครอน (Particulate Size Less Than 10 Micron) บริเวณพื้นที่โครงการ ตรวจวัดระหว่างวันที่ 16-17 กันยายน 2568 เปรียบเทียบผลการตรวจวัดกับมาตรฐาน พบว่า บริเวณที่ทำการตรวจวัดมีค่าอยู่ในเกณฑ์ที่มาตรฐานกำหนด แสดงดังตารางที่ 3 สรุปได้ดังนี้

ตารางที่ 3

ผลการตรวจวิเคราะห์คุณภาพอากาศในบรรยากาศโดยทั่วไป
บริเวณพื้นที่โครงการ
(ตรวจวัดระหว่างวันที่ 16-17 กันยายน 2568)

วันที่ตรวจวัด	ผลการตรวจวัด	
	ฝุ่นละอองขนาดเล็กไม่เกิน 100 ไมครอน (TSP) (mg/m ³)	ฝุ่นละอองขนาดเล็กไม่เกิน 10 ไมครอน (PM10) (mg/m ³)
16-17 ก.ย. 68	0.051	0.027
มาตรฐาน ^{1/}	0.330	0.120

หมายเหตุ : ^{1/} มาตรฐานตามประกาศคณะกรรมการสิ่งแวดล้อมแห่งชาติ ฉบับที่ 10 พ.ศ.2538 และฉบับที่ 24 พ.ศ.2547 เรื่อง กำหนดมาตรฐานคุณภาพอากาศในบรรยากาศโดยทั่วไป

5. ข้อเสนอแนะ

จากผลการตรวจวัดปริมาณฝุ่นละอองรวมหรือฝุ่นละอองขนาดเล็กไม่เกิน 100 ไมครอน (TSP) และฝุ่นละอองขนาดเล็กไม่เกิน 10 ไมครอน (Particulate Size Less Than 10 Micron) พบว่า บริเวณที่ทำการตรวจวัดมีค่าอยู่ในเกณฑ์ที่มาตรฐานกำหนด อย่างไรก็ตาม ผลการตรวจวัดในแต่ละช่วงเวลาอาจมีค่าแตกต่างกันมีสาเหตุมาจากปัจจัยหลายประการ เช่น สภาพภูมิอากาศที่แตกต่างกัน ความเร็วและทิศทางลม รวมถึงกิจกรรมต่างๆ อย่างไรก็ตาม ทางโครงการควรมีมาตรการป้องกันและลดผลกระทบต่อคุณภาพอากาศ โดยป้องกันมิให้กิจกรรมดังกล่าวส่งผลกระทบต่อชุมชนโดยรอบ และจัดให้มีการติดตามตรวจวัดคุณภาพอากาศอย่างสม่ำเสมอ

.....

รูปถ่ายแสดงจุดเก็บตัวอย่างและการเก็บตัวอย่าง



รูปภาพแสดงการตรวจวัดคุณภาพอากาศในบรรยากาศโดยทั่วไป
โครงการ โรงแรม ไม้ขาว ดรีม (เปลี่ยนการใช้อาคาร)
บริเวณพื้นที่โครงการ
ตรวจวัดระหว่างวันที่ 16-17 กันยายน 2568



ANALYSIS REPORT

Customer Name : Southern Thai Consulting Co., Ltd.
Address : 59/45 Moo 5, Srisoontorn, Thalang, Phuket 83110
Project Name : โครงการ โรงแรม ไม้ขาว ดรีม (เปลี่ยนการใช้อาคาร)
Project Location : เลขที่ 151/34 หมู่ที่ 4 ซอยไม้ขาว 8 ตำบลไม้ขาว อำเภอถลาง จังหวัดภูเก็ต
Sampling Source : Ambient Air Quality
Sampling Point : พื้นที่โครงการ
GPS. Coordinate : UTM (WGS84) 47P 0423545 E, 0899301 N
Sampling Date : September 16-17, 2025
Sampling Time : 10:40
Sampling Method : U.S. EPA 40 CFR Part 50
Sampling By : Mr.Sittiporn Wongkham
Analyzed By : Environment Research & Technology Co., Ltd.

Quotation No. : ER2025-00109
Analysis No. : 2025-AE894
Received Date : September 18, 2025
Analytical Date : September 18-29, 2025
Report No. : 2025-RAAX120
Report Date : September 29, 2025

Parameter	Unit	Method of Analysis	Result	Standard ^{1'}
Total Suspended Particulate (TSP) 24 Hours Average	mg/m ³	High-Volume, Gravimetric	0.051	0.330
Particulate Size Less Than 10 Micron (PM10) 24 Hours Average	mg/m ³	PM10 Size Selective, High-Volume, Gravimetric	0.027	0.120

Remark : ^{1'} Notification of National Environmental Board, No.10, B.E.2538 (1995), published in the Royal Government Gazette No.112 Part 42D dated May 25, B.E.2538 (1995) and Notification No.24, B.E.2547 (2004), published in the Royal Government Gazette No.121 Special Part 104D dated September 22, B.E.2547 (2004), under the Enhancement and Conservation of National Environmental Quality Act B.E.2535 (1992).

Nat. S
(Ms.Natnicha Sermmatiwong)
Laboratory Reviewer



(Ms.Ramita Taengthai)
Laboratory Supervisor

ที่ อก ๐๓๑๐(๑)/ ๖๔๗๖



กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๐๓ กรกฎาคม ๒๕๖๗

เรื่อง ต่ออายุหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

เรียน กรรมการผู้จัดการ บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๒๔ เมษายน ๒๕๖๗

- สิ่งที่ส่งมาด้วย ๑. รายชื่อผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๑ แผ่น
๒. รายชื่อเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๒ แผ่น
๓. ขอบข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๑๔ แผ่น

ตามคำขอที่อ้างถึง บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด ขอต่ออายุหนังสือ
รับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ว-๐๙๙ สถานที่ตั้งเลขที่ ๒๕/๑๑๔ หมู่ที่ ๖
ซอยชินเขต ๑ ถนนงามวงศ์วาน แขวงทุ่งสองห้อง เขตหลักสี่ กรุงเทพมหานคร ต่อกรมโรงงานอุตสาหกรรม นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด
ต่ออายุหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน โดยมีองค์ประกอบดังนี้

- ก. ผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๒๐ ราย ตามสิ่งที่ส่งมาด้วย ๑
ข. เจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน ๖๑ ราย ตามสิ่งที่ส่งมาด้วย ๒
ค. ขอบข่ายชนิดสารมลพิษที่ได้รับขึ้นทะเบียนให้วิเคราะห์ในน้ำ/น้ำเสีย น้ำใต้ดิน อากาศเสีย
สิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว และดิน ตามสิ่งที่ส่งมาด้วย ๓

หนังสือฉบับนี้จะหมดอายุในวันที่ ๑๘ พฤษภาคม ๒๕๗๑ หากประสงค์จะต่ออายุหนังสือรับขึ้น
ทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน ให้ยื่นคำขอต่ออายุพร้อมเอกสารประกอบคำขอต่อกรมโรงงานอุตสาหกรรม
ภายใน ๖๐ วัน ก่อนวันสิ้นอายุของหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายพรยศ กลั่นกรอง)

รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมโรงงานอุตสาหกรรม

กองวิจัยและเตือนภัยมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๙๙

ไปรษณีย์อิเล็กทรอนิกส์ saraban@diw.mail.go.th



“อุตสาหกรรมก้าวไกล ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว”



เอกสารแนบท้ายหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

เลขทะเบียน ว-๐๙๙

ที่ อก ๐๓๑๐(๑)/ ๖๔๗ ๖

ลงวันที่ ๐๓ กรกฎาคม ๒๕๖๗

ก. ผู้ควบคุมห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๒๐ ราย

- | | |
|---------------------------------|----------------------------|
| ๑) นางสาวสุดารัตน์ เขจรรักษ์ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๑ |
| ๒) นางสาวพิชิตา เขียววรภัย | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๒ |
| ๓) นางสาววลิตา โพธิ์เจริญ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๓ |
| ๔) ว่าที่ร้อยตรีวันชนะ สีหามาตร | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๔ |
| ๕) นางสาวรัชนีวรรณ ภูประเสริฐ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๕ |
| ๖) นางสาวปณิชา พรหมชัย | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๖ |
| ๗) นางณัฐรดา เลี้ยงรักษา | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๗ |
| ๘) นายมงคล บุรภักดิ์ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๘ |
| ๙) นางสาวธนิดา บุญรุ่งเรือง | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๐๙ |
| ๑๐) นางสาวรมิตา แต่งไทย | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๐ |
| ๑๑) นางสาวไรวินทร์ โพธิ์สิทธิ์ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๑ |
| ๑๒) นางสาวณัฐนิชา เสริมมตังค์ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๒ |
| ๑๓) นายนพสิทธิ์ ทวีพรประดิษฐ์ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๓ |
| ๑๔) นางสาวธิดารัตน์ ปุกคะ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๔ |
| ๑๕) นายอภิชาติ พูลพล | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๕ |
| ๑๖) นายนันทน์ ศิริชาติ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๖ |
| ๑๗) นายสุทธิชาญ สังข์ทอง | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๗ |
| ๑๘) นางสาวยุวดี ณ ระนอง | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๘ |
| ๑๙) นางสาวสุภาวรรณ สุวรรณภา | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๑๙ |
| ๒๐) นางสาวนภาพรสิริ หมั่นวงษ์ | ทะเบียนเลขที่ ว-๐๙๙-ค-๐๐๒๐ |

วิภา

เอกสารแนบท้ายหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

เลขทะเบียน ว-๐๙๙

ที่ ออก ๐๓๑๐(๑)/ ๖๔๗๖

ลงวันที่ ๐๓ กรกฎาคม ๒๕๖๗

ข. เจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๖๑ ราย

๑) นางสาวณัฐธิดา ขาวสุทธิ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๐๒
๒) นางสาวสุธิดา ทองประภา	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๐๕
๓) นายจิรยุทธ์ สามารถ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๐๗
๔) นายอัษฎา ไชยวงศ์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๐๘
๕) นางสาวณัฐริสา บุญหนัก	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๐๙
๖) นายนฤตม์ โชติกาญจน์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๒
๗) นางสาวพรทิพย์ อัมภรัตน์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๓
๘) นายอัศววัฒน์ คชบก	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๕
๙) นางสาวธัญพิชชา สุตเขียน	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๖
๑๐) นางสาวพาขวัญ นนพละ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๗
๑๑) นางสาววิมลรัตน์ แปรทอง	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๘
๑๒) นางสาวจรรยาวิทย์ ขำแบ่ง	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๑๙
๑๓) นางสาวธารารัตน์ สมัยใหม่	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๐
๑๔) นางสาวรัตนชนก ชนะคำ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๑
๑๕) นางสาวกมลทิพย์ พุ่มตาก้อง	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๒
๑๖) นางสาวสุพัตตรา ผาสุขพัคตร์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๓
๑๗) นางสาวฉัตรยาลักษณ์ บรรดิษฐ์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๔
๑๘) นางสาวอาภัสรา หล้าสูงเนิน	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๕
๑๙) นางสาวพิมพ์ิศา ทับพันธ์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๖
๒๐) นางสาวอัจฉรี แก้วเพชรวงศ์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๗
๒๑) นางสาวชลธิชา กันยานุช	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๘
๒๒) นางสาวพิชามณูช ยังฝ่อง	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๙
๒๓) นางสาวณิชารีย์ ปริญาณวัตร	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๐
๒๔) นายวัชรพล บุตรดีขัน	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๑
๒๕) นางสาวณัฐติมา ปัดชา	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๒
๒๖) นายวัชรพงษ์ พูลเขตกิจ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๓
๒๗) นายศิวักร วงสุตาล	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๔
๒๘) นางสาววิภา จาระณะ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๕
๒๙) นางสาวธัญญาภรณ์ คณะศรี	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๖
๓๐) นางสาวพัชรพร อนุสร	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๗
๓๑) นายธนากร อริยพงษ์โสภณ	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๘
๓๒) นางสาวบุษกร สมรักษ์	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๙
๓๓) นางสาววิลาวัลย์ แก้วยม	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๐
๓๔) นางสาวธัญญาลักษณ์ แสงโยธา	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๑
๓๕) นายสุชาพงศ์ รุ่งเรือง	ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๒

วิภา

๓๖) นายสิทธิพร...

- ๓๖) นายสิทธิพร วงษ์คำ
- ๓๗) นางเตชินี สืบเสระ
- ๓๘) นางสาวธันชพร คนแรง
- ๓๙) นายภาณุพล โพธิ์แดง
- ๔๐) นายวัชรกร กองแสง
- ๔๑) นางสาวสุธาทิพย์ อิ่มน้อย
- ๔๒) นางสาวชมพูนุท กสิชีวิน
- ๔๓) นางสาวรวีวรรณ สุขารมย์
- ๔๔) นางสาวกัญญาลักษณ์ กระทาง
- ๔๕) นางสาวปิยธิดา ประแดงโค
- ๔๖) นางสาวปวีตรา นาเหล็ก
- ๔๗) นางสาวทักษพร ไกรสิงห์
- ๔๘) นางสาวเบญจวรรณ คำหงษา
- ๔๙) นางสาวพัชชา แก้วย้อย
- ๕๐) นางสาวณัฐชา สัมฤทธิ์ดี
- ๕๑) นายรอมซี กาเต๊ะ
- ๕๒) นางสาวอังคณา อุ่นตา
- ๕๓) นายสุริยะ ชูทอง
- ๕๔) นายฉันทวิชญ์ เหลวกุล
- ๕๕) นายศิวาวุธ ธรรมนิทา
- ๕๖) นายอนุวัฒน์ เรืองอ่อน
- ๕๗) นายฉัตรชัย โยวะผุย
- ๕๘) นายกลยุทธ อินทร์คำ
- ๕๙) นางสาวนันทชา เนื่อนวล
- ๖๐) นางสาวจิตตวรรณ ลิ้มสมบูรณ์
- ๖๑) ว่าที่ร้อยตรีณัฐพล สุทธิมล

- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๓
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๔
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๕
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๖
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๗
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๘
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๙
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๐
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๑
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๒
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๓
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๔
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๕
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๖
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๗
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๘
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๕๙
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๐
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๑
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๒
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๓
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๔
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๕
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๖
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๗
- ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๘

วิมล

เอกสารแนบท้ายหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

บริษัท เอ็นไวรอนเม้นท์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

เลขทะเบียน ว-๐๙๙

ที่ อก ๐๓๑๐(๑)/ ๖๔๗๖

ลงวันที่ ๐๓ กรกฎาคม ๒๕๖๗

ขอขยายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๑๙๓ รายการ

น้ำ/น้ำเสีย จำนวน 27 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Arsenic	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4]
2	Barium	2) Digestion, Inductively Coupled Plasma Method ^[4]
3	Biochemical Oxygen Demand	Digestion, Inductively Coupled Plasma Method ^[4]
4	Cadmium	1) 5-Day BOD Test, Azide Modification Method ^[4]
5	Chemical Oxygen Demand	2) 5-Day BOD Test, Membrane Electrode Method ^[4]
6	Chromium	Digestion, Inductively Coupled Plasma Method ^[4]
7	Color	Closed Reflux, Titrimetric Method ^[4]
8	Copper	Digestion, Inductively Coupled Plasma Method ^[4]
9	Cyanide	ADMI Weighted-Ordinate Spectrophotometric Method ^[4]
10	Formaldehyde	Digestion, Inductively Coupled Plasma Method ^[4]
11	Free Chlorine	Distillation, Colorimetric Method ^[3]
12	Hexavalent Chromium	1) Iodometric Method ^[4]
13	Lead	2) DPD Colorimetric Method ^[4]
14	Manganese	Colorimetric Method ^[4]
15	Mercury	1) Digestion, Electrothermal Atomic Absorption Spectrometric Method ^[4]
16	Nickel	2) Digestion, Inductively Coupled Plasma Method ^[4]
17	Oil & Grease	Digestion, Inductively Coupled Plasma Method ^[4]
18	pH	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[4]
19	Phenols	Digestion, Inductively Coupled Plasma Method ^[4]
20	Selenium	Liquid-Liquid, Partition-Gravimetric Method ^[4]
		Electrometric Method ^[4]
		Distillation, Direct Photometric Method ^[4]
		1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4]
		2) Digestion, Inductively Coupled Plasma Method ^[4]

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
21	Sulfide	Iodometric Method ^[4]
22	Temperature	Laboratory and Field Methods ^[4]
23	Total Dissolved Solids	Dried at 180 °C ^[4]
24	Total Kjeldahl Nitrogen	1) Macro-Kjeldahl Method ^[4] 2) Semi-Micro-Kjeldahl Method ^[4]
25	Total Suspended Solids	Dried from 103 to 105 °C ^[4]
26	Trivalent Chromium	Digestion, Inductively Coupled Plasma Method; Colorimetric Method; Calculation ^[4]
27	Zinc	Digestion, Inductively Coupled Plasma Method ^[4]

น้ำใต้ดิน จำนวน 61 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Acetone	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
2	Antimony	Digestion, Inductively Coupled Plasma Method ^[4]
3	Arsenic	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
4	Barium	Digestion, Inductively Coupled Plasma Method ^[4]
5	Benzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
6	Beryllium	Digestion, Inductively Coupled Plasma Method ^[4]
7	Bromodichloromethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
8	Bromoform	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
9	Cadmium	Digestion, Inductively Coupled Plasma Method ^[4]
10	Carbon disulfide	Purge and Trap Gas Chromatographic/ Mass Spectrometric Method ^[4]
11	Carbon tetrachloride	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
12	Chlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
13	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
14	Chloroform	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
15	Chromium	Digestion, Inductively Coupled Plasma Method ^[4]
16	Chromium (III)	Digestion, Inductively Coupled Plasma Method; Colorimetric Method; Calculation ^[4]
17	Chromium (VI)	Colorimetric Method ^[4]
18	Cyanide	Distillation, Colorimetric Method ^[4]
19	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
20	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
21	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
22	1,1-Dichloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
23	1,2-Dichloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
24	1,1-Dichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
25	cis-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
26	trans-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
27	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
28	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
29	1,3-Dichloropropene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
30	Ethylbenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]

30/1

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
31	Hexachloro-1,3-butadiene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
32	Lead	1) Digestion, Electrothermal Atomic Absorption Spectrometric Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
33	Manganese	Digestion, Inductively Coupled Plasma Method ^[4]
34	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[4]
35	Methyl bromide	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
36	Methylene chloride	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
37	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
38	Naphthalene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
39	Nickel	Digestion, Inductively Coupled Plasma Method ^[4]
40	pH	Electrometric Method ^[4]
41	Selenium	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
42	Silver	Digestion, Inductively Coupled Plasma Method ^[4]
43	Styrene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
44	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
45	Tetrachloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
46	Toluene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[4]
47	TPH (C ₅ -C ₈)	Purge and Trap, Gas Chromatographic Method ^[11,19]
48	TPH (C _{>8} -C ₁₆)	Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^[9,19]

3mm

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
49	TPH (C ₁₆ -C ₃₅)	Separatory Funnel Liquid-Liquid Extraction, Gas Chromatographic Method ^[9,19]
50	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
51	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
52	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
53	Trichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
54	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
55	Vanadium	Digestion, Inductively Coupled Plasma Method ^[4]
56	Vinyl chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
57	m-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
59	o-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
59	p-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
60	Xylene (Total)	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
61	Zinc	Digestion, Inductively Coupled Plasma Method ^[4]

อากาศเสีย (ปล่อยระบาย) จำนวน 26 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Antimony	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
2	Arsenic	1) Isokinetic Sampling, Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[5] 2) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]

3mg

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
3	Beryllium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
4	Cadmium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
5	Carbon Monoxide	Instrumental Analyzer Method ^[5]
6	Chlorine	1) Absorption Sampling, Ion Chromatographic Method ^[5] 2) Isokinetic Sampling, Ion Chromatographic Method ^[5]
7	Chromium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
8	Cobalt	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
9	Copper	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
10	Dioxins/Furans	Isokinetic Sampling ^[5]
11	Hydrogen Chloride	1) Absorption Sampling, Ion Chromatographic Method ^[5] 2) Isokinetic Sampling, Ion Chromatographic Method ^[5]
12	Hydrogen Fluoride	1) Absorption Sampling, Ion Chromatographic Method ^[5] 2) Isokinetic Sampling, Ion Chromatographic Method ^[5]
13	Hydrogen Sulfide	Absorption Sampling, Iodometric Method ^[5]
14	Lead	1) Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5] 2) Isokinetic Sampling, Digestion, Direct Air-Acetylene Flame Method ^[5]
15	Manganese	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
16	Mercury	Isokinetic Sampling, Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[5]
17	Nickel	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
18	Opacity	Ringelmann's Method ^[2]
19	Oxides of Nitrogen	1) Absorption Sampling, Alkaline Permanganate/Colorimetric Method ^[5] 2) Instrumental Analyzer Method ^[5]
20	Selenium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]

31/10/2564

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
21	Sulfur Dioxide	1) Isokinetic Sampling, Barium-Thorin Titrimetric Method ^[5] 2) Absorption Sampling, Barium-Thorin Titrimetric Method ^[5] 3) Instrumental Analyzer Method ^[5]
22	Sulfuric Acid	Isokinetic Sampling, Barium-Thorin Titrimetric Method ^[5]
23	Tin	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
24	Total Suspended Particulate	Isokinetic Sampling, Gravimetric Method ^[5]
25	Vanadium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
26	Xylene	Adsorption Sampling, Gas Chromatographic Method ^[5]

สิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว จำนวน 20 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Antimony	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
2	Arsenic	1) Waste Extraction, Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[1,6,14] 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 3) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[7,14] 4) Digestion, Inductively Coupled Plasma Method ^[7,13]
3	Barium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
4	Beryllium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
5	Cadmium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
6	Chromium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]
7	Chromium (III)	2) Digestion, Inductively Coupled Plasma Method ^[7,13] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method; Waste Extraction, Colorimetric Method; Calculation ^[1,6,13,15]
8	Chromium (VI)	2) Digestion, Inductively Coupled Plasma Method; Alkaline Digestion, Colorimetric Method; Calculation ^[7,8,13,15] 1) Waste Extraction, Colorimetric Method ^[1,15]
9	Cobalt	2) Alkaline Digestion, Colorimetric Method ^[8,15] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]
10	Copper	2) Digestion, Inductively Coupled Plasma Method ^[7,13] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]
11	Lead	2) Digestion, Inductively Coupled Plasma Method ^[7,13] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]
12	Mercury	2) Digestion, Inductively Coupled Plasma Method ^[7,13] 1) Waste Extraction, Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[1,6,16]
13	Molybdenum	2) Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[17] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]
14	Nickel	2) Digestion, Inductively Coupled Plasma Method ^[7,13] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]
15	pH	2) Digestion, Inductively Coupled Plasma Method ^[7,13] Electrometric Method ^[21,22]
16	Selenium	1) Waste Extraction, Digestion, Hydride Generation/ Atomic Absorption Spectrometric Method ^[1,6,18] 2) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13]



ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
17	Silver	3) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[7,18] 4) Digestion, Inductively Coupled Plasma Method ^[7,13] 1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
18	Thallium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
19	Vanadium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
20	Zinc	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[1,6,13] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]

ดิน จำนวน 59 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Acetone	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
2	Antimony	Digestion, Inductively Coupled Plasma Method ^[7,13]
3	Arsenic	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[7,14] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
4	Barium	Digestion, Inductively Coupled Plasma Method ^[7,13]
5	Benzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
6	Beryllium	Digestion, Inductively Coupled Plasma Method ^[7,13]
7	Bromodichloromethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
8	Bromoform	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
9	Cadmium	Digestion, Inductively Coupled Plasma Method ^[7,13]

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
10	Carbon disulfide	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
11	Carbon tetrachloride	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
12	Chlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
13	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
14	Chloroform	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
15	Chromium	Digestion, Inductively Coupled Plasma Method ^[7,13]
16	Chromium (III)	Digestion, Inductively Coupled Plasma Method; Alkaline Digestion, Colorimetric Method; Calculation ^[7,8,13,15]
17	Chromium (VI)	Alkaline Digestion, Colorimetric Method ^[8,15]
18	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
19	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
20	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
21	1,1-Dichloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
22	1,2-Dichloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
23	1,1-Dichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
24	cis-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
25	trans-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
26	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
27	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
28	1,3-Dichloropropene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
29	Ethylbenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
30	Hexachloro-1,3-butadiene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
31	Lead	Digestion, Inductively Coupled Plasma Method ^[7,13]
32	Manganese	Digestion, Inductively Coupled Plasma Method ^[7,13]
33	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[17]
34	Methyl bromide	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
35	Methylene chloride	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
36	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
37	Naphthalene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
38	Nickel	Digestion, Inductively Coupled Plasma Method ^[7,13]
39	Selenium	1) Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[7,18] 2) Digestion, Inductively Coupled Plasma Method ^[7,13]
40	Silver	Digestion, Inductively Coupled Plasma Method ^[7,13]
41	Styrene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
42	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
43	Tetrachloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
44	Toluene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
45	TPH (C ₅ -C ₈)	Purge and Trap, Gas Chromatographic Method ^[12,19]
46	TPH (C _{>8} -C ₁₆)	Ultrasonic Extraction, Gas Chromatographic Method ^[10,19]

อินท

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
47	TPH (C _{>16} -C ₃₅)	Ultrasonic Extraction, Gas Chromatographic Method ^[10,19]
48	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
49	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
50	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
51	Trichloroethylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
52	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
53	Vanadium	Digestion, Inductively Coupled Plasma Method ^[7,13]
54	Vinyl chloride	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
55	m-Xylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
56	o-Xylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
57	p-Xylene	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
58	Xylene (Total)	Purge and Trap, Gas Chromatographic/ Mass Spectrometric Method ^[12,20]
59	Zinc	Digestion, Inductively Coupled Plasma Method ^[7,13]

เอกสารอ้างอิง

- กระทรวงอุตสาหกรรม. ประกาศกระทรวงอุตสาหกรรม, พ.ศ. 2566. เรื่อง การจัดการสิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว. ราชกิจจานุเบกษา. 31 พฤษภาคม 2566. เล่มที่ 140 ตอนพิเศษ 126 ง.
- กระทรวงอุตสาหกรรม. ประกาศกระทรวงอุตสาหกรรม, พ.ศ. 2549. เรื่อง กำหนดค่าปริมาณเขม่าควันที่เจือปนในอากาศที่ระบายออกจากปล่องของหม้อน้ำโรงสีข้าวที่ใช้กลบเป็นเชื้อเพลิง. ราชกิจจานุเบกษา. 4 ธันวาคม 2549. เล่มที่ 123 ตอนพิเศษ 125ง.
- สมาคมวิศวกรรมสิ่งแวดล้อมแห่งประเทศไทย. คู่มือวิเคราะห์น้ำเสีย. พิมพ์ครั้งที่ 4. กรุงเทพฯ: เรือนแก้วการพิมพ์, 2547.
- APHA, AWWA, WEF. Standard Methods for the Examination of Water and Wastewater. 24th ed. Washington, DC: APHA, 2023.

5. United States Environmental Protection Agency. **Standards of Performance for New Stationary Sources**. 40 CFR 60. Appendix A, 2023.
6. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. SW-846, 1997.
7. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Acid Digestion of Sludges and Sediments and Soils**. SW-846 Method 3050B, 1996.
8. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Alkaline Digestion for Hexavalent Chromium**. SW-846 Method 3060A, 1996.
9. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Separatory Funnel Liquid-Liquid Extraction**. SW-846 Method 3510C, 1996.
10. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Ultrasonic Extraction**. SW-846 Method 3550C, 2007.
11. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Purge-and-Trap for Aqueous Samples**. SW-846 Method 5030C, 2003.
12. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Closed-System Purge-and-Trap and Extraction for Volatile Organics in Soil and Waste Samples**. SW-846 Method 5035A, 2002.
13. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Inductively Coupled Plasma - Atomic Emission Spectrometry**. SW-846 Method 6010D, 2018.
14. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Antimony and Arsenic (Atomic Absorption, Borohydride Reduction)**. SW-846 Method 7062, 1994.
15. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Chromium, Hexavalent (Colorimetric)**. SW-846 Method 7196A, 1992.
16. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Mercury in Liquid Waste (Manual Cold-Vapor Technique)**. SW-846 Method 7470A, 1994.
17. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Mercury in Solid or Semisolid Waste (Manual Cold-Vapor Technique)**. SW-846 Method 7471B, 2007.
18. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods**. **Selenium (Atomic Absorption, Borohydride Reduction)**. SW-846 Method 7742, 1994. *3mg/L*

19. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Nonhalogenated Organics Using GC/FID. SW-846 Method 8015D**, 2003.

20. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/ Chemical Methods. **Volatile Organic Compounds by Gas Chromatography/ Mass Spectrometry (GC/MS). SW-846 Method 8260C**, 1996.

21. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **pH Electrometric Measurement. SW-846 Method 9040C**, 2004.

22. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Soil and Waste pH. SW-846 Method 9045D**, 2004.

3mg/l

ที่ อก ๐๓๑๐(๑)/ ๑๑๕๒๓



กรมโรงงานอุตสาหกรรม

ถนนพระรามที่ ๖ แขวงทุ่งพญาไท

เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๒๑ พฤศจิกายน ๒๕๖๗

เรื่อง เปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๒๓ กันยายน ๒๕๖๗

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด จำนวน ๒ แผ่น

ตามคำขอที่อ้างถึง บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด ห้องปฏิบัติการวิเคราะห์
เอกชน เลขทะเบียน ว-๐๙๙ สถานที่ตั้งเลขที่ ๒๕/๑๑๔ หมู่ที่ ๖ ซอยชินเขต ๑ ถนนงามวงศ์วาน แขวงทุ่งสองห้อง
เขตหลักสี่ กรุงเทพมหานคร ขอเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์ ต่อกรมโรงงานอุตสาหกรรม นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว มีความเห็นดังนี้

๑. ให้ยกเลิกเจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๒ ราย

๑) นางสาวกมลทิพย์ พุ่มตาก้อง

ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๒

๒) นายศิวาวุธ ธรรมนิทา

ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๖๒

๒. ให้เพิ่มขอบข่ายชนิดสารมลพิษที่วิเคราะห์ในน้ำ/น้ำเสีย น้ำใต้ดิน และดิน ตามสิ่งที่ส่งมาด้วย

อนึ่ง หนังสือฉบับนี้จะหมดอายุพร้อมหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

ในวันที่ ๑๘ พฤษภาคม ๒๕๗๑

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายธีรศักดิ์ อิศรางกูร ณ อยุธยา)

รองอธิบดี ปฏิบัติราชการแทน

อธิบดีกรมโรงงานอุตสาหกรรม

กองวิจัยและเตือนภัยมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๙๙

ไปรษณีย์อิเล็กทรอนิกส์ saraban@diw.mail.go.th



เอกสารแนบท้ายหนังสือเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

บริษัท เอ็นไวรอนเม้นท์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

เลขทะเบียน ว-๐๙๙

ที่ ออก ๐๓๑๐(๑)/ ๑๑ ๕๒ ๓

ลงวันที่ ๒๑ พฤศจิกายน ๒๕๖๗

ขอข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๔๗ รายการ

น้ำ/น้ำเสีย จำนวน 19 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
2	α -BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
3	β -BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
4	δ -BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
5	γ -BHC	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
6	Chlordane	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
7	o,p'-DDT	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
8	4,4'-DDD	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
9	4,4'-DDE	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
10	4,4'-DDT	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
11	Dieldrin	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
12	Endosulfan I	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
13	Endosulfan II	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
14	Endosulfan sulfate	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
15	Endrin	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
16	Endrin aldehyde	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
17	Heptachlor	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
18	Heptachlor epoxide	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
19	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]

น้ำใต้ดิน จำนวน 14 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
2	Chlordane	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
3	DDD	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
4	DDE	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
5	DDT	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
6	Dieldrin	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]

7 Endosulfan...

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
7	Endosulfan	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
8	Endrin	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
9	Heptachlor	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
10	Heptachlor epoxide	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
11	α -HCH	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
12	β -HCH	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
13	γ -HCH	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]
14	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]

ดิน จำนวน 14 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
2	Chlordane	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
3	DDD	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
4	DDE	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
5	DDT	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
6	Dieldrin	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
7	Endosulfan	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
8	Endrin	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
9	Heptachlor	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
10	Heptachlor epoxide	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
11	α -HCH	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
12	β -HCH	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
13	γ -HCH	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]
14	Methoxychlor	Ultrasonic Extraction, Gas Chromatographic Method ^[2,3]

เอกสารอ้างอิง

1. APHA, AWWA, WEF. **Standard Methods for the Examination of Water and Wastewater.** 24th ed. Washington, DC: APHA, 2023.
2. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Ultrasonic Extraction. SW-846 Method 3550C,** 2007.
3. United States Environmental Protection Agency. **Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Organochlorine Pesticides by Gas Chromatography. SW-846 Method 8081B,** 2007.

ที่ อก ๐๓๑๐(๑)/ ๑๖๐๘



กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๕๐๐

๒๘ กุมภาพันธ์ ๒๕๖๘

เรื่อง เปลี่ยนแปลงสารมลพิษที่วิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๒๗ มกราคม ๒๕๖๘

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือเปลี่ยนแปลงสารมลพิษที่วิเคราะห์

บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด จำนวน ๑ แผ่น

ตามคำขอที่อ้างถึง บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด ห้องปฏิบัติการวิเคราะห์
เอกชน เลขทะเบียน ว-๐๙๙ สถานที่ตั้งเลขที่ ๒๕/๑๑๔ หมู่ที่ ๖ ซอยชินเขต ๑ ถนนงามวงศ์วาน แขวงทุ่งสองห้อง
เขตหลักสี่ กรุงเทพมหานคร ขอเปลี่ยนแปลงสารมลพิษที่วิเคราะห์ ต่อกรมโรงงานอุตสาหกรรม นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด
เพิ่มขอบข่ายชนิดสารมลพิษที่วิเคราะห์ในน้ำ/น้ำเสีย น้ำใต้ดิน อากาศเสีย และดิน ตามสิ่งที่ส่งมาด้วย

อนึ่ง หนังสือฉบับนี้จะสิ้นอายุพร้อมหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน
ในวันที่ ๑๘ พฤษภาคม ๒๕๗๑

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

รังสรรค์

(นายธีรทัศน์ อิศรางกูร ณ อยุธยา)

รองอธิบดี ปฏิบัติราชการแทน

อธิบดีกรมโรงงานอุตสาหกรรม

กองวิจัยและเตือนภัยมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๙๙

ไปรษณีย์อิเล็กทรอนิกส์ saraban@diw.mail.go.th



เอกสารแนบท้ายหนังสือเปลี่ยนแปลงสารมลพิษที่วิเคราะห์

บริษัท เอ็นไวรอนเม้นท์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

เลขทะเบียน ว-๐๙๙

ที่ อก ๐๓๑๐(๑)/ ๑๖๐๘

ลงวันที่ ๒๘ กุมภาพันธ์ ๒๕๖๘

ขอข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๔ รายการ

น้ำ/น้ำเสีย จำนวน 1 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Toxaphene	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]

น้ำใต้ดิน จำนวน 1 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Toxaphene	Liquid-Liquid Extraction, Gas Chromatographic Method ^[1]

อากาศเสีย (ปล่องระบาย) จำนวน 1 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Cresol	Adsorption Sampling, Gas Chromatographic Method ^[2]

ดิน จำนวน 1 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Toxaphene	Ultrasonic Extraction, Gas Chromatographic Method ^[3,4]

เอกสารอ้างอิง

1. APHA, AWWA, WEF. **Standard Methods for the Examination of Water and Wastewater.** 24th ed. Washington, DC: APHA, 2017.
2. United States Environmental Protection Agency. **Standards of Performance for New Stationary Sources.** 40 CFR 60. Appendix A, 2023.
3. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Ultrasonic Extraction. SW-846 Method 3550C,** 2007.
4. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Organochlorine Pesticides by Gas Chromatography. SW-846 Method 8081B,** 2007.

ที่ อก ๐๓๑๐(๑)/ ๕๗ ๖ ๓



กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๔๐๐

๐๘ กรกฎาคม ๒๕๖๘

เรื่อง ยกเลิกบุคลากรของห้องปฏิบัติการวิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๑ กรกฎาคม ๒๕๖๘

ตามคำขอที่อ้างถึง บริษัท เอ็นไวรอนเมนต์ รีเสิร์ช แอนด์ เทคโนโลยี จำกัด ห้องปฏิบัติการวิเคราะห์เอกชน
เลขทะเบียน ว-๐๙๙ สถานที่ตั้งเลขที่ ๒๕/๑๑๔ หมู่ที่ ๖ ซอยชินเขต ๑ ถนนงามวงศ์วาน แขวงทุ่งสองห้อง
เขตหลักสี่ กรุงเทพมหานคร ขอยกเลิกบุคลากร ความละเอียดแจ้งแล้ว นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้ยกเลิกเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน
จำนวน ๑๐ ราย ได้แก่

- | | |
|--------------------------------|----------------------------|
| ๑) นางสาวสุพัตรา ผาสุขพัทตร์ | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๓ |
| ๒) นางสาวฉัตรยาลักษณ์ บรรดิษฐ์ | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๒๔ |
| ๓) นางสาวณัฐติมา ปัดชา | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๒ |
| ๔) นายวัชรพงษ์ พูลเขตกิจ | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๓ |
| ๕) นางสาววิภา จาระณะ | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๕ |
| ๖) นางสาวธัญญาภรณ์ คณะศรี | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๖ |
| ๗) นางสาวบุษกร สมรักษ์ | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๓๙ |
| ๘) นางสาววิลาวัลย์ แก้วยม | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๐ |
| ๙) นางสาวธัญญาลักษณ์ แสงโยธา | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๑ |
| ๑๐) นางสาวชมพูนุท กสิชีวิน | ทะเบียนเลขที่ ว-๐๙๙-จ-๐๐๔๙ |

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายประสม ดำรงพงษ์)

ผู้อำนวยการกองวิจัยและเตือนภัยมลพิษโรงงาน
ปฏิบัติราชการแทนอธิบดีกรมโรงงานอุตสาหกรรม

กองวิจัยและเตือนภัยมลพิษโรงงาน

กลุ่มมาตรฐานวิธีการวิเคราะห์ทดสอบมลพิษและทะเบียนห้องปฏิบัติการ

โทร. ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๐๓-๕

โทรสาร ๐ ๒๔๓๐ ๖๓๑๒ ต่อ ๒๑๙๙

ไปรษณีย์อิเล็กทรอนิกส์ saraban@diw.mail.go.th




TSP HIGH VOLUME AIR SAMPLER CALIBRATION REPORT

Quotation	2025-00109			Date	August 9, 2025
Sampler Location	พื้นที่โครงการ			Start Time	2:40 PM
Sampler Number	TSP No.A4	Transfer Standard Type	Orifice	Stop Time	2:50 PM
Instrument Model	HIVOL-BBCBE	Calibrator Model	TE-5025A	Calibrated By	Mr. Wanchalerm Chaiyawong
Motor Serial Number	2012-07	Calibrator Serial Number	2716		
Recorder Serial Number	4648				

Plate No.	(Delta H)			(A)	(X)	(I)	(Y)	Temperature	Barometric Pressure	Start Meter	Stop Meter
	Pressure Drop Across Orifice (inH ₂ O)			[ΔH ₂ O(Pa/P _{std})(T _{std} /Ta)] ^{1/2}	Qstd = (1/m)[(A-b)] (m ³ /min)	ample Flow Rate Indication (ft ³ /min)	IC = I/[(Pa/P _{std})(T _{std} /Ta)] ^{1/2}	(*K = °C+273)	(mmHg)		
	Positive	Negative	ΔH ₂ O								
5	1.3	1.3	2.6	1.59488	0.77794	20.0	19.78	303.0	756.0		
7	2.4	2.4	4.8	2.16701	1.05304	27.0	26.71	303.0	756.0		
10	3.7	3.7	7.4	2.69065	1.30482	34.0	33.63	303.0	756.0		
13	4.8	4.8	9.6	3.06462	1.48463	38.0	37.59	303.0	756.0		
18	6.0	6.0	12.0	3.42635	1.65856	43.0	42.53	303.0	756.0		
Linear Regression Y ON X : Y= mX + b							Average	303.0	756.0		
1	Slope (m)			2.07975	Linear Equation			r ²	0.999205	Pstd(mmHg)	760.0
2	Intercept (b)			-0.02305	Set Point Flow Rate (X) (m ³ /min)		1.133	r	0.9996024	T _{NTP}	298.0
3	Correlation Coefficient (r)			0.99982	Final Set Flow Rate = (I)		0	(Pa/Pstd)*(Tstd/Ta)		0.978322043	
Result								C=(Pa/Pstd)*(Tstd/Ta)^0.5		0.989101634	

COMMENT

Andersen Instruments, Inc.



Checked By

(Mr. Prayun Detkla)
Technician



Approved By

(Mr. Panupon Podang)
Environmental Scientist


PM10 HIGH VOLUME AIR SAMPLER CALIBRATION REPORT

Quotation	2025-00109			Date	August 9, 2025
Sampler Location	พื้นที่โครงการ			Start Time	2:30 PM
Sampler Number	PM-10 No.8	Transfer Standard Type	Orifice	Stop Time	2:40 PM
Instrument Model	HIVOL-BMBBE	Calibrator Model	TE-5025A	Calibrated By	Mr. Wanchalem Chaiyawong
Motor Serial Number	BLA0901	Calibrator Serial Number	2716		
Recorder Serial Number	R0411-001				

Plate No.	(Delta H)			(A)	(X)	(I)	(Y)	Temperature	Barometric Pressure	Start Meter	Stop Meter
	Pressure Drop Across Orifice (inH ₂ O)			[(ΔH ₂ O/(Pa/P _{std})(T _{std} /Ta)) ^{1/2}	Qstd = (1/m)[(A-b)] (m ³ /min)	ample Flow Rate Indication (ft ³ /min)	IC = I[(Pa/P _{std})(T _{std} /Ta)) ^{1/2}	T (°K = °C+273)	(mmHg)		
	Positive	Negative	ΔH ₂ O								
5	1.5	1.5	3.0	1.71317	0.83482	28.0	27.69	303.0	756.0		
7	2.6	2.6	5.2	2.25550	1.09559	39.0	38.57	303.0	756.0		
10	3.8	3.8	7.6	2.72677	1.32219	48.0	47.48	303.0	756.0		
13	5.2	5.2	10.4	3.18976	1.54480	57.0	56.38	303.0	756.0		
18	6.5	6.5	13.0	3.56626	1.72584	64.0	63.30	303.0	756.0		
Linear Regression Y ON X : Y= mX + b							Average	303.0	756.0		
1	Slope (m)			2.07975	Linear Equation			r ²	0.999788	Pstd(mmHg)	760.
2	Intercept (b)			-0.02305	Set Point Flow Rate (X) (m ³ /min)		1.133	r	0.999894	T _{NTP}	298.
3	Correlation Coefficient (r)			0.99982	Final Set Flow Rate = (I)		0	(Pa/Pstd)*(Tstd/Ta)		0.978322043	
Result								C=(Pa/Pstd)*(Tstd/Ta)^0.5		0.989101634	


COMMENT

Andersen Instruments, Inc.



Checked By

(Mr. Prayun Detkla)
Technician



Approved By

(Mr. Panupon Podang)
Environmental Scientist



JIRANATEE ASSOCIATES CO.,LTD.

Jiranatee Associates Co.,Ltd.
63/14-15, 67/35-36
Petchkasem 7,7/1, Rd. Watthapra, Bangkokyai,
Bangkok 10600 (Thailand)
Tel: +6608680812
Mobile: +66863999453
E-mail: jnac-calibration@jiranatee.com
Web site: www.jiranatee.com

Accredited calibration laboratory
ISO/IEC 17025:2017
NSC-TISI-TIS 17025
CALIBRATION 0367

Flow measurement laboratory
Calibration services department.



CERTIFICATE OF CALIBRATION

Certificate No. : COF-035-67

Page 1 of 2 Pages

MEASUREMENT ITEM : Top Load Orifice
MANUFACTURER : TISCH
MODEL/TYPE : TE-5025A
SERIAL NUMBER : 2716
ID NUMBER : -
CONDITION AS-RECEIVED : Used item
CUSTOMER : Environment Research & Technology Co., Ltd.
25/114 Moo 6 Soi Chinaket 1, Ngamwongwan Road,
Toongsonghong, Laksi, Bangkok 10210

RECEIVED DATE : 05 Sep 2024
MEASUREMENT DATE : 11 Sep 2024
ISSUE DATE : 12 Sep 2024

ENVIRONMENTAL CONDITIONS:

Ambient condition in the laboratory are as follow:

Temperature	: 23.0 ± 3.0	°C
Relative Humidity	: 55.0 ± 15.0	%RH
Atmospheric Pressure	: 1010 ± 10	hPa

CALIBRATION CONDITION:

Preconditioning : 24 hours at ambient conditions.
Measurement Condition : The average values during measurement are 23.9 °C and 51.2 %RH.

NOTED: The certificate is valid only to the item calibrated on date and place of calibration.

TABULATION OF RESULTS:

The table on next page give the measured values.

Calibrated by:

- ☐ Mr. Sorawit Thachalad
☒ Miss Jitraporn Lertsomphol



Approved signatory:

Mr. Parinya Booncharoen
Calibration Department Manager

Calibration procedure:

The Orifice gas flow device was calibrated against Standard Rotary Displacement Meter (Roots Meter) Model G65/IMC/W2-dp. The WI-CL-004 was used as a calibration guideline.

Traceability:

This certificate provides a traceability of the measurement to recognized the national standards, and to realization of the international system of units (SI) through the NIMT (National Metrology Institute of Thailand) via Certificate number: MW-0063-23.

Uncertainty of Measurement:

The reported uncertainty of measurement is based on the standard uncertainty multiplied by a coverage factor $k=2$, Which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty has been determined in accordance with the GUM 'Evaluation of measurement data - Guide to the expression of uncertainty in measurement'

MEASUREMENT RESULTS:

The Orifice gas flow device was calibrated by direct comparison method with the Standard Rotary Displacement Meter (Roots Meter). The Humid air was used as a medium in the system. The standard conditions are 25°C (298.15 K) and 760 mmHg for standard temperature and standard pressure respectively.

Table 1: The results of Q Standard calibration data

Plate	Flow rate m^3/min	Pressure [Pa] mmHg	Temperature [Ta] °C	Temperature [Tm] °C	Δp_{meter} mmHg	$\Delta p_{Orifice}$ inH ₂ O	γ	Standard Flow [Q_s] m^3/min
1	0.701	756.493	23.93	23.07	51.459	1.794	1.339	0.654
2	1.005	756.534	24.06	23.49	56.170	3.670	1.914	0.930
3	1.115	756.571	24.23	23.72	36.795	4.744	2.176	1.061
4	1.167	756.567	24.31	23.85	27.415	5.376	2.316	1.124
5	1.410	756.522	24.40	23.71	27.764	7.879	2.803	1.358

Slope (m): 2.07975
 Intercept (b): -0.02305
 Correlation coefficient (r): 0.99982
 Uncertainty ($k=2$): 0.015 m^3/min

Table 2: The results of Q actual calibration data

Plate	Flow rate m^3/min	Pressure [Pa] mmHg	Temperature [Ta] °C	Temperature [Tm] °C	Δp_{meter} mmHg	$\Delta p_{Orifice}$ inH ₂ O	γ	Standard Flow [Q_s] m^3/min
1	0.701	756.493	23.93	23.07	51.459	1.794	0.839	0.655
2	1.005	756.534	24.06	23.49	56.170	3.670	1.201	0.932
3	1.115	756.571	24.23	23.72	36.795	4.744	1.365	1.063
4	1.167	756.567	24.31	23.85	27.415	5.376	1.454	1.126
5	1.410	756.522	24.40	23.71	27.764	7.879	1.760	1.362

Slope (m): 1.30261
 Intercept (b): -0.01444
 Correlation coefficient (r): 0.99982
 Uncertainty ($k=2$): 0.015 m^3/min

End of Certificate of Calibration



Mettler-Toledo (Thailand) Ltd.

846/4 - 846/5 Lasalle Rd., Bangna Tai Sub-District

Bangna District, Bangkok 10260

+662 723 0382

MT-TH.ServiceSupport@mt.com



NSC-TISI-TIS 17025
CALIBRATION 0062

Accuracy Calibration Certificate

Customer

Company: Environment Research & Technology Co., Ltd.
Address: 25/114 Moo 6, Soi Chinaket 1, Ngamwongwan Rd., Toongsonghong
City: Laksi **Contact:** Ramita Taengthai
Zip / Postal: 10210
State / Province: Bangkok
Order Number: 
0 3 3 3 6 1 0 1 9

Weighing Device

Manufacturer: Mettler Toledo **Instrument Type:** Weighing Instrument
Model: AB204-S **Asset Number:** ERTC-L-IN-0048
Serial No.: 1123103723 **Terminal Model:** N/A
Building: N/A **Terminal Serial No.:** N/A
Floor: 4 **Terminal Asset No.:** N/A
Room: 406

Range	Max. Capacity	Readability (d)
1	220 g	0.0001 g

Procedure

Calibration Guideline: EURAMET cg-18 v. 4.0 (11/2015)
METTLER TOLEDO Work Instruction: CP/W002/20

This calibration certificate contains measurements for As Found calibration. No As Left calibration was performed because the device was not modified after As Found calibration. Therefore, results for As Left correspond to As Found.

The sensitivity/span of the weighing instrument was adjusted before calibration with a built-in weight.

In accordance with EURAMET cg-18 (11/2015), the test loads were selected to reflect the specific use of the weighing device or to accommodate specific calibration conditions.

	Temperature		Humidity	
As Found	Start: 23.1 °C	End: 23.3 °C	Start: 35.7 %	End: 35.2 %

As Found Calibration Date: 16-Jan-2025
As Left Calibration Date: N/A
Issue Date: 18-Jan-2025

Calibrator: 
Nithit Jongkrod

Approved Signatory: 
Technical Manager / Head of Calibration Center

Measurement Results


Repeatability

Test Load: 100 g

	As Found	As Left
1	100.0000 g	N/A
2	100.0000 g	N/A
3	100.0001 g	N/A
4	100.0001 g	N/A
5	100.0000 g	N/A
6	100.0001 g	N/A
7	100.0000 g	N/A
8	99.9999 g	N/A
9	100.0000 g	N/A
10	100.0000 g	N/A

Standard Deviation	0.00006 g	N/A
--------------------	-----------	-----

○ As Found
◆ As Left



The "d" in the graph represents the readability of the range/interval in which the test was performed.


The results of this graph are based upon the absolute values of the differences from the mean value.

Eccentricity

Test Load: 100 g

Position	As Found	As Left
1	100.0000 g	N/A
2	100.0001 g	N/A
3	100.0002 g	N/A
4	99.9999 g	N/A
5	99.9998 g	N/A

Maximum Deviation	0.0002 g	N/A
-------------------	----------	-----




As Found

The "d" in the graph represents the readability of the range/interval in which the test was performed.

Error of Indication

As Found

	Reference Value	Indication	Error of Indication	Expanded Uncertainty	k
1	0.0000 g	0.0000 g	0.0000 g	0.14 mg	2
2	0.0500 g	0.0500 g	0.0000 g	0.15 mg	2
3	0.1000 g	0.1000 g	0.0000 g	0.15 mg	2
4	0.5000 g	0.5000 g	0.0000 g	0.15 mg	2
5	1.0000 g	1.0000 g	0.0000 g	0.15 mg	2
6	5.0000 g	5.0000 g	0.0000 g	0.16 mg	2
7	10.0000 g	10.0000 g	0.0000 g	0.16 mg	2
8	50.0001 g	50.0001 g	0.0000 g	0.20 mg	2
9	99.9999 g	100.0000 g	0.0001 g	0.27 mg	2
10	150.0000 g	150.0002 g	0.0002 g	0.38 mg	2
11	200.0001 g	200.0003 g	0.0002 g	0.44 mg	2



○ As Found

◆ As Left

For improved legibility of the graphics only increasing measurement points are shown and measurement points close to zero are not displayed.

The expanded measurement uncertainty is reported as the standard measurement uncertainty multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95 %.

The user is responsible for maintaining environmental conditions and the settings of the weighing instrument when it was calibrated.
The results of this calibration certificate relate only to the calibrated item.

Test Equipment

All weights used for metrological testing are traceable to national or international standards. The weights were calibrated and certified by an accredited calibration laboratory.

Weight Set 1: OIML E2

Weight Set No.:	WS52	Date of Issue:	17-Apr-2024
Certificate Number:	191753	Calibration Due Date:	15-Oct-2025

Weight Set 2: OIML E2

Weight Set No.:	WS52-1	Date of Issue:	17-May-2024
Certificate Number:	C420107128	Calibration Due Date:	17-Oct-2025

Weight Set 3: OIML E2

Weight Set No.:	WS52-2	Date of Issue:	17-May-2024
Certificate Number:	C420107129	Calibration Due Date:	28-Oct-2025

Thermo Hygrometer

Equipment No.:	IN302	Date of Issue:	31-Oct-2024
Certificate Number:	SG-H-00908/67	Calibration Due Date:	17-Oct-2025

Remarks

Equipment condition: Good

Next calibration according to customer's procedure

Calibration data not decide by calibration laboratory

End of Accredited Section

The information below and any attachments to this calibration certificate are not part of the accredited calibration.

Measurement Uncertainty of the Weighing Instrument in Use

Stated is the expanded uncertainty with $k=2$ in use. The formula shall be used for the estimation of the uncertainty under consideration of the errors of indication. The value R represents the net load indication in the unit of measure of the device.

Temperature coefficient for the evaluation of the measurement uncertainty in use: $3.0 \cdot 10^{-6} / K$

Temperature range on site for the evaluation of the measurement uncertainty in use: 3 K


Linearization of Uncertainty Equation

Range			As Found	As Left
	d	Max		
1	0.0001 g	220 g	$U_1 = 0.15 \text{ mg} + 0.00712 \text{ mg/g} \cdot R$	N/A


To optimize the stability of the linearization, besides of the zero load only increasing measurement points with a test load of 5% of the measurement range or larger are taken for the calculation of the linear equation.

Absolute and Relative Measurement Uncertainty in Use for Various Net Indications (Examples)

Net Indication	As Found		As Left	
0.0220 g	0.15 mg	0.68%	N/A	N/A
0.2200 g	0.15 mg	0.069%	N/A	N/A
2.2000 g	0.17 mg	0.0075%	N/A	N/A
22.0000 g	0.31 mg	0.0014%	N/A	N/A
220.0000 g	1.7 mg	0.00078%	N/A	N/A



As Found



As Left

GWP® Certificate



As
Found



As
Left



The weighing device meets the given process requirements.

The weighing device meets the given process requirements.

Tests Performed:



As Found



As Left



No adjustments/modifications made. As Left results correspond to As Found.


Process Requirements

Weighing Tolerance: 1%

Smallest Net Weight: 0.0500 g

Safety Factor: 2

Safe Weighing Range



While the values in this graph reflect the actual calibration results, the measurement uncertainty curves are simply a visual representation. This graph reflects As Left testing, unless only As Found was performed.

Minimum Weight

As Found Minimum Weight Table

Minimum weights for different weighing tolerances and safety factors					
	Safety Factor				
Tolerance	1	2	3	5	10
0.1%	0.15163 g	0.30546 g	0.46152 g	0.78056 g	1.62097 g
0.2%	0.07555 g	0.15163 g	0.22827 g	0.38321 g	0.78056 g
0.5%	0.03015 g	0.06039 g	0.09072 g	0.15163 g	0.30546 g
1%	0.01507 g	0.03015 g	0.04526 g	0.07555 g	0.15163 g
2%	0.00753 g	0.01507 g	0.02261 g	0.03771 g	0.07555 g
5%	0.00301 g	0.00602 g	0.00904 g	0.01507 g	0.03015 g



Pass: The determined minimum weight meets the requirement for the smallest net weight.

As Left Minimum Weight Table

Minimum weights for different weighing tolerances and safety factors					
	Safety Factor				
Tolerance	1	2	3	5	10
0.1%	0.15163 g	0.30546 g	0.46152 g	0.78056 g	1.62097 g
0.2%	0.07555 g	0.15163 g	0.22827 g	0.38321 g	0.78056 g
0.5%	0.03015 g	0.06039 g	0.09072 g	0.15163 g	0.30546 g
1%	0.01507 g	0.03015 g	0.04526 g	0.07555 g	0.15163 g
2%	0.00753 g	0.01507 g	0.02261 g	0.03771 g	0.07555 g
5%	0.00301 g	0.00602 g	0.00904 g	0.01507 g	0.03015 g



Pass: The determined minimum weight meets the requirement for the smallest net weight.

At these net minimum weight values, the measurement uncertainty of the weighing device is equal to or less than 1/1 (no safety factor), 1/2, 1/3, 1/5, or 1/10 of the required tolerance. The values are calculated with $k = 2$ and based on the linear formula of the measurement uncertainty of the weighing device in use.

The safety factor for As Found is always 1. This implies no safety factor. As Found testing looks at the behavior of the instrument from the past until test occurred. For the past, it is necessary to know that the tolerance was met, but not the safety factor. The safety factor is a proactive measure to apply for future measurements.

Notes on minimum weight values in above table:

1. If "N/A" is shown above, no appropriate value could be calculated.
2. METTLER TOLEDO is not responsible for the definition of the process requirements.

Measurement Results

Results Summary

	Repeatability	Eccentricity	Error of Indication
As Found	✓	✓	✓
As Left	✓	✓	✓

✓ = Passed

✗ = Failed

⚠ = Safety Factor not met

Repeatability

Test Load: 100 g

Tolerance	Control Limit	As Found		As Left	
		Std. Deviation	Result	Std. Deviation	Result
0.1%	N/A	0.00006 g*	N/A	0.00006 g*	N/A
0.2%	0.00005 g		✗		✗
0.5%	0.00013 g		✓		✓
1%	0.00025 g		✓		✓
2%	0.00050 g		✓		✓
5%	0.00125 g		✓		✓

*The calculated standard deviation value is below the rounding error of the balance. The $0.41 \cdot d$ rule is used for the assessment of this repeatability test and the calculation of the minimum weight.

The weighing tolerance is met if the standard deviation is less than or equal to the corresponding control limit.

Eccentricity

Test Load: 100 g

Tolerance	Control Limit	As Found		As Left	
		Deviation	Result	Deviation	Result
0.1%	0.0500 g	0.0002 g	✓	0.0002 g	✓
0.2%	0.1000 g		✓		✓
0.5%	0.2500 g		✓		✓
1%	0.5000 g		✓		✓
2%	1.0000 g		✓		✓
5%	2.5000 g		✓		✓

The weighing tolerance is met if the deviation is less than or equal to the corresponding control limit.

Error of Indication**As Found**

		Control limits for various weighing tolerances					
Reference Value	Error	0.1%	0.2%	0.5%	1%	2%	5%
0.0000 g	0.0000 g	N/A	N/A	N/A	N/A	N/A	N/A
50.0001 g	0.0000 g	0.0250 g	0.0500 g	0.1250 g	0.2500 g	0.5000 g	1.2500 g
99.9999 g	0.0001 g	0.0500 g	0.1000 g	0.2500 g	0.5000 g	1.0000 g	2.5000 g
150.0000 g	0.0002 g	0.0750 g	0.1500 g	0.3750 g	0.7500 g	1.5000 g	3.7500 g
200.0001 g	0.0002 g	0.1000 g	0.2000 g	0.5000 g	1.0000 g	2.0000 g	5.0000 g
Result		✓	✓	✓	✓	✓	✓

As Left

		Control limits for various weighing tolerances					
Reference Value	Error	0.1%	0.2%	0.5%	1%	2%	5%
0.0000 g	0.0000 g	N/A	N/A	N/A	N/A	N/A	N/A
50.0001 g	0.0000 g	0.0250 g	0.0500 g	0.1250 g	0.2500 g	0.5000 g	1.2500 g
99.9999 g	0.0001 g	0.0500 g	0.1000 g	0.2500 g	0.5000 g	1.0000 g	2.5000 g
150.0000 g	0.0002 g	0.0750 g	0.1500 g	0.3750 g	0.7500 g	1.5000 g	3.7500 g
200.0001 g	0.0002 g	0.1000 g	0.2000 g	0.5000 g	1.0000 g	2.0000 g	5.0000 g
Result		✓	✓	✓	✓	✓	✓

The weighing tolerance is met if the error (of indication) for each test point is less than or equal to the corresponding control limit for that particular weighing tolerance. Results at or close to the zero point cannot be assessed.



ประกาศคณะกรรมการสิ่งแวดล้อมแห่งชาติ

ฉบับที่ ๑๐ (พ.ศ. ๒๕๓๘)

ออกตามความในพระราชบัญญัติส่งเสริมและรักษาคุณภาพสิ่งแวดล้อมแห่งชาติ

พ.ศ. ๒๕๓๕

เรื่อง กำหนดมาตรฐานคุณภาพอากาศในบรรยากาศโดยทั่วไป

อาศัยอำนาจตามความในมาตรา ๓๒ แห่งพระราชบัญญัติส่งเสริมและรักษาคุณภาพสิ่งแวดล้อมแห่งชาติ พ.ศ. ๒๕๓๕ คณะกรรมการสิ่งแวดล้อมแห่งชาติกำหนดมาตรฐานคุณภาพอากาศในบรรยากาศโดยทั่วไป ไว้ดังต่อไปนี้

ข้อ ๑ ในประกาศนี้

“เครื่องวัด ระบบนั้ดิสเพอร์ซีฟ อินฟราเรด ดีเทกชัน (Non- dispersive Infrared Detection)” หมายความว่า เครื่องมือวัดค่าก๊าซคาร์บอนมอนอกไซด์โดยใช้รังสีอินฟราเรด

“เครื่องวัดระบบเคมีลูมิเนสเซน (Chemiluminescence)” หมายความว่า

(๑) เครื่องมือวัดค่าก๊าซไนโตรเจนไดออกไซด์โดยใช้ก๊าซไอโซนทำปฏิกิริยากับก๊าซไนตริกออกไซด์ ซึ่งถูกเปลี่ยนมาจากก๊าซไนโตรเจนไดออกไซด์แล้ววัดความเข้มของแสงซึ่งเกิดจากปฏิกิริยานั้น ณ ที่ความยาวคลื่นที่สูงกว่า ๖๐๐ นาโนเมตร (Nanometer) หรือ

(๒) เครื่องมือวัดค่าก๊าซไอโซนโดยใช้ก๊าซเอซีลินทำปฏิกิริยากับก๊าซไอโซนแล้ววัดความเข้มของแสงซึ่งเกิดจากปฏิกิริยานั้น ณ ที่ความยาวคลื่นระหว่าง ๓๕๐ ถึง ๕๕๐ นาโนเมตร

“ระบบพาราโรซานิลีน (Pararosaniline)” หมายความว่า การวัดค่าก๊าซซัลเฟอร์ไดออกไซด์ โดยการดูดอากาศผ่านสารละลายโปตัสเซียม เตตราคลอโรเมอร์คิวเรต (Potassium Tetrachloromercurate) เกิดเป็นสารไดคลอโรซัลไฟโตเมอร์คิวเรต คอมเพลกซ์

(Dichlorosulfite Mercurate Complex) ทำปฏิกิริยากับสารพาราโรซานิลีนและฟอร์มัลดีไฮด์ (Pararosaniline and Formaldehyde) เกิดเป็นสีของพาราโรซานิลีนเมทิล ซัลฟอนิก แอซิด (Pararosaniline Methyl Sulfonic Acid) ซึ่งจะถูกวัดความสามารถในการดูดซึมแสง ณ ที่ช่วงคลื่น ๕๔๘ นาโนเมตร

“เครื่องวัดระบบอะตอมมิก แอ็บซอร์ปชัน สเปกโตรมิเตอร์ (Atomic Absorption Spectrometer)” หมายความว่า เครื่องมือวัดปริมาณของตะกั่ว โดยใช้เปลวไฟอะเซทิลีน (Acetylene Flame) ที่ความยาวคลื่น ๒๘๓.๓ หรือ ๒๑๓ นาโนเมตร

“ระบบกราวิเมตริก (Gravimetric)” หมายความว่า การวัดค่าฝุ่นละออง โดยดูดอากาศผ่านแผ่นกรอง ซึ่งมีประสิทธิภาพในการกรองฝุ่นละอองขนาด ๐.๓ ไมครอน (Micron) ได้ร้อยละ ๙๙ แล้วหาน้ำหนักฝุ่นละอองจากแผ่นกรองนั้น

ข้อ ๒ ค่าก๊าซในบรรยากาศโดยทั่วไปในช่วงเวลาหนึ่งเวลาใดให้เป็นไปดังต่อไปนี้

(๑) ค่าเฉลี่ยของก๊าซคาร์บอนมอนอกไซด์ในเวลา ๑ ชั่วโมง จะต้องไม่เกิน ๓๐ ส่วนในล้านส่วน (ppm) หรือไม่เกิน ๓๔.๒ มิลลิกรัมต่อลูกบาศก์เมตรและในเวลา ๘ ชั่วโมง จะต้องไม่เกิน ๕ ส่วนในล้านส่วน หรือไม่เกิน ๑๐.๒๖ มิลลิกรัมต่อลูกบาศก์เมตร

(๒) ค่าเฉลี่ยของก๊าซไนโตรเจนไดออกไซด์ในเวลา ๑ ชั่วโมง จะต้องไม่เกิน ๐.๑๓ ส่วนในล้านส่วน หรือไม่เกิน ๐.๓๒ มิลลิกรัมต่อลูกบาศก์เมตร

(๓) ค่าเฉลี่ยของก๊าซโอโซนในเวลา ๑ ชั่วโมง จะต้องไม่เกิน ๐.๑๐ ส่วนในล้านส่วน หรือไม่เกิน ๐.๒๐ มิลลิกรัมต่อลูกบาศก์เมตร

(๔) ค่าเฉลี่ยของก๊าซซัลเฟอร์ไดออกไซด์ในเวลา ๒๔ ชั่วโมง จะต้องไม่เกิน ๐.๑๒ ส่วนในล้านส่วน หรือไม่เกิน ๐.๓๐ มิลลิกรัมต่อลูกบาศก์เมตร และค่ามัธยิมเรขาคณิต (Geometric Mean) ในเวลา ๑ ปี จะต้องไม่เกิน ๐.๐๔ ส่วนในล้านส่วน หรือไม่เกิน ๐.๑๐ มิลลิกรัมต่อลูกบาศก์เมตร

ข้อ ๓ การคำนวณค่าความเข้มข้นของก๊าซแต่ละชนิดในบรรยากาศโดยทั่วไปให้คำนวณเทียบที่ความดัน ๑ บรรยากาศ และอุณหภูมิ ๒๕ องศาเซลเซียส

ข้อ ๔ ค่าสารในบรรยากาศโดยทั่วไป ในช่วงเวลาหนึ่งเวลาใดให้เป็นไปดังต่อไปนี้

(๑) ค่าเฉลี่ยของตะกั่วในเวลา ๑ เดือน จะต้องไม่เกิน ๑.๕ ไมโครกรัมต่อลูกบาศก์เมตร

(๒) ค่าเฉลี่ยของฝุ่นละอองขนาดไม่เกิน ๑๐ ไมครอน ในเวลา ๒๔ ชั่วโมง จะต้องไม่เกิน ๐.๑๒ มิลลิกรัมต่อลูกบาศก์เมตร และค่ามัธยิมเรขาคณิตของสารดังกล่าวในเวลา ๑ ปี จะต้องไม่เกิน ๐.๑๕ มิลลิกรัมต่อลูกบาศก์เมตร

(๓) ค่าเฉลี่ยของฝุ่นละอองรวมหรือฝุ่นละอองขนาดเล็กไม่เกิน ๑๐๐ ไมครอน ในเวลา ๒๔ ชั่วโมง จะต้องไม่เกิน ๐.๓๓ มิลลิกรัมต่อลูกบาศก์เมตร และค่ามัธยฐานเรขาคณิตของสารดังกล่าวในเวลา ๑ ปี จะต้องไม่เกิน ๐.๑๐ มิลลิกรัมต่อลูกบาศก์เมตร

ข้อ ๕ การวัดหาค่าเฉลี่ยของก๊าซคาร์บอนมอนอกไซด์ในเวลา ๑ ชั่วโมงหรือในเวลา ๘ ชั่วโมง ให้ใช้เครื่องวัดระบบนันทิสเปอร์ซีฟ อินฟราเรด ดีเทคชั่น หรือระบบอื่นที่กรมควบคุมมลพิษให้ความเห็นชอบ

ข้อ ๖ การวัดหาค่าเฉลี่ยของก๊าซไนโตรเจนไดออกไซด์หรือก๊าซโอโซนในเวลา ๑ ชั่วโมง ให้ใช้เครื่องวัดระบบเคมีลูมิเนสเซน หรือระบบอื่นที่กรมควบคุมมลพิษให้ความเห็นชอบ

ข้อ ๗ การวัดหาค่าเฉลี่ยของก๊าซซัลเฟอร์ไดออกไซด์ในเวลา ๒๔ ชั่วโมง หรือในเวลา ๑ ปี ให้ใช้วิธีการวัดตามระบบพาราโรซานิลิน หรือระบบอื่นที่กรมควบคุมมลพิษให้ความเห็นชอบ

ข้อ ๘ การวัดหาค่าเฉลี่ยของตะกั่วในเวลา ๑ เดือน ให้เก็บอากาศผ่านแผ่นกรองในเครื่องเก็บตัวอย่างอากาศชนิดไฮวอลุ่ม (High Volume-Air Sampler) สกัดตะกั่วออกจากแผ่นกรองโดยใช้กรดดินประสิวและกรดเกลือ แล้วนำไปวัดค่าของตะกั่วโดยใช้เครื่องวัดระบบอะตอมมิก แอบซอร์ปชัน สเปกโตรมิเตอร์ หรือระบบอื่นที่กรมควบคุมมลพิษให้ความเห็นชอบ

ข้อ ๙ การวัดหาค่าเฉลี่ยของฝุ่นละอองรวมหรือฝุ่นละอองขนาดเล็กไม่เกิน ๑๐ ไมครอน ในเวลา ๒๔ ชั่วโมง หรือในเวลา ๑ ปี ให้ใช้วิธีการวัดตามระบบกราวิเมตริก หรือระบบอื่นที่กรมควบคุมมลพิษให้ความเห็นชอบ

ข้อ ๑๐ การวัดหาค่าเฉลี่ยของก๊าซหรือสารอย่างหนึ่งอย่างใดตามข้อ ๕ ถึงข้อ ๗ ให้ทำในบรรยากาศทั่วๆ ไป และต้องสูงจากพื้นดินอย่างน้อย ๓ เมตร แต่ไม่เกิน ๖ เมตร

การวัดหาค่าเฉลี่ยของตะกั่วและฝุ่นละอองตามข้อ ๘ และข้อ ๙ ให้ทำในบรรยากาศทั่วๆ ไป และต้องสูงจากพื้นดินอย่างน้อย ๑.๕๐ เมตร แต่ไม่เกิน ๖ เมตร

ประกาศ ณ วันที่ ๑๗ เมษายน พ.ศ. ๒๕๓๘

ชวน หลีกภัย

นายกรัฐมนตรี

ประธานคณะกรรมการสิ่งแวดล้อมแห่งชาติ

(ประกาศในราชกิจจานุเบกษา เล่ม ๑๑๒ ตอนที่ ๔๒ ง วันที่ ๒๕ พฤษภาคม ๒๕๓๘)

แก้คำผิด

ประกาศคณะกรรมการสิ่งแวดล้อมแห่งชาติ
ฉบับที่ ๑๐ (พ.ศ. ๒๕๓๘) ออกตามความในพระราชบัญญัติส่งเสริมและรักษา
คุณภาพสิ่งแวดล้อมแห่งชาติ พ.ศ. ๒๕๓๕

เรื่อง กำหนดมาตรฐานคุณภาพอากาศในบรรยากาศโดยทั่วไป
ซึ่งประกาศในราชกิจจานุเบกษา

ฉบับประกาศทั่วไป เล่ม ๑๑๒ ตอนที่ ๔๒ ง ลงวันที่ ๒๕ พฤษภาคม ๒๕๓๘

หน้า ๕๑ บรรทัดที่ ๑๕ คำว่า

“ไม่เกิน ๐.๑๕ มิลลิกรัม” ให้แก้เป็น

“ไม่เกิน ๐.๐๕ มิลลิกรัม”

(ประกาศในราชกิจจานุเบกษา เล่ม ๑๑๒ ตอนที่ ๗๑ ง วันที่ ๕ กันยายน ๒๕๓๘)