

ภาคผนวก ค
รายงานผลการตรวจวัดคุณภาพน้ำ

รายงานผลการตรวจวัดคุณภาพน้ำ
เดือนมกราคม พ.ศ. 2569

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : JANUARY 8, 2026
SAMPLING TIME : 09:22 HOUR
SAMPLING METHOD ° : GRAB
SAMPLING BY ° : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : JANUARY 9, 2026
ANALYTICAL DATE : JANUARY 9-15, 2026
ISSUE DATE : JANUARY 27, 2026
REPORT NO. : 2026-U003786
WORK NO. : 2025-009061
ANALYSIS NO. : T26AA262-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาทน้ำทิ้งบริเวณหลังผ่านระบบบำบัดน้ำเสียส่วนกลาง T26AA262-0001			
pH [®]	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.6 (27.8°C)	5.5-9.0	-	-
SETTLEABLE SOLIDS [°]	ml/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	36.3	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	37.1	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	468	≤ 1,000	-	25
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^p	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	79.2	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	3	≤ 20	-	3



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาทน้ำทิ้งบริเวณหลังผ่านระบบบำบัดน้ำเสียส่วนกลาง T26AA262-0001			
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	160,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			BROWN/TURBID			
SEDIMENT			BLUE			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

[Redacted Signature]

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : JANUARY 8, 2026
SAMPLING TIME : 09:35 HOUR
SAMPLING METHOD ° : GRAB
SAMPLING BY ° : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : JANUARY 9, 2026
ANALYTICAL DATE : JANUARY 9-15, 2026
ISSUE DATE : JANUARY 27, 2026
REPORT NO. : 2026-U003787
WORK NO. : 2025-009061
ANALYSIS NO. : T26AA262-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ไม่พบน้ำทิ้งบริเวณก่อนระบายออกจากพื้นที่โครงการ T26AA262-0002			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	8.0 (28.6°C)	5.5-9.0	-	-
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	15.7	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	9.4	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	332	≤ 1,000	-	25
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	2.1	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	25.9	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			บ่อพักน้ำทิ้งบริเวณก่อนระบายออกจากพื้นที่โครงการ T26AA262-0002			
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	>160,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/TURBID			
SEDIMENT			GREY			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

รายงานผลการตรวจวัดคุณภาพน้ำ
เดือนกุมภาพันธ์ พ.ศ. 2569

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : FEBRUARY 5, 2026
SAMPLING TIME : 10:20 HOUR
SAMPLING METHOD ^c : GRAB
SAMPLING BY ^c : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : FEBRUARY 5, 2026
ANALYTICAL DATE : FEBRUARY 5-12, 2026
ISSUE DATE : FEBRUARY 13, 2026
REPORT NO. : 2026-U011404
WORK NO. : 2025-009061
ANALYSIS NO. : T26AC297-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาททั้งบริเวณแหล่ง ผ่านระบบบำบัดน้ำเสีย ส่วนกลาง T26AC297-0001			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.3 (29.5°C)	5.5-9.0	-	-
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	27.3	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	55.4	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	502	≤ 1,000	-	25
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ -F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	80.4	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			บ่อพักน้ำทิ้งบริเวณหลังผ่านระบบบำบัดน้ำเสียส่วนกลาง T26AC297-0001			
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	54,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			GREY/TURBID			
SEDIMENT			GREY			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

[Redacted Signature]

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : FEBRUARY 5, 2026
SAMPLING TIME : 10:00 HOUR
SAMPLING METHOD ^c : GRAB
SAMPLING BY ^c : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : FEBRUARY 5, 2026
ANALYTICAL DATE : FEBRUARY 5-12, 2026
ISSUE DATE : FEBRUARY 13, 2026
REPORT NO. : 2026-U011405
WORK NO. : 2025-009061
ANALYSIS NO. : T26AC297-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาททั้งบริเวณก่อน ระบายออกจากพื้นที่ โครงการ T26AC297-0002			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.8 (30.6°C)	5.5-9.0	-	-
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	26.2	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	12.6	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	459	≤ 1,000	-	25
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	0.54	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	38.6	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ปอพักน้ำทิ้งบริเวณก่อนระบายออกจากพื้นที่โครงการ T26AC297-0002			
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	>160,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			GREY/CLEAR			
SEDIMENT			GREY			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.

[Redacted Signature]

(MISS WILAILAK SRISUK)
LABORATORY SUPERVISOR

รายงานผลการตรวจวัดคุณภาพน้ำ
เดือนมีนาคม พ.ศ. 2569

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : MARCH 5, 2026
SAMPLING TIME : 09:30 HOUR
SAMPLING METHOD ^c : GRAB
SAMPLING BY ^c : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : MARCH 5, 2026
ANALYTICAL DATE : MARCH 5-12, 2026
ISSUE DATE : MARCH 16, 2026
REPORT NO. : 2026-U019167
WORK NO. : 2025-009061
ANALYSIS NO. : T26AE462-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาททั้งบริเวณหลังผ่านระบบบำบัดน้ำเสียส่วนกลาง T26AE462-0001			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.4 (31.6°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	20.8	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	20.5	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	500	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE TP:WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	79.2	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	22,000	-	18	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/TURBID			
SEDIMENT			BLACK			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : MARCH 5, 2026
SAMPLING TIME : 09:20 HOUR
SAMPLING METHOD ^c : GRAB
SAMPLING BY ^c : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : MARCH 5, 2026
ANALYTICAL DATE : MARCH 5-12, 2026
ISSUE DATE : MARCH 16, 2026
REPORT NO. : 2026-U019168
WORK NO. : 2025-009061
ANALYSIS NO. : T26AE462-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ปอพักน้ำทั้งบริเวณก่อนระบายออกจากพื้นที่โครงการ T26AE462-0002			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.7 (31.9°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	21.1	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	6.0	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	443	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	27.3	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3



PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ปล่อยน้ำทิ้งบริเวณก่อนระบายออกจากพื้นที่โครงการ T26AE462-0002			
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	>160,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/CLEAR			
SEDIMENT			BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR

รายงานผลการตรวจวัดคุณภาพน้ำ
เดือนเมษายน พ.ศ. 2569

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : APRIL 9, 2026
SAMPLING TIME : 09:50 HOUR
SAMPLING METHOD : GRAB, GRAB AND STERILE TECHNIQUE
SAMPLING BY : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : APRIL 9, 2026
ANALYTICAL DATE : APRIL 9-22, 2026
ISSUE DATE : APRIL 24, 2026
REPORT NO. : 2026-U032428
WORK NO. : 2025-009061
ANALYSIS NO. : T26AH789-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาทนี้ทั้งบริเวณหลังผ่านระบบบำบัดน้ำเสียส่วนกลาง T26AH789-0001			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H* B AND 1060 B	7.3 (33.5°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	36.9	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	29.9	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	426	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ² -F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	73.8	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	13,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/TURBID			
SEDIMENT			BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : APRIL 9, 2026
SAMPLING TIME : 09:40 HOUR
SAMPLING METHOD : GRAB, GRAB AND STERILE TECHNIQUE
SAMPLING BY : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : APRIL 9, 2026
ANALYTICAL DATE : APRIL 9-22, 2026
ISSUE DATE : APRIL 24, 2026
REPORT NO. : 2026-U032429
WORK NO. : 2025-009061
ANALYSIS NO. : T26AH789-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาทที่จังหวัดขอนแก่น ระบายนอกจากพื้นที่ โครงการ T26AH789-0002			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H* B AND 1060 B	7.6 (35.0°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	22.1	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	10.2	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	421	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ² -F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	27.2	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	92,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/TURBID			
SEDIMENT			GREY			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR



รายงานผลการตรวจวัดคุณภาพน้ำ
เดือนพฤษภาคม พ.ศ. 2569

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : MAY 14, 2026
SAMPLING TIME : 09:30 HOUR
SAMPLING METHOD : GRAB, GRAB AND STERILE TECHNIQUE
SAMPLING BY : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM

RECEIVED DATE : MAY 14, 2026
ANALYTICAL DATE : MAY 14-22, 2026
ISSUE DATE : MAY 25, 2026
REPORT NO. : 2026-U043058
WORK NO. : 2025-009061
ANALYSIS NO. : T26AK388-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาททั้งบริเวณแหล่ง ผ่านระบบบำบัดน้ำเสีย ส่วนกลาง T26AK388-0001			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.1 (33.1°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	13.4	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	16.9	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	518	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	70.8	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	54,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/TURBID			
SEDIMENT			BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR



ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : MAY 14, 2026
SAMPLING TIME : 09:20 HOUR
SAMPLING METHOD : GRAB, GRAB AND STERILE TECHNIQUE
SAMPLING BY : MR WEERAYUT MOKKAEW
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : MAY 14, 2026
ANALYTICAL DATE : MAY 14-22, 2026
ISSUE DATE : MAY 25, 2026
REPORT NO. : 2026-U043060
WORK NO. : 2025-009061
ANALYSIS NO. : T26AK388-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			มื่อพักน้ำที่บริเวณก่อนระบายออกจากพื้นที่โครงการ T26AK388-0002			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H ⁺ B AND 1060 B	7.6 (32.5°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	6.1	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	28.5	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	484	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ²⁻ F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	40.0	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	>160,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/CLEAR			
SEDIMENT			BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR

รายงานผลการตรวจวัดคุณภาพน้ำ
เดือนมิถุนายน พ.ศ. 2569

ANALYSIS REPORT

CUSTOMER NAME : NATIONAL HOUSING AUTHORITY
ADDRESS : 905 KHLONG CHAN BANG KAPI BANGKOK 10240
CONTACT INFORMATION : TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th
SAMPLING SOURCE : -
SAMPLE TYPE : EFFLUENT
SAMPLING DATE : JUNE 11, 2026
SAMPLING TIME : 09:00 HOUR
SAMPLING METHOD : GRAB, GRAB AND STERILE TECHNIQUE
SAMPLING BY : MISS NATCHA TAWPAP
ANALYZED BY : MISS NAPAPORN KHUNNOKKHUM
RECEIVED DATE : JUNE 11, 2026
ANALYTICAL DATE : JUNE 11-19, 2026
ISSUE DATE : JUNE 23, 2026
REPORT NO. : 2026-U054377
WORK NO. : 2025-009061
ANALYSIS NO. : T26AM926-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาททั้งบริเวณแหล่งผ่านระบบบำบัดน้ำเสียส่วนกลาง T26AM926-0001			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H* B AND 1060 B	7.4 (32.1°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	12.3	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	8.6	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	569	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ² F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	64.0	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	54,000	-	18	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/CLEAR			
SEDIMENT			BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR

ISO 9001:2015 CERTIFIED
ISO 14001:2015 CERTIFIED
ISO 45001:2018 CERTIFIED

• PROHIBITED TO PARTIALLY COPY ANALYSIS REPORT PRIOR TO WRITTEN PERMISSION BY THE LABORATORY.
• THIS ANALYSIS REPORT APPROVES ONLY FOR THE SAMPLES AS RECEIVED.



ANALYSIS REPORT

CUSTOMER NAME	: NATIONAL HOUSING AUTHORITY	RECEIVED DATE	: JUNE 11, 2026
ADDRESS	: 905 KHLONG CHAN BANG KAPI BANGKOK 10240	ANALYTICAL DATE	: JUNE 11-19, 2026
CONTACT INFORMATION	: TEL : 08 1935 3678 e-mail : panuwat_tho@nha.co.th	ISSUE DATE	: JUNE 23, 2026
SAMPLING SOURCE	: -	REPORT NO.	: 2026-U054378
SAMPLE TYPE	: EFFLUENT	WORK NO.	: 2025-009061
SAMPLING DATE	: JUNE 11, 2026	ANALYSIS NO.	: T26AM926-0002
SAMPLING TIME	: 08:55 HOUR		
SAMPLING METHOD	: GRAB, GRAB AND STERILE TECHNIQUE		
SAMPLING BY	: MISS NATCHA TAWPAP		
ANALYZED BY	: MISS NAPAPORN KHUNNOKKHUM		

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	REGULATORY STANDARD	DETECTION LIMIT	LIMIT OF QUANTITATION (LOQ)
			ข้อพิพาททั้งบริเวณก่อน ระบายนอกจากพื้นที่ โครงการ T26AM926-0002			
pH ^a	-	ELECTROMETRIC METHOD (AT SITE) SM: PART 4500-H* B AND 1060 B	7.7 (33.1°C)	5.5-9.0	-	-
BIOCHEMICAL OXYGEN DEMAND ^a	mg/L	MEMBRANE ELECTRODE METHOD (SM: PART 5210 B AND PART 4500-O G)	13.0	≤ 30	-	2.0
TOTAL SUSPENDED SOLIDS ^a	mg/L	TOTAL SUSPENDED SOLIDS DRIED FROM 103 TO 105 °C (SM: PART 2540 D)	8.2	≤ 40	-	5.0
TOTAL DISSOLVED SOLIDS ^b	mg/L	TOTAL DISSOLVED SOLIDS DRIED AT 180 °C (SM: PART 2540 C)	350	≤ 1,000	-	25
SETTLABLE SOLIDS ^c	mL/L	IMHOFF CONE (SM: PART 2540 F)	< 0.1	-	0.1	-
SULPHIDE ^b	mg/L	IODOMETRIC METHOD (SM: PART 4500-S ² F)	< 0.50	≤ 1.0	-	0.50
TOTAL KJELDAHL NITROGEN ^b	mg/L	IN-HOUSE METHOD: UAE.TP.WAS.001 (KJELDAHL METHOD); SM: PART 4500-Norg C	18.7	≤ 35	1.5	5.0
OIL AND GREASE ^a	mg/L	LIQUID-LIQUID, PARTITION-GRAVIMETRIC METHOD (SM: PART 5520 B)	< 3	≤ 20	-	3
MICROBIOLOGY						
FAECAL COLIFORMS ^b	MPN/100 mL	MULTIPLE-TUBE FERMENTATION TECHNIQUE (SM: PART 9221 B, C AND E)	>160,000	-	1.8	-
SAMPLE CONDITION						
WATER'S COLOUR/TURBID			YELLOW/TURBID			
SEDIMENT			BROWN			

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT NOT IN SCOPE OF ACCREDITATION

SM : STANDARD METHODS FOR THE EXAMINATION OF WATER AND WASTEWATER, APHA, AWWA, WEF, 24th EDITION, 2023.

REGULATORY STANDARD : RANGE OR MAXIMUM PERMITTED VALUE FOR BUILDING EFFLUENT STANDARDS CLASS B, NOTIFICATION OF THE MINISTRY OF RESOURCES AND ENVIRONMENT, PUBLISHED IN THE ROYAL GOVERNMENT GAZETTE, VOL 141, PART 233 D, DATED AUGUST 27, 2024.



(MISS CHAWEEWAN BOONLA)
LABORATORY SUPERVISOR

ISO 9001:2015 CERTIFIED
ISO 14001:2015 CERTIFIED
ISO 45001:2018 CERTIFIED

• PROHIBITED TO PARTIALLY COPY ANALYSIS REPORT PRIOR TO WRITTEN PERMISSION BY THE LABORATORY.
• THIS ANALYSIS REPORT APPROVES ONLY FOR THE SAMPLES AS RECEIVED.

