

ภาคผนวก

ภาคผนวกที่	1	ผลการติดตามตรวจสอบคุณภาพสิ่งแวดล้อม
ภาคผนวกที่	2	เอกสารขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน และใบอนุญาตเป็นผู้ให้บริการตรวจวัดและวิเคราะห์ระดับความเข้มข้นของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตรายระดับความร้อน แสงสว่าง และเสียง จากกรมสวัสดิการและคุ้มครองแรงงาน
ภาคผนวกที่	3	ใบรับรองความสามารถห้องปฏิบัติการ
ภาคผนวกที่	4	สรุปเอกสารการสอบเทียบอุปกรณ์เครื่องมือ
ภาคผนวกที่	5	เอกสาร Detection Limit ของรายการทดสอบ
ภาคผนวกที่	6	ผลการพิจารณารายงานการประเมินผลกระทบสิ่งแวดล้อมของโครงการ
ภาคผนวกที่	7	หนังสือแจ้งขอเปลี่ยนแปลงรายละเอียดโครงการ
ภาคผนวกที่	8	เอกสารตรวจสอบระบบระบายอากาศ
ภาคผนวกที่	9	เอกสารตรวจสอบอุปกรณ์เครื่องใช้ไฟฟ้า และเครื่องจักร
ภาคผนวกที่	10	สรุปปริมาณน้ำเสีย ประจำเดือนมกราคม-มิถุนายน 2569
ภาคผนวกที่	11	เอกสารการซ่อมบำรุงอุปกรณ์ของระบบบำบัดน้ำเสีย
ภาคผนวกที่	12	เอกสารตรวจสอบหม้อแปลงไฟฟ้าโดยเจ้าหน้าที่การไฟฟ้าส่วนภูมิภาค
ภาคผนวกที่	13	สรุปปริมาณขยะมูลฝอย ประจำเดือนมกราคม-มิถุนายน 2569
ภาคผนวกที่	14	บันทึกจำนวนผู้เข้าพักโรงแรม
ภาคผนวกที่	15	แผนป้องกันและระงับอัคคีภัย และเอกสารซ่อมแผนอพยพหนีไฟประจำปี 2568
ภาคผนวกที่	16	เอกสารการตรวจสอบระบบป้องกันอัคคีภัย ประจำเดือนมกราคม-มิถุนายน 2569
ภาคผนวกที่	17	ผังจราจร
ภาคผนวกที่	18	เอกสารตรวจสอบระบบท่อในอาคาร
ภาคผนวกที่	19	หนังสือตอบรับการส่งรายงานการปฏิบัติตามมาตรการป้องกันแก้ไข และลดผลกระทบสิ่งแวดล้อมและติดตามตรวจสอบผลกระทบ สิ่งแวดล้อม ประจำเดือนกรกฎาคม-ธันวาคม 2568
ภาคผนวกที่	20	ผลการตรวจวัด pH Meter และ Free and Total Chlorine ประจำเดือนมกราคม-มิถุนายน 2569

ภาคผนวกที่ 1

ผลการติดตามตรวจสอบคุณภาพสิ่งแวดล้อม

Test Report

Request No : W6902004

Report No : 6902-1198

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69020014

Sample Name : น้ำสระว่ายน้ำ

Sampling Date : 31/01/2026

Sampling By : ETC

Sampling Time : 8:50 AM

Sampling Method : Grab

Received Date : 02/02/2026

Tested Date : 02/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result	Standard/ ¹
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	≤10
Fecal Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221E)	ND	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1./1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550


เรื่องการควบคุมการประกอบกิจการสระว่ายน้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , Fecal Coliform Bacteria = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6902004

Report No : 6902-1199

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69020015

Sample Name : ดึงเก็บน้ำ

Sampling Date : 31/01/2026

Sampling By : ETC

Sampling Time : 8:40 AM

Sampling Method : Grab

Received Date : 02/02/2026

Tested Date : 02/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result	Standard/I
E.coli	MPN:100 mL	MPN Test Method (SM:9221F)	ND	ไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1. /I Water Supply of Provincial Waterworks Authority (WHO 2017)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of E.coli = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6902004

Report No : 6902-1200

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69020016

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 31/01/2026 **

Sampling By : ETC **

Sampling Time : 9:10 AM **

Sampling Method : Grab **

Received Date : 02/02/2026

Tested Date : 02/02/2026 - 17/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	153
Oil and Grease *	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	36.5
pH (on site) *		Electrometric Method	6.1
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S ₂ - F)	4.90
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	25
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	302
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	95

Physical Apperance : 1. Sample : Wastewater (ycllow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ท-0034)*

4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ท-0007)

18/02/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ท-0005)

18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902004

Report No : 6902-1200

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69020016

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 31/01/2026 **

Sampling By : ETC **

Sampling Time : 9:10 AM **

Sampling Method : Grab **

Received Date : 02/02/2026

Tested Date : 02/02/2026 - 17/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	581

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ท-0034)*


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ท-0007)

18/02/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ท-0005)

18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6902004

Report No : 6902-1200

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69020016

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย

Sampling Date : 31/01/2026

Sampling By : ETC

Sampling Time : 9:10 AM

Sampling Method : Grab

Received Date : 02/02/2026

Tested Date : 02/02/2026 - 17/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	12.0


Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Parameter Outside The Scope of The Registration of Department of Industrial Works

3. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6902004

Report No : 6902-1201

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69020017
Sample Name : น้ำออกกระบบบำบัดน้ำเสีย ** Sampling Date : 31/01/2026 **
Sampling By : ETC ** Sampling Time : 9:00 AM **
Sampling Method : Grab ** Received Date : 02/02/2026
Tested Date : 02/02/2026 - 17/02/2026 Reported Date : 18/02/2026


Parameter	Unit	Method	Result	Standard ^{1/}
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	9.2	≤20
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	< 3.0	≤20
pH (on site) *		Electrometric Method	6.5	5.5-9.0
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	3.82	≤1
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	26	-
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	174	≤1000
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	9	≤35

Physical Apperance : 1. Sample : Wastewater (yellow , lightlth SS)
2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม
เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)
2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,
SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.
3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.
4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *
5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)
(จ-003-ค-0007)
18/02/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)
(จ-003-ค-0005)
18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902004

Report No : 6902-1201

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69020017

Sample Name : น้ำออกระบบบำบัดน้ำเสีย **

Sampling Date : 31/01/2026 **

Sampling By : ETC **

Sampling Time : 9:00 AM **

Sampling Method : Grab **

Received Date : 02/02/2026

Tested Date : 02/02/2026 - 17/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result	Standard ¹
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	7	≤30

Physical Apperance : 1. Sample : Wastewater (yellow , lightlh SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.


4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *

5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)
(จ-003-ค-0007)

18/02/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)
(จ-003-ค-0005)

18/02/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902004

Report No : 6902-1201

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakhon 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69020017

Sample Name : น้ำออกกระบบบำบัดน้ำเสีย

Sampling Date : 31/01/2026

Sampling By : ETC

Sampling Time : 9:00 AM

Sampling Method : Grab

Received Date : 02/02/2026

Tested Date : 02/02/2026 - 17/02/2026

Reported Date : 18/02/2026

Parameter	Unit	Method	Result	Standard ¹
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2	-

Physical Apperance : 1. Sample : Wastewater (yellow , lightth SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

18/02/2026

Test Report

Request No : W6902526

Report No : 6903-0435

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69021658

Sample Name : น้ำสระว่ายน้ำ

Sampling Date : 23/02/2026

Sampling By : ETC

Sampling Time : 11:15 AM

Sampling Method : Grab

Received Date : 24/02/2026

Tested Date : 04/03/2026

Reported Date : 10/03/2026

Parameter	Unit	Method	Result	Standard ¹
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	≤10
Fecal Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221E)	ND	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1./1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550


เรื่องการควบคุมการประกอบกิจการสระว่ายน้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , Fecal Coliform Bacteria = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

10/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902526

Report No : 6903-0436

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69021659

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 23/02/2026 **

Sampling By : ETC **

Sampling Time : 11:40 AM **

Sampling Method : Grab **

Received Date : 24/02/2026

Tested Date : 24/02/2026 - 05/03/2026

Reported Date : 10/03/2026

Parameter	Unit	Method	Result
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	102
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	17.0
pH (on site) *		Electrometric Method	6.6
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500-S2-F)	2.63
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	30
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	318
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	53

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *

4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

10/03/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

10/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling By : ETC **

Sampling Method : Grab **

Tested Date : 24/02/2026 - 05/03/2026

Sample No : W 69021659

Sampling Date : 23/02/2026 **

Sampling Time : 11:40 AM **

Received Date : 24/02/2026

Reported Date : 10/03/2026

Parameter	Unit	Method	Result
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	111

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *


4. ** = These data are non laboratory data.

Examined By : 


(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

10/03/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By : 

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

10/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902526

Report No : 6903-0436

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69021659

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย

Sampling Date : 23/02/2026

Sampling By : ETC

Sampling Time : 11:40 AM

Sampling Method : Grab

Received Date : 24/02/2026

Tested Date : 24/02/2026 - 05/03/2026

Reported Date : 10/03/2026

Parameter	Unit	Method	Result
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	0.2


Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Parameter Outside The Scope of The Registration of Department of Industrial Works

3. Sampling By Mr. Aocha Khwansirimongkhon



Examined By :

(Miss Apiradee Chuen-arom)

10/03/2026

บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902526

Report No : 6903-0437

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69021660
Sample Name : น้ำออกกระบบบำบัดน้ำเสีย ** Sampling Date : 23/02/2026 **
Sampling By : ETC ** Sampling Time : 11:30 AM **
Sampling Method : Grab ** Received Date : 24/02/2026
Tested Date : 24/02/2026 - 05/03/2026 Reported Date : 10/03/2026

Parameter	Unit	Method	Result	Standard ¹
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	8.1	≤20
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	< 3.0	≤20
pH (on site) *		Electrometric Method	7.2	5.5-9.0
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	0.75	≤1
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	30	-
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	186	≤1000
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	9	≤35

Physical Appearance : 1. Sample : Wastewater (yellowish , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI, # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *

5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

10/03/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

10/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample Name : น้ำออกระบบบำบัดน้ำเสีย **

Sampling By : ETC **

Sampling Method : Grab **

Tested Date : 24/02/2026 - 05/03/2026

Sample No : W 69021660

Sampling Date : 23/02/2026 **

Sampling Time : 11:30 AM **

Received Date : 24/02/2026

Reported Date : 10/03/2026

Request No : W6902526

Report No : 6903-0437

Parameter	Unit	Method	Result	Standard/l
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	6	≤30

Physical Apperance : 1. Sample : Wastewater (yellowish , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.


3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *

5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)
(จ-003-ค-0007)
10/03/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)
(จ-003-ค-0005)
10/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902526

Report No : 6903-0437

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakhon 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69021660

Sample Name : น้ำออกระบบบำบัดน้ำเสีย

Sampling Date : 23/02/2026

Sampling By : ETC

Sampling Time : 11:30 AM

Sampling Method : Grab

Received Date : 24/02/2026

Tested Date : 24/02/2026 - 05/03/2026

Reported Date : 10/03/2026

Parameter	Unit	Method	Result	Standard ¹
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2	-

Physical Apperance : 1. Sample : Wastewater (ycllowish , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]


Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Deparument of Industrial Works

4. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

10/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902521

Report No : 6903-0753

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69021632

Sample Name : น้ำสระว่ายน้ำ

Sampling Date : 23/02/2026

Sampling By : ETC

Sampling Time : 11:15 AM

Sampling Method : Grab

Received Date : 24/02/2026

Tested Date : 14/03/2026

Reported Date : 16/03/2026

Parameter	Unit	Method	Result	Standard/ ¹
Legionella pneumophila #	CFU/1000 mL	ISO 11731:2017	1,600	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)


2. Container : Normal [G 1.0 L]

Remark : 1./1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550

เรื่องการควบคุมการประกอบกิจการสระว่ายน้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. # Tested by the office of Public Health and Environmental Technology Services Faculty of Public Health Mahidol University

3. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

16/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
 THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902521

Report No : 6903-0754

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69021633

Sample Name : ป้อออนเซ็น (ชาย)

Sampling Date : 23/02/2026

Sampling By : ETC

Sampling Time : 11:20 AM

Sampling Method : Grab

Received Date : 24/02/2026

Tested Date : 14/03/2026

Reported Date : 16/03/2026

Parameter	Unit	Method	Result	Standard ¹
Legionella pneumophila #	CFU/1000 mL	ISO 11731:2017	20,000	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)


2. Container : Normal [G 1.0 L]

Remark : 1./1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550

เรื่องการควบคุมการประกอบกิจการสระว่ายน้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. # Tested by the office of Public Health and Environmental Technology Services Faculty of Public Health Mahidol University

3. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By : (Miss Apiradee Chuen-arom)
16/03/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6902521

Report No : 6903-0755

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69021634

Sample Name : Store Tank

Sampling Date : 23/02/2026

Sampling By : ETC

Sampling Time : 11:10 AM

Sampling Method : Grab

Received Date : 24/02/2026

Tested Date : 14/03/2026

Reported Date : 16/03/2026

Parameter	Unit	Method	Result	Standard/1
Legionella pneumophila #	CFU/1000 mL	ISO 11731:2017	<60	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)


2. Container : Normal [G 1.0 L]

Remark : 1. /1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550

เรื่องการควบคุมการประกอบกิจการสระว่ายน้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. # Tested by the office of Public Health and Environmental Technology Services Faculty of Public Health Mahidol University

3. Sampling By Mr. Aocha Khwansirimongkhon



Examined By :

(Miss Apiradee Chuen-arom)
16/03/2026

บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0448

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69031747

Sample Name : น้ำสระเวย์น้ำ

Sampling Date : 23/03/2026

Sampling By : ETC

Sampling Time : 11:18 AM

Sampling Method : Grab

Received Date : 24/03/2026

Tested Date : 30/03/2026

Reported Date : 09/04/2026

Parameter	Unit	Method	Result	Standard ¹
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	≤10
Fecal Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221E)	ND	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1./1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550


เรื่องการควบคุมการประกอบกิจการสระเวย์น้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , Fecal Coliform Bacteria = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Supharerk Phatklang



Examined By :

(Miss Apiradee Chuen-arom)

09/04/2026

บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0449

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69031748

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 23/03/2026 **

Sampling By : ETC **

Sampling Time : 11:35 AM **

Sampling Method : Grab **

Received Date : 24/03/2026

Tested Date : 24/03/2026 - 07/04/2026

Reported Date : 09/04/2026

Parameter	Unit	Method	Result
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	341
Oil and Grease *	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	64.0
pH (on site) *		Electrometric Method	6.8
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	21.9
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	29
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	336
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	188

Physical Apperance : 1. Sample : Wastewater (yellow , medium SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Supharerk Phatklang (จ-003-ก-0031) *


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ก-0007)

09/04/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ก-0005)

09/04/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0449

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69031748

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 23/03/2026 **

Sampling By : ETC **

Sampling Time : 11:35 AM **

Sampling Method : Grab **

Received Date : 24/03/2026

Tested Date : 24/03/2026 - 07/04/2026

Reported Date : 09/04/2026

Parameter	Unit	Method	Result
Total Suspended Solids *	mg/L	Dried at 103-105 degree celsius (SM:2540D)	7,866

Physical Apperance : 1. Sample : Wastewater (yellow , medium SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Supharerk Phatklang (จ-003-ท-0031) *


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ท-0007)

09/04/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ท-0005)

09/04/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0449

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69031748

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย

Sampling Date : 23/03/2026

Sampling By : ETC

Sampling Time : 11:35 AM

Sampling Method : Grab

Received Date : 24/03/2026

Tested Date : 24/03/2026 - 07/04/2026

Reported Date : 09/04/2026

Parameter	Unit	Method	Result
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	160


Physical Apperance : 1. Sample : Wastewater (yellow , medium SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Parameter Outside The Scope of The Registration of Department of Industrial Works

3. Sampling By Mr. Supharerk Phatklang



Examined By :

(Miss Apiradee Chuen-arom)
09/04/2026

บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0450

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69031749
Sample Name : น้ำออกระบบบำบัดน้ำเสีย ** Sampling Date : 23/03/2026 **
Sampling By : ETC ** Sampling Time : 11:30 AM **
Sampling Method : Grab ** Received Date : 24/03/2026
Tested Date : 24/03/2026 - 07/04/2026 Reported Date : 09/04/2026

Parameter	Unit	Method	Result	Standard ¹
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	2.7	≤20
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	< 3.0	≤20
pH (on site) *		Electrometric Method	7.1	5.5-9.0
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	< 0.50	≤1
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	29	-
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	164	≤1000
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	< 5	≤35

Physical Apperance : 1. Sample : Wastewater (yellowish , lightly SS)
2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]


Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

- @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,
SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.
- Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.
- * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Supharerk Phatklang (จ-003-ค-0031) *
- ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)
(จ-003-ค-0007)
09/04/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)
(จ-003-ค-0005)
09/04/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0450

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69031749
Sample Name : น้ำออกกระบบบำบัดน้ำเสีย ** Sampling Date : 23/03/2026 **
Sampling By : ETC ** Sampling Time : 11:30 AM **
Sampling Method : Grab ** Received Date : 24/03/2026
Tested Date : 24/03/2026 - 07/04/2026 Reported Date : 09/04/2026

Parameter	Unit	Method	Result	Standard ¹
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	< 5	≤ 30

Physical Apperance : 1. Sample : Wastewater (yellowish , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]

Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Supharerk Phatklang (จ-003-ค-0031) *


5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

09/04/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

09/04/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904- 0450

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69031749

Sample Name : น้ำออกระบบบำบัดน้ำเสีย

Sampling Date : 23/03/2026

Sampling By : ETC

Sampling Time : 11:30 AM

Sampling Method : Grab

Received Date : 24/03/2026

Tested Date : 24/03/2026 - 07/04/2026

Reported Date : 09/04/2026

Parameter	Unit	Method	Result	Standard/ ¹
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2	-

Physical Apperance : 1. Sample : Wastewater (yellowish , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.8 L, G 1.0 L]


Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. Sampling By Mr. Supharerk Phatklang



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

09/04/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6903579

Report No : 6904-0451

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69031750

Sample Name : น้ำดื่ม

Sampling Date : 23/03/2026

Sampling By : ETC

Sampling Time : 11:20 AM

Sampling Method : Grab

Received Date : 24/03/2026

Tested Date : 30/03/2026

Reported Date : 09/04/2026

Parameter	Unit	Method	Result	Standard ¹
C.perfringens	CFU:100 mL	Compendium 2003 , Chapter 34	ND	-
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	<1.1
E.coli	MPN:100 mL	MPN Test Method (SM:9221F)	ND	<1.1
S.aureus	colonies/100 mL	AWWA (2017) (SM:9213 B)	ND	-
Salmonella sp.	colonies/100 mL	AWWA (2017) (SM:9260 B)	ND	-

Physical Apperance : 1. Sample : Water (clear)

2. Container : Normal [G 1.0 L]


Remark : 1. /1 Drinking Water in Sealed Container Standard, Notification of the Ministry of Public Health No. 462, B.E. 2568 (2025).

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , E.coli = 1.1 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Supharerk Phatklang



Examined By :

(Miss Apiradee Chuen-arom)
09/04/2026

บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6904585

Report No : 6905-0494

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69041715

Sample Name : น้ำสระว่ายน้ำ

Sampling Date : 24/04/2026

Sampling By : ETC

Sampling Time : 11:20 AM

Sampling Method : Grab

Received Date : 25/04/2026

Tested Date : 08/05/2026

Reported Date : 11/05/2026

Parameter	Unit	Method	Result	Standard ¹
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	≤10
Fecal Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221E)	ND	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1./1 ค่าแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550

เรื่องการควบคุมการประกอบกิจการสระว่ายน้ำ หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , Fecal Coliform Bacteria = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Songpon Phiwan



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By : 

(Miss Apiradee Chuen-arom)

11/05/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6904585

Report No : 6905-0495

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69041716

Sample Name : ถังเก็บน้ำ

Sampling Date : 24/04/2026

Sampling By : ETC

Sampling Time : 11:10 AM

Sampling Method : Grab

Received Date : 25/04/2026

Tested Date : 08/05/2026

Reported Date : 11/05/2026


Parameter	Unit	Method	Result	Standard/ ¹
E.coli	MPN:100 mL	MPN Test Method (SM:9221F)	ND	ไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1. /1 Water Supply of Provincial Waterworks Authority (WHO 2017)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.
3. Parameter Outside The Scope of The Registration of Department of Industrial Works
4. LOQ = Level of Quantitation [LOQ of E.coli = 1.8 MPN : 100 mL] / ND = Not Detected
5. Sampling By Mr. Songpon Phiwuan



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By : 

(Miss Apiradee Chuen-arom)

11/05/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W 6904585

Report No : 6905-0496

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69041717
Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย ** Sampling Date : 24/04/2026 **
Sampling By : ETC ** Sampling Time : 11:40 AM **
Sampling Method : Grab ** Received Date : 25/04/2026
Tested Date : 25/04/2026 - 02/05/2026 Reported Date : 11/05/2026


Parameter	Unit	Method	Result
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	168
Oil and Grease *	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	30.9
pH (on site) *		Electrometric Method	7.7
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	2.89
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	32
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	288
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	42

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)
2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.
2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.
3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Songpon Phiwan (จ-003-ค-0016) *
4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)
(จ-003-ค-0007)
11/05/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)
(จ-003-ค-0005)
11/05/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6904585

Report No : 6905-0496

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakhon 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69041717

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 24/04/2026 **

Sampling By : ETC **

Sampling Time : 11:40 AM **

Sampling Method : Grab **

Received Date : 25/04/2026

Tested Date : 25/04/2026 - 02/05/2026

Reported Date : 11/05/2026

Parameter	Unit	Method	Result
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	93

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Songpon Phiwuan (จ-003-ค-0016) *


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

11/05/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

11/05/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6904585

Report No : 6905-0496

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69041717

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย

Sampling Date : 24/04/2026

Sampling By : ETC

Sampling Time : 11:40 AM

Sampling Method : Grab

Received Date : 25/04/2026

Tested Date : 25/04/2026 - 02/05/2026

Reported Date : 11/05/2026

Parameter	Unit	Method	Result
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	1.5


Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Parameter Outside The Scope of The Registration of Department of Industrial Works

3. Sampling By Mr. Songpon Phiwan



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

11/05/2026

Test Report

Request No : W6904585

Report No : 6905-0497

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69041718
Sample Name : น้ำออกระบบบำบัดน้ำเสีย ** Sampling Date : 24/04/2026 **
Sampling By : ETC ** Sampling Time : 11:30 AM **
Sampling Method : Grab ** Received Date : 25/04/2026
Tested Date : 25/04/2026 - 02/05/2026 Reported Date : 11/05/2026


Parameter	Unit	Method	Result	Standard ¹
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	5.3	≤20
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	< 3.0	≤20
pH (on site) *		Electrometric Method	7.2	5.5-9.0
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500-S2-F)	< 0.50	≤1
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	29	-
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	244	≤1000
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	5	≤35

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)
2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L (2 Bottle), G 1.0 L]

Remark : 1. / ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)
2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,
SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.
3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.
4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Songpon Phiwan (ว-003-ค-0016) *
5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)
(ว-003-ค-0007)
11/05/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)
(ว-003-ค-0005)
11/05/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6904585

Report No : 6905-0497

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69041718
Sample Name : น้ำออกระบบบำบัดน้ำเสีย ** Sampling Date : 24/04/2026 **
Sampling By : ETC ** Sampling Time : 11:30 AM **
Sampling Method : Grab ** Received Date : 25/04/2026
Tested Date : 25/04/2026 - 02/05/2026 Reported Date : 11/05/2026

Parameter	Unit	Method	Result	Standard ¹
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	9	≤30

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L (2 Bottle), G 1.0 L]

Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Songpon Phiwan (จ-003-ค-0016) *


5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

11/05/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY

THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL

WITHOUT THE WRITTEN APPROVAL LABORATORY

Page 2 of 2

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

11/05/2026

COPY

Test Report

Request No : W6904585

Report No : 6905-0497

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69041718

Sample Name : น้ำออกระบบบำบัดน้ำเสีย

Sampling Date : 24/04/2026

Sampling By : ETC

Sampling Time : 11:30 AM

Sampling Method : Grab

Received Date : 25/04/2026

Tested Date : 25/04/2026 - 02/05/2026

Reported Date : 11/05/2026

Parameter	Unit	Method	Result	Standard ¹
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2	-

Physical Appearance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L (2 Bottle), G 1.0 L]


Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. Sampling By Mr. Songpon Phiwuan



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

11/05/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6905650

Report No : 6906-0255

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69051914

Sample Name : น้ำสระว่ายนํ้า

Sampling Date : 25/05/2026

Sampling By : ETC

Sampling Time : 9:40 AM

Sampling Method : Grab

Received Date : 26/05/2026

Tested Date : 28/05/2026

Reported Date : 04/06/2026

Parameter	Unit	Method	Result	Standard ¹
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	≤10
Fecal Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221E)	ND	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1./1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550


เรื่องการควบคุมการประกอบกิจการสระว่ายนํ้า หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , Fecal Coliform Bacteria = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Teerapong Nualin



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

04/06/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6905650

Report No : 6906-0256

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69051915
Sample Name : น้ำเข้าระบบบำบัด ** Sampling Date : 25/05/2026 **
Sampling By : ETC ** Sampling Time : 9:45 AM **
Sampling Method : Grab ** Received Date : 26/05/2026
Tested Date : 26/05/2026 - 02/06/2026 Reported Date : 04/06/2026

Parameter	Unit	Method	Result
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	133
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	4.0
pH (on site) *		Electrometric Method	6.4
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	2.01
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	32
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	334
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	46

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Teerapong Nualin (จ-003-ค-0014) *


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

04/06/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

04/06/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6905650

Report No : 6906-0256

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakhon 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69051915
Sample Name : น้ำเข้าระบบบำบัด ** Sampling Date : 25/05/2026 **
Sampling By : ETC ** Sampling Time : 9:45 AM **
Sampling Method : Grab ** Received Date : 26/05/2026
Tested Date : 26/05/2026 - 02/06/2026 Reported Date : 04/06/2026

Parameter	Unit	Method	Result
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	42

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. @ = ISO/IEC 17025:2017 Accredited by TISL, # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Teerapong Nualin (จ-003-ท-0014) *


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ท-0007)

04/06/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ท-0005)

04/06/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6905650

Report No : 6906- 0256

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69051915

Sample Name : น้ำเข้าระบบบำบัด

Sampling Date : 25/05/2026

Sampling By : ETC

Sampling Time : 9:45 AM

Sampling Method : Grab

Received Date : 26/05/2026

Tested Date : 26/05/2026 - 02/06/2026

Reported Date : 04/06/2026

Parameter	Unit	Method	Result
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2


Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Parameter Outside The Scope of The Registration of Department of Industrial Works

3. Sampling By Mr. Teerapong Nualin



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)
04/06/2026REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Request No : W6905650


Report No : 6906-0257


Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69051916
Sample Name : น้ำออกระบบบำบัด ** Sampling Date : 25/05/2026 **
Sampling By : ETC ** Sampling Time : 9:50 AM **
Sampling Method : Grab ** Received Date : 26/05/2026
Tested Date : 26/05/2026 - 02/06/2026 Reported Date : 04/06/2026

Parameter	Unit	Method	Result	Standard ¹
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	13.9	≤20
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	< 3.0	≤20
pH (on site) *		Electrometric Method	6.3	5.5-9.0
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	< 0.50	≤1
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	31	-
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	192	≤1000
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	< 5	≤35

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)
2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]


Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)
2. @ = ISO/IEC 17025:2017 Accredited by TISI, # = ISO/IEC 17025:2017 Accredited by DSS,
SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.
3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.
4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Teerapong Nualin (จ-003-ค-0014) *
5. ** = These data are non laboratory data.

Examined By : 
(Miss Apiradee Chuen-arom)
(จ-003-ค-0007)
04/06/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Approved By : 
(Miss Nunnaphat Bakhuntod)
(จ-003-ค-0005)
04/06/2026

Test Report

Request No : W6905650

Report No : 6906-0257

Customer : V.M.P.C. Co.,Ltd. **
Address : 222/2 Sriracha Nakhon 3 Road T.Sriracha A.Sriracha Chonburi 20110 **
Sampling Source : V.M.P.C. Co.,Ltd. ** Sample No : W 69051916
Sample Name : น้ำออกกระบบบำบัด ** Sampling Date : 25/05/2026 **
Sampling By : ETC ** Sampling Time : 9:50 AM **
Sampling Method : Grab ** Received Date : 26/05/2026
Tested Date : 26/05/2026 - 02/06/2026 Reported Date : 04/06/2026

Parameter	Unit	Method	Result	Standard ¹
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	12	≤30

Physical Appearance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Teerapong Nualin (ว-003-ก-0014) *


5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(ว-003-ก-0007)

04/06/2026



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(ว-003-ก-0005)

04/06/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6905650

Report No : 6906-0257

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69051916

Sample Name : น้ำออกระบบบำบัด

Sampling Date : 25/05/2026

Sampling By : ETC

Sampling Time : 9:50 AM

Sampling Method : Grab

Received Date : 26/05/2026

Tested Date : 26/05/2026 - 02/06/2026

Reported Date : 04/06/2026

Parameter	Unit	Method	Result	Standard/ ¹
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2	-

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]


Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. Sampling By Mr. Teerapong Nualin



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)
04/06/2026REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

COPY

Test Report

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample Name : น้ำสระว่ายนํ้า

Sampling By : ETC

Sampling Method : Grab

Tested Date : 30/06/2026

Request No : W6906638

Report No : 6907-0166

Sample No : W 69061860

Sampling Date : 24/06/2026

Sampling Time : 11:20 AM

Received Date : 25/06/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result	Standard/ ¹
Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221B)	ND	≤10
Fecal Coliform Bacteria	MPN:100 mL	MPN Test Method (SM:9221E)	ND	ตรวจไม่พบ

Physical Apperance : 1. Sample : Water (lightly SS)

2. Container : Normal [G 0.25 L]

Remark : 1. /1 คำแนะนำของคณะกรรมการสาธารณสุข ฉบับที่ 1/2550

เรื่องการควบคุมการประกอบกิจการสระว่ายนํ้า หรือกิจการอื่น ๆ ในทำนองเดียวกัน

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. LOQ = Level of Quantitation [LOQ of Coliform Bacteria , Fecal Coliform Bacteria = 1.8 MPN : 100 mL] / ND = Not Detected

5. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By : 

(Miss Apiradee Chuen-arom)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6906638

Report No : 6907-0167

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69061861

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling Date : 24/06/2026 **

Sampling By : ETC **

Sampling Time : 11:25 AM **

Sampling Method : Grab **

Received Date : 25/06/2026

Tested Date : 25/06/2026 - 01/07/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	290
Oil and Grease *	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	33.7
pH (on site) *		Electrometric Method	6.3
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	1.32
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	31
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	378
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	17

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034)*


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

03/07/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย **

Sampling By : ETC **

Sampling Method : Grab **

Tested Date : 25/06/2026 - 01/07/2026

Request No : W6906638

Report No : 6907-0167

Sample No : W 69061861

Sampling Date : 24/06/2026 **

Sampling Time : 11:25 AM **

Received Date : 25/06/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	134

Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. # = ISO/IEC 17025:2017 Accredited by DSS, SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

3. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ก-0034)*


4. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ก-0007)

03/07/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ก-0005)

03/07/2026

Test Report

Request No : W6906638

Report No : 6907-0167

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69061861

Sample Name : น้ำเข้าระบบบำบัดน้ำเสีย

Sampling Date : 24/06/2026

Sampling By : ETC

Sampling Time : 11:25 AM

Sampling Method : Grab

Received Date : 25/06/2026

Tested Date : 25/06/2026 - 01/07/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	16


Physical Apperance : 1. Sample : Wastewater (yellow , turbid)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

2. Parameter Outside The Scope of The Registration of Department of Industrial Works

3. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6906638

Report No : 6907-0168

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample No : W 69061862

Sample Name : น้ำออกกระบบบำบัดน้ำเสีย **

Sampling Date : 24/06/2026 **

Sampling By : ETC **

Sampling Time : 11:35 AM **

Sampling Method : Grab **

Received Date : 25/06/2026

Tested Date : 25/06/2026 - 01/07/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result	Standard/l
Biochemical Oxygen Demand #	mg/L	5-Day BOD Test, Membrane Electrode Method (SM:5210B)	14.4	≤20
Oil and Grease @	mg/L	Liquid-Liquid, Partition-Gravimetric Method (SM:5520B)	< 3.0	≤20
pH (on site) *		Electrometric Method	6.0	5.5-9.0
Sulfide *	mg/L as H ₂ S	ZnS Precipitation, Iodometric Method (SM:4500 -S2- F)	< 0.50	≤1
Temperature *	°C	Laboratory and Field Method (SM:2550 B)	30	-
Total Dissolved Solids #	mg/L	Dried at 180 degree celsius (SM:2540C)	187	≤1000
Total Kjeldahl Nitrogen *	mg/L as NH ₃ -N	Macro Kjeldahl Method (SM:4500 -Norg B)	< 5	≤35

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ก-0034) *


5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ก-0007)

03/07/2026



บริษัท อีสเทิร์นไทยคอนซัลติง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ก-0005)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Customer : V.M.P.C. Co.,Ltd. **

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110 **

Sampling Source : V.M.P.C. Co.,Ltd. **

Sample Name : น้ำออกกระบบบำบัดน้ำเสีย **

Sampling By : ETC **

Sampling Method : Grab **

Tested Date : 25/06/2026 - 01/07/2026

Request No : W6906638

Report No : 6907-0168

Sample No : W 69061862

Sampling Date : 24/06/2026 **

Sampling Time : 11:35 AM **

Received Date : 25/06/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result	Standard/ ¹
Total Suspended Solids #	mg/L	Dried at 103-105 degree celsius (SM:2540D)	< 5	≤30

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]

Remark : 1. /1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. @ = ISO/IEC 17025:2017 Accredited by TISI., # = ISO/IEC 17025:2017 Accredited by DSS,

SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Miss Apiradee Chuen-arom is Section Head / Miss Nunnaphat Bakhuntod is Technical Management.

4. * = Test Report/Sampling marked Not Accredited, Sampling By Mr. Aocha Khwansirimongkhon (จ-003-ค-0034) *


5. ** = These data are non laboratory data.

Examined By :

(Miss Apiradee Chuen-arom)

(จ-003-ค-0007)

03/07/2026



บริษัท อีสเทิร์นไทยคอนซัลตัง 1992 จำกัด

Approved By :

(Miss Nunnaphat Bakhuntod)

(จ-003-ค-0005)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Test Report

Request No : W6906638

Report No : 6907-0168

Customer : V.M.P.C. Co.,Ltd.

Address : 222/2 Sriracha Nakham 3 Road T.Sriracha A.Sriracha Chonburi 20110

Sampling Source : V.M.P.C. Co.,Ltd.

Sample No : W 69061862

Sample Name : น้ำออกระบบบำบัดน้ำเสีย

Sampling Date : 24/06/2026

Sampling By : ETC

Sampling Time : 11:35 AM

Sampling Method : Grab

Received Date : 25/06/2026

Tested Date : 25/06/2026 - 01/07/2026

Reported Date : 03/07/2026

Parameter	Unit	Method	Result	Standard ¹
Settleable Solid	mL/L	Volumetric Method (SM:2540F)	< 0.2	-

Physical Apperance : 1. Sample : Wastewater (yellow , lightly SS)

2. Container : Normal [PE 0.5 L (2 Bottle), PE 1.0 L, PE 1.8 L, G 1.0 L]


Remark : 1./1 ประกาศกระทรวงทรัพยากรธรรมชาติและสิ่งแวดล้อม

เรื่อง กำหนดมาตรฐานควบคุมการระบายน้ำทิ้งจากอาคารบางประเภทและบางขนาด (พ.ศ.2567) (อาคารประเภท ก)

2. SM = Standard Methods for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th Edition, 2023.

3. Parameter Outside The Scope of The Registration of Department of Industrial Works

4. Sampling By Mr. Aocha Khwansirimongkhon



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Examined By :

(Miss Apiradee Chuen-arom)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. ATR6906076

Report No. 6906-1277 - 6906-1279

TEST REPORT

CUSTOMER : V.M.P.C. Co.,Ltd. (Branch 00006)
 ADDRESS : 222/2 Sriracha Nakhon 3 Road, T. Sriracha, A. Sriracha, Chonburi 20110
 SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)
 SAMPLE NAME : บริเวณพื้นที่สีเขียวกลางโครงการ
 RECEIVED DATE : 29/06/2026 SAMPLE NO. : A69061277 - A69061279
 TESTED DATE : 29/06/2026-30/06/2026 REPORTED DATE : 03/07/2026


PARAMETER*	TEST METHOD	SAMPLING DATE	RESULT	STD ^{1/}	UNIT
Particulate matter less than or Equal					
10 micrometers (PM 10)	Gravimetric Method	18-19/06/2026	17.7	100	µg/m ³
		19-20/06/2026	13.9	100	µg/m ³
		20-21/06/2026	21.4	100	µg/m ³

REMARK:

^{1/} Notification of The National Environment Board on Ambient Air Quality Standards, B.E. 2569 (2026) Standard for 24-hr Average.

* Parameter Outside The Scope of The Registration of The Department of Industrial Works.

(Sampling By Mr. Seksan Pluemwong)



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By

(Miss Thanatporn Klinsopon)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
 THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. ATR6906076

Report No. 6906-1280 - 6906-1282

TEST REPORT

CUSTOMER : V.M.P.C. Co.,Ltd. (Branch 00006)
 ADDRESS : 222/2 Sriracha Nakhon 3 Road, T. Sriracha, A. Sriracha, Chonburi 20110
 SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)
 SAMPLE NAME : บริเวณพื้นที่สีเขียวกลางโครงการ
 RECEIVED DATE : 29/06/2026 SAMPLE NO. : A69061280 - A69061282
 TESTED DATE : 29/06/2026-30/06/2026 REPORTED DATE : 03/07/2026

PARAMETER*	TEST METHOD	SAMPLING DATE	RESULT	STD ^{1/}	UNIT
Total Suspended Particulate (TSP)	Gravimetric Method	18-19/06/2026	36.0	200	µg/m ³
		19-20/06/2026	24.9	200	µg/m ³
		20-21/06/2026	40.6	200	µg/m ³

REMARK:

^{1/} Notification of The National Environment Board on Ambient Air Quality Standards, B.E. 2569 (2026) Standard for 24-hr Average.

* Parameter Outside The Scope of The Registration of The Department of Industrial Works.

(Sampling By Mr. Seksan Pluemwong)



Approved By

(Miss Thanatporn Klinsopon)

03/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
 THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. LA69-R06154


Report No. R6906-8233 - R6906-8235

TEST REPORT

CUSTOMER : V.M.P.C. Co., Ltd. (Branch 00006)
 ADDRESS : 222/2 Sriracha Nakorn 3 Road T. Sri Racha A. Sri Racha, Chonburi 20110
 SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)
 SAMPLE POINT : บริเวณพื้นที่สีเขียวกลางโครงการ
 PARAMETER* : Sulfur Dioxide
 DETERMINATION METHOD : Ultraviolet Fluorescence
 INSTRUMENT : API Model T100 S/N 6459

SAMPLE NO. : 23451-23453
 SAMPLING DATE : 18-21/06/2026
 RECEIVED DATE : 21/06/2026
 REPORTED DATE : 01/07/2026

TIME / DATE	18-19/06/2026	19-20/06/2026	20-21/06/2026	UNIT
11:00 - 12:00 ^{/2}	7.0	8.0	6.0	ppb
12:00 - 13:00	8.6	7.0	5.7	ppb
13:00 - 14:00	8.9	8.1	6.4	ppb
14:00 - 15:00	3.9	8.8	7.1	ppb
15:00 - 16:00	3.5	10.6	5.9	ppb
16:00 - 17:00	7.7	11.3	5.8	ppb
17:00 - 18:00	5.6	11.7	6.1	ppb
18:00 - 19:00	4.0	10.7	7.2	ppb
19:00 - 20:00	2.6	9.6	7.0	ppb
20:00 - 21:00	6.0	9.1	6.9	ppb
21:00 - 22:00	2.2	8.8	6.8	ppb
22:00 - 23:00	2.2	8.6	6.0	ppb
23:00 - 00:00	9.5	8.5	5.4	ppb
00:00 - 01:00	8.6	8.9	5.3	ppb
01:00 - 02:00	8.3	9.2	5.3	ppb
02:00 - 03:00	6.9	9.1	5.2	ppb
03:00 - 04:00	5.8	8.3	5.2	ppb
04:00 - 05:00	5.4	7.7	6.1	ppb
05:00 - 06:00	4.9	8.8	6.1	ppb
06:00 - 07:00	5.4	8.8	6.0	ppb
07:00 - 08:00	5.4	8.6	5.9	ppb
08:00 - 09:00	4.8	8.3	4.9	ppb
09:00 - 10:00	3.8	7.8	4.1	ppb
10:00 - 11:00	3.3	6.4	4.1	ppb
Maximum 1 hr.	9.5	11.7	7.2	ppb
Average 24 hr.	5.6	8.9	5.9	ppb
Standard (1 hr.) ^{/1}	100	100	100	ppb
Standard (Average 24 hr.) ^{/1}	50	50	50	ppb

REMARK : ^{/1} Notification of The National Environmental Board on Ambient Air Quality Standards, B.E. 2569 (2026)^{/2} Start Time* Parameter Outside The Scope of The Registration of The Department of Industrial Works
(Measurement By Mr. Seksan Pluemwong)

บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By.....

(MS. THANATPORN KLINSOPON)

01/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
 THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. LA69-R06154


Report No. R6906-8236 - R6906-8238

TEST REPORT

CUSTOMER : V.M.P.C. Co., Ltd. (Branch 00006)
 ADDRESS : 222/2 Sriracha Nakorn 3 Road T. Sri Racha A. Sri Racha, Chonburi 20110
 SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)
 SAMPLE POINT : บริเวณพื้นที่สีเขียวกลางโครงการ
 PARAMETER* : Nitrogen Dioxide
 DETERMINATION METHOD : Chemiluminescence
 INSTRUMENT : API Model T200 S/N 7866

SAMPLE NO. : 23454-23456
 SAMPLING DATE : 18-21/06/2026
 RECEIVED DATE : 21/06/2026
 REPORTED DATE : 01/07/2026

TIME / DATE	18-19/06/2026	19-20/06/2026	20-21/06/2026	UNIT
11:00 - 12:00 ^{/2}	12.8	16.6	16.3	ppb
12:00 - 13:00	14.9	21.1	15.8	ppb
13:00 - 14:00	14.7	16.2	15.3	ppb
14:00 - 15:00	16.7	18.7	15.8	ppb
15:00 - 16:00	15.2	15.5	15.7	ppb
16:00 - 17:00	15.3	19.5	20.0	ppb
17:00 - 18:00	18.3	20.8	21.5	ppb
18:00 - 19:00	14.3	19.6	25.7	ppb
19:00 - 20:00	21.8	12.7	20.6	ppb
20:00 - 21:00	23.6	13.2	17.4	ppb
21:00 - 22:00	21.7	12.7	17.4	ppb
22:00 - 23:00	19.9	21.7	15.9	ppb
23:00 - 00:00	20.3	17.4	23.6	ppb
00:00 - 01:00	18.5	15.0	20.7	ppb
01:00 - 02:00	19.8	12.6	24.2	ppb
02:00 - 03:00	25.4	20.2	24.0	ppb
03:00 - 04:00	24.5	22.7	23.1	ppb
04:00 - 05:00	29.2	25.1	23.9	ppb
05:00 - 06:00	31.2	24.3	28.2	ppb
06:00 - 07:00	26.4	21.3	26.2	ppb
07:00 - 08:00	26.7	23.8	25.7	ppb
08:00 - 09:00	28.1	24.3	23.4	ppb
09:00 - 10:00	19.7	24.8	17.0	ppb
10:00 - 11:00	17.8	18.7	15.3	ppb
Maximum 1 hr.	31.2	25.1	28.2	ppb
Average 24 hr.	20.7	19.1	20.5	ppb
Standard (1 hr.) ^{/1}	120	120	120	ppb

REMARK : ^{/1} Notification of The National Environmental Board on Ambient Air Quality Standards, B.E. 2569 (2026)^{/2} Start Time* Parameter Outside The Scope of The Registration of The Department of Industrial Works
(Measurement By Mr. Seksan Pluemwong)

บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By.....

(MS. THANATPORN KLINSOPON)

01/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
 THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. LA69-R06154

Report No. R6906-8239 - R6906-8241

TEST REPORT

CUSTOMER : V.M.P.C. Co., Ltd. (Branch 00006)
 ADDRESS : 222/2 Sriracha Nakorn 3 Road T. Sri Racha A. Sri Racha, Chonburi 20110
 SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)
 SAMPLE POINT : บริเวณพื้นที่สีเขียวกลางโครงการ
 PARAMETER* : Carbon monoxide
 DETERMINATION METHOD : Non-Dispersive Infrared Detection
 INSTRUMENT : API Model T300 S/N 5403

SAMPLE NO. : 23457-23459
 SAMPLING DATE : 18-21/06/2026
 RECEIVED DATE : 21/06/2026
 REPORTED DATE : 01/07/2026

TIME / DATE	18-19/06/2026	19-20/06/2026	20-21/06/2026	UNIT
11:00 - 12:00 ^{/2}	1.09	1.19	1.14	ppm
12:00 - 13:00	1.50	1.22	1.14	ppm
13:00 - 14:00	1.78	1.19	1.15	ppm
14:00 - 15:00	1.53	1.17	1.14	ppm
15:00 - 16:00	1.63	1.15	1.12	ppm
16:00 - 17:00	1.34	1.18	1.15	ppm
17:00 - 18:00	1.29	1.20	1.44	ppm
18:00 - 19:00	1.27	1.19	2.11	ppm
19:00 - 20:00	1.08	1.14	1.39	ppm
20:00 - 21:00	1.41	1.13	1.46	ppm
21:00 - 22:00	1.37	1.11	1.48	ppm
22:00 - 23:00	1.34	1.19	1.47	ppm
23:00 - 00:00	1.34	1.17	1.50	ppm
00:00 - 01:00	1.32	1.13	1.50	ppm
01:00 - 02:00	1.28	1.13	1.44	ppm
02:00 - 03:00	1.30	1.17	1.37	ppm
03:00 - 04:00	1.30	1.17	1.30	ppm
04:00 - 05:00	1.32	1.16	1.26	ppm
05:00 - 06:00	1.35	1.20	1.23	ppm
06:00 - 07:00	1.37	1.24	1.28	ppm
07:00 - 08:00	1.46	1.41	1.33	ppm
08:00 - 09:00	1.52	1.48	1.36	ppm
09:00 - 10:00	1.47	1.43	1.14	ppm
10:00 - 11:00	1.22	1.19	1.10	ppm
Maximum 1 hr.	1.78	1.48	2.11	ppm
Average 24 hr.	1.37	1.21	1.33	ppm
Standard (1 hr.) ^{/1}	30	30	30	ppm

REMARK : ^{/1} Notification of The National Environmental Board on Ambient Air Quality Standards, B.E. 2569 (2026) (Standard for 1-hr. Average)^{/2} Start Time* Parameter Outside The Scope of The Registration of The Department of Industrial Works
(Measurement By Mr. Seksan Pluemwong)

Approved By.....

(MS. THANATPORN KLINSOPON)

01/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY
 THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. LA69-R06154

Report No. R6906-8239 - R6906-8241

TEST REPORT

CUSTOMER : V.M.P.C. Co., Ltd. (Branch 00006)

ADDRESS : 222/2 Sriracha Nakorn 3 Road T. Sri Racha A. Sri Racha, Chonburi 20110

SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)

SAMPLE POINT : บริเวณพื้นที่สีเขียวกลางโครงการ SAMPLE NO. : 23457-23459

DETERMINATION METHOD : Non-Dispersive Infrared Detection RECEIVED DATE : 21/06/2026

INSTRUMENT : API Model T300 S/N 5403 REPORTED DATE : 01/07/2026


PARAMETER*	SAMPLING DATE	TIME	RESULT	STANDARD ^{/1}	UNIT
Carbon monoxide (CO)	18/06/2026	11:00-19:00	1.43	9	ppm
	19/06/2026	11:00-19:00	1.19	9	ppm
	20/06/2026	11:00-19:00	1.30	9	ppm

REMARK : ^{/1} Notification of The National Environmental Board on Ambient Air Quality Standards, B.E. 2569 (2026)

Standard for 8-hr Average

* Parameter Outside The Scope of The Registration of The Department of Industrial Works

(Measurement By Mr. Seksan Pluemwong)



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By.....

(MS. THANATPORN KLINSOPON)

01/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY

THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL

WITHOUT THE WRITTEN APPROVAL LABORATORY

Request No. LA69-R06154

Report No. R6906-8242 - R6906-8244

TEST REPORT

CUSTOMER : V.M.P.C. Co., Ltd. (Branch 00006)

ADDRESS : 222/2 Sriracha Nakorn 3 Road T. Sri Racha A. Sri Racha, Chonburi 20110


SAMPLE SOURCE : โรงแรม ATARA HOTEL SRIRACHA (Oakwood Hotel & Residence)

SAMPLE POINT : บริเวณพื้นที่สีเขียวกลางโครงการ RECEIVED DATE : 21/06/2026

SAMPLE NO. : 23460-23462 REPORTED DATE : 01/07/2026

PARAMETER*	TEST METHOD	SAMPLING DATE	RESULT	UNIT
Total Hydrocarbon	Flame Ionization Detector	18-19/06/2026	2.83	ppm
(THC)		19-20/06/2026	2.09	ppm
		20-21/06/2026	2.31	ppm

REMARK : * Parameter Outside The Scope of The Registration of The Department of Industrial Works
(Measurement By Mr. Seksan Pluemwong)



บริษัท อีสเทิร์นไทยคอนซัลติ้ง 1992 จำกัด

Approved By.....

(MS. THANATPORN KLINSOPON)

01/07/2026

REPORTED TEST REFER TO SUBMITTED SAMPLES ONLY

THIS REPORT SHALL NOT REPRODUCED EXCEPT IN FULL

WITHOUT THE WRITTEN APPROVAL LABORATORY

เอกสารขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน และใบอนุญาต
เป็นผู้ให้บริการตรวจวัดและวิเคราะห์ระดับความเข้มข้นของสารเคมีอันตราย
ในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย
ระดับความร้อน แสงสว่าง และเสียง จากกรมสวัสดิการและคุ้มครองแรงงาน



ที่ อก ๐๓๒๐/๑๑๓๔๒

กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๔๐๐

๒๗ กรกฎาคม ๒๕๖๖

เรื่อง ต่ออายุหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

เรียน กรรมการผู้จัดการ บริษัท อีสเทิร์น ไทย คอนซัลติง ๑๙๙๒ จำกัด

อ้างถึง คำขอต่ออายุของห้องปฏิบัติการวิเคราะห์เอกชน ลงวันที่ ๗ มิถุนายน ๒๕๖๖

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือรับต่ออายุขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

๑. รายชื่อผู้ควบคุมดูแลห้องปฏิบัติการวิเคราะห์ จำนวน ๔๐ ราย
๒. รายชื่อเจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๒๕ ราย
๓. ขอบข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๒๙๒ รายการ จำนวน ๑๙ แผ่น

ตามหนังสือที่อ้างถึง บริษัท อีสเทิร์น ไทย คอนซัลติง ๑๙๙๒ จำกัด ขอต่ออายุหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน เลขทะเบียน ๖-๐๐๓ สถานที่ตั้งเลขที่ ๖๘๓ หมู่ที่ ๑๑ ถนนสุขาภิบาล ๘ ตำบลหนองขาม อำเภอศรีราชา จังหวัดชลบุรี ต่อกรมโรงงานอุตสาหกรรม นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว ให้บริษัท อีสเทิร์น ไทย คอนซัลติง ๑๙๙๒ จำกัด ต่ออายุหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน โดยมีองค์ประกอบดังนี้

- ก. ผู้ควบคุมดูแลห้องปฏิบัติการวิเคราะห์ จำนวน ๔๐ ราย ตามสิ่งที่ส่งมาด้วย ๑
- ข. เจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๒๕ ราย ตามสิ่งที่ส่งมาด้วย ๒
- ค. ขอบข่ายสารมลพิษที่ได้รับขึ้นทะเบียนให้วิเคราะห์ในน้ำเสีย จำนวน ๔๗ รายการ อากาศเสีย (ปล่องระบาย) จำนวน ๒๑ รายการ น้ำใต้ดิน จำนวน ๑๑๑ รายการ สิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว จำนวน ๑๘ รายการ และดิน จำนวน ๙๕ รายการ รวมทั้งสิ้นจำนวน ๒๙๒ รายการ ตามสิ่งที่ส่งมาด้วย ๓

หนังสือฉบับนี้จะหมดอายุในวันที่ ๕ กรกฎาคม ๒๕๖๙ หากประสงค์จะต่ออายุหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน ให้ยื่นคำขอต่ออายุพร้อมเอกสารประกอบคำขอต่อกรมโรงงานอุตสาหกรรม ภายใน ๓๐ วัน ก่อนวันสิ้นสุดอายุของหนังสือรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน ทั้งนี้ สามารถยื่นคำขอผ่านระบบอิเล็กทรอนิกส์ได้ที่หน้าเว็บไซต์กรมโรงงานอุตสาหกรรม

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายทวี อำพาพันธ์)

ผู้อำนวยการศูนย์วิจัยและเตือนภัยมลพิษโรงงานภาคตะวันออก
ปฏิบัติราชการแทนอธิบดีกรมโรงงานอุตสาหกรรม

ศูนย์วิจัยและเตือนภัยมลพิษโรงงานภาคตะวันออก

โทร. ๐ ๓๓๑๓๓ ๖๐๕๙ ต่อ ๕๐๐๑-๒

ไปรษณีย์อิเล็กทรอนิกส์ eirw@diw.mail.go.th



"อุตสาหกรรมก้าวหน้า ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว"



COPY

เอกสารแนบท้ายหนังสือรับต่ออายุขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

บริษัท อีสเทิร์น ไทย คอนซัลติง ๑๙๙๒ จำกัด เลขทะเบียน ๖-๐๐๓

ที่ อก ๐๓๒๐/๑๑๓๔๒

ลงวันที่ ๒๗ กรกฎาคม ๒๕๖๖

ก. ผู้ควบคุมดูแลห้องปฏิบัติการวิเคราะห์ จำนวน ๔๐ ราย

๑) นางสาวมาลีเกษ เลขวิจักกุล	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๑
๒) นายวัฒนา โคตรหล้า	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๒
๓) นางวรรณเพ็ญ เหลาจินดาว์ณ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๓
๔) นายกะวีร์ สุธาทรัพย์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๔
๕) นางสาวนันท์นภัส แบนทนต์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๕
๖) นางสาวพณภา หลงคำหงษ์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๖
๗) นางสาวอภิรดี ชื่นอารมย์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๗
๘) นางสาวอัจฉริ จิตตะยโคตร	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๘
๙) นางสาวจิรพร ปานคง	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๐๙
๑๐) นายสุทธา ส่องธนิย์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๐
๑๑) นางสาวนันประภา อุดสูงเนิน	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๑
๑๒) นายธงไชย บุญศักดิ์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๒
๑๓) นางสาวธนัชพร กลิ่นโสภณ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๓
๑๔) นายธีระพงษ์ นวลอินทร์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๔
๑๕) นางสาวแพรว พลเสน	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๕
๑๖) นายทรงพล ผิวอ้วน	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๖
๑๗) นายภาคภูมิ บัวสวัสดิ์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๗
๑๘) นางสาวจันทน์ สายพันธ์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๘
๑๙) นายภาณุพงศ์ บำรุงรส	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๑๙
๒๐) นางสาวภาณิน จันดีสอน	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๐
๒๑) นายวรการ ไทหะเสวี	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๑
๒๒) นางสาววรรณภา ไชยศิริ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๒
๒๓) นางสาวพรพิมล ภูมิคอนสาร	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๓
๒๔) นางสาวธมลวรรณ ผลอ้อ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๔
๒๕) นางสาวบุญเรือง บุญถม	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๕
๒๖) นางสาวกัสนันท์ ป้อมน้อย	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๖
๒๗) นายชานูวัฒน์ ไชยวงศ์	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๗
๒๘) นางสาวพจณีย์ งามวิสัย	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๘
๒๙) นายวิษณุวัตร สิงห์โต	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๒๙
๓๐) นางสาวนฤกุล อภารศรี	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๓๐
๓๑) นายศุภฤกษ์ พาดกลาง	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๓๑
๓๒) นายณิชาพล ทองหล่อ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๓๒
๓๓) นายธรรมรัตน์ โพธิ์ตันคำ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๓๓
๓๔) นายโอชา ขวัญศิริมงคล	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๓๔
๓๕) นายเมธี สุขประเสริฐ	ทะเบียนเลขที่	๖-๐๐๓-๖-๐๐๓๕

๓๖) นางสาวพรพินันท์...

COPY

๓๖) นางสาวพรพินันท์ วิริยกุลกุล	ทะเบียนเลขที่	ว-๐๐๓-ค-๐๐๓๖
๓๗) นางสาวอาภาภรณ์ เสริมสนธิ	ทะเบียนเลขที่	ว-๐๐๓-ค-๐๐๓๗
๓๘) นางสาวนภัทรธมณต์ ประดิษฐ์นุช	ทะเบียนเลขที่	ว-๐๐๓-ค-๐๐๓๘
๓๙) นางสาวสุนิษา เอ็งเส้ง	ทะเบียนเลขที่	ว-๐๐๓-ค-๐๐๓๙
๔๐) นางสาวระพีณ อินัน	ทะเบียนเลขที่	ว-๐๐๓-ค-๐๐๔๐

ข. เจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๒๕ ราย

๑) นางสาวดวงกมล เนื้อทอง	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๑
๒) นางสาววิชรภรณ์ อินทสุข	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๒
๓) นางสาวกัญจน์ฉวีภา จันทร์ชอดแก้ว	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๓
๔) นางสาวฉัตรสุดา มงคลโกชน	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๔
๕) นางสาวณัฐวิทย์ อามาททัศน์	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๕
๖) นางสาวนิอรอุมา ปาระ	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๖
๗) นางสาวธัญลักษณ์ ชื่นโต	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๗
๘) นางสาวสุทธิดา สร้างแก้ว	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๘
๙) นายอุดมทรัพย์ เจนจบจริง	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๐๙
๑๐) นายณราธิป สงวนศิลป์	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๐
๑๑) นายวีระชัย พอใจ	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๑
๑๒) นายอัญชลี ทะพงษ์	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๒
๑๓) นางสาวสุมลิตรา มีแก่น	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๓
๑๔) นางสาวสรวรยา เพชรประไพ	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๔
๑๕) นางสาวจุฑามาศ เจริญพรหม	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๕
๑๖) นางสาวนิภาพร คำชมภู	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๖
๑๗) นางสาวอรุษา พันธุ์เมือง	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๗
๑๘) นายกิตติ ไพโรจน์	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๘
๑๙) นายชาญณรงค์ ตั้งธรรมรักษ์	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๑๙
๒๐) นางสาวปวีศา เอลันทิยะ	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๒๐
๒๑) นางสาวจุฑาทิพย์ กิจดี	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๒๑
๒๒) นางสาวสุภาวดี ศรีระยอง	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๒๒
๒๓) นางสาวณัฐชยา บรรพบุตร	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๒๓
๒๔) นางสาวณัฐนิช นนตานอก	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๒๔
๒๕) นางสาวดวงสุดา แสนวันดี	ทะเบียนเลขที่	ว-๐๐๓-จ-๐๐๒๕

เอกสารแนบท้ายหนังสือรับต่ออายุขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

บริษัท อีสเทิร์น ไทย คอนซัลติง ๑๙๙๒ จำกัด เลขทะเบียน ว-๐๐๓

ที่ อก ๐๓๒๐/๑๑๓๔๒

ลงวันที่ ๒๗ กรกฎาคม ๒๕๖๖

ขอขยายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๒๕๒ รายการ

น้ำเสีย จำนวน 47 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
2	Arsenic	1) Continuous Hydride Generation/Atomic Absorption Spectrometric Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
3	Barium	Digestion, Inductively Coupled Plasma Method ^[4]
4	α-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
5	β-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
6	δ-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
7	γ-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
8	Biochemical Oxygen Demand	1) 5-Day BOD Test, Membrane Electrode Method ^[4] 2) 5-Day BOD Test, Azide Modification Method ^[4]
9	Cadmium	Digestion, Inductively Coupled Plasma Method ^[4]
10	Chemical Oxygen Demand	Closed Reflux, Titrimetric Method ^[4]
11	cis-Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
12	trans-Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
13	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]

COPY

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
14	Color	ADMI Weighted-Ordinate Spectrophotometric Method ^[4]
15	Copper	1) Digestion, Direct Air-Acetylene Flame Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
16	Cyanide	Distillation, Colorimetric Method ^[4]
17	4,4'-DDD	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
18	4,4'-DDE	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
19	DDT	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
20	Dieldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
21	Endosulfan I	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
22	Endosulfan II	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
23	Endosulfan sulfate	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
24	Endrin	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
25	Endrin aldehyde	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
26	Endrin ketone	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
27	Formaldehyde	Distillation, Colorimetric Method ^[3]
28	Free Chlorine	1) Iodometric Method ^[4] 2) Colorimetric Method ^[4]

29 Heptachlor...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
29	Heptachlor	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
30	Heptachlor Epoxide	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
31	Hexavalent Chromium	Filtration, Colorimetric Method ^[4]
32	Lead	1) Digestion, Direct Air-Acetylene Flame Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
33	Manganese	Digestion, Inductively Coupled Plasma Method ^[4]
34	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[4]
35	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[4]
36	Nickel	1) Digestion, Direct Air-Acetylene Flame Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
37	Oil and Grease	Liquid-Liquid, Partition-Gravimetric Method ^[4]
38	pH	Electrometric Method ^[4]
39	Phenols	Distillation, Direct Photometric Method ^[4]
40	Selenium	Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4]
41	Sulfide	ZnS Precipitation, Iodometric Method ^[4]
42	Temperature	Field Method ^[4]
43	Trivalent Chromium	1) Digestion, Direct Air-Acetylene Flame Method; Filtration, Colorimetric Method; Calculation ^[4] 2) Digestion, Inductively Coupled Plasma Method; Colorimetric Method; Calculation ^[4]
44	Total Dissolved Solids	Dried at 180 °C ^[4]
45	Total Kjeldahl Nitrogen	Macro Kjeldahl Method ^[4]
46	Total Suspended Solids	Dried at 103-105 °C ^[4]
47	Zinc	Digestion, Inductively Coupled Plasma Method ^[4]

อากาศเสีย...

COPY

อากาศเสีย (ปล่องระบาย) จำนวน 21 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Antimony	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
2	Arsenic	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
3	Cadmium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
4	Carbon Monoxide	1) Bag, Non-Dispersive Infrared Method ^[5] 2) Instrumental Analyzer Method ^[5]
5	Chromium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
6	Cobalt	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
7	Copper	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
8	Hydrogen Sulfide	Absorption Sampling, Iodometric Method ^[5]
9	Lead	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
10	Manganese	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
11	Mercury	Isokinetic Sampling, Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[5]
12	Nickel	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
13	Opacity	Ringelmann's Method ^[1,5]
14	Oxides of Nitrogen	1) Absorption Sampling, Phenoldisulfonic Acid Method ^[8] 2) Instrumental Analyzer Method ^[7]
15	Selenium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
16	Sulfur Dioxide	1) Absorption Sampling, Barium-Thorin Titrimetric Method ^[5] 2) Instrumental Analyzer Method ^[5]
17	Sulfuric Acid	Isokinetic Sampling, Barium-Thorin Titrimetric Method ^[6]
18	Tin	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]

19 Total Suspended Particulate...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
19	Total Suspended Particulate	Isokinetic Sampling, Gravimetric Method ^[6]
20	Vanadium	Isokinetic Sampling, Digestion, Inductively Coupled Plasma Method ^[5]
21	Xylene	Adsorption Sampling, Gas Chromatographic Method ^[6]

น้ำใต้ดิน จำนวน 111 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Acenaphthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
2	Acetone	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
3	Aldrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
4	Anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
5	Antimony	Digestion, Inductively Coupled Plasma Method ^[4]
6	Arsenic	1) Continuous Hydride Generation/Atomic Absorption Spectrometric Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
7	Barium	Digestion, Inductively Coupled Plasma Method ^[4]
8	Benz(a)anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
9	Benzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
10	Benzo(b)fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
11	Benzo(k)fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
12	Benzo(a)pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
13	Benzo[g,h,i]perylene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
14	Beryllium	Digestion, Inductively Coupled Plasma Method ^[4]

15 Bis(2-chloroethyl)ether...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
15	Bis(2-chloroethyl)ether	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
16	Bis(2-ethylhexyl)phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
17	Bromodichloromethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
18	Bromoform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
19	Butanol	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
20	Butyl benzyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
21	Cadmium	Digestion, Inductively Coupled Plasma Method ^[4]
22	Carbazole	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
23	Carbon disulfide	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
24	Carbon tetrachloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
25	Chlordane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
26	p-Chloroaniline	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
27	Chlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
28	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
29	Chloroform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
30	2-Chlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
31	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ^[4] 2) Digestion, Inductively Coupled Plasma Method ^[4]
32	Chromium (III)	1) Digestion, Direct Air-Acetylene Flame Method; Filtration, Colorimetric Method; Calculation ^[4] 2) Digestion, Inductively Coupled Plasma Method; Filtration, Colorimetric Method; Calculation ^[4]

33 Chromium (VI)

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
33	Chromium (VI)	Filtration, Colorimetric Method ^[4]
34	Chrysene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
35	Cyanide	Distillation, Colorimetric Method ^[4]
36	DDD	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
37	DDE	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
38	DDT	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
39	Dibenz(a,h)anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
40	Di-n-butyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
41	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
42	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
43	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
44	1,1-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
45	1,2-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
46	1,1-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
47	cis-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
48	trans-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
49	2,4-Dichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
50	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
51	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]

52 Dieldrin...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
52	Dieldrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
53	Diethyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
54	2,4-Dimethylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
55	2,4-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
56	2,6-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
57	Di-n-octyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
58	Endosulfan	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
59	Endrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
60	Ethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
61	Fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
62	Fluorene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
63	Heptachlor	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
64	Heptachlor epoxide	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
65	Hexachlorobenzene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
66	Hexachloro-1,3-butadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
67	n-Hexane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
68	α -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
69	β -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

70 γ -HCH...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
70	γ -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
71	Hexachlorocyclopentadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
72	Hexachloroethane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
73	Indeno(1,2,3-cd)pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
74	Isophorone	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
75	Lead	1) Digestion, Direct Air-Acetylene Flame Method ⁽⁴⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
76	Manganese	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
77	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ⁽⁴⁾
78	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
79	Methylene chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
80	2-Methylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
81	2-Methylnaphthalene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
82	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
83	Naphthalene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
84	Nickel	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
85	Nitrobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
86	N-Nitrosodi-n-propylamine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
87	pH	Electrometric Method ⁽⁴⁾
88	Phenanthrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

89 Phenol...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
89	Phenol	1) Distillation, Direct Photometric Method ⁽⁴⁾ 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
90	Pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
91	Selenium	Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ⁽⁴⁾
92	Silver	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
93	Styrene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
94	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
95	Trichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
96	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
97	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
98	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
99	Tetrachloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
100	Toluene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
101	2,4,5-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
102	2,4,6-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
103	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
104	Vanadium	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
105	Vinyl acetate	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
106	Vinyl chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾

107 m-Xylene...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
107	m-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
108	o-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
109	p-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
110	Xylene (Total)	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
111	Zinc	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾

สิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว จำนวน 18 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Antimony	Digestion, Inductively Coupled Plasma Method ^(9,10)
2	Arsenic	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)
3	Barium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)
4	Beryllium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)
5	Cadmium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)
6	Chromium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)
7	Chromium (VI)	1) Waste Extraction, Digestion, Colorimetric Method ^(2,13) 2) Alkaline Digestion, Colorimetric Method ^(9,13)
8	Cobalt	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)
9	Copper	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^(2,9,10) 2) Digestion, Inductively Coupled Plasma Method ^(9,10)

10 Lead...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
10	Lead	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10]
11	Mercury	2) Digestion, Inductively Coupled Plasma Method ^[9,10] 1) Waste Extraction, Digestion, Cold Vapor Atomic Absorption Spectrometric Method ^[2,11] 2) Digestion, Cold vapor Atomic Absorption Spectrometric Method ^[9,11]
12	Nickel	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]
13	Molybdenum	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]
14	Selenium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]
15	Silver	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]
16	Thallium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]
17	Vanadium	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]
18	Zinc	1) Waste Extraction, Digestion, Inductively Coupled Plasma Method ^[2,9,10] 2) Digestion, Inductively Coupled Plasma Method ^[9,10]

ดิน...

COPY

ดิน จำนวน 95 รายการ

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
1	Acenaphthene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
2	Acetone	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
3	Anthracene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
4	Antimony	Digestion, Inductively Coupled Plasma Method ^[9,10]
5	Arsenic	Digestion, Inductively Coupled Plasma Method ^[9,10]
6	Barium	Digestion, Inductively Coupled Plasma Method ^[9,10]
7	Benz(a)anthracene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
8	Benzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
9	Benzo(b)fluoranthene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
10	Benzo(k)fluoranthene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
11	Benzo(a)pyrene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
12	Benzo[g,h,i]perylene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
13	Beryllium	Digestion, Inductively Coupled Plasma Method ^[9,10]
14	Bis(2-chloroethyl)ether	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
15	Bis(2-ethylhexyl)phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
16	Bromodichloromethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
17	Bromoform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
18	Butanol	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]

19 Butyl benzyl phthalate...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
19	Butyl benzyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
20	Cadmium	Digestion, Inductively Coupled Plasma Method ^(9,10)
21	Carbazole	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
22	Carbon disulfide	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
23	Carbon tetrachloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
24	p-Chloroaniline	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
25	Chlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
26	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
27	Chloroform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
28	2-Chlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
29	Chromium	Digestion, Inductively Coupled Plasma Method ^(9,10)
30	Chromium (III)	Digestion, Inductively Coupled Plasma Method; Filtration, Colorimetric Method; Calculation ^(9,10)
31	Chromium (VI)	Alkaline Digestion, Colorimetric Method ^(12,13)
32	Chrysene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
33	Dibenz(a,h)anthracene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
34	Di-n-butyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
35	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
36	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
37	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)

38 1,1-Dichloroethane...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
38	1,1-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
39	1,2-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
40	1,1-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
41	cis-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
42	trans-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
43	2,4-Dichlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
44	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
45	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
46	Diethyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
47	2,4-Dimethylphenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
48	2,4-Dinitrotoluene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
49	2,6-Dinitrotoluene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
50	Di-n-octyl phthalate	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
51	Ethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^(14,16)
52	Fluoranthene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
53	Fluorene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
54	Hexachlorobenzene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)
55	Hexachloro-1,3-butadiene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(15,17)

56 n-Hexane...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
56	n-Hexane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
57	Hexachlorocyclopentadiene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
58	Hexachloroethane	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
59	Indeno(1,2,3-cd)pyrene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
60	Isophorone	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
61	Lead	Digestion, Inductively Coupled Plasma Method ^[9,10]
62	Manganese	Digestion, Inductively Coupled Plasma Method ^[9,10]
63	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[9,11]
64	Methylene chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
65	2-Methylphenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
66	2-Methylnaphthalene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
67	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
68	Naphthalene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
69	Nickel	Digestion, Inductively Coupled Plasma Method ^[9,10]
70	Nitrobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
71	N-Nitrosodi-n-propylamine	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
72	Phenanthrene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
73	Phenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
74	Pyrene	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]

75 Selenium...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
75	Selenium	Digestion, Inductively Coupled Plasma Method ^[9,10]
76	Silver	Digestion, Inductively Coupled Plasma Method ^[9,10]
77	Styrene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
78	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
79	Tetrachloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
80	Toluene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
81	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
82	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
83	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
84	Trichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
85	2,4,5-Trichlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
86	2,4,6-Trichlorophenol	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[15,17]
87	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
88	Vanadium	Digestion, Inductively Coupled Plasma Method ^[9,10]
89	Vinyl acetate	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
90	Vinyl chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
91	m-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
92	o-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
93	p-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]

94 Xylene (Total)...

COPY

ลำดับที่	สารมลพิษ	วิธีวิเคราะห์
94	Xylene (Total)	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[14,16]
95	Zinc	Digestion, Inductively Coupled Plasma Method ^[9,10]

เอกสารอ้างอิง

1. กระทรวงอุตสาหกรรม. ประกาศกระทรวงอุตสาหกรรม พ.ศ.2549 เรื่องกำหนดค่าปริมาณเขม่าควันที่เจือปนในอากาศที่ระบายออกจากปล่องของหม้อน้ำโรงสีข้าวที่ใช้แก๊สเป็นเชื้อเพลิง. ราชกิจจานุเบกษา. 4 ธันวาคม 2549. เล่มที่ 123 ตอนพิเศษ 125 ง.
2. กระทรวงอุตสาหกรรม. ประกาศกระทรวงอุตสาหกรรม พ.ศ.2548 เรื่อง การกำจัดสิ่งปฏิกูลหรือวัสดุที่ไม่ใช้แล้ว. ราชกิจจานุเบกษา. 25 มกราคม 2549. เล่มที่ 123 ตอนพิเศษ 11 ง.
3. สมาคมวิศวกรรมสิ่งแวดล้อมแห่งประเทศไทย. คู่มือวิเคราะห์น้ำเสีย. พิมพ์ครั้งที่ 4. กรุงเทพฯ: เรือนแก้วการพิมพ์, 2547.
4. APHA, AWWA, WEF. Standard Methods for the Examination of Water and Wastewater. 23rd ed. Washington, DC : APHA, 2017
5. United States Environmental Protection Agency. Standard of Performance for New Stationary Sources. 40 CFR Part 60. Appendix A, 2017.
6. United States Environmental Protection Agency. Standard of Performance for New Stationary Sources. 40 CFR Part 60. Appendix A, 2019.
7. United States Environmental Protection Agency. Standard of Performance for New Stationary Sources. 40 CFR Part 60. Appendix A, 2020.
8. United States Environmental Protection Agency. Standard of Performance for New Stationary Sources. 40 CFR Part 60. Appendix A, 2023.
9. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Acid Digestion of Sediments Sludge and Soils. SW-846 Method 3050B, 1996.
10. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Inductively Coupled Plasma-Atomic Emission spectrometry. SW-846 Method 6010C, 2007.
11. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Mercury in Solid or Semisolid Waste (Manual Cold-Vapor Technique). SW-846 Method 7471B, 2007.
12. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Alkaline digestion for Hexavalent Chromium. SW-846 Method 3060A, 1996.



13 United...

COPY

13. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Chromium. Hexavalent (Colorimetric). SW-846 Method 7196A, 1992

14. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Closed-System Purge-and-Trap and Extraction for Volatile Organics in Soil and Waste Samples. SW-846 Method 5035A, 2002

15. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Ultrasonic Extraction. SW-846 Method 3550C, 2007

16. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Volatile Organic Compounds by Gas Chromatography/Mass Spectrometry (GC/MS). SW-846 Method 8260D, 2018

17. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Semivolatile Organic Compounds by Gas Chromatography/Mass Spectrometry. SW-846 Method 8270E, 2018



COPY



ที่ อก ๐๓๒๐/ ๔ ๖ ๐๔

กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๔๐๐

๑๔ พฤษภาคม ๒๕๖๗

เรื่อง เปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ เปลี่ยนแปลงสารมลพิษในดิน และเปลี่ยนแปลงบุคลากร
ของห้องปฏิบัติการวิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท อีสเทิร์น ไทย คอนสตรัคติง ๑๙๙๒ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๔ มีนาคม ๒๕๖๗

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ และเปลี่ยนแปลง
สารมลพิษบริษัท อีสเทิร์น ไทย คอนสตรัคติง ๑๙๙๒ จำกัด จำนวน ๑๒ แผ่น

ตามคำขอฯ ที่อ้างถึง บริษัท อีสเทิร์น ไทย คอนสตรัคติง ๑๙๙๒ จำกัด ห้องปฏิบัติการวิเคราะห์
เอกชน เลขทะเบียน ว-๐๐๓ สถานที่ตั้งเลขที่ ๖๘๓ หมู่ที่ ๑๑ ถนนสุขุมวิท ๘ ตำบลหนองขาม
อำเภอศรีราชา จังหวัดชลบุรี แจ้งขอเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษในน้ำเสีย น้ำใต้ดิน
เปลี่ยนแปลงสารมลพิษในดิน และเปลี่ยนแปลงบุคลากร นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว มีความเห็นดังนี้

๑. ให้ยกเลิกผู้ควบคุมดูแลห้องปฏิบัติการวิเคราะห์ จำนวน ๑ ราย

นายวัฒนา โคตรหล้า ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๐๒

๒. ให้ยกเลิกเจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๓ ราย

๑) นางสาวอัญชลี ทะพงษ์ ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๑๒

๒) นางสาวจุฑามาศ เจริญพรหม ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๑๕

๓) นางสาวณัฐนิช นนตานอก ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๒๔

๓. ให้ยกเลิกขอขยายรายการสารมลพิษในน้ำเสีย และน้ำใต้ดินตามรายการเอกสารแนบท้าย
หนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชนที่ อก ๐๓๒๐/๑๓๔๒ ลงวันที่ ๒๗ กรกฎาคม ๒๕๖๖

๔. ให้วิเคราะห์สารมลพิษตามขอขยายที่ได้รับขึ้นทะเบียนให้วิเคราะห์ในน้ำเสีย จำนวน ๔๗ รายการ
และน้ำใต้ดิน จำนวน ๑๑๑ รายการ รวมทั้งสิ้นจำนวน ๑๕๘ รายการ ตามเอกสารแนบท้ายหนังสือเปลี่ยนแปลง
เอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ เปลี่ยนแปลงสารมลพิษในดิน และเปลี่ยนแปลงบุคลากร ดังสิ่งที่ส่งมาด้วย

๕. ให้วิเคราะห์สารมลพิษตามขอขยายที่ได้รับขึ้นทะเบียนให้วิเคราะห์เพิ่มเติมในดิน จำนวน
๑๒ รายการ ตามเอกสารแนบท้ายหนังสือเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษเปลี่ยนแปลงสารมลพิษ
ในดิน และเปลี่ยนแปลงบุคลากร ดังสิ่งที่ส่งมาด้วย

อนึ่ง หนังสือ

-๒-

อนึ่ง หนังสือฉบับนี้จะหมดอายุพร้อมหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์
เอกชนในวันที่ ๕ กรกฎาคม ๒๕๖๙

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายพรยศ กลั่นกรอง)

รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมโรงงานอุตสาหกรรม

ศูนย์วิจัยและเตือนภัยมลพิษโรงงานภาคตะวันออก

โทร. ๐ ๓๓๑๓ ๖๐๕๙ ต่อ ๕๐๐๑-๒

ไปรษณีย์อิเล็กทรอนิกส์ sirw@diw.mail.go.th



“อุตสาหกรรมก้าวไกล ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว”



COPY



“อุตสาหกรรมก้าวไกล ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว”



COPY

เอกสารแนบท้ายหนังสือเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ

บริษัท อีสเทิร์น ไทย คอนซัลติ้ง ๑๙๙๒ จำกัด

เลขทะเบียน ๖-๐๐๓

ที่ อก ๐๓๒๐/

ลงวันที่

ขอขยายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๑๗๐ รายการ

น้ำเสีย จำนวน 47 รายการ

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
2	Arsenic	1) Continuous Hydride Generation/Atomic Absorption Spectrometric Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
3	Barium	Digestion, Inductively Coupled Plasma Method ^[1]
4	α-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
5	β-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
6	δ-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
7	γ-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
8	Biochemical Oxygen Demand	1) 5-Day BOD Test, Membrane Electrode Method ^[1] 2) 5-Day BOD Test, Azide Modification Method ^[1]
9	Cadmium	Digestion, Inductively Coupled Plasma Method ^[1]
10	Chemical Oxygen Demand	Closed Reflux, Titrimetric Method ^[1]
11	cis-Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]

12 trans-Chlordane ...

COPY

-๒-

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
12	trans-Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
13	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
14	Color	ADMI Weighted-Ordinate Spectrophotometric Method ^[1]
15	Copper	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
16	Cyanide	Distillation, Colorimetric Method ^[1]
17	4,4'-DDD	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
18	4,4'-DDE	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
19	DDT	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
20	Dieldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
21	Endosulfan I	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
22	Endosulfan II	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
23	Endosulfan sulfate	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
24	Endrin	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]

25 Endrin aldehyde ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
25	Endrin aldehyde	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
26	Endrin ketone	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
27	Formaldehyde	Distillation, Colorimetric Method ^[4]
28	Free Chlorine	1) Iodometric Method ^[1] 2) Colorimetric Method ^[1]
29	Heptachlor	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
30	Heptachlor Epoxide	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
31	Hexavalent Chromium	Filtration, Colorimetric Method ^[1]
32	Lead	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
33	Manganese	Digestion, Inductively Coupled Plasma Method ^[1]
34	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[1]
35	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
36	Nickel	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
37	Oil and Grease	Liquid-Liquid, Partition-Gravimetric Method ^[1]
38	pH	Electrometric Method ^[1]
39	Phenols	Distillation, Direct Photometric Method ^[1]
40	Selenium	Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[1]

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
41	Sulfide	ZnS Precipitation, Iodometric Method ^[1]
42	Temperature	Field Method ^[1]
43	Trivalent Chromium	1) Digestion, Direct Air-Acetylene Flame Method; Filtration, Colorimetric Method; Calculation ^[1] 2) Digestion, Inductively Coupled Plasma Method; Colorimetric Method; Calculation ^[1]
44	Total Dissolved Solids	Dried at 180 °C ^[1]
45	Total Kjeldahl Nitrogen	Macro Kjeldahl Method ^[1]
46	Total Suspended Solids	Dried at 103-105 °C ^[1]
47	Zinc	Digestion, Inductively Coupled Plasma Method ^[1]

น้ำใต้ดิน จำนวน 111 รายการ

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
1	Acenaphthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
2	Acetone	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
3	Aldrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
4	Anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
5	Antimony	Digestion, Inductively Coupled Plasma Method ^[1]
6	Arsenic	1) Continuous Hydride Generation/Atomic Absorption Spectrometric Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
7	Barium	Digestion, Inductively Coupled Plasma Method ^[1]
8	Benz(a)anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]

COPY

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
9	Benzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
10	Benzo(b)fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
11	Benzo(k)fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
12	Benzo(a)pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
13	Benzo(g,h,i)perylene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
14	Beryllium	Digestion, Inductively Coupled Plasma Method ⁽¹⁾
15	Bis(2-chloroethyl)ether	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
16	Bis(2-ethylhexyl)phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
17	Bromodichloromethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
18	Bromoform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
19	Butanol	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
20	Butyl benzyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
21	Cadmium	Digestion, Inductively Coupled Plasma Method ⁽¹⁾
22	Carbazole	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
23	Carbon disulfide	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
24	Carbon tetrachloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾

25 Chlordane ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
25	Chlordane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
26	p-Chloroaniline	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
27	Chlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
28	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
29	Chloroform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
30	2-Chlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
31	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ⁽¹⁾ 2) Digestion, Inductively Coupled Plasma Method ⁽¹⁾
32	Chromium (III)	1) Digestion, Direct Air-Acetylene Flame Method; Filtration, Colorimetric Method; Calculation ⁽¹⁾ 2) Digestion, Inductively Coupled Plasma Method; Filtration, Colorimetric Method; Calculation ⁽¹⁾
33	Chromium (VI)	Filtration, Colorimetric Method ⁽¹⁾
34	Chrysene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
35	Cyanide	Distillation, Colorimetric Method ⁽¹⁾
36	DDD	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
37	DDE	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
38	DDT	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
39	Dibenz(a,h)anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾

40 Di-n-butyl phthalate ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
40	Di-n-butyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
41	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
42	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
43	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
44	1,1-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
45	1,2-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
46	1,1-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
47	cis-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
48	trans-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
49	2,4-Dichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
50	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
51	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
52	Dieldrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
53	Diethyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
54	2,4-Dimethylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾

55 2,4-Dinitrotoluene ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
55	2,4-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
56	2,6-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
57	Di-n-octyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
58	Endosulfan	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
59	Endrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
60	Ethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
61	Fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
62	Fluorene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
63	Heptachlor	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
64	Heptachlor epoxide	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
65	Hexachlorobenzene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
66	Hexachloro-1,3-butadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
67	n-Hexane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
68	α -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾
69	β -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽¹⁾

70 γ -HCH ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
70	γ -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
71	Hexachlorocyclopentadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
72	Hexachloroethane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
73	Indeno(1,2,3-cd)pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
74	Isophorone	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
75	Lead	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
76	Manganese	Digestion, Inductively Coupled Plasma Method ^[1]
77	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[1]
78	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
79	Methylene chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
80	2-Methylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
81	2-Methylnaphthalene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
82	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
83	Naphthalene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
84	Nickel	Digestion, Inductively Coupled Plasma Method ^[1]
85	Nitrobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]

86 N-Nitrosodi-n-propylamine ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
86	N-Nitrosodi-n-propylamine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
87	pH	Electrometric Method ^[4]
88	Phenanthrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
89	Phenol	1) Distillation, Direct Photometric Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
90	Pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
91	Selenium	Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4]
92	Silver	Digestion, Inductively Coupled Plasma Method ^[4]
93	Styrene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
94	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
95	Trichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
96	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
97	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
98	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
99	Tetrachloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
100	Toluene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
101	2,4,5-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]

102 2,4,6-Trichlorophenol ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
102	2,4,6-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
103	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
104	Vanadium	Digestion, Inductively Coupled Plasma Method ^[4]
105	Vinyl acetate	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
106	Vinyl chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
107	m-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
108	o-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
109	p-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
110	Xylene (Total)	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
111	Zinc	Digestion, Inductively Coupled Plasma Method ^[4]

ดิน จำนวน 12 รายการ

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
1	α-HCH	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
2	β-HCH	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
3	γ-HCH	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
4	Heptachlor	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]

5 Aldrin ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
5	Aldrin	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
6	Heptachlor epoxide	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
7	Chlordane	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
8	Dieldrin	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
9	Endrin	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
10	DDD	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
11	DDT	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]
12	Methoxychlor	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^[2,3]

เอกสารอ้างอิง

1. APHA, AWWA, WEF. **Standard Methods for the Examination of Water and Wastewater**. 24th ed. Washington, DC: APHA, 2023.
2. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Ultrasonic Extraction**. SW-846 Method 3550C, 2007
3. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Semivolatile Organic Compounds by Gas Chromatography/Mass Spectrometry**. SW-846 Method 8270E, 2018
4. สมาคมวิศวกรรมสิ่งแวดล้อมแห่งประเทศไทย. คู่มือวิเคราะห์น้ำเสีย. พิมพ์ครั้งที่ 4. กรุงเทพฯ: เรือนแก้วการพิมพ์, 2547.

COPY



ที่ อก ๐๓๒๐/ ๔๖๐๔

กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๔๐๐

๑๔ พฤษภาคม ๒๕๖๗

เรื่อง เปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ เปลี่ยนแปลงสารมลพิษในดิน และเปลี่ยนแปลงบุคลากร
ของห้องปฏิบัติการวิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท อีสเทิร์น ไทย คอนซัลตติ้ง ๑๙๙๒ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๔ มีนาคม ๒๕๖๗

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ และเปลี่ยนแปลง
สารมลพิษบริษัท อีสเทิร์น ไทย คอนซัลตติ้ง ๑๙๙๒ จำกัด จำนวน ๑๒ แผ่น

ตามคำขอฯ ที่อ้างถึง บริษัท อีสเทิร์น ไทย คอนซัลตติ้ง ๑๙๙๒ จำกัด ห้องปฏิบัติการวิเคราะห์
เอกชน เลขทะเบียน ว-๐๐๓ สถานที่ตั้งเลขที่ ๖๘๓ หมู่ที่ ๑๑ ถนนสุขุมวิท ๘ ตำบลหนองขาม
อำเภอศรีราชา จังหวัดชลบุรี แจ้งขอเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษในน้ำเสีย น้ำใต้ดิน
เปลี่ยนแปลงสารมลพิษในดิน และเปลี่ยนแปลงบุคลากร นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว มีความเห็นดังนี้

๑. ให้ยกเลิกผู้ควบคุมดูแลห้องปฏิบัติการวิเคราะห์ จำนวน ๑ ราย

นายวัฒนา โคตรหล้า ทะเบียนเลขที่ ว-๐๐๓-ก-๐๐๐๒

๒. ให้ยกเลิกเจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๓ ราย

๑) นางสาวอัญชลี ทะพงษ์ ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๑๒

๒) นางสาวจุฑามาศ เจริญพรหม ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๑๕

๓) นางสาวณัฐนิช นนตานอก ทะเบียนเลขที่ ว-๐๐๓-จ-๐๐๒๔

๓. ให้ยกเลิกขอบข่ายรายการสารมลพิษในน้ำเสีย และน้ำใต้ดินตามรายการเอกสารแนบท้าย
หนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชนที่ อก ๐๓๒๐/๑๑๓๔๒ ลงวันที่ ๒๗ กรกฎาคม ๒๕๖๖

๔. ให้วิเคราะห์สารมลพิษตามขอบข่ายที่ได้รับขึ้นทะเบียนให้วิเคราะห์ในน้ำเสีย จำนวน ๔๗ รายการ
และน้ำใต้ดิน จำนวน ๑๑๑ รายการ รวมทั้งสิ้นจำนวน ๑๕๘ รายการ ตามเอกสารแนบท้ายหนังสือเปลี่ยนแปลง
เอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ เปลี่ยนแปลงสารมลพิษในดิน และเปลี่ยนแปลงบุคลากร ดังสิ่งที่ส่งมาด้วย

๕. ให้วิเคราะห์สารมลพิษตามขอบข่ายที่ได้รับขึ้นทะเบียนให้วิเคราะห์เพิ่มเติมในดิน จำนวน
๑๒ รายการ ตามเอกสารแนบท้ายหนังสือเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษเปลี่ยนแปลงสารมลพิษ
ในดิน และเปลี่ยนแปลงบุคลากร ดังสิ่งที่ส่งมาด้วย

อนึ่ง หนังสือ

-๒-

อนึ่ง หนังสือฉบับนี้จะหมดอายุพร้อมหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์
เอกชนในวันที่ ๕ กรกฎาคม ๒๕๖๙

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นายพรยศ ก้านกรอง)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมโรงงานอุตสาหกรรม

ศูนย์วิจัยและเตือนภัยมลพิษโรงงานภาคตะวันออก

โทร. ๐ ๓๓๑๓ ๖๐๕๙ ต่อ ๕๐๐๑-๒

ไปรษณีย์อิเล็กทรอนิกส์ airw@dlw.mail.go.th



“อุตสาหกรรมก้าวไกล ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว”



COPY



“อุตสาหกรรมก้าวไกล ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว”



COPY

เอกสารแนบท้ายหนังสือเปลี่ยนแปลงเอกสารอ้างอิงวิธีวิเคราะห์สารมลพิษ

บริษัท อีสเทิร์น ไทย คอนซัลตติ้ง ๑๙๙๒ จำกัด

เลขทะเบียน ๖-๐๐๓

ที่ อก ๐๓๒๐/

ลงวันที่

ขอบข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๑๗๐ รายการ

น้ำเสีย จำนวน 47 รายการ

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
1	Aldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
2	Arsenic	1) Continuous Hydride Generation/Atomic Absorption Spectrometric Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
3	Barium	Digestion, Inductively Coupled Plasma Method ^[1]
4	α-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
5	β-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
6	δ-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
7	γ-BHC	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
8	Biochemical Oxygen Demand	1) 5-Day BOD Test, Membrane Electrode Method ^[1] 2) 5-Day BOD Test, Azide Modification Method ^[1]
9	Cadmium	Digestion, Inductively Coupled Plasma Method ^[1]
10	Chemical Oxygen Demand	Closed Reflux, Titrimetric Method ^[1]
11	cis-Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]

12 trans-Chlordane ...

COPY

-๒-

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
12	trans-Chlordane	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
13	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
14	Color	ADMI Weighted-Ordinate Spectrophotometric Method ^[1]
15	Copper	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
16	Cyanide	Distillation, Colorimetric Method ^[1]
17	4,4'-DDD	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
18	4,4'-DDE	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
19	DDT	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
20	Dieldrin	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
21	Endosulfan I	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
22	Endosulfan II	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
23	Endosulfan sulfate	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
24	Endrin	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]

25 Endrin aldehyde ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
25	Endrin aldehyde	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
26	Endrin ketone	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
27	Formaldehyde	Distillation, Colorimetric Method ^[4]
28	Free Chlorine	1) Iodometric Method ^[1] 2) Colorimetric Method ^[1]
29	Heptachlor	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
30	Heptachlor Epoxide	1) Liquid-Liquid Extraction, Gas Chromatographic Method ^[1] 2) Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
31	Hexavalent Chromium	Filtration, Colorimetric Method ^[1]
32	Lead	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
33	Manganese	Digestion, Inductively Coupled Plasma Method ^[1]
34	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[1]
35	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic / Mass Spectrometric Method ^[1]
36	Nickel	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
37	Oil and Grease	Liquid-Liquid, Partition-Gravimetric Method ^[1]
38	pH	Electrometric Method ^[1]
39	Phenols	Distillation, Direct Photometric Method ^[1]
40	Selenium	Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[1]

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
41	Sulfide	ZnS Precipitation, Iodometric Method ^[1]
42	Temperature	Field Method ^[1]
43	Trivalent Chromium	1) Digestion, Direct Air-Acetylene Flame Method; Filtration, Colorimetric Method; Calculation ^[1] 2) Digestion, Inductively Coupled Plasma Method; Colorimetric Method; Calculation ^[1]
44	Total Dissolved Solids	Dried at 180 °C ^[1]
45	Total Kjeldahl Nitrogen	Macro Kjeldahl Method ^[1]
46	Total Suspended Solids	Dried at 103-105 °C ^[1]
47	Zinc	Digestion, Inductively Coupled Plasma Method ^[1]

น้ำใต้ดิน จำนวน 111 รายการ

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
1	Acenaphthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
2	Acetone	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
3	Aldrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
4	Anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
5	Antimony	Digestion, Inductively Coupled Plasma Method ^[1]
6	Arsenic	1) Continuous Hydride Generation/Atomic Absorption Spectrometric Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
7	Barium	Digestion, Inductively Coupled Plasma Method ^[1]
8	Benz(a)anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
9	Benzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
10	Benzo(b)fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
11	Benzo(k)fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
12	Benzo(a)pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
13	Benzo(g,h,i)perylene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
14	Beryllium	Digestion, Inductively Coupled Plasma Method ^[1]
15	Bis(2-chloroethyl)ether	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
16	Bis(2-ethylhexyl)phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
17	Bromodichloromethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
18	Bromoform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
19	Butanol	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
20	Butyl benzyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
21	Cadmium	Digestion, Inductively Coupled Plasma Method ^[1]
22	Carbazole	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
23	Carbon disulfide	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
24	Carbon tetrachloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]

25 Chlordane ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
25	Chlordane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
26	p-Chloroaniline	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
27	Chlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
28	Chlorodibromomethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
29	Chloroform	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
30	2-Chlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
31	Chromium	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
32	Chromium (III)	1) Digestion, Direct Air-Acetylene Flame Method; Filtration, Colorimetric Method; Calculation ^[1] 2) Digestion, Inductively Coupled Plasma Method; Filtration, Colorimetric Method; Calculation ^[1]
33	Chromium (VI)	Filtration, Colorimetric Method ^[1]
34	Chrysene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
35	Cyanide	Distillation, Colorimetric Method ^[1]
36	DDD	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
37	DDE	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
38	DDT	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
39	Dibenz(a,h)anthracene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]

40 Di-n-butyl phthalate ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
40	Di-n-butyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
41	1,2-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
42	1,3-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
43	1,4-Dichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
44	1,1-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
45	1,2-Dichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
46	1,1-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
47	cis-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
48	trans-1,2-Dichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
49	2,4-Dichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
50	1,2-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
51	1,3-Dichloropropane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
52	Dieldrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
53	Diethyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
54	2,4-Dimethylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]

55 2,4-Dinitrotoluene ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
55	2,4-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
56	2,6-Dinitrotoluene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
57	Di-n-octyl phthalate	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
58	Endosulfan	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
59	Endrin	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
60	Ethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
61	Fluoranthene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
62	Fluorene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
63	Heptachlor	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
64	Heptachlor epoxide	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
65	Hexachlorobenzene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
66	Hexachloro-1,3-butadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
67	n-Hexane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
68	α -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
69	β -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]

70 γ -HCH ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
70	γ -HCH	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
71	Hexachlorocyclopentadiene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
72	Hexachloroethane	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
73	Indeno(1,2,3-cd)pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
74	Isophorone	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
75	Lead	1) Digestion, Direct Air-Acetylene Flame Method ^[1] 2) Digestion, Inductively Coupled Plasma Method ^[1]
76	Manganese	Digestion, Inductively Coupled Plasma Method ^[1]
77	Mercury	Digestion, Cold-Vapor Atomic Absorption Spectrometric Method ^[1]
78	Methoxychlor	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
79	Methylene chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
80	2-Methylphenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
81	2-Methylnaphthalene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
82	Methyl tert-butyl ether	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
83	Naphthalene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]
84	Nickel	Digestion, Inductively Coupled Plasma Method ^[1]
85	Nitrobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[1]

86 N-Nitrosodi-n-propylamine ...

COPY

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
86	N-Nitrosodi-n-propylamine	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[1]
87	pH	Electrometric Method ^[4]
88	Phenanthrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
89	Phenol	1) Distillation, Direct Photometric Method ^[4] 2) Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
90	Pyrene	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]
91	Selenium	Digestion, Hydride Generation/Atomic Absorption Spectrometric Method ^[4]
92	Silver	Digestion, Inductively Coupled Plasma Method ^[4]
93	Styrene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
94	1,1,2,2-Tetrachloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
95	Trichloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
96	1,2,4-Trichlorobenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
97	1,1,1-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
98	1,1,2-Trichloroethane	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
99	Tetrachloroethylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
100	Toluene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ^[4]
101	2,4,5-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ^[4]

102 2,4,6-Trichlorophenol ...

COPY

-๑๑-

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
102	2,4,6-Trichlorophenol	Liquid-Liquid Extraction, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
103	1,3,5-Trimethylbenzene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
104	Vanadium	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾
105	Vinyl acetate	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
106	Vinyl chloride	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
107	m-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
108	o-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
109	p-Xylene	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
110	Xylene (Total)	Purge and Trap, Gas Chromatographic/Mass Spectrometric Method ⁽⁴⁾
111	Zinc	Digestion, Inductively Coupled Plasma Method ⁽⁴⁾

ดิน จำนวน 12 รายการ

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
1	α-HCH	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
2	β-HCH	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
3	γ-HCH	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
4	Heptachlor	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)

5 Aldrin ...

COPY

-๑๒-

ลำดับ ที่	สารมลพิษ	วิธีวิเคราะห์
5	Aldrin	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
6	Heptachlor epoxide	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
7	Chlordane	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
8	Dieldrin	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
9	Endrin	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
10	DDD	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
11	DDT	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)
12	Methoxychlor	Ultrasonic Extraction, Gas Chromatographic/Mass Spectrometric Method ^(2,3)

เอกสารอ้างอิง

1. APHA, AWWA, WEF. **Standard Methods for the Examination of Water and Wastewater**. 24th ed. Washington, DC: APHA, 2023.
2. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Ultrasonic Extraction**. SW-846 Method 3550C, 2007
3. United States Environment Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. **Semivolatile Organic Compounds by Gas Chromatography/Mass Spectrometry**. SW-846 Method 8270E, 2018
4. สมาคมวิศวกรรมสิ่งแวดล้อมแห่งประเทศไทย. คู่มือวิเคราะห์น้ำเสีย. พิมพ์ครั้งที่ 4. กรุงเทพฯ: เรือนแก้วการพิมพ์, 2547.

ศูนย์วิจัยและเตือนภัยมลพิษโรงงานภาคตะวันออก กรมโรงงานอุตสาหกรรม โทร. ๐ ๒๓๓๓ ๖๐๕๔ ต่อ ๕๐๐๑๒

COPY



ที่ อก ๐๓๑๐(๓)/ ๘๓ ๔ ๕

กรมโรงงานอุตสาหกรรม
ถนนพระรามที่ ๖ แขวงทุ่งพญาไท
เขตราชเทวี กรุงเทพฯ ๑๐๔๐๐

๐๙ ตุลาคม ๒๕๖๔

เรื่อง เปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

เรียน กรรมการผู้จัดการ บริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง ๑๙๙๒ จำกัด

อ้างถึง คำขอขึ้นทะเบียน/ต่ออายุ/เปลี่ยนแปลงบุคลากร และชนิดสารมลพิษของห้องปฏิบัติการวิเคราะห์เอกชน
ลงวันที่ ๒๙ สิงหาคม ๒๕๖๔

สิ่งที่ส่งมาด้วย เอกสารแนบท้ายหนังสือเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์
บริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง ๑๙๙๒ จำกัด จำนวน ๑ แผ่น

ตามคำขอที่อ้างถึง บริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง ๑๙๙๒ จำกัด ห้องปฏิบัติการวิเคราะห์
เอกชน เลขทะเบียน ๖-๐๐๓ สถานที่ตั้งเลขที่ ๖๘๓ หมู่ที่ ๑๑ ถนนสุขาภิบาล ๘ ตำบลหนองขาม อำเภอศรีราชา
จังหวัดชลบุรี ขอเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์ ต่อกรมโรงงานอุตสาหกรรม นั้น

กรมโรงงานอุตสาหกรรมพิจารณาแล้ว มีความเห็นดังนี้

๑. ให้ยกเลิกผู้ควบคุมดูแลห้องปฏิบัติการวิเคราะห์ จำนวน ๑ ราย

นายภาคภูมิ บัวสวัสดิ์ ทะเบียนเลขที่ ๖-๐๐๓-ค-๐๐๑๓

๒. ให้ยกเลิกเจ้าหน้าที่ประจำห้องปฏิบัติการวิเคราะห์ จำนวน ๓ ราย

๑) นางสาวนิอรธมา ปาระ ทะเบียนเลขที่ ๖-๐๐๓-จ-๐๐๐๖

๒) นางสาวสุทธิดา สร้างแก้ว ทะเบียนเลขที่ ๖-๐๐๓-จ-๐๐๐๘

๓) นางสาวดวงสุดา แสนวันดี ทะเบียนเลขที่ ๖-๐๐๓-จ-๐๐๒๕

๓. ให้เพิ่มเจ้าหน้าที่ห้องปฏิบัติการวิเคราะห์เอกชน จำนวน ๑ ราย

นายวรารุณ อารีเอื้อ ทะเบียนเลขที่ ๖-๐๐๓-จ-๐๐๒๖

๔. ให้เพิ่มขอบข่ายชนิดสารมลพิษที่วิเคราะห์ในน้ำใต้ดิน และดิน ตามสิ่งที่ส่งมาด้วย

อนึ่ง หนังสือฉบับนี้จะสิ้นสุดอายุพร้อมหนังสือต่ออายุรับขึ้นทะเบียนห้องปฏิบัติการวิเคราะห์เอกชน

ในวันที่ ๕ กรกฎาคม ๒๕๖๔

จึงเรียนมาเพื่อทราบ

ขอแสดงความนับถือ

(นางสาวปัทมวรรณ คุณประเสริฐ)

ผู้อำนวยการกองวิจัยและเตือนภัยมลพิษโรงงาน

ปฏิบัติราชการแทนอธิบดีกรมโรงงานอุตสาหกรรม

ศูนย์วิจัยและเตือนภัยมลพิษโรงงานภาคตะวันออก

โทร. ๐ ๓๓๑๓ ๖๐๕๙ ต่อ ๕๐๐๑-๒

ไปรษณีย์อิเล็กทรอนิกส์ erw@dw.mail.go.th



อุตสาหกรรมก้าวไกล ประเทศไทยก้าวหน้า ร่วมกันพัฒนา อุตสาหกรรมสีเขียว



COPY

เอกสารแนบท้ายหนังสือเปลี่ยนแปลงบุคลากรและสารมลพิษที่วิเคราะห์

บริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง ๑๙๙๒ จำกัด

เลขทะเบียน ๖-๐๐๓

ที่ อก ๐๓๑๐(๓)/ ๘๓ ๔ ๕

ลงวันที่ ๐๙ ตุลาคม ๒๕๖๔

ขอบข่ายสารมลพิษที่ได้รับขึ้นทะเบียนจากกรมโรงงานอุตสาหกรรม จำนวน ๙ รายการ

น้ำใต้ดิน จำนวน 4 รายการ

ลำดับที่	ชนิดสารมลพิษ	วิธีวิเคราะห์
1	Aluminum	Digestion, Inductively Coupled Plasma Method ⁽¹⁾
2	Copper	Digestion, Inductively Coupled Plasma Method ⁽¹⁾
3	Iron	Digestion, Inductively Coupled Plasma Method ⁽¹⁾
4	Molybdenum	Digestion, Inductively Coupled Plasma Method ⁽¹⁾

ดิน จำนวน 5 รายการ

ลำดับที่	ชนิดสารมลพิษ	วิธีวิเคราะห์
1	Aluminum	Digestion, Inductively Coupled Plasma Method ^(2,3)
2	Copper	Digestion, Inductively Coupled Plasma Method ^(2,3)
3	Iron	Digestion, Inductively Coupled Plasma Method ^(2,3)
4	Molybdenum	Digestion, Inductively Coupled Plasma Method ^(2,3)
5	pH	Electrometric Method ⁽⁴⁾

เอกสารอ้างอิง

1. APHA, AWWA, WEF. Standard Methods for the Examination of Water and Wastewater. 24th ed. Washington, DC : APHA, 2023

2. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Acid Digestion of Sediments, Sludges, and Soils. SW-846 Method 3050B, 1996.

3. United States Environmental Protection Agency. Inductively Coupled Plasma - Atomic Emission Spectrometry. SW-846 Method 6010C, 2007

4. United States Environmental Protection Agency. Test Methods for Evaluation Solid Waste Physical/Chemical Methods. Soil and Waste pH. SW-846 Method 9045D, 2004.

COPY



แบบ ภ.บ.ญ
นิติบุคคล

กรมสวัสดิการและคุ้มครองแรงงาน

ใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการตรวจวัดระดับความเข้มข้นของสารเคมีอันตราย
ในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย

ใบอนุญาตเลขที่ ๐๒๐๑-๐๓-๒๕๖๔-๐๐๐๘

อนุญาตให้ บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด.....

เลขทะเบียนนิติบุคคล ๐๒๐๕๕๓๕๐๐๔๕๗๘.....

ตั้งอยู่ เลขที่ ๙๙๙ หมู่ที่ ๑๑ ตำบลหนองขาม อำเภอสรีราชา จังหวัดชลบุรี.....

เป็นนิติบุคคลผู้ให้บริการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน ตามกฎกระทรวง
กำหนดมาตรฐานในการบริหาร จัดการ และดำเนินการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อม
ในการทำงานเกี่ยวกับสารเคมีอันตราย พ.ศ. ๒๕๕๖ ในการเป็นผู้ให้บริการตรวจวัดระดับความเข้มข้น
ของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย ประกอบกับ
กฎกระทรวงการขึ้นทะเบียนและการอนุญาตให้บริการเพื่อส่งเสริมความปลอดภัย อาชีวอนามัย และสภาพแวดล้อม
ในการทำงาน พ.ศ. ๒๕๖๔ แห่งพระราชบัญญัติความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน
พ.ศ. ๒๕๕๔ โดยมีบุคลากร จำนวน ๒๖ ราย และรายการเครื่องมือตรวจวัด จำนวน ๘๒ เครื่อง ดังรายละเอียด
แนบท้ายใบอนุญาตนี้

ทั้งนี้ ตั้งแต่วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗

(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

รายชื่อบุคลากรแนบท้ายใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการตรวจวัดระดับความเข้มข้นของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงาน
และสถานที่เก็บรักษาสารเคมีอันตราย

ของบริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด

ใบอนุญาตเลขที่ ๐๒๐๑-๐๓-๒๕๖๔-๐๐๐๘

๑. นางวรรณเพ็ญ	เหล่าจินดาวัฒน์
๒. นางสาวธัญพร	กลิ่นไสภณ
๓. นายธงไชย	บุญศักดิ์
๔. นายวิษณุชวัล	สิงห์โต
๕. นายโอชา	ขวัญศิริมงคล
๖. นายธีระพงษ์	นวลอินทร์
๗. นายวรากร	ไวยทยะเสวี
๘. นายณิชาพล	ทองหล่อ
๙. นายสุทธา	สองธนิย์
๑๐. นายธรรมรัตน์	โพธิ์ตันคำ
๑๑. นายเมธี	สุขประเสริฐ
๑๒. นายคมกฤษ	ครรสอน
๑๓. นายนราธิป	สงวนศิลป์
๑๔. นายวีระชัย	พอใจ
๑๕. นางสาวนันทประภา	อูยสูงเนิน
๑๖. นางสาวจันทน์	สายพันธ์
๑๗. นายทรงพล	ผิวอ้วน
๑๘. นายศุภฤกษ์	พาดกลาง
๑๙. นางสาวพรนภา	พงษ์เพชร
๒๐. นางสาวจุฑารัตน์	สุชชาเกต
๒๑. นางสาวศวิตา	กิตติเนาวรัตน์
๒๒. นางสาวอรอนงค์	สิวงค์ศักดิ์
๒๓. นางสาวปภาดา	เจริญพร
๒๔. นายวราวุธ	อารีเอื้อ

๒๕. นายสุกกร...


COPY

COPY

๒๕. นายศุภกร นพพรพิทักษ์
๒๖. นายศุภชัย ภารการ

ทั้งนี้ ตั้งแต่วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน


COPY

รายชื่อบุคลากร (เพิ่มเติม)
แนบท้ายใบอนุญาตเป็นนิติบุคคลผู้ให้บริการตรวจวัดระดับความเข้มข้นของสารเคมีอันตราย
ในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย
ของบริษัท ฮีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๒๐๓-๐๓-๒๕๖๔-๐๐๐๘

๑. นางสาวรัตณี นาคเกตุ
๒. นางสาวดวงใจ แยมประโคน

ทั้งนี้ ตั้งแต่วันที่ ๒๒ พฤษภาคม พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๒ พฤษภาคม พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายชื่อบุคลากร (เพิ่มเติม)
 แนบท้ายใบอนุญาตเป็นนิติบุคคลผู้ให้บริการตรวจวัดระดับความเข้มข้นของสารเคมีอันตราย
 ในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย
 ของบริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๒๐๑-๐๓-๒๕๖๔-๐๐๐๘

๑. นายวิทยา แสนตอ
๒. นางสาวนฤมล โนนหิน
๓. นางสาววรกานต์ เสาวรส
๔. นางสาวจิรนนทพร พันธนา
๕. นางสาวชศรินทร์ พุทธา

ทั้งนี้ ตั้งแต่วันที่ ๒๔ ธันวาคม พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๔ ธันวาคม พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)
 รองอธิบดี ปฏิบัติราชการแทน
 อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายการเครื่องมือตรวจวัดแนบท้ายใบอนุญาต
 เป็นนิติบุคคลผู้ให้บริการตรวจวัดระดับความเข้มข้นของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงาน
 และสถานที่เก็บรักษาสารเคมีอันตราย
 ของบริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๒๐๑-๐๓-๒๕๖๔-๐๐๐๘

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องมือเก็บตัวอย่างอากาศ (Personal Air Sampling Pump)	ยี่ห้อ รุ่น Serial No.	Gilian GilAir-5 20040902003 20040902004 20100401018 20100401019 20100401020 20100401021 20100401022 20100401023 20100401024 20100401025 20100402002	๑๑
		ยี่ห้อ รุ่น Serial No.	Gilian GilAir-3 20150302001 20150302002 20150302003 20150302004 20150302005 20160502011 20160502012 20160502013 20160502014 20160502015 20160502016 20160502017	๑๕

COPY

-๒-

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องมือเก็บตัวอย่างอากาศ (Personal Air Sampling Pump) (ต่อ)	Serial No.	20160502018 20160502019 20160502020	
		ยี่ห้อ รุ่น Serial No.	Gilian BDX-II 20180903076 20180903078 20180903079 20180903080 20180903081 20180903082 20180903083 20180903084 20180903085 20180903092 20180903093 20180903094 20181001041 20181001042 20181001044 20200403061 20200403062 20200403063 20200403064 20200403065 20200403071 20200403072 20200403073 20200403074 20200403075 20200403076	๓๔

COPY

-๓-


ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องมือเก็บตัวอย่างอากาศ (Personal Air Sampling Pump) (ต่อ)	Serial No.	20200403077 20200403078 20200403079 20200403080 20211102097 20211102098 20211102099 20211102103 20211102105 20211102125 20211103003 20211103024 20211103029	
		ยี่ห้อ รุ่น Serial No.	SKC Pocket Pump TOUCH 218383 218385 218388 218391 218402 218403 218405 218406 218408 218411 218412 218413 218432 218444 218445	๑๕

COPY

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๒	เครื่องมือและอุปกรณ์สำหรับ ปรับความถูกต้อง (Pump calibrator)	ยี่ห้อ รุ่น Serial No.	MesaLabs Defender 510-M 183893	๑
		ยี่ห้อ รุ่น Serial No.	BIOS Defender 510-L 110619	๑

ทั้งนี้ ตั้งแต่วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน



แบบ ภก.บญ
นิติบุคคล

กรมสวัสดิการและคุ้มครองแรงงาน

ใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการวิเคราะห์ระดับความเข้มข้นของสารเคมีอันตราย
ในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย

ใบอนุญาตเลขที่ ๐๒๐๒๒-๐๓-๒๕๖๔-๐๐๐๕

อนุญาตให้ บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด.....

เลขทะเบียนนิติบุคคล ๐๒๐๕๕๓๕๐๐๔๔๗๘

ตั้งอยู่ เลขที่ ๙๙๙ หมู่ที่ ๑๑ ตำบลหนองขาม อำเภอศรีราชา จังหวัดชลบุรี.....

เป็นนิติบุคคลผู้ให้บริการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน ตามกฎกระทรวง
กำหนดมาตรฐานในการบริหาร จัดการ และดำเนินการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อม
ในการทำงานเกี่ยวกับสารเคมีอันตราย พ.ศ. ๒๕๕๖ ในการเป็นผู้ให้บริการวิเคราะห์ระดับความเข้มข้น
ของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงานและสถานที่เก็บรักษาสารเคมีอันตราย ประกอบกับ
กฎกระทรวงการขึ้นทะเบียนและการอนุญาตให้บริการเพื่อส่งเสริมความปลอดภัย อาชีวอนามัย และสภาพแวดล้อม
ในการทำงาน พ.ศ. ๒๕๖๔ แห่งพระราชบัญญัติความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน
พ.ศ. ๒๕๕๔ โดยมีบุคลากร จำนวน ๒๕ ราย และรายการเครื่องมือวิเคราะห์ จำนวน ๑๒ เครื่อง ดังรายละเอียด
แนบท้ายใบอนุญาตนี้

ทั้งนี้ ตั้งแต่วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

COPY

รายชื่อบุคลากรแนบท้ายใบอนุญาต
 เป็นนิติบุคคลผู้ให้บริการวิเคราะห์ระดับความเข้มข้นของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงาน
 และสถานที่เก็บรักษาสารเคมีอันตราย
 ของบริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๒๐๒-๐๓-๒๕๖๔-๐๐๐๕

- | | |
|---------------------|---------------|
| ๑. นายกะวีร์ | สุธาทรัพย์ |
| ๒. นางสาวนันท์ณภัส | แบขุนทด |
| ๓. นางสาวกัสนันท์ | ป้อมน้อย |
| ๔. นางสาวอัจฉรี | จิตตะยโสธร |
| ๕. นางสาววรรณภา | ไชยศิริ |
| ๖. นางสาวพรพิมล | ภูมิคอนสาร |
| ๗. นางสาวธมลวรรณ | ผลอ้อ |
| ๘. นายภาณุพงศ์ | บำรุงรส |
| ๙. นางสาวฉัตรสุดา | มงคลโกชน์ |
| ๑๐. นางสาวอภิตี | ชินอารมย์ |
| ๑๑. นายขานุวัฒน์ | โชตะวงศ์ |
| ๑๒. นางสาวพจนีย์ | งามวิสัย |
| ๑๓. นางสาวบุญเรือง | บุญถม |
| ๑๔. นางสาวภาณิน | จันต๊ะสอน |
| ๑๕. นางสาวสุนิษา | เฮ้งเส็ง |
| ๑๖. นางสาวธัญลักษณ์ | ขันโต |
| ๑๗. นางสาวณัฐวดี | อำมาตย์คัน |
| ๑๘. นางสาวระพีณ | อันขัน |
| ๑๙. นางสาวสุมิลตรา | มีแก่น |
| ๒๐. นางสาวอรุษา | พันธ์เมือง |
| ๒๑. นายกิตติ | ไพโรจน์ |
| ๒๒. นายชาญณรงค์ | ตั้งธรรมรักษ์ |
| ๒๓. นางสาวดวงกมล | เนื่อทอง |

๒๔. นางสาวคณัญญา โสดาลี
 ๒๕. นางสาววัชรภรณ์ อินทสุข

ทั้งนี้ ตั้งแต่วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตุลารุ)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
 อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

๒๔. นางสาวคณัญญา...

COPY

COPY

รายการเครื่องมือวิเคราะห์แบบหทัยใบอนุญาต
 เป็นนิติบุคคลผู้ให้บริการวิเคราะห์ระดับความเข้มข้นของสารเคมีอันตรายในบรรยากาศของสถานที่ทำงาน
 และสถานที่เก็บรักษาสารเคมีอันตราย
 ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๒๐๒-๐๓-๒๕๖๔-๐๐๐๕


ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	Atomic Absorption Spectrophotometer (AAS)	ยี่ห้อ รุ่น Serial No.	PerkinElmer PinAAcle 900F PFBS22080801	๑
๒	Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES)	ยี่ห้อ รุ่น Serial No.	Teledyne Prodigy 7 P70177	๑
		ยี่ห้อ รุ่น Serial No.	PerkinElmer Avio 550 Max M81S2210101	๑
๓	Gas Chromatograph (GC-FID)	ยี่ห้อ รุ่น Serial No.	Shimadzu GC-2010 Plus C1209520086	๑
		ยี่ห้อ รุ่น Serial No.	Agilent 7890A CN10051046	๑
๔	Gas Chromatography (GC-MS)	ยี่ห้อ รุ่น Serial No.	Shimadzu QP2020 NX 021745801748	๑
๕	Ion Chromatography (IC)	ยี่ห้อ รุ่น Serial No.	Thermo Dionex Integrion RFIC 20053176	๑
๖	UV-VIS Spectrophotometer	ยี่ห้อ รุ่น Serial No.	Shimadzu UV-1800 A11635101643CD	๑

-๒-

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๗	เครื่องชั่ง (Electronic Balance)	ยี่ห้อ รุ่น Serial No.	Mettler-Toledo XS205DU 1126323724	๑
๘	Flue Gas Analyzer	ยี่ห้อ รุ่น Serial No.	Testo Testo 350 60378478 63455658 63455616	๓
		หมายเหตุ เครื่องมือลำดับที่ ๘ ใช้สำหรับการวิเคราะห์คาร์บอนมอนอกไซด์ (Carbon monoxide: CO) ภายในห้องปฏิบัติการเท่านั้น		

ทั้งนี้ ตั้งแต่วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๖ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
 อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

COPY



แบบ กภ.บุญ
นิติบุคคล

กรมสวัสดิการและคุ้มครองแรงงาน

ใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับความร้อน

ใบอนุญาตเลขที่ ๐๔๐๑๑-๐๓-๒๕๖๔-๐๐๐๙

อนุญาตให้...บริษัท.อีสเทิร์น ไทย คอนซิลต์ติง 1992 จำกัด.....

เลขทะเบียนนิติบุคคล...๐๒๐๕๕๓๕๐๐๔๕๙๙๘.....

ตั้งอยู่เลขที่...๙๙๙ หมู่ที่ ๑๑ ตำบลหนองขาม อำเภอศรีวิชัย จังหวัดชลบุรี.....

เป็นนิติบุคคลผู้ให้บริการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน ตามกฎกระทรวง กำหนดมาตรฐานในการบริหาร จัดการ และดำเนินการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงานเกี่ยวกับความร้อน แสงสว่าง และเสียง พ.ศ. ๒๕๕๙ ในการตรวจวัดและวิเคราะห์สภาวะการทำงาน เกี่ยวกับระดับความร้อน ประกอบกับกฎกระทรวงการขึ้นทะเบียนและการอนุญาตให้บริการเพื่อส่งเสริมความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน พ.ศ. ๒๕๖๔ แห่งพระราชบัญญัติความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน พ.ศ. ๒๕๕๔ โดยมีบุคลากร จำนวน ๑๐ ราย และรายการเครื่องมือ ตรวจวัด จำนวน ๑๘ เครื่อง ดังรายละเอียดแนบท้ายใบอนุญาตนี้

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗

(นายศักดิ์ศิลป์ ดุลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

รายชื่อบุคลากรแนบท้ายใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับความร้อน
ของบริษัท อีสเทิร์น ไทย คอนซิลต์ติง 1992 จำกัด

ใบอนุญาตเลขที่ ๐๔๐๑๑-๐๓-๒๕๖๔-๐๐๐๙

- | | |
|--------------------|----------------|
| ๑. นางวรรณเพ็ญ | เหลาจินดาวัฒน์ |
| ๒. นางสาวอัมพร | กลิ่นโสภณ |
| ๓. นางสาวปนัดดา | ร่มรุกข์ |
| ๔. นางสาวอภิรดี | ชื่นอารมย์ |
| ๕. นางสาวอัญลักษณ์ | ชันโต |
| ๖. นางสาวจุฑารัตน์ | สุชชาเกต |
| ๗. นางสาวศิวดา | กิตติเนาวรัตน์ |
| ๘. นางสาวพรนภา | พงษ์เพชร |
| ๙. นางสาวอรอนงค์ | สิ่งศักดิ์ |
| ๑๐. นายศุภชัย | ภารการ |

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗

(นายศักดิ์ศิลป์ ดุลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

COPY

รายชื่อบุคลากร (เพิ่มเติม) แนบท้ายใบอนุญาต
เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับความร้อน
ของบริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๑-๐๓-๒๕๖๔-๐๐๐๔

๑. นางสาวรัตมณี นาคเกตุ
๒. นางสาวดวงใจ แยมประโคน

ทั้งนี้ ตั้งแต่วันที่ ๒๔ มิถุนายน พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๔ มิถุนายน พ.ศ. ๒๕๖๘




(นายศักดิ์ศิลป์ ตุลาธร)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

รายชื่อบุคลากร (เพิ่มเติม)
แนบท้ายใบอนุญาตเป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับความร้อน
ของบริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๑-๐๓-๒๕๖๔-๐๐๐๔

๑. นางสาวณมล โนนหิน
๒. นางสาววราภรณ์ เสาวรส
๓. นางสาวจิรนนท์พร พันธนา
๔. นางสาวชิตรินทร์ พุทธา

ทั้งนี้ ตั้งแต่วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตุลาธร)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

COPY

รายการเครื่องมือตรวจวัดแบบห้ายาใบอนุญาต
 เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับความร้อน
 ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๕๐๑-๐๓-๒๕๖๕-๐๐๐๙

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	อุปกรณ์ตรวจวัดระดับความร้อน ชนิดอิเล็กทรอนิกส์ที่สามารถอ่าน และคำนวณค่าอุณหภูมิระดับโลก (WBGT)	ยี่ห้อ	TSI QUEST	๑
		รุ่น	QUESTemp ^o 32	
		Serial No.	TPH060001	
		มาตรฐาน	ISO 7243	
		ยี่ห้อ	QUEST TECHNOLOGIES	๒
		รุ่น	QUESTemp ^o 32	
		Serial No.	TP1050069 TP1050070	
		มาตรฐาน	ISO 7243	
		ยี่ห้อ	3M	๖
		รุ่น	QUESTemp ^o 32	
		Serial No.	TPL060039 TPL060040 TPL090016 TPL090017 TPQ030023 TPQ030024	
		มาตรฐาน	ISO 7243	
		ยี่ห้อ	TSI QUEST	๕
		รุ่น	QUESTemp ^o 34	
		Serial No.	TEU080011 TEU080012 TEU080013 TEU080014 TEU080015	
		มาตรฐาน	ISO 7243	

COPY

-๒-

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
	อุปกรณ์ตรวจวัดระดับความร้อน ชนิดอิเล็กทรอนิกส์ที่สามารถอ่าน และคำนวณค่าอุณหภูมิระดับโลก (WBGT) (ต่อ)	ยี่ห้อ	DELTA OHM	๔
		รุ่น	HD32.2	
		Serial No.	22004316 22004318 22004319 22004320	
		มาตรฐาน	ISO 7243	

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY



แบบ กก.บุญ
นิติบุคคล

กรมสวัสดิการและคุ้มครองแรงงาน

ใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง

ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

อนุญาตให้...บริษัท อีสเทิร์น ไทย คอนซัลตติ้ง 1992 จำกัด.....

เลขทะเบียนนิติบุคคล...๐๒๐๕๕๓๕๐๐๔๕๗๘

ตั้งอยู่เลขที่...๙๙ หมู่ที่ ๑๑ ตำบลหนองขาม อำเภอศรีราชา จังหวัดชลบุรี.....

เป็นนิติบุคคลผู้ให้บริการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน ตามกฎกระทรวง กำหนดมาตรฐานในการบริหาร จัดการ และดำเนินการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงานเกี่ยวกับความร้อน แสงสว่าง และเสียง พ.ศ. ๒๕๕๙ ในการตรวจวัดและวิเคราะห์สภาวะการทำงาน เกี่ยวกับระดับแสงสว่าง ประกอบกับกฎกระทรวงการขึ้นทะเบียนและการอนุญาตให้บริการเพื่อส่งเสริมความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน พ.ศ. ๒๕๖๔ แห่งพระราชบัญญัติความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน พ.ศ. ๒๕๕๔ โดยมีบุคลากร จำนวน ๑๐ ราย และรายการเครื่องมือ ตรวจวัด จำนวน ๗ เครื่อง ดังรายละเอียดแนบท้ายใบอนุญาตนี้

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗

(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายชื่อบุคลากรแนบท้ายใบอนุญาต
เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง
ของบริษัท อีสเทิร์น ไทย คอนซัลตติ้ง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

๑. นางวรรณเพ็ญ	เหล่าจินดาวัฒน์
๒. นางสาวธนัชพร	กลั่นโสภณ
๓. นางสาวปนัดดา	ร่วมรุกข์
๔. นางสาวอภิรดี	ชื่นอารมย์
๕. นางสาวธัญลักษณ์	ขันโต
๖. นางสาวจุฑารัตน์	สุชะเกต
๗. นางสาวศวิตา	กิตติเนาวรัตน์
๘. นางสาวพรนภา	พงษ์เพชร
๙. นางสาวอรอนงค์	สิวงค์ศักดิ์
๑๐. นายศุภชัย	ภารการ

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗

(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายชื่อบุคลากร (เพิ่มเติม) แนบท้ายใบอนุญาต
เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง
ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

- | | |
|-----------------|------------|
| ๑. นางสาวรัตมณี | นาคเกตุ |
| ๒. นางสาวดวงใจ | แย้มประโคน |

ทั้งนี้ ตั้งแต่วันที่ ๒๕ มิถุนายน พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๕ มิถุนายน พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

รายชื่อบุคลากร (เพิ่มเติม)
แนบท้ายใบอนุญาตเป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง
ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

- | | |
|--------------------|---------|
| ๑. นางสาวนฤมล | โนนหิน |
| ๒. นางสาวรากานต์ | เสาวรส |
| ๓. นางสาวจิรนนท์พร | พันธ์นา |
| ๔. นางสาวชศิรินทร์ | พุทรา |

ทั้งนี้ ตั้งแต่วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

COPY

รายการเครื่องมือตรวจวัดแบบท่ายใบอนุญาต
เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง
ของบริษัท ฮิสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องวัดแสง	ยี่ห้อ	DIGICON	๓
		รุ่น	LX-72	
		Serial No.	Q606371	
			Q606412	
			Q608662	๒
		มาตรฐาน	CIE	
		ยี่ห้อ	DIGICON	
		รุ่น	LX-73	
		Serial No.	S.008890	๒
			R.032544	
		มาตรฐาน	CIE	
		ยี่ห้อ	TENMARS	
		รุ่น	TM-209M	
		Serial No.	220800468	
			230203566	
		มาตรฐาน	JIS C 1609	

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)
ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายการเครื่องมือตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง (เพิ่มเติม)
ของบริษัท ฮิสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องวัดแสง	ยี่ห้อ	KYORITSU	๔
		รุ่น	5202	
		Serial No.	X1001377	
			X1001380	
			Y1001188	
			Y1001191	
		มาตรฐาน	JIS C 1609	

ทั้งนี้ ตั้งแต่วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายการเครื่องมือตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับแสงสว่าง (เพิ่มเติม)
ของบริษัท เอสเทิร์น ไทย คอนซัลติง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๒-๐๓-๒๕๖๔-๐๐๐๙

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องวัดแสง	ยี่ห้อ	KYORITSU	๔
		รุ่น	5202	
		Serial No.	X1001377	
			X1001380	
			Y1001188	
			Y1001191	
		มาตรฐาน	JIS C 1609	

ทั้งนี้ ตั้งแต่วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)

รองอธิบดี ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน



แบบ กบ.บญ
นิติบุคคล

กรมสวัสดิการและคุ้มครองแรงงาน

ใบอนุญาต

เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง

ใบอนุญาตเลขที่ ๐๔๐๓-๐๓-๒๕๖๔-๐๐๐๙

อนุญาตให้...บริษัท เอสเทิร์น ไทย คอนซัลติง 1992 จำกัด


เลขทะเบียนนิติบุคคล...๐๒๐๕๕๓๕๐๐๙๕๗๘

ตั้งอยู่เลขที่...๙๙๙ หมู่ที่ ๑๑ ตำบลหนองขาม อำเภอศรีราชา จังหวัดชลบุรี

เป็นนิติบุคคลผู้ให้บริการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน ตามกฎกระทรวง กำหนดมาตรฐานในการบริหาร จัดการ และดำเนินการด้านความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงานเกี่ยวกับความร้อน แสงสว่าง และเสียง พ.ศ. ๒๕๕๙ ในการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง ประกอบกับกฎกระทรวงการขึ้นทะเบียนและการอนุญาตให้บริการเพื่อส่งเสริมความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน พ.ศ. ๒๕๖๔ แห่งพระราชบัญญัติความปลอดภัย อาชีวอนามัย และสภาพแวดล้อมในการทำงาน พ.ศ. ๒๕๕๔ โดยมีบุคลากร จำนวน ๑๐ ราย และรายการเครื่องมือตรวจวัด จำนวน ๗๔ เครื่อง ดังรายละเอียดแนบท้ายใบอนุญาตนี้

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY


COPY

รายชื่อบุคลากรแนบท้ายใบอนุญาต
เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง
ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๓-๐๓-๒๕๖๔-๐๐๐๙

- | | |
|--------------------|----------------|
| ๑. นางวรรณเพ็ญ | เหลาจินดาวัฒน์ |
| ๒. นางสาวธนัชพร | กลิ่นโสมณ |
| ๓. นางสาวปนัดดา | ร่มรุกข์ |
| ๔. นางสาวอภิรดี | ชินอารมย์ |
| ๕. นางสาวธัญลักษณ์ | ขันโต |
| ๖. นางสาวจุฑารัตน์ | สุขขาเขต |
| ๗. นางสาวศविดา | กิตติเนาวรัตน์ |
| ๘. นางสาวพรนภา | พงษ์เพชร |
| ๙. นางสาวอรอนงค์ | สิวงค์ศักดิ์ |
| ๑๐. นายศุภชัย | ภารการ |

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)


ผู้ตรวจราชการกรม ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

รายชื่อบุคลากร (เพิ่มเติม) แนบท้ายใบอนุญาต
เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง
ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๓-๐๓-๒๕๖๔-๐๐๐๙

- | | |
|-----------------|------------|
| ๑. นางสาวรัตมณี | นาคเกตุ |
| ๒. นางสาวดวงใจ | แย้มประโคน |

ทั้งนี้ ตั้งแต่วันที่ ๒ มิถุนายน พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒ มิถุนายน พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตูลาธร)
รองอธิบดี ปฏิบัติราชการแทน
อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

COPY

รายชื่อบุคลากร (เพิ่มเติม)
 แนบท้ายใบอนุญาตเป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง
 ของบริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๔๐๓-๐๓-๒๕๖๔-๐๐๐๔

๑. นางสาวณมล โนนหิน
๒. นางสาววราภรณ์ เสาวรส
๓. นางสาวจิรันทพร พันธนา
๔. นางสาวชศรินทร์ พุทธา

ทั้งนี้ ตั้งแต่วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๔ ถึงวันที่ ๒๔ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๓ ธันวาคม พ.ศ. ๒๕๖๔



(นายศักดิ์ศิลป์ ตูลาธร)
 รองอธิบดี ปฏิบัติราชการแทน
 อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

รายการเครื่องมือตรวจวัดแนบท้ายใบอนุญาต
 เป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง
 ของบริษัท อีสเทิร์น ไทย คอนซัลต์ติ้ง 1992 จำกัด
 ใบอนุญาตเลขที่ ๐๔๐๓-๐๓-๒๕๖๔-๐๐๐๔

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
๑	เครื่องวัดเสียง และ เครื่องวัดเสียงกระทบหรือเสียงกระทบ	ยี่ห้อ	RION	๑๐
		รุ่น	NL-21	
		Serial No.	00209079	
			00310455	
			00310456	
			00310458	
			00443357	
			00443358	
			00443359	
			01209912	
			01209914	
			01209916	
		มาตรฐาน	IEC 61672	๓
		ยี่ห้อ	RION	
		รุ่น	NL-42	
		Serial No.	01147298	
			01147299	๗
			01147300	
		มาตรฐาน	IEC 61672	
		ยี่ห้อ	CIRRUS	
		รุ่น	CR:172A	
		Serial No.	G300957	
			G301013	
			G301039	
			G301635	
			G301638	
			G301660	
			G301661	
		มาตรฐาน	IEC 61672	

COPY

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
	เครื่องวัดเสียง และ เครื่องวัดเสียงกระทบหรือเสียงกระแทก (ต่อ)	ยี่ห้อ	RION	๑๗
		รุ่น	NL-42A	
		Serial No.	00222592	
			00222593	
			00222594	
			00322744	
			00322745	
			00322746	
			00322747	
			00322748	
			00322749	
			00322750	
			00322751	
			00322752	
			00322753	
			00322754	
			00322755	
			00322756	
			00322757	
		มาตรฐาน	IEC 61672	
๒	เครื่องวัดปริมาณเสียงสะสม	ยี่ห้อ	TES	๑
		รุ่น	1355	
		Serial No.	070204292	
		มาตรฐาน	IEC 61252	
		ยี่ห้อ	3M	๗
		รุ่น	NoisePro DLX	
		Serial No.	NXL060044	
			NXL060045	
			NXL060046	
			NXL060048	
			NXQ070006	
			NXQ070007	
			NXQ070008	
		มาตรฐาน	IEC 61252	

COPY


ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
	เครื่องวัดปริมาณเสียงสะสม (ต่อ)	ยี่ห้อ	CIRRUS	๒๐
		รุ่น	CR110A	
		Serial No.	CA8879	
			CA8886	
			CA8887	
			CA8888	
			CA8889	
			CB0640	
			CB0641	
			CB0642	
			CB0643	
			CB0644	
			CB0954	
			CB0955	
			CB0956	
			CB0957	
			CB0958	
			CB1365	
			CB1497	
			CB1498	
			CB1499	
			CB1500	
		มาตรฐาน	IEC 61252	
๓	อุปกรณ์ตรวจสอบความถูกต้อง	ยี่ห้อ	RION	๔
		รุ่น	NC-75	
		Serial No.	34234715	
			34234716	
			34302326	
			34802645	
		มาตรฐาน	IEC 60942	

COPY

ลำดับที่	รายการเครื่องมือ	รายละเอียด	จำนวน (เครื่อง)
	อุปกรณ์ตรวจสอบความถูกต้อง (ต่อ)	ยี่ห้อ CIRRUS	๑
		รุ่น CR:517	
		Serial No. 92863	
		มาตรฐาน IEC 60942	
		ยี่ห้อ CIRRUS	๔
		รุ่น RC:110A	
		Serial No. 73967	
		Serial No. 87366	
		92433	
		98650	
		มาตรฐาน IEC 60942	

ทั้งนี้ ตั้งแต่วันที่ ๓๐ ธันวาคม พ.ศ. ๒๕๖๗ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒๗ ธันวาคม พ.ศ. ๒๕๖๗



(นายศักดิ์ศิลป์ ตูลาธร)

ผู้ตรวจราชการกรม ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

รายการเครื่องมือตรวจวัด (เพิ่มเติม)
แนบท้ายใบอนุญาตเป็นนิติบุคคลผู้ให้บริการตรวจวัดและวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับเสียง
ของบริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
ใบอนุญาตเลขที่ ๐๔๐๓-๐๓-๒๕๖๔-๐๐๐๙

ลำดับที่	รายการเครื่องมือ	รายละเอียด	จำนวน (เครื่อง)
๑	เครื่องวัดเสียง และเครื่องวัดเสียง กระทบหรือเสียงกระทบ	ยี่ห้อ Rion	๑๘
		รุ่น NL- 52A	
		Serial No. 01120943	
		01120944	
		01120945	
		01120947	
		01120948	
		01120949	
		01120950	
		01120952	
		01120953	
		00230985	
		00230986	
		00230987	
		00230988	
		00230989	
		00230992	
		00230993	
		00230994	
		00230995	
		มาตรฐาน IEC 61672	๔
		ยี่ห้อ Rion	
		รุ่น NL- 43	
		Serial No. 00641700	
		00641701	
		00641702	
		00641703	
		มาตรฐาน IEC 61672	๔
		ยี่ห้อ Rion	
		รุ่น NL- 53	


COPY

COPY

ลำดับที่	รายการเครื่องมือ	รายละเอียด		จำนวน (เครื่อง)
		Serial No.	00741217 00741218 00741219 00741254	
		มาตรฐาน	IEC 61672	
๒	อุปกรณ์ตรวจสอบความถูกต้อง	ยี่ห้อ	Rion	๕
		รุ่น	NL- 75	
		Serial No.	34745929 34946010 34946011 34946012 34946013	
		มาตรฐาน	IEC 60942	

ทั้งนี้ ตั้งแต่วันที่ ๒ มิถุนายน พ.ศ. ๒๕๖๘ ถึงวันที่ ๒๙ ธันวาคม พ.ศ. ๒๕๗๐

ให้ไว้ ณ วันที่ ๒ มิถุนายน พ.ศ. ๒๕๖๘



(นายศักดิ์ศิลป์ ตุลาธร)

รองอธิบดี ปฏิบัติราชการแทน

อธิบดีกรมสวัสดิการและคุ้มครองแรงงาน

COPY

ภาคผนวกที่ 3

ใบรับรองความสามารถห้องปฏิบัติการ



ที่ อว 0303/18183

ใบรับรองความสามารถห้องปฏิบัติการทดสอบ

ใบรับรองฉบับนี้ให้ไว้เพื่อแสดงว่า

ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
อำเภอศรีราชา จังหวัดชลบุรี 20230

ได้ผ่านการประเมินความสามารถห้องปฏิบัติการทดสอบตามมาตรฐาน ISO/IEC 17025 : 2017
และข้อกำหนด กฎระเบียบ และเงื่อนไขการรับรองความสามารถห้องปฏิบัติการทดสอบ
ของกองบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ

หมายเลขการรับรองระบบงานที่ ทดสอบ - 0159

รายละเอียดการรับรองดังข้อข่ายการรับรองแนบท้าย

ออกให้ ณ วันที่ : 7 พฤศจิกายน 2566

หมดอายุ วันที่ : 6 พฤศจิกายน 2570

ลงชื่อ : รัชพรพงศ์ วงศ์พจน์
(นางจันทรีรัตน์ วรสรพรวิทย์)

นักวิทยาศาสตร์ชำนาญการพิเศษ

รักษาการแทน ผู้อำนวยการกองบริหารและรับรองห้องปฏิบัติการ

กองบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ
กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

COPY

ข้อข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด

สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
อำเภอศรีราชา จังหวัดชลบุรี 20230

หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159

สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
1	น้ำ	- ซีไอดี 40 mg/L ถึง 5 000 mg/L - โปรท 0.001 mg/L ถึง 0.02 mg/L - บีไอดี 2 mg/L ถึง 5 000 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23rd ed., 2017, part 5220 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23rd ed., 2017, part 3112 B Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23rd ed., 2017, part 5210 B

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

COPY

กองบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลตติ้ง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอสรรพยา จังหวัดชัยภูมิ 20230

หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159

สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
1 (ต่อ)	น้ำ	- สารที่ละลายได้ทั้งหมด ที่อุณหภูมิ 180 °C 25 mg/L ถึง 10 000 mg/L - สารแขวนลอยทั้งหมด ที่อุณหภูมิ 103 °C ถึง 105 °C 5 mg/L ถึง 2 000 mg/L - ฟลูออไรด์ 0.5 mg/L ถึง 10 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 2540 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 2540 D Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 4500-F °C

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

กองบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

ฉบับที่ 4
COPY

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลตติ้ง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอสรรพยา จังหวัดชัยภูมิ 20230

หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159

สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
2	น้ำเสีย	- ซีโอดี 40 mg/L ถึง 5 000 mg/L - โปรท 0.001 mg/L ถึง 0.02 mg/L - บีโอดี 2 mg/L ถึง 5 000 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 5220 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 3112 B Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 5210 B

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

กองบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

ฉบับที่ 5
COPY


ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอศรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159

สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
2 (ต่อ)	น้ำเสีย	- สารที่ละลายได้ทั้งหมด ที่อุณหภูมิ 180 °C 25 mg/L ถึง 10 000 mg/L - สารแขวนลอยทั้งหมด ที่อุณหภูมิ 103 °C ถึง 105 °C 5 mg/L ถึง 2 000 mg/L - ฟลูออไรด์ 0.5 mg/L ถึง 10 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 2540 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 2540 D Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 23 rd ed., 2017, part 4500-F C

ออกให้ ณ วันที่ : 7 พฤศจิกายน 2566

ลงชื่อ : 
 (นางจันทน์ วรสรรพวิทย)

นักวิทยาศาสตร์ชำนาญการพิเศษ

รักษาการแทน ผู้อำนวยการกองบริหารและรับรองห้องปฏิบัติการ

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 4

กองบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัยและนวัตกรรม

COPY



ที่ อว 0303/169

ใบรับรองความสามารถห้องปฏิบัติการทดสอบ

ใบรับรองฉบับนี้ให้ไว้เพื่อแสดงว่า

ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
 เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอศรีราชา จังหวัดชลบุรี 20230

ได้ผ่านการประเมินความสามารถห้องปฏิบัติการทดสอบตามมาตรฐาน ISO/IEC 17025 : 2017
 และข้อกำหนด กฎระเบียบ และเงื่อนไขการรับรองความสามารถห้องปฏิบัติการทดสอบ
 ของสำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ

หมายเลขการรับรองระบบงานที่ ทดสอบ - 0159

รายละเอียดการรับรองดังขอข่ายการรับรองแนบท้าย

ออกให้ ณ วันที่ : 10 มกราคม 2568

หมดอายุ วันที่ : 6 พฤศจิกายน 2570

ลงชื่อ : 
 (นางจันทน์ วรสรรพวิทย)

ผู้อำนวยการสำนักบริหารและรับรองห้องปฏิบัติการ

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ
 กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัยและนวัตกรรม

COPY

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลตัง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอสรรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159
 สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
1	น้ำ	- ซีโอดี 40 mg/L ถึง 5 000 mg/L - โปรท 0.001 mg/L ถึง 0.02 mg/L - บีโอดี 2 mg/L ถึง 5 000 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 5220 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 3112 B Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 5210 B

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 5

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

COPY

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลตัง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอสรรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159
 สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
1 (ต่อ)	น้ำ	- สารที่ละลายได้ทั้งหมด ที่อุณหภูมิ 180 °C 25 mg/L ถึง 10 000 mg/L - สารแขวนลอยทั้งหมด ที่อุณหภูมิ 103 °C ถึง 105 °C 5 mg/L ถึง 2 000 mg/L - ฟลูออไรด์ 0.5 mg/L ถึง 10 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2540 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2540 D Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 4500-F °C

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 5

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

COPY

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลตัง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอศรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159
 สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ ชั่วคราว ☐ เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
1 (ต่อ)	น้ำ	- คลอไรด์ 50 mg/L ถึง 2 000 mg/L - ความกระด้างทั้งหมด (คำนวณเป็นแคลเซียมคาร์บอเนต) 50 mg/L ถึง 500 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 4500-Cl ⁻ B Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2340 C

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 5

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

COPY

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลตัง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอศรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159
 สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ ชั่วคราว ☐ เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
2	น้ำเสีย	- ซีโอดี 40 mg/L ถึง 5 000 mg/L - โปรท 0.001 mg/L ถึง 0.02 mg/L - บีโอดี 2 mg/L ถึง 5 000 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 5220 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 3112 B Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 5210 B

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 5

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

COPY

ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอศรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159
 สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
2 (ต่อ)	น้ำเสีย	- สารที่ละลายได้ทั้งหมด ที่อุณหภูมิ 180 °C 25 mg/L ถึง 10 000 mg/L - สารแขวนลอยทั้งหมด ที่อุณหภูมิ 103 °C ถึง 105 °C 5 mg/L ถึง 2 000 mg/L - ฟลูออไรด์ 0.5 mg/L ถึง 10 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2540 C Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2540 D Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 4500-F °C

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 5

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

LA-F-30-10/11-24

หน้า 5/6

COPY


ขอข่ายการรับรองความสามารถห้องปฏิบัติการทดสอบ

ชื่อห้องปฏิบัติการ : ห้องปฏิบัติการ บริษัท อีสเทิร์น ไทย คอนซัลติง 1992 จำกัด
 สถานที่ตั้ง : เลขที่ 683 หมู่ที่ 11 ถนนสุขาภิบาล 8 ตำบลหนองขาม
 อำเภอศรีราชา จังหวัดชลบุรี 20230
 หมายเลขการรับรองระบบงานที่ : ทดสอบ - 0159
 สถานะของห้องปฏิบัติการ : ☒ ถาวร ☐ นอกสถานที่ ☐ชั่วคราว ☐เคลื่อนที่

ลำดับ ที่	วัสดุ / ผลิตภัณฑ์ที่ทดสอบ	รายการที่ทดสอบ / ช่วงของการทดสอบ	วิธีทดสอบ / เทคนิคที่ใช้
2 (ต่อ)	น้ำเสีย	- คลอไรต์ 50 mg/L ถึง 2 000 mg/L - ความกระด้างทั้งหมด (คำนวณเป็นแคลเซียมคาร์บอเนต) 50 mg/L ถึง 500 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 4500-Cl ⁻ B Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2340 C
3	น้ำทะเล	- สารแขวนลอยทั้งหมด ที่อุณหภูมิ 103 °C ถึง 105 °C 5 mg/L ถึง 100 mg/L	Standard Methods for the Examination of Water and Wastewater, APHA, AWWA & WEF, 24 th ed., 2023, part 2540 D

ออกให้ ณ วันที่ : 10 มกราคม 2568

ลงชื่อ :


 (นางจันทิมา วรสรพวิทย)

ผู้อำนวยการสำนักบริหารและรับรองห้องปฏิบัติการ

ออกครั้งแรก ณ วันที่ 21 พฤศจิกายน 2560

ฉบับที่ 5

สำนักบริหารและรับรองห้องปฏิบัติการ กรมวิทยาศาสตร์บริการ กระทรวงการอุดมศึกษา วิทยาศาสตร์ วิจัย และนวัตกรรม

LA-F-30-10/11-24

หน้า 6/6

COPY



แบบ กษช./สมอ.๒
Form NSC/TISI 2

ใบรับรองเลขที่ 23-LB0251
(Certificate No.)

ใบรับรองระบบงาน (Certificate of Accreditation)

อาศัยอำนาจตามความในพระราชบัญญัติการมาตรฐานแห่งชาติ พ.ศ. ๒๕๕๑
(By Virtue of National Standardization Act B.E. 2551 (2008))

เลขาธิการสำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม
(Secretary-General, Thai Industrial Standards Institute)

ออกใบรับรองฉบับนี้ให้
(Issues this certificate to)

บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
(Eastern Thai Consulting 1992 Co., Ltd.)

ตั้งอยู่เลขที่
(Address)

๖๘๓ หมู่ที่ ๑๑ ถนนสุขาภิบาล ๘ ตำบลหนองขาม อำเภอศรีราชา จังหวัดชลบุรี
(683 Moo 11, Sukhaphibarn 8 Road, Nongkharn, Sriracha, Chonburi)

ได้รับการรับรองความสามารถ
(Certificate of competence)

ตามมาตรฐานเลขที่ มอก. ๑๗๐๒๕ - ๒๕๖๑
(Standard No. TIS 17025-2561 (2018) (ISO/IEC 17025: 2017))

ข้อกำหนดทั่วไปว่าด้วยความสามารถของ ห้องปฏิบัติการทดสอบและห้องปฏิบัติการสอบเทียบ
(General requirements for the competence of testing and calibration laboratories)

หมายเลขการรับรองที่ ทดสอบ ๑๗๑๒
(Accreditation No. Testing 1712)

โดยมีรายละเอียดสาขาและขอบข่ายที่ได้อ้างอิง แสดงไว้ใน QR CODE และ www.tisi.go.th
(Details of the scheme and scope of the certificate are shown in QR CODE and www.tisi.go.th)

ออกให้ ณ วันที่ ๒๓ สิงหาคม พ.ศ. ๒๕๖๖
(Issue date : 23 August B.E. 2566 (2023))

(นายเอกนิติ รมยานนท์)
รองเลขาธิการสำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม
ปฏิบัติราชการแทน
เลขาธิการสำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม



กระทรวงอุตสาหกรรม สำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม
(Ministry of Industry, Thai Industrial Standards Institute)



รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ
(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251
(Certification No. 23-LB0251)



ชื่อห้องปฏิบัติการ
(Laboratory Name)

บริษัท อีสเทิร์น ไทย คอนซัลติ้ง 1992 จำกัด
(Eastern Thai Consulting 1992 Co., Ltd.)

หมายเลขการรับรองที่
(Accreditation No.)

ทดสอบ 1712
(Testing 1712)

ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E. 2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E. 2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☒ ถาวร (Permanent) ☐ นอกสถานที่ (Site) ☐ชั่วคราว (Temporary)

☐ เคลื่อนที่ (Mobile) ☐ หลายสถานที่ (Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field) 1. น้ำ (Water)	- โลหะหนัก (Heavy metals) • โครเมียม (Cr) (Chromium (Cr)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • ทองแดง (Cu) (Copper (Cu)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • เหล็ก (Fe) (Iron (Fe)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • ตะกั่ว (Pb) (Lead (Pb)) 0.01 มิลลิกรัมต่อลิตร ถึง 1.00 มิลลิกรัมต่อลิตร (0.01 mg/L to 1.00 mg/L)	- Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24 th edition, 2023, part 3030 F and part 3120 B

กระทรวงอุตสาหกรรม สำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม
(Ministry of Industry, Thai Industrial Standards Institute)

หน้า 1/9

COPY

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ

(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251

(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E.2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E.2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☒ ถาวร (Permanent)

☐ นอกสถานที่ (Site)

☐ ชั่วคราว (Temporary)

☐ เคลื่อนที่ (Mobile)

☐ หลายสถานที่ (Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field)		
1. น้ำ (ต่อ) (Water) (Cont.)	- โลหะหนัก (ต่อ) (Heavy metals) (Cont.) • นิกเกิล (Ni) (Nickel (Ni)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • อลูมิเนียม (Al) (Aluminum (Al)) 0.10 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.10 mg/L to 2.00 mg/L) • แบเรียม (Ba) (Barium (Ba)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • แคดเมียม (Cd) (Cadmium (Cd)) 0.003 มิลลิกรัมต่อลิตร ถึง 1.00 มิลลิกรัมต่อลิตร (0.003 mg/L to 1.00 mg/L) • แมงกานีส (Mn) (Manganese (Mn)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L)	- Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 3030 F and part 3120 B

กระทรวงอุตสาหกรรมสำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม
(Ministry of Industry, Thai Industrial Standards Institute)

หน้าที่ 2/9

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ

(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251

(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E.2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E.2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☒ ถาวร (Permanent)

☐ นอกสถานที่ (Site)

☐ ชั่วคราว (Temporary)

☐ เคลื่อนที่ (Mobile)

☐ หลายสถานที่ (Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field)		
1. น้ำ (ต่อ) (Water) (Cont.)	- โลหะหนัก (ต่อ) (Heavy metals) (Cont.) • เงิน (Ag) (Silver (Ag)) 0.05 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.05 mg/L to 2.00 mg/L) • สังกะสี (Zn) (Zinc (Zn)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) - ไขมันและน้ำมัน (Oil & Grease) 3.0 มิลลิกรัมต่อลิตร ถึง 20.0 มิลลิกรัมต่อลิตร (3.0 mg/L to 20.0 mg/L)	- Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 3030 F and part 3120 B - Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 5520 B

กระทรวงอุตสาหกรรมสำนักงานมาตรฐานผลิตภัณฑ์อุตสาหกรรม
(Ministry of Industry, Thai Industrial Standards Institute)

หน้าที่ 3/9

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ

(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251

(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E.2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E.2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☒ ถาวร
(Permanent)

☐ นอกสถานที่
(Site)

☐ชั่วคราว
(Temporary)

☐เคลื่อนที่
(Mobile)

☐หลายสถานที่
(Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field)		
2. น้ำเสีย (Wastewater)	- โลหะหนัก (Heavy metals) • โครเมียม (Cr) (Chromium (Cr)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • ทองแดง (Cu) (Copper (Cu)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • เหล็ก (Fe) (Iron (Fe)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • ตะกั่ว (Pb) (Lead (Pb)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • นิกเกิล (Ni) (Nickel (Ni)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L)	- Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 3030 F and part 3120 B

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ

(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251

(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E.2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E.2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☒ ถาวร
(Permanent)

☐นอกสถานที่
(Site)

☐ชั่วคราว
(Temporary)

☐เคลื่อนที่
(Mobile)

☐หลายสถานที่
(Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field)		
2. น้ำเสีย (ต่อ) (Wastewater) (Cont.)	- โลหะหนัก (ต่อ) (Heavy metals) (Cont.) • อลูมิเนียม (Al) (Aluminum (Al)) 0.10 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.10 mg/L to 2.00 mg/L) • แบเรียม (Ba) (Barium (Ba)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • แคดเมียม (Cd) (Cadmium (Cd)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • แมงกานีส (Mn) (Manganese (Mn)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) • เงิน (Ag) (Silver (Ag)) 0.05 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.05 mg/L to 2.00 mg/L)	- Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 3030 F and part 3120 B

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ

(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251

(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E.2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E.2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☒ ถาวร
(Permanent)

☐ นอกสถานที่
(Site)

☐ชั่วคราว
(Temporary)

☐เคลื่อนที่
(Mobile)

☐หลายสถานที่
(Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field) 2. น้ำเสีย (ต่อ) (Wastewater) (Cont.)	- โลหะหนัก (ต่อ) (Heavy metal) (cont.) • สังกะสี (Zn) (Zinc (Zn)) 0.03 มิลลิกรัมต่อลิตร ถึง 2.00 มิลลิกรัมต่อลิตร (0.03 mg/L to 2.00 mg/L) - น้ำมันและน้ำมัน (Oil & Grease) 3.0 มิลลิกรัมต่อลิตร ถึง 20.0 มิลลิกรัมต่อลิตร (3.0 mg/L to 20.0 mg/L)	- Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 3030 F and part 3120 B - Standard Method for the Examination of Water and Wastewater, APHA, AWWA, WEF, 24th edition, 2023, part 5520 B

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ

(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251

(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E.2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E.2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☐ ถาวร
(Permanent)

☒ นอกสถานที่
(Site)

☐ชั่วคราว
(Temporary)

☐เคลื่อนที่
(Mobile)

☐หลายสถานที่
(Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field) 3. บริเวณปฏิบัติงาน (Work station)	- ระดับเสียง (Sound level) • ระดับเสียงเฉลี่ย (Equivalent A-weighted sound pressure level: $L_{Aeq,T}$) $L_{Aeq,T}$ 30 เดซิเบลเอ ถึง 130 เดซิเบลเอ (L_{eq} 30 dB (A) to 130 dB (A)) • ระดับเสียงสูงสุด (Maximum sound level: L_{max}) L_{max} 30 เดซิเบลเอ ถึง 130 เดซิเบลเอ (L_{max} 30 dB (A) to 130 dB (A))	- ISO 11202 : 2010 - ประกาศกระทรวงอุตสาหกรรม เรื่อง มาตรการคุ้มครองความปลอดภัย ในการประกอบกิจการโรงงานเกี่ยวกับ สภาวะแวดล้อมในการทำงาน พ.ศ. 2546 ลงวันที่ 3 ธันวาคม 2546 (Notification of The Ministry of Industry B.E. 2546 (2003) on the Safety Protection Measures in Factory Regarding Working Area Environment, dated December 3, 2003)

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ
(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251
(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E. 2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E. 2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☐ ถาวร
(Permanent)

☒ นอกสถานที่
(Site)

☐ชั่วคราว
(Temporary)

☐ เคลื่อนที่
(Mobile)

☐ หลายสถานที่
(Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field)		
3. บริเวณปฏิบัติงาน (Work station)	- ระดับเสียง (ต่อ) (Sound level) (Cont.) • ระดับเสียงเฉลี่ย (Equivalent A-weighted sound pressure level: $L_{Aeq,T}$) $L_{Aeq,T}$ 30 เดซิเบลเอ ถึง 130 เดซิเบลเอ ($L_{eq,T}$ 30 dB (A) to 130 dB (A)) • ระดับเสียงสูงสุด (Maximum sound level: L_{max}) L_{max} 30 เดซิเบลเอ ถึง 130 เดซิเบลเอ (L_{max} 30 dB (A) to 130 dB (A))	- ประกาศกรมสวัสดิการและคุ้มครองแรงงาน เรื่อง มาตรฐานระดับเสียงที่ยอมให้ลูกจ้างได้รับเฉลี่ยตลอดระยะเวลาการทำงานในแต่ละวัน ลงวันที่ 26 มกราคม 2561 (Notification of The Department of Labor Protection and Welfare on the standard of noise level that employees are allowed to receive in average period of work each day, dated January 26, 2018.) - ประกาศกรมสวัสดิการและคุ้มครองแรงงาน เรื่อง หลักเกณฑ์ วิธีการตรวจวัดและการวิเคราะห์สภาวะการทำงานเกี่ยวกับระดับความร้อน แสงสว่าง หรือเสียง รวมทั้งระยะเวลาและประเภทกิจการที่ต้องดำเนินการ ลงวันที่ 12 มีนาคม 2561 (Notification of The Department of Labor Protection and Welfare on Criteria, Measurement Methods, and Analysis of Working Conditions Regarding Heat, Light, or Noise Levels, Including Duration and Types of Businesses to Be Performed, dated March 12, 2018.)

COPY

รายละเอียดสาขาและขอบข่ายใบรับรองห้องปฏิบัติการ
(Scope of Accreditation for Testing)

ใบรับรองเลขที่ 23-LB0251
(Certification No. 23-LB0251)



ฉบับที่ 02
(Issue No. 02)

ออกให้ตั้งแต่วันที่ 23 มิถุนายน พ.ศ. 2568
(Valid from) (23 June B.E. 2568 (2025))

ถึงวันที่ 16 กรกฎาคม พ.ศ. 2571
(Until) (16 July B.E. 2571 (2028))

สถานภาพห้องปฏิบัติการ
(Laboratory status)

☐ ถาวร
(Permanent)

☒ นอกสถานที่
(Site)

☐ชั่วคราว
(Temporary)

☐ เคลื่อนที่
(Mobile)

☐ หลายสถานที่
(Multisite)

สาขาการทดสอบ (Field of Testing)	รายการทดสอบ (Parameter)	วิธีทดสอบ (Test Method)
สาขาสิ่งแวดล้อม (Environmental field)		
4. เสียงในสิ่งแวดล้อม (Environmental noise)	- ระดับเสียง (Sound level) • ระดับเสียงเฉลี่ย (Equivalent A-weighted sound pressure level: $L_{Aeq,T}$) $L_{Aeq,T}$ 30.0 เดซิเบลเอ ถึง 130.0 เดซิเบลเอ ($L_{eq,T}$ 30.0 dB(A) to 130.0 dB(A)) • ระดับเสียงสูงสุด (Maximum sound level: L_{max}) L_{max} 30.0 เดซิเบลเอ ถึง 130.0 เดซิเบลเอ (L_{max} 30.0 dB(A) to 130.0 dB(A))	- ISO 1996 - 1 : 2016 - ประกาศกรมโรงงานอุตสาหกรรม เรื่อง วิธีการตรวจวัดระดับเสียงการรบกวน ระดับเสียงเฉลี่ย 24 ชั่วโมง และระดับเสียงสูงสุดที่เกิดจากการประกอบกิจการโรงงาน พ.ศ. 2567 ลงวันที่ 21 กุมภาพันธ์ 2567 (Notification of The Department of Industrial Works on Methods for Measuring Noise Annoyance, Noise Levels 24-Hour Average and Maximum Noise Level from Factory B.E. 2567, dated February 21, 2024.) - ประกาศคณะกรรมการสิ่งแวดล้อมแห่งชาติ ฉบับที่ 15 (พ.ศ. 2540) เรื่องกำหนดมาตรฐานระดับเสียงโดยทั่วไป ลงวันที่ 3 เมษายน 2540 (Notification of The National Environmental Board Volume 15 B.E. 2540 (1997) on the general noise level standards, dated April 3, 1997) - ประกาศกรมควบคุมมลพิษ เรื่อง การคำนวณค่าระดับเสียง ลงวันที่ 25 พฤศจิกายน 2540 (Notification of The Pollution Control Department on the calculation of the noise level, dated November 25, 1997.)

COPY

ภาคผนวกที่ 4

สรุปเอกสารการสอบเทียบอุปกรณ์เครื่องมือ

ANALYTICAL BALANCE

Model : MS204TS/00

Serial No. : B904136539

Certificate No. : 25-205714
Sample Code : 25-90375-004

CERTIFICATE OF CALIBRATION

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd, Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Analytical Balance Room)

Equipment : ELECTRONIC BALANCE

Manufacturer : METTLER TOLEDO

Model : MS204TS/00

Serial No. : B904136539

ID No. : LABE 05/4

Date of Receipt : 26 November 2025

Date of Calibration : 26 November 2025

Calibrated by Mr. Pisek Into
Scientist

Approved by (Mr. Somchai Neampunt)
Signed for Director

Issue date 28 November 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC)

Certificate No. : 25-205714
Sample Code : 25-90375-004

REPORT OF CALIBRATION

Equipment : ELECTRONIC BALANCE
Manufacturer : METTLER TOLEDO
Model : MS204TS/00
Capacity : Max 220 g
Resolution : 0.0001 g
Serial No. : B904136539
ID No. : LABE 05/4

Result of Calibration

1. Test weight and repeatability of reading

Repeatability is a measure of the ability of a balance to supply the same result in repetitive weighings with one and the same load under the same measurement condition. The measurement of the repeatability must include both the balance specifications and the ambient (vibration, fluctuating air current/temperature/humidity, etc.) Operator handling of the balance is also included in the standard deviation.

Unit : g	Range : 220	☒ Before adjustment		☒ After adjustment	
		100	200	100	200
☐ No adjustment	Nominal value	100.000045	200.000047	100.000045	200.000047
☒ Adjustment	Standard weight	100.00002	200.00004	100.00000	200.00000
	Average reading of indicator	0.00005	0.00006	0.00005	0.00005
	Standard deviation				

Unit : g	Range : 220	☐ Before adjustment		☐ After adjustment	
		100	200	100	200
☐ No adjustment	Nominal value				
☐ No adjustment	Standard weight				
☐ Adjustment	Average reading of indicator				
	Standard deviation				

Certificate No. : 25-205714
Sample Code : 25-90375-004

REPORT OF CALIBRATION

Result of Calibration

2. Sensitivity or value of a scale division

Change in the output variable of a measuring instrument divided by the associated change in the input variable.

Unit : g

Range : 220

Range : -

Test Point	Sensitivity, S	Test Point	Sensitivity, S
0	0.8972		
100	0.9969		
200	0.9969		

3. Departure of indication from nominal value, Linearity

Unit : g

Nominal Value	Standard Value	Average Reading of Indicator	Correction Value	Expanded Uncertainty	Coverage Factor (k)
Unload	0.0000000	0.0000	0.0000	0.000094	2.01
0.01	0.0100031	0.0100	0.0000	0.000094	2.01
0.05	0.0500055	0.0500	0.0000	0.000094	2.01
0.1	0.1000023	0.1000	0.0000	0.000094	2.01
1	1.0000136	1.0000	0.0000	0.000095	2.01
5	5.0000210	5.0000	0.0000	0.000096	2.01
10	10.000002	10.0000	0.0000	0.000097	2.01
50	50.000016	50.0000	0.0000	0.00012	2.01
100	100.000045	100.0000	0.0000	0.00016	2.00
150	150.000061	150.0000	0.0001	0.00022	2.00
200	200.000047	200.0000	0.0000	0.00027	2.00

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor, which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

Certificate No. : 25-205714
Sample Code : 25-90375-004

REPORT OF CALIBRATION

Result of Calibration

4. Eccentric or off-centre loading

Deviation of the measurement value through off-center (eccentric) loading. The corner load increases with the weight of the load and its removal from the center of the pan support.

☐ Triangular


☐ Rectangular

☒ Circle

Test weight : 100

Unit : g

Range	Position	Reading of indicator	Reading of indicator
220			
	1	100.0000	
	2	100.0001	
	3	99.9999	
	4	100.0001	
	5	99.9999	
	6	100.0000	
Maximum difference		0.0001	



Condition of Calibration

1. Calibration Method : WI CL-004 base on UKAS LAB 14: 2019

2. This result of calibration was found accurate as shown on date and place of calibration only.

3. Condition of Calibration Item: Normal

4. This certification is traceable to the International System of Unit maintained at :

- Through the reference standard laboratory of Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (Instrument number 1).

5. Reference standard instrument :

Instrument : E2
1) STANDARD WEIGHT 1 mg to 1 kg

Class : E2
ID No. : LB-WE-79

Certificate No. : 25-142885
Due Date : 27 July 2026

End of Report

Ambient conditions	Min	Max
Temperature (°C)	23.9	24.6
Relative Humidity (%Rh)	44.9	47.2
Air pressure (hPa)	1008.8	1008.3

COPY

COPY

BAROMETER

Serial No. : N/A[S41020124]



CALIBRATION LABORATORY CO., LTD.

210-11,14/50-100 Pracha Manat Road, Pracha Manat Road, Ladphrae, Bangkok 10710
Tel: 02-5060534 Fax: 02-5060532 www.cllaboratory.com E-mail: cllaboratory.com



CERTIFICATE OF CALIBRATION

FOR

NOMENCLATURE : BAROMETER
MANUFACTURER : BARIO
MODEL / TYPE : N/A
SERIAL NO. : N/A[S41020124]
CLID. NO. : 212500828
JOB CONTROL NO. : 260507056453
CALIBRATION SERVICE : ☒ IN-LABORATORY ☐ ON-SITE

CUSTOMER : EASTERN THAI CONSULTING 1992 CO., LTD.
683 MOO 11, SUKHAPIBARN 8 RD,
NONGKHAM, SRIRACHA, CHONBURI 20230

DATE OF RECEIVED : 07 May 2026

DATE OF ISSUED : 11 May 2026

The report of calibration shall not be reproduced except in full without approval of the Calibration Laboratory Co., Ltd.

Calibrated By : Sittipong Pimdee
Calibration Engineer

Approved By : Mongkol Yotsoontorn
Authorized Signatory
11 May 2026



This Calibration Certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI)

Certificate No. Q26056453

F3-011-05/12-23

page 1 of 3



CALIBRATION LABORATORY CO., LTD.

210-11,14/50-100 Pracha Manat Road, Pracha Manat Road, Ladphrae, Bangkok 10710
Tel: 02-5060534 Fax: 02-5060532 www.cllaboratory.com E-mail: cllaboratory.com



REPORT OF CALIBRATION

FOR

NOMENCLATURE : BAROMETER
MANUFACTURER : BARIO
MODEL / TYPE : N/A
SERIAL NO. : N/A[S41020124]
DATE OF CALIBRATION : 09 May 2026

ENVIRONMENT CONDITIONS :

Temperature : $(23 \pm 2) ^\circ\text{C}$

Relative Humidity : $(55 \pm 10) \% \text{RH}$

PROCEDURE USED :

This instrument was calibrated under procedure No. CLC-CPPP-08 according to DKD-R 6-1 as calibration guidelines.

The calibration was performed by direct measurement with Reference Pressure Monitor which maintained by the Calibration Laboratory Co., Ltd.

REFERENCE STANDARD USED :

Reference Pressure Monitor, Fluke Model RPM3 S/N. 829.

TRACEABILITY :

The measurements are traceable to International System of Units (SI), through National Institute of Metrology (Thailand).
Certificate No. MP-0284-25, Due Date 28 November 2026.

UNCERTAINTY :

The reported uncertainty is based on a standard uncertainty multiplied by coverage factor of $k = 2$. It has been evaluated according to the "Calibration of Pressure Gauges (DKD-R 6-1)" which provides :

Certificate No. Q26056453

F3-011-05/12-23

page 2 of 3





10. $\{x_1, x_2, x_3, x_4\}$ is a linearly independent subset of V and $\{x_1, x_2, x_3, x_4, x_5\}$ is a basis for V . Find $\dim W$ if $W = \langle x_1, x_2, x_3, x_4, x_5 \rangle$.



MEASUREMENT RESULTS : (X) without adjustment () adjustment

CALIBRATION DATA

DUC Test point (hPa)	STD Reading (hPa)		Correction (hPa)	
	Up	Down	Up	Down
990	990.9	991.0	+0.9	+1.0
1000	1001.0	1001.1	+1.0	+1.1
1010	1011.2	1011.3	+1.2	+1.3
1020	1021.3	1021.4	+1.3	+1.4
1030	1031.4	1031.4	+1.4	+1.4

Transmitting fluid : Air

Note: The Scope of Accredited ANAB Certificate No. ACDM-2814 Version 018 Page 47 of 73

This report is valid for the above stated instrument/s only.

End of Certificate

Certificate No. Q26056453

13-011-05/12-23

page 3 of 3



CERTIFICATE OF ANALYSIS

EPA PROTOCOL GAS

Cylinder No. : EB0178603

CERTIFICATE OF ANALYSIS

Grade of Product: EPA PROTOCOL STANDARD

Customer: BANGKOK INDUSTRIAL
GAS CO LTD
Part Number: E04NI99E15A4385
Cylinder Number: EB0178603
Laboratory: 124 - Plumsteadville - PA
PGVP Number: A12025
Gas Code: CO,NO,NOX,SO2,BALN

Reference Number: 160-403281986-1
Cylinder Volume: 143.7 CF
Cylinder Pressure: 2016 PSIG
Valve Outlet: 660
Certification Date: Mar 17, 2025

Expiration Date: Mar 17, 2033

Certification performed in accordance with "EPA Traceability Protocol for Assay and Certification of Gaseous Calibration Standards (May 2012)" document EPA 600/R-12/531, using the assay procedures listed. Analytical Methodology does not require correction for analytical interference. This cylinder has a total analytical uncertainty as stated below with a confidence level of 95%. There are no significant impurities which affect the use of this calibration mixture. All concentrations are on a mole/mole basis unless otherwise noted. The results relate only to the items tested. The report shall not be reproduced except in full without approval of the laboratory. Do Not Use This Cylinder below 100 psig, i.e. 0.7 megapascals.

ANALYTICAL RESULTS

Component	Requested Concentration	Actual Concentration	Protocol Method	Total Relative Uncertainty	Assay Dates
NOX	50.00 PPM	49.91 PPM	G1	+/- 1.4% NIST Traceable	03/10/2025, 03/17/2025
NITRIC OXIDE	50.00 PPM	49.87 PPM	G1	+/- 1.4% NIST Traceable	03/10/2025, 03/17/2025
SULFUR DIOXIDE	50.00 PPM	50.11 PPM	G1	+/- 0.7% NIST Traceable	03/10/2025, 03/17/2025
CARBON MONOXIDE	3000 PPM	2963 PPM	G1	+/- 0.6% NIST Traceable	03/11/2025
NITROGEN	Balance				

CALIBRATION STANDARDS

Type	Lot ID	Cylinder No	Concentration	Uncertainty	Expiration Date
GMIS	402531833-1	CC463968	52.13 PPM NITRIC OXIDE/NITROGEN	+/- 1.0%	Dec 05, 2030
NTRM	210607-21	CC708065	48.41 PPM NITRIC OXIDE/NITROGEN	+/- 1.2%	Sep 21, 2025
GMIS	DCCK1201202242	CC750410	49.10 PPM NITRIC OXIDE/NITROGEN	+/- 0.5%	May 03, 2026
PRM	12404	APEX 1324257	50.04 PPM NITRIC OXIDE/NITROGEN	+/- 0.4%	Dec 22, 2023
GMIS	124206889126	CC323202	4.367 PPM NITROGEN DIOXIDE/NITROGEN	+/- 2.0%	Jan 04, 2027
PRM	C2392001.1	D153445	9.87 PPM NITROGEN DIOXIDE/NITROGEN	+/- 2.0%	Nov 22, 2024
GMIS	15310042024202	CC502382	9.897 PPM NITROGEN DIOXIDE/AIR	+/- 2.1%	Sep 18, 2027
SRM	1693a	FF25467	50.33 PPM SULFUR DIOXIDE/NITROGEN	+/- 0.7%	Jun 27, 2023
GMIS	0712202304	CC265390	49.93 PPM SULFUR DIOXIDE/NITROGEN	+/- 0.7%	Jun 18, 2027
GMIS	0712202327	EB0141202	49.93 PPM SULFUR DIOXIDE/NITROGEN	+/- 0.7%	Jun 12, 2027
CO	220608	CC744768	2501.8 PPM CARBON MONOXIDE/NITROGEN	+/- 0.5%	Sep 30, 2028

The SRM, NTRM, PRM, or RGM noted above is only in reference to the GMIS used in the assay and not part of the analysis.

ANALYTICAL EQUIPMENT

Instrument/Make/Model	Analytical Principle	Last Multipoint Calibration
MKS FTIR 017675074	FTIR	Mar 04, 2025
Nicolet iS50 FTIR AUP2010245 NO	FTIR	Mar 06, 2025
Nicolet iS50 FTIR AUP2010245 NO2	FTIR	Feb 20, 2025
Nicolet iS50 FTIR AUP2010245 SO2	FTIR	Mar 13, 2025

Triad Data Available Upon Request

NOTES: Gross Weight 27.9 Kg
Net Weight 4.8 Kg
PO# 4225000779



Michael A. Auler
Approved for Release



COPY

Michael A. Auler
Approved for Release



COPY

Hot Air Oven

Model : UFE 500

Serial No. : G511.0182

CERTIFICATE OF CALIBRATION

Certificate No. : 25-215653

Sample Code : 25-94507-006

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
583 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Hot Lab)

Equipment : Temperature controlled enclosures (Hot air oven)

Manufacturer : Memmert Model : UFE 500

Serial No. : G511.0182 ID No. : LABE 17/4

Date of Receipt : 16 December 2025 Date of Calibration : 16 December 2025

Condition of Calibration

1. Environment
- | | | | | |
|---------------------------|-----------|-----------|-----------|-----------|
| 1.1 Ambient temperature | : Maximum | 27.6 °C | : Minimum | 26.4 °C |
| 1.2 Relative humidity | : Maximum | 61.4 % | : Minimum | 54.0 % |
| 1.3 Line voltage supplied | : Maximum | 229.7 VAC | : Minimum | 225.6 VAC |

2. Calibration method

TLAS-G-20: Guidelines for calibration and checks of temperature controlled enclosures.

3. Reference standard instrument

Instrument	ID No.	Certificate No.	Due Date
Data acquisition with sensor (RTD-Prt100)	LB-DA-19 (RTD-302 to RTD-303, RTD-311, RTD-305 to RTD-310)	25-010559	04 February 2026

4. This certificate is traceable to the international system of unit (SI Unit).

The measurement is traceable to Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by Mr. Natthanan Phosri
Scientist

Approved by

(Mr. Somchai Nearpunt)
Signed for Director

Issue date 17 December 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

REPORT OF CALIBRATION

Certificate No. : 25-215653

Sample Code : 25-94507-006

Results of Calibration

Resolution : 0.5 °C

1. Reporting of Temperature

Calibration point (°C)	UUC* setting (°C)	UUC* reading (°C)	Measured temperature at each positions (°C)									Uncertainty $\pm$ (°C)	Coverage factor k
			# 1	# 2	# 3	# 4	# 5	# 6	# 7	# 8	# 9 ^{Ref}		
104	103.5	103.5	103.98	103.97	103.67	103.76	104.10	104.22	103.80	103.52	103.92	0.47	2.00

2. Characterization results

Calibration point (°C)	Stability (°C)	Uniformity (°C)	Open thermocouple (°C)
104	0.07	0.46	0.84

Notes

- * UUC* = Unit Under Calibration



COPY

COPY

NSC-TIS-TIS 17025
CALIBRATION 0152

REPORT OF CALIBRATION

Page 3 of 3


Certificate No. : 25-215653

Sample Code : 25-94507-006

Results of Calibration

Notes

1. Sensor installation locations
 - 1.1 All sensors at any corners or walls should be positioned 5 cm (a x b x c) from the wall.
 - 1.2 The reference sensor is preferably located of the geometric center of the chamber.
2. Interior dimensions approx of chamber :
W = 56 cm ; D = 40 cm ; H = 48 cm
3. Air valve or fresh air level : Off
4. Fan level : Open
5. The quoted uncertainty includes " Stability of chamber and loading effect in chamber at 20% of uniformity ".
6. Uniformity - the maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.
7. Stability - one-half of the greatest maximum difference of measured temperatures at any one sensor.
8. Overall variation - the difference of the maximum and the minimum measured temperatures throughout observation time.
9. UUC* reading - the average reading of indicating device that forms the integral part of the enclosure.
10. Calibration results without adjustment.

Figure: Example of sensor
installation Positions

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003

- End of Report -

COPY

ORIFICE TRANSFER STANDARD CERTIFICATION

WORKSHEET TE-5025A

ROOTSMETER S/N 0438320



TISCH ENVIRONMENTAL, INC.
145 SOUTH MIAMI AVE
VILLAGE OF CLEVELAND, OH
44102
513.467.9000
877.263.7810 TOLL FREE
513.467.9009 FAX

ORIFICE TRANSFER STANDARD CERTIFICATION WORKSHEET TE-5025A

Date - Mar 24, 2016 Rootmeter S/N 0438320 Ta (K) - 295
Operator Tisch Orifice I.D. - 0136 Pa (mm) - 742.95

PLATE OR Run #	VOLUME START (m3)	VOLUME STOP (m3)	DIFF VOLUME (m3)	DIFF TIME (min)	METER DIFF Hg (mm)	ORFICE DIFF H2O (in.)
1	NA	NA	1.00	1.3400	3.2	2.00
2	NA	NA	1.00	0.9510	6.3	4.00
3	NA	NA	1.00	0.8510	7.8	5.00
4	NA	NA	1.00	0.8130	8.6	5.50
5	NA	NA	1.00	0.6690	12.6	8.00

DATA TABULATION

Vstd	(x axis) Qstd	(y axis)		Va	(x axis) Qa	(y axis)
0.9832	0.7337	1.4054		0.9957	0.7430	0.8911
0.9791	1.0296	1.9875		0.9915	1.0426	1.2603
0.9770	1.1481	2.2221		0.9894	1.1626	1.4090
0.9760	1.2006	2.3305		0.9884	1.2157	1.4778
0.9707	1.4510	2.8107		0.9830	1.4694	1.7823
Qstd slope (m) = 1.96262				Qa slope (m) = 1.22896		
intercept (b) = -0.03249				intercept (b) = -0.02060		
coefficient (r) = 0.99993				coefficient (r) = 0.99993		

y axis = SQRT[H2O(Pa/760) (298/Ta)]

y axis = SQRT[H2O(Ta/Pa)]

CALCULATIONS

Vstd = Diff. Vol [(Pa-Diff. Hg)/760] (298/Ta)
Qstd = Vstd/Time

Va = Diff Vol [(Pa-Diff Hg)/Pa]
Qa = Va/Time

For subsequent flow rate calculations:

Qstd = 1/m{ [SQRT(H2O(Pa/760) (298/Ta))] - b}
Qa = 1/m{ [SQRT H2O(Ta/Pa)] - b}

COPY

THERMO-HYGROMETER

Model : 608-H1

Serial No. : 45106737

NSC-TISI-TIS 17025
CALIBRATION 0152

Page 1 of 2

CERTIFICATE OF CALIBRATION

Certificate No. : 26-072409

Sample Code : 26-030912-002

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.

683 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230Location of Calibration : Asia Medical and Agricultural Laboratory and Research Center Public Company Limited
(Calibration laboratory)

Equipment : Digital thermo-hygrometer

Manufacturer : testo

Model : 608-H1

Serial No. : 45106737

ID No. : LABE 09/7

Date of Receipt : 30 April 2026

Date of Calibration : 06 May 2026

Condition of Calibration

1. Environment
- 1.1 Ambient temperature : 23.0 °C ± 3.0 °C
- 1.2 Relative humidity : 55.0 % ± 15.0 %

2. Calibration method

- 2.1 In-house method: WI-CL-045 By comparison with thermometer standard / chilled mirror hygrometer in controlled chamber.
- 2.2 The calibration by comparison unit under calibration (UUC) to the thermometer standard / chilled mirror hygrometer in a chamber at the controlled temperature / relative humidity.

3. Reference standard instrument

Instrument	Model	ID No.	Certificate No.	Due Date
3.1 Chilled Mirror	Optidew 401	LB-DP-04 & LB-DP-04 (DP)	TH-0045-25	22 July 2026
3.2 Digital Thermometer	Optidew 401	LB-DP-04 & LB-DP-04 (Temp.)	25-157165	19 August 2026
3.3 Digital Thermometer	34972A	LB-DA-07 with RTD-89	25-115069	18 August 2026

4. This certificate is traceable to the international system of unit (SI Unit).

- 4.1 Instrument No. 3.1 through National Institute of Metrology (Thailand).
- 4.2 Instrument No. 3.2 and 3.3 through Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by

Miss Pornsuda Lohabal
Scientist

Approved by

(Mr. Nuttaput Timula)
Signed for Director

Issue date

08 May 2026

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

NSC-TISI-TIS 17025
CALIBRATION 0157

Page 2 of 2

REPORT OF CALIBRATION

Certificate No. : 26-072409

Sample Code : 26-030912-002

Results of Calibration

Temperature measurement

Resolution : 0.1 °C

Range : 0 °C to 50 °C

Calibration point °C	Average of standard reading		Unit under calibration		uncertainty °C
	Controlled humidity %RH	Temperature °C	Average reading °C	Correction value °C	
20	50	20.00	19.9	+ 0.10	± 0.39
25	50	25.00	24.9	+ 0.10	± 0.39
30	50	30.02	29.8	+ 0.22	± 0.39

Humidity measurement

Resolution : 0.1 %RH

Range : 10 %RH to 95 %RH

Calibration point %RH	Average of standard reading		Unit under calibration		uncertainty %RH
	Air temperature °C	Calculated humidity %RH	Average reading %RH	Correction value %RH	
45	25.00	45.04	50.2	- 5.16	± 1.3
60	25.00	60.10	65.1	- 5.00	± 1.5
75	25.01	75.06	85.7	- 10.64	± 1.7

Notes

- Calibration results without adjustment.

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2.00$, which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

- End of Report -

ANALYTICAL BALANCE (DU)

Model : XS205DU

Serial No. : B344940005

Certificate No. : 25-205716
Sample Code : 25-90375-006

CERTIFICATE OF CALIBRATION

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd, Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Analytical Balance Room)

Equipment : ELECTRONIC BALANCE

Manufacturer : METTLER TOLEDO

Model : XS205DU

Serial No. : B344940005

ID No. : LABE 05/3

Date of Receipt : 26 November 2025

Date of Calibration : 26 November 2025

Calibrated by Mr. Thanadol Pholthep
Scientist

Approved by (Mr. Somchai Neampunt)
Signed for Director

Issue date 28 November 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

Certificate No. : 25-205716
Sample Code : 25-90375-006

REPORT OF CALIBRATION

Equipment : ELECTRONIC BALANCE
Manufacturer : METTLER TOLEDO
Model : XS205DU
Capacity : Max 81 g / 200 g
Resolution : 0.00001 g / 0.0001 g
Serial No. : B344940005
ID No. : LABE 05/3

Result of Calibration

1. Test weight and repeatability of reading

Repeatability is a measure of the ability of a balance to supply the same result in repetitive weighings with one and the same load under the same measurement condition. The measurement of the repeatability must include both the balance specifications and the ambient (vibration, fluctuating air current/temperature/humidity, etc.) Operator handling of the balance is also included in the standard deviation.

Unit : g	Range : 81	☐ Before adjustment	☐ After adjustment
	Nominal value	40	80
☒ No adjustment	Standard weight	40.000087	80.000088
☐ Adjustment	Average reading of indicator	40.00004	80.00004
	Standard deviation	0.000007	0.000007

Unit : g	Range : 200	☐ Before adjustment	☐ After adjustment
	Nominal value	100	200
☒ No adjustment	Standard weight	99.999988	200.000015
☐ Adjustment	Average reading of indicator	99.9999	199.9997
	Standard deviation	0.00005	0.00005

Certificate No. : 25-205716
Sample Code : 25-90375-006

Page 3 of 4

REPORT OF CALIBRATION

Result of Calibration

2. Sensitivity or value of a scale division

Change in the output variable of a measuring instrument divided by the associated change in the input variable.

Unit : g

Range : 81

Range : 200

Test Point	Sensitivity, S	Test Point	Sensitivity, S
0	1.00000	0	1.0000
40	1.00000	100	1.0000
80	1.00000	200	1.0000

3. Departure of indication from nominal value, Linearity

Unit : g

Nominal Value	Standard Value	Average Reading of Indicator	Correction Value	Expanded Uncertainty	Coverage Factor (k)
Unload	0.0000000	0.00000	0.00000	0.000011	2.04
0.01	0.0100016	0.01000	0.00000	0.000011	2.04
0.1	0.1000056	0.10000	0.00001	0.000012	2.02
1	1.0000110	1.00000	0.00001	0.000015	2.01
5	4.9999996	4.99998	0.00002	0.000020	2.00
10	9.9999994	9.99999	0.00000	0.000026	2.00
20	20.000042	20.00000	0.00004	0.000037	2.00
50	50.000052	50.00003	0.00002	0.000067	2.00
100	99.999988	100.00000	0.00000	0.00016	2.00
150	150.000040	150.00001	-0.00001	0.00022	2.00
200	200.000015	200.00001	-0.00001	0.00027	2.00

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

Certificate No. : 25-205716
Sample Code : 25-90375-006

Page 4 of 4


REPORT OF CALIBRATION

Result of Calibration :

4. Eccentric or off-centre loading

Deviation of the measurement value through off - center (eccentric) loading. The corner load increases with the weight of the load and its removal from the center of the pan support.

☐ Triangular ☒ Rectangular ☐ Circle			Test weight : 50 and 100	
Weighing pan			Unit : g	
Range	81	200		
Position	Reading of indicator	Reading of indicator		
1	50.00000	100.0000		
2	49.99997	100.0000		
3	49.99993	99.9999		
4	49.99999	100.0000		
5	50.00003	99.9999		
6	50.00000	100.0000		
Maximum difference	0.00007	0.0001		



Condition of Calibration

- Calibration Method : WI-CL-004 base on UKAS LAB 14: 2019
- This result of calibration was found accurate as shown on date and place of calibration only.
- Condition of Calibration item: Normal
- This certification is traceable to the International System of Unit maintained at : -
- Through the reference standard laboratory of Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (Instrument number 1).
- Reference standard instrument :

Instrument	Class	ID No.	Certificate No.	Due Date
1) STANDARD WEIGHT 1 mg to 1 kg	E2	LB-WE-78	25-134074	18 July 2026

- End of Report -

6. Ambient conditions	Min	Max
Temperature (°C)	22.9	24.3
Relative Humidity (%Rh)	45.4	47.7
Air pressure (hPa)	1007.2	1011.0

COPY

ANALYTICAL BALANCE

Model : SECURA224-1S

Serial No. : 0036707137

Certificate No. : 25-205715
Sample Code : 25-90375-005

CERTIFICATE OF CALIBRATION

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd, Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Analytical Balance Room)

Equipment : ELECTRONIC BALANCE

Manufacturer : SARTORIUS

Model : SECURA224-1S

Serial No. : 0036707137

ID No. : LABE 05/2

Date of Receipt : 26 November 2025

Date of Calibration : 26 November 2025

Calibrated by : Mr. Pisek Into
Scientist

Approved by : (Mr. Somchai Neampunt)
Signed for Director

Issue date : 28 November 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

Certificate No. : 25-205715
Sample Code : 25-90375-005

REPORT OF CALIBRATION

Equipment : ELECTRONIC BALANCE
Manufacturer : SARTORIUS
Model : SECURA224-1S
Capacity : Max 220 g
Resolution : 0.0001 g
Serial No. : 0036707137
ID No. : LABE 05/2

Result of Calibration

1. Test weight and repeatability of reading

Repeatability is a measure of the ability of a balance to supply the same result in repetitive weighings with one and the same load under the same measurement condition. The measurement of the repeatability must include both the balance specifications and the ambient (vibration, fluctuating air current/temperature/humidity, etc.) Operator handling of the balance is also included in the standard deviation.

Unit : g	Range : 220	☒ Before adjustment	☒ After adjustment
	Nominal value	100	200
☐ No adjustment	Standard weight	100.000045	200.000047
☒ Adjustment	Average reading of indicator	99.9999	199.9998
	Standard deviation	0.00006	0.00008

Unit : -	Range : -	☐ Before adjustment	☐ After adjustment
	Nominal value	-	-
☐ No adjustment	Standard weight	-	-
☐ Adjustment	Average reading of indicator	-	-
	Standard deviation	-	-

COPY

Certificate No. : 25-205715
Sample Code : 25-90375-005

Page 3 of 4

REPORT OF CALIBRATION

Result of Calibration

2. Sensitivity or value of a scale division

Change in the output variable of a measuring instrument divided by the associated change in the input variable.

Unit : g

Range : 220

Range : -

Test Point	Sensitivity, S	Test Point	Sensitivity, S
0	1.0966	-	-
100	0.9969	-	-
200	0.9969	-	-

3. Departure of indication from nominal value, Linearity

Unit : g

Nominal Value	Standard Value	Average Reading of Indicator	Correction Value	Expanded Uncertainty	Coverage Factor (k)
Unload	0.0000000	0.0000	0.0000	0.000094	2.01
0.01	0.0100031	0.0100	0.0000	0.000094	2.01
0.1	0.1000023	0.1000	0.0000	0.000094	2.01
1	1.0000136	1.0000	0.0000	0.000095	2.01
2	2.0000101	2.0000	0.0000	0.000095	2.01
5	5.0000210	5.0000	0.0000	0.000096	2.01
10	10.000002	10.0000	0.0000	0.000097	2.01
20	20.000033	20.0000	0.0000	0.00011	2.01
50	50.000016	50.0000	0.0000	0.00012	2.01
100	100.000045	100.0000	0.0000	0.00016	2.00
200	200.000047	200.0000	0.0000	0.00027	2.00

COPY

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

Certificate No. : 25-205715
Sample Code : 25-90375-005

Page 4 of 4


REPORT OF CALIBRATION

Result of Calibration :

4. Eccentric or off-centre loading

Deviation of the measurement value through off - center (eccentric) loading. The corner load increases with the weight of the load and its removal from the center of the pan support.

Weighing pan	☐ Triangular ☐ Rectangular ☒ Circle	Test weight : 100 Unit : g
Range	220	-
Position	Reading of indicator	Reading of indicator
1	100.0000	-
2	100.0001	-
3	99.9999	-
4	99.9998	-
5	100.0001	-
6	100.0000	-
Maximum difference	0.0002	-



Condition of Calibration

1. Calibration Method : WI-CL-004 base on UKAS LAB 14: 2019

2. This result of calibration was found accurate as shown on date and place of calibration only.

3. Condition of Calibration item: Normal

4. This certification is traceable to the International System of Unit maintained at : -

- Through the reference standard laboratory of Asia Medical and Agricultural Laboratory and Research Center Public

Company Limited (Instrument number 1).

5. Reference standard instrument :

Instrument	Class	ID No.	Certificate No.	Due Date
1) STANDARD WEIGHT 1 mg to 1 kg	E2	LB-WE-79	25-142885	27 July 2026

- End of Report -

COPY

AUTOCLAVE

Model : FLS-1000

Serial No. : 55169083

CERTIFICATE OF CALIBRATION

Page 1 of 2

Certificate No. : 25-118068

Sample Code : 25-51697-004

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Autoclave Room)

Equipment : Autoclave

Manufacturer : TOMY Model : FLS-1000

Serial No. : 55169083 ID No. : LABE 43/2

Date of Receipt : 25 June 2025 Date of Calibration : 25 June 2025

Condition of Calibration

1. Environment
- | | |
|---------------------------|---|
| 1.1 Ambient temperature | : Maximum 32.0 °C ; Minimum 29.7 °C |
| 1.2 Relative humidity | : Maximum 68.1 % ; Minimum 65.2 % |
| 1.3 Line voltage supplied | : Maximum 222.3 VAC ; Minimum 218.3 VAC |

2. Calibration method

The calibration use in-house method: WI-CL-025 based on BS 2646-1: 2021

3. Reference standard instrument

Instrument	Model	ID No.	Certificate No.	Due Date
3.1 Temperature Data Logger	HiTemp 140	LB-TEM-25	25-034993	12 March 2026
3.2 Temperature Data Logger	HiTemp 140	LB-TEM-26	25-034994	12 March 2026
3.3 Temperature Data Logger	HiTemp 140	LB-TEM-27	25-034995	12 March 2026

4. This certificate is traceable to the international system of unit (SI Unit).

The measurement is traceable to Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by

Mr. Pattanapong Pulngern
Scientist

Approved by

(Mr. Somchai Neampunt)

Issue date

26 June 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

REPORT OF CALIBRATION

Page 2 of 2

Certificate No. : 25-118068

Sample Code : 25-51697-004

Results of Calibration

Resolution : 1 °C

1. Reporting of Temperature

Calibration point (°C)	UUC* setting (°C)	UUC* reading		Measured Temperature at each positions (°C)			Uncertainty ± (°C)	Coverage factor k
		Temperature (°C)	Pressure (MPa)	# 1	# 2 ^{Ref}	# 3		
121	121	122	0.11	121.75	121.76	121.77	0.63	2.00

2. Characterization results

Calibration Point (°C)	Stability ± (°C)	Uniformity (°C)	Overall Variation (°C)
121	0.03	0.03	0.06

Notes

- UUC* = Unit Under Calibration
- The quoted uncertainty includes "Stability of chamber and loading effect in chamber at 20% of uniformity".
- Uniformity - the maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.
- Stability - one-half of the greatest maximum difference of measured temperatures at any one sensor.
- Overall variation - the difference of the maximum and the minimum measured temperatures throughout observation time.
- UUC* reading - the average reading of indicating device that forms the integral part of the autoclave.
- Calibration results without adjustment.




Figure: Example of sensor
installation Positions

- Standard 1 = In the chamber drain, within 100 mm.
Standard 2 = In the upper half of the chamber.
Standard 3 = Attached to the load temperature probe, within 15 mm.

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

- End of Report -

BOD INCUBATOR

Model : LABE 19/3

CERTIFICATE OF CALIBRATION

Certificate No. : 25-118065

Sample Code : 25-51697-001

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Laboratory)

Equipment : Temperature controlled enclosures (Incubator)

Manufacturer : บริษัท เจริญชัย Model : N/A

Serial No. : S43020027 ID No. : LABE 19/3

Date of Receipt : 25 June 2025 Date of Calibration : 25 June 2025

Condition of Calibration

1. Environment
- | | | |
|---------------------------|---------------------|---------------------|
| 1.1 Ambient temperature | : Maximum 34.6 °C | : Minimum 32.2 °C |
| 1.2 Relative humidity | : Maximum 64.0 % | : Minimum 58.7 % |
| 1.3 Line voltage supplied | : Maximum 224.5 VAC | : Minimum 223.8 VAC |

2. Calibration method

TLAS-G-20: Guidelines for calibration and checks of temperature controlled enclosures.

3. Reference standard instrument

Instrument	ID No.	Certificate No.	Due Date
Data Acquisition With Sensor (RTD-Pt100)	LB-DA-08 (RTD-411 to RTD-419)	25-082913	18 May 2026

4. This certificate is traceable to the international system of unit (SI Unit).

The measurement is traceable to Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by

Mr. Pattanapong Pulngern

Approved by

(Mr. Somchai Neampunt)

Scientist

Signed for Director

Issue date

26 June 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

REPORT OF CALIBRATION

Certificate No. : 25-118065

Sample Code : 25-51697-001

Results of Calibration

Resolution : 0.1 °C

1. Reporting of Temperature

Calibration point (°C)	UUC* setting (°C)	UUC* reading (°C)	Measured temperature at each positions (°C)										Uncertainty ± (°C)	Coverage factor k
			#1	#2	#3	#4	#5	#6	#7	#8	#9 ^{Ref}	#10		
20	20.0	20.0	20.61	20.42	19.97	19.90	20.29	20.47	20.25	19.96	20.18		0.24	2.00

2. Characterization results

Calibration point (°C)	Stability ± (°C)	Uniformity (°C)	Overall variation (°C)
20	0.09	0.46	0.89

Notes

- UUC* = Unit Under Calibration



REPORT OF CALIBRATION

Page 3 of 3

Certificate No. : 25-118065

Sample Code : 25-51697-001

Results of Calibration

Notes

1. Sensor installation locations
 - 1.1 All sensors at any corners or walls should be positioned 5 cm (a x b x c) from the wall.
 - 1.2 The reference sensor is preferably located of the geometric center of the chamber.
2. Interior dimensions approx of chamber :
W = 70 cm ; D = 55 cm ; H = 140 cm
3. Air valve or fresh air level : Off
4. Fan level : Open
5. The quoted uncertainty includes " Stability of chamber and loading effect in chamber at 20% of uniformity ".
6. Uniformity - the maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.
7. Stability - one-half of the greatest maximum difference of measured temperatures at any one sensor.
8. Overall variation - the difference of the maximum and the minimum measured temperatures throughout observation time.
9. UUC* reading - the average reading of indicating device that forms the integral part of the enclosure.
10. Calibration results without adjustment.




Figure: Example of sensor
installation Positions

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

- End of Report -



COPY

BOD INCUBATOR

Model : LABE 19/5



Page 1 of 3

CERTIFICATE OF CALIBRATION

Certificate No. : 25-042561

Sample Code : 25-18090-002

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Laboratory)

Equipment : Temperature controlled enclosures (Incubator)

Manufacturer : Lovibond Model : TC 445 S

Serial No. : 0520/005227 ID No. : LABE 19/5

Date of Receipt : 20 March 2025 Date of Calibration : 20 March 2025

Condition of Calibration

1. Environment
- 1.1 Ambient temperature : Maximum 29.9 °C ; Minimum 27.5 °C
- 1.2 Relative humidity : Maximum 51.9 % ; Minimum 43.4 %
- 1.3 Line voltage supplied : Maximum 239.4 VAC ; Minimum 232.8 VAC

2. Calibration method

TLAS-G-20: Guidelines for calibration and checks of temperature controlled enclosures.

3. Reference standard instrument

Instrument	ID No.	Certificate No.	Due Date
Data Acquisition With Sensor (RTD-P1100)	LB-DA-11 (RTD-148 to RTD-155, RTD-227)	24-040190	03 April 2025

4. This certificate is traceable to the international system of unit (SI Unit).

The measurement is traceable to Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by Mr. Pattanapong Pulngern
Scientist

Approved by

(Mr. Somchai Neampunt)

Signed for Director

Issue date 24 March 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).



Page 2 of 3

REPORT OF CALIBRATION

Certificate No. : 25-042561

Sample Code : 25-18090-002

Results of Calibration

Resolution : 0.1 °C

1. Reporting of Temperature

Calibration point (°C)	UUC* setting (°C)	UUC* reading (°C)	Measured temperature at each positions (°C)										Uncertainty ± (°C)	Coverage factor k
			#1	#2	#3	#4	#5	#6	#7	#8	#9 ^{ref}			
20	20.5	20.5	19.91	19.78	19.82	19.86	19.78	19.85	19.93	19.63	19.79		0.38	2.00

2. Characterization results

Calibration point (°C)	Stability ± (°C)	Uniformity (°C)	Overall variation (°C)
20	0.28	0.25	0.83

Notes

- UUC* = Unit Under Calibration



NSC-TISI-TISI7025
CALIBRATION 0152

Page 3 of 3

REPORT OF CALIBRATION

Certificate No. : 25-042561

Sample Code : 25-18090-002

Results of Calibration

Notes

1. Sensor installation locations
 - 1.1 All sensors at any corners or walls should be positioned 5 cm (a x b x c) from the wall.
 - 1.2 The reference sensor is preferably located of the geometric center of the chamber.
2. Interior dimensions approx of chamber :
W = 60 cm ; D = 56 cm ; H = 146 cm
3. Air valve or fresh air level : Off
4. Fan level : Open
5. The quoted uncertainty includes* Stability of chamber and loading effect in chamber at 20% of uniformity*.
6. Uniformity - the maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.
7. Stability - one-half of the greatest maximum difference of measured temperatures at any one sensor.
8. Overall variation - the difference of the maximum and the minimum measured temperatures throughout observation time.
9. UUC* reading - the average reading of indicating device that forms the integral part of the enclosure.
10. Calibration results without adjustment.




Figure: Example of sensor
installation Positions

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003

- End of Report -

COPY

BOD INCUBATOR

Model : LABE 19/5

CERTIFICATE OF CALIBRATION

Certificate No. : 26-031063

Sample Code : 26-013575-002

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.

683 Moo 11, Sukhapiarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Laboratory)

Equipment : Temperature controlled enclosures (Incubator)

Manufacturer : Lovibond Model : TC 445 S

Serial No. : 0520/005227 ID No. : LABE 19/5

Date of Receipt : 24 February 2026 Date of Calibration : 24 February 2026

Condition of Calibration

1. Environment
- 1.1 Ambient temperature : Maximum 32.3 °C ; Minimum 30.1 °C
- 1.2 Relative humidity : Maximum 56.5 % ; Minimum 49.3 %
- 1.3 Line voltage supplied : Maximum 230.6 VAC ; Minimum 225.3 VAC

2. Calibration method

TLAS-G-20: Guidelines for calibration and checks of temperature controlled enclosures.

3. Reference standard instrument

Instrument	ID No.	Certificate No.	Due Date
Data Acquisition With Sensor (RTD-Pt100)	LB-DA-11 (RTD-441 to RTD-449)	25-040942	01 April 2026

4. This certificate is traceable to the international system of unit (SI Unit).

The measurement is traceable to Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by

Mr. Pattanapong Pulngern

Approved by

(Mr. Nuttaput Timula)

Issue date

27 February 2026

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

REPORT OF CALIBRATION

Certificate No. : 26-031063

Sample Code : 26-013575-002

Results of Calibration

Resolution : 0.1 °C

1. Reporting of Temperature

Calibration point (°C)	UUC* setting (°C)	UUC* reading (°C)	Measured temperature at each positions (°C)									Uncertainty ± (°C)	Coverage factor k
			# 1	# 2	# 3	# 4	# 5	# 6	# 7	# 8	# 9 ^{ref}		
20	20.5	20.5	19.84	19.83	19.85	19.83	19.80	19.70	19.88	19.70	19.72	0.40	2.00

2. Characterization results

Calibration point (°C)	Stability ± (°C)	Uniformity (°C)	Overall variation (°C)
20	0.30	0.32	0.70

Notes

- UUC* = Unit Under Calibration




REPORT OF CALIBRATION

Certificate No. : 26-031063

Sample Code : 26-013575-002

Results of Calibration

Notes

1. Sensor installation locations
 - 1.1 All sensors at any corners or walls should be positioned 5 cm (a x b x c) from the wall.
 - 1.2 The reference sensor is preferably located of the geometric center of the chamber.
2. Interior dimensions approx of chamber :
W = 60 cm ; D = 56 cm ; H = 146 cm
3. Air valve or fresh air level : Off
4. Fan level : Open
5. The quoted uncertainty includes "Stability of chamber and loading effect in chamber at 20% of uniformity".
6. Uniformity - the maximum difference of measured temperatures at any sensors and the measured temperature at the reference location which are observed at the same time.
7. Stability - one-half of the greatest maximum difference of measured temperatures at any one sensor.
8. Overall variation - the difference of the maximum and the minimum measured temperatures throughout observation time.
9. UUC* reading - the average reading of indicating device that forms the integral part of the enclosure.
10. Calibration results without adjustment.





Figure: Example of sensor
installation Positions

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

- End of Report -



COPY

Hot Air Oven

Model : UM 400

Serial No. : 900982

NSC-TISI-TIS17025
CALIBRATION 0152

Page 1 of 3

CERTIFICATE OF CALIBRATION

Certificate No. : 25-215652

Sample Code : 25-94507-005

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapiarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Hot Lab)

Equipment : Temperature controlled enclosures (Hot air oven)

Manufacturer : Memmert Model : UM 400

Serial No. : 900982 ID No. : LABE 17/1

Date of Receipt : 16 December 2025 Date of Calibration : 16 December 2025

Condition of Calibration

1. Environment
- | | | | | |
|---------------------------|-----------|-----------|-----------|-----------|
| 1.1 Ambient temperature | : Maximum | 27.6 °C | ; Minimum | 26.4 °C |
| 1.2 Relative humidity | : Maximum | 61.4 % | ; Minimum | 54.0 % |
| 1.3 Line voltage supplied | : Maximum | 229.7 VAC | ; Minimum | 225.6 VAC |

2. Calibration method

TLAS-G-20: Guidelines for calibration and checks of temperature controlled enclosures.

3. Reference standard instrument

Instrument	ID No.	Certificate No.	Due Date
Data acquisition with sensor (RTD-Pt100)	LB-DA-20 (RTD-322 to RTD-330)	25-010526	18 February 2026

4. This certificate is traceable to the international system of unit (SI unit).

The measurement is traceable to Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by

Mr. Natthanan Phosri
Scientist

Approved by

(Mr. Somchai Neampunt)
Signed for Director

Issue date

17 December 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

NSC-TISI-TIS17025
CALIBRATION 0152

Page 2 of 3

REPORT OF CALIBRATION

Certificate No. : 25-215652

Sample Code : 25-94507-005

Results of Calibration

Resolution : 0.1 °C

1. Reporting of Temperature

Calibration point (°C)	UUC* setting (°C)	UUC* reading (°C)	Measured temperature at each positions (°C)									Uncertainty ± (°C)	Coverage factor <i>k</i>
			# 1	# 2	# 3	# 4	# 5	# 6	# 7	# 8	# 9 ^{Ref}		
60	60.0	60.0	61.27	61.38	61.49	60.82	59.60	59.82	59.89	59.80	60.50	0.38	2.00
85	85.0	85.0	85.92	86.20	85.98	85.69	83.63	83.93	84.33	84.04	84.84	0.40	2.00

2. Characterization results

Calibration point (°C)	Stability ± (°C)	Uniformity (°C)	Overall variation (°C)
60	0.19	1.08	2.05
85	0.11	1.44	2.72

Notes

- UUC* = Unit Under Calibration

NSC-TISI-TISI17025
CALIBRATION 0152

REPORT OF CALIBRATION

Page 3 of 3

Certificate No. : 25-215652

Sample Code : 25-94507-005

Results of Calibration

Notes

1. Sensor installation locations

- 1.1 All sensors at any corners or walls should be positioned
5 cm (a x b x c) from the wall.

- 1.2 The reference sensor is preferably located of the geometric center
of the chamber.

2. Interior dimensions approx of chamber :

W = 40 cm; D = 28 cm; H = 39 cm

3. Air valve or fresh air level : Off

4. Fan level : Open

5. The quoted uncertainty includes "Stability of chamber and loading effect
in chamber at 20% of uniformity".6. Uniformity - the maximum difference of measured temperatures at any sensors and the measured temperature at the reference
location which are observed at the same time.

7. Stability - one-half of the greatest maximum difference of measured temperatures at any one sensor.

8. Overall variation - the difference of the maximum and the minimum measured temperatures throughout observation time.

9. UUC* reading - the average reading of indicating device that forms the integral part of the enclosure.

10. Calibration results without adjustment.




Figure: Example of sensor
installation Positions

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

- End of Report -

COPY

LIQUID IN GLASS THERMOMETER

Model / Type : 0-100 °C

Serial No. : 43560



CALIBRATION LABORATORY CO.,LTD.

2/10-11,14,55 Soi Prasert Manukit 29 Yaek 4, Prasert Manukit Rd., Ladphrao, Bangkok 10230
Tel. 02-578-0353-4 Fax: 02-578-2672 www.cal-laboratory.com E-mail:sale@cal-laboratory.com



CERTIFICATE OF CALIBRATION

FOR

NOMENCLATURE : LIQUID IN GLASS THERMOMETER
MANUFACTURER : AA PRECISION
MODEL / TYPE : 0-100 °C
SERIAL NO. : 43560[LABE 16/1]
CLID. NO. : 232403905
JOB CONTROL NO. : 251115135334
CALIBRATION SERVICE : ☒ IN-LABORATORY ☐ ON-SITE

CUSTOMER : EASTERN THAI CONSULTING 1992 CO., LTD.
683 MOO 11, SUKHAPIBARN 8 RD,
NONGKHAM, SRIRACHA, CHONBURI 20230

DATE OF RECEIVED : 15 November 2025 DATE OF ISSUED : 18 November 2025

The report of calibration shall not be reproduced except in full without approval of the Calibration Laboratory Co., Ltd.

Calibrated By : Pimsiri Hemtanon
Calibration Engineer

Approved By : Mongkol Yotsoontorn
Authorized Signatory
18 November 2025



This Calibration Certificate documents the traceability to national standards, which realize the units of measurement according to the International System of Units (SI)

Certificate No. Q25135334

F3-011-05/12-23

COPY



@clccalibration



CALIBRATION LABORATORY CO.,LTD.

2/10-11,14,55 Soi Prasert Manukit 29 Yaek 4, Prasert Manukit Rd., Ladphrao, Bangkok 10230
Tel. 02-578-0353-4 Fax: 02-578-2672 www.cal-laboratory.com E-mail:sale@cal-laboratory.com



REPORT OF CALIBRATION

FOR

NOMENCLATURE : LIQUID IN GLASS THERMOMETER
MANUFACTURER : AA PRECISION
MODEL / TYPE : 0-100 °C
SERIAL NO. : 43560[LABE 16/1]
DATE OF CALIBRATION : 17 November 2025

ENVIRONMENT CONDITIONS :

Temperature : $(23 \pm 2) ^\circ\text{C}$ Relative Humidity : $(55 \pm 10) \%$

PROCEDURE USED :

This instrument was calibrated under procedure No. CLC-CPTH-02 based on ASTM E 77-07 as calibration guidelines.
The calibration was performed by comparison with Calibration Bath, Precision Thermometer and IPRT which maintained by the Calibration Laboratory Co., Ltd.

REFERENCE STANDARD USED :

1. Calibration Bath, Kambic Model OB-22/2 ULT,OB-22/2 S/N. 17115653,17115654.
2. Precision Thermometer, ASL Model F200-A-8 S/N. 014433/03 with IPRT S/N. L0193A-1-1,PO106346-1-13.

TRACEABILITY :

1. The measurements are traceable to International System of Units (SI), through Calibration Laboratory Co., Ltd. Certificate No. Q24120999,Q25124610. Due Date 26 November 2025,07 November 2026.
2. The measurements are traceable to International System of Units (SI), through Thailand Institute of Scientific and Technological Research (TISTR) and National Institute of Metrology (Thailand). Certificate No. PSL-T 0177/68,TT-0169-24,TT-1008-25. Due Date 10 February 2026,11 December 2025,04 March 2026.

UNCERTAINTY :

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k = 2$ which for a normal distribution corresponds to a coverage probability of approximately 95 %. It has been evaluated according to the "Evaluation of the Uncertainty of Measurement in Calibration (EA-4/02 M:2022)"

Certificate No. Q25135334

F3-011-05/12-23

COPY



@clccalibration



CALIBRATION LABORATORY Co.,LTD.

2/10-11,14,55 Soi Prasert Manukit 29 Yaek 4, Prasert Manukit Rd., Ladphrao, Bangkok 10230
Tel. 02-578-0353-4 Fax: 02-578-2672 www.cal-laboratory.com E-mail:sale@cal-laboratory.com



CONDITION OF CALIBRATION ITEM : RECEIVED IN GOOD OPERATIONAL CONDITION

MEASUREMENT RESULTS : (X) without adjustment () adjustment

The DUC Reading were recorded and the means value were reported of four times measurement in the table below.

CALIBRATION DATA

CORRECTION OF TEMPERATURE

STD Reading (°C)	DUC Reading (°C)	Correction (°C)	Uncertainty $\pm$ (°C)
0.01	0.00	+0.01	0.06
25.02	25.00	+0.02	
50.03	50.00	+0.03	
100.01	100.00	+0.01	

Range : 0 °C to 100 °C

Graduation : 0.1 °C

Immersion Type : Total Immersion.

Correction of Reference Temperature (0 °C) = 0.00 °C

Note. The Scope of Accredited ANAB Certificate No. ACDM-2814 Version 016 Page 60 of 73

This report is valid for the above stated instrument/s only.

End of Certificate

Certificate No. Q25135334

F3-011-05/12-23

COPY



@clccalibration

pH Meter

Model : SevenCompact S220

Serial No. : B448305208

NSC-TISI-TIS17025
CALIBRATION 0152

Page 1 of 3

CERTIFICATE OF CALIBRATION

Certificate No. : 25-215648

Sample Code : 25-94507-001

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : EASTERN THAI CONSULTING 1992 CO., LTD.
(Laboratory)

Equipment : pH Meter

Manufacturer : METTLER TOLEDO **Model** : SevenCompact S220

Serial No. : B448305208 **ID No.** : LABE 11/4

Date of Receipt : 18 December 2025 **Date of Calibration** : 16 December 2025

Condition of Calibration

1. **Environment** Ambient temperature : 15.0 to 35.0 °C Relative humidity : 35.0 to 80.0 %RH
1.1 Start time : 23.3 °C ; End time : 24.0 °C 1.2 Start time : 46.7 %RH ; End time : 45.8 %RH

2. Calibration method

In house method WI-CL-019 : Direct measurement with standard voltage calibrator and direct measurement with certified reference material (CRM).

3. Reference standard / Certified reference material

Instrument	ID No.	Certificate No.	Due Date
3.1 Voltage Calibrator	LB-DPC-01	LF25-0350	22 June 2026
3.2 Digital Thermometer	LB-DPC-01	25-141888	29 July 2026
Certified Reference Material		Lot. No.	Expire Date
3.3 Buffer Solution pH 4.008	1174256	PH216.L5	13 December 2027
3.4 Buffer Solution pH 7.000	C03292	S11M004	14 July 2027
3.5 Buffer Solution pH 10.010	1174257	PH220.L5	13 December 2026

4. This certificate is traceable to the international system of unit (SI Unit).

- 4.1 Instrument No. 3.1 through Measuretronix Limited.
- 4.2 Instrument No. 3.2 through Asia Medical and Agricultural Laboratory and Research Center Public Company Limited.
- 4.3 Buffer Solution No. 3.3 and No. 3.5 traceable to CPA chem (through primary measurement method-Harned cell using calibrated thermometer, barometer, and nanovoltmeter Accredited laboratory ISO/IEC 17025 and ISO 17034).
- 4.4 Buffer Solution No. 3.4 traceable to HACH (Certified Reference Material from PTB Certificate Nr. PTB-PHOA-563/30504/23 and Certificate Nr. PTB-PHOB-555/30620/22. According to DIN EN ISO 17034:2017).

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of calibration item : Normal

Calibrated by Mr. Chakrin Chiangsorn
Scientist

Approved by

(Mr. Somchai Neampunt)
Signed for Director

Issue date 18 December 2025

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

NSC-TISI-TIS17025
CALIBRATION 0152

Page 2 of 3

REPORT OF CALIBRATION

Certificate No. : 25-215648

Sample Code : 25-94507-001

Equipment : pH Meter **Resolution** : 0.01 pH ; 0.1 mV ; 0.1 °C

Manufacturer : METTLER TOLEDO **Model** : SevenCompact S220

Serial No. : B448305208 **ID No.** : LABE 11/4

Range : -2.000 pH to 20.000 pH ; -2000.0 mV to 2000.0 mV ; -5.0°C to 130.0°C

Results of Calibration

Part 1. DC Voltage measurement

pH Meter Serial No. : B448305208

Nominal Value	Applied DC Voltage	Average indicator reading		Uncertainty	Coverage factor
		mV	pH		
0	414.113	414.0	0.00	± 0.083	2.00
4	177.477	177.5	4.00	± 0.083	2.00
7	0.000	0.1	7.00	± 0.083	2.00
10	-177.477	-177.3	10.00	± 0.083	2.00
14	-414.113	-413.8	14.00	± 0.083	2.00

Part 2. Performance of Electrode system

Electrode Manufacturer : METTLER TOLEDO Model : InLab Expert Pro-ISM

Electrode Serial No. : 4290677

Three-Point Calibration at pH4 and pH7 Percent Slope : 99.2 , at pH7 and pH10 Percent Slope : 99.7

Standard Buffer Solution	Average indicator reading		Error Value	Uncertainty	Coverage factor
	pH	mV			
pH (@ 25 °C)			pH	pH	k
4.008	4.02	163.7	0.012	± 0.0093	2.00
7.000	7.01	-11.6	0.010	± 0.0093	2.00
10.010	10.00	-187.7	-0.010	± 0.0099	2.00

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

NSC-TISI-TIS17025
CALIBRATION 0152

Page 3 of 3

REPORT OF CALIBRATION

Certificate No. : 25-215648

Sample Code : 25-94507-001

Equipment : pH Meter (Digital Thermometer with sensor)

Thermometer readout

Manufacturer : METTLER TOLEDO Model : SevenCompact S220
Serial No. : B448305208 ID No. : LABE 11/4
Resolution : 0.1 °C Range : -5.0 °C to 130.0 °C

Thermometer sensor

Manufacturer : METTLER TOLEDO Model : InLab Expert Pro-ISM
Serial No. : 4290677 ID No. : N/A

Condition of Calibration

1. Environment 1.1 Ambient temperature : 24.1 °C ± 0.0 °C
1.2 Relative humidity : 45.0 % ± 0.2 %

2. Calibration method

- 2.1 The calibration use in house method WI-CL-021 : by comparison with standard thermometer
2.2 The calibration by comparison unit under calibration (UUC) to the standard thermometer in a calibration bath at the controlled temperature.
2.3 The temperature scale in use of this laboratory is the international temperature scale of 1990 (ITS-90).

3. Reference standard instrument

Instrument	Model	ID. No.	Certificate No.	Due date
3.1 Resistance Thermometer	PT-100	RTD-366	25-141888	29 July 2026
3.2 Thermometer Readout	753	LB-DPC-01	25-141888	29 July 2026

4. This certificate is traceable to the international system of unit (SI Unit).

Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (Accreditation Under TLAS Laboratory Calibration No.0152)

5. This result of calibration was found accurate as shown on date and place of calibration only.

6. Condition of Calibration item : Normal

Results of Calibration

Calibration point °C	Average of standard reading °C	Unit under calibration			Expanded uncertainty °C	Coverage factor k
		Immersion depth mm	Average reading °C	Correction value °C		
25	25.00	100	24.9	+ 0.10	± 0.14	2.00

Notes

- Calibration results without adjustment

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor k , which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003.

- End of report -

STANDARD WEIGHT 50 g

Certificate No. : 24-062445
Sample Code : 24-25551-001

CERTIFICATE OF CALIBRATION

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., Nongkham,
Sriracha, Chonburi 20230

Location of Calibration : Asia Medical and Agricultural Laboratory and Research Center Public Company Limited
(Calibration Laboratory)

Equipment : Standard Weight 50 g

Manufacturer : METTLER TOLEDO

Class : F1

Serial No. : N/A

ID No. : LABE 10/1

Date of Receipt : 23 May 2024

Date of Calibration : 03 June 2024

Calibrated by Mr. Somwang Sangdee
Scientist

Issue date 04 June 2024

Approved by (Mr. Somchai Neampunt)
Signed for Director

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

Certificate No. : 24-062445
Sample Code : 24-25551-001

REPORT OF CALIBRATION

Equipment : Standard Weight 50 g

Manufacturer : METTLER TOLEDO

Class : F1

Serial No. : N/A

ID No. : LABE 10/1

Result of Calibration : ☒ Without adjustment ☐ Adjustment

Conventional value of the result of weighing in air. For a weight taken at a reference temperature (t_{ref}) of 20°C, the conventional mass is the mass of a reference weight of a density (ρ_{ref}) of 8000 kg.m⁻³ which it balances in air of a reference density (ρ_0) of 1.2 kg.m⁻³

Description	Deviation (mg)	Conventional Mass	Expanded Uncertainty (mg)	Maximum Permissible Error $\pm$ (mg)	ID No.
50 g	-0.343	49.999657 g	0.10	0.30	LABE 10/1

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor $k = 2.0$, which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003

Certificate No. : 24-062445

Sample Code : 24-25551-001

Page 3 of 3

REPORT OF CALIBRATION

Condition of Calibration

1. Ambient Conditions : Temperature $20^{\circ}\text{C} \pm 1.5^{\circ}\text{C}$, Relative humidity $50\% \pm 10\%$ and air density 1.19 kg/m^3

2. Calibration Method : Direct comparison weighing according to OIML R111-1 : 2004(E)

3. Reference standard instrument

Instrument	Class	ID No.	Certificate No.	Due Date
1) Standard Weight 1 mg to 1 kg	E2	LB-WE-83	24-001894	11 January 2025

4. This certification is traceable to the International System of Unit maintained at : -

Asia Medical and Agricultural Laboratory and Research Center Public Company Limited

(Instrument number 1).

5. Condition of Calibration item: Normal

6. Description of Calibrated item :

Type and Nominal Value :	Standard Weight 50 g
Shape :	Cylindrical weight with knob
Material :	Stainless steel
Case :	Wooden Box
Comments :	Recalibration

- End of Report -



COPY

STANDARD WEIGHT 100 g

Certificate No. : 24-079772
Sample Code : 24-31841-002

CERTIFICATE OF CALIBRATION

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., NongKham,
Sriracha, Chonburi 20230

Location of Calibration : Asia Medical and Agricultural Laboratory and Research Center Public Company Limited
(Calibration Laboratory)

Equipment : Standard Weight 100 g

Manufacturer : N/A

Class : N/A

Serial No. : N/A

ID No. : LABE 10/2

Date of Receipt : 25 June 2024

Date of Calibration : 30 June 2024

Calibrated by Mr. Nawa Sisuwan
Scientist

Approved by (Mr. Somchai Neampunt)
Signed for Director

Issue date 03 July 2024

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

Certificate No. : 24-079772
Sample Code : 24-31841-002

REPORT OF CALIBRATION

Equipment : Standard Weight 100 g

Manufacturer : N/A

Class : N/A

Serial No. : N/A

ID No. : LABE 10/2

Result of Calibration :

☒ Without adjustment☐ Adjustment

Conventional value of the result of weighing in air. For a weight taken at a reference temperature (t_{ref}) of 20°C, the conventional mass is the mass of a reference weight of a density (ρ_{rel}) of 8000 kg.m⁻³ which it balances in air of a reference density (ρ_0) of 1.2 kg.m⁻³

Description	Deviation	Conventional	Expanded	Maximum	ID No.
	(mg)	Mass	Uncertainty	Permissible Error	
			(mg)	± (mg)	
100 g	-0.173	99.999827 g	0.16	0.50	LABE 10/2

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor $k = 2.0$, which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003

COPY

Certificate No. : 24-079772
Sample Code : 24-31841-002

Page 3 of 3

REPORT OF CALIBRATION

Condition of Calibration

1. Ambient Conditions : Temperature $20^{\circ}\text{C} \pm 1.5^{\circ}\text{C}$, Relative humidity $50\% \pm 10\%$ and air density 1.19 kg/m^3

2. Calibration Method : WI-CL-007 base on OIML R 111-1 : 2004(E)

3. Reference standard instrument

Instrument	Class	ID.No.	Certificate No.	Due Date
1) Standard Weight 1 mg to 1 kg	E2	LB-WE-83	24-001894	11 January 2025

4. This certification is traceable to the International System of Unit maintained at : -

Asia Medical and Agricultural Laboratory and Research Center Public Company Limited

(Instrument number 1).

5. Condition of Calibration item: Normal

6. Description of Calibrated Item :

Type and Nominal Value :	Standard Weight 100 g
Shape :	Cylindrical weight with knob
Material :	Stainless steel
Case :	Wooden Box
Comments :	Recalibration

- End of Report -

COPY

STANDARD WEIGHT 50 g

Certificate No. : 24-079773
Sample Code : 24-31841-003

CERTIFICATE OF CALIBRATION

Customer : EASTERN THAI CONSULTING 1992 CO., LTD.
683 Moo 11, Sukhapibarn 8 Rd., NongKham,
Sriracha, Chonburi 20230

Location of Calibration : Asia Medical and Agricultural Laboratory and Research Center Public Company Limited
(Calibration Laboratory)

Equipment : Standard Weight 50 g

Manufacturer : N/A

Class : N/A

Serial No. : N/A

ID No. : LABE 10/4

Date of Receipt : 25 June 2024

Date of Calibration : 30 June 2024

Calibrated by Mr. Nawa Sisuwan
Scientist

Approved by (Mr. Somchai Neampunt)
Signed for Director

Issue date 03 July 2024

The uncertainties are for a confidence probability of approximately 95%.

The calibration result is applied only to the above calibrated item and was found accurate as shown on date and place of calibration only.

This Certificate is issued in accordance with the conditions of accreditation granted by the Thai Laboratory Accreditation scheme which has assessed the measurement capability of the laboratory and its traceability to recognized national standards and to the unit of measurement realized at the corresponding national standards laboratory. This certificate may not be reproduced other than in full except with the prior written approval of the Asia Medical and Agricultural Laboratory and Research Center Public Company Limited (AMARC).

Certificate No. : 24-079773
Sample Code : 24-31841-003

REPORT OF CALIBRATION

Equipment : Standard Weight 50 g

Manufacturer : N/A

Class : N/A

Serial No. : N/A

ID No. : LABE 10/4

Result of Calibration : ☒ Without adjustment ☐ Adjustment

Conventional value of the result of weighing in air. For a weight taken at a reference temperature (t_{ref}) of 20°C, the conventional mass is the mass of a reference weight of a density (ρ_{ref}) of 8000 kg.m⁻³ which it balances in air of a reference density (ρ_0) of 1.2 kg.m⁻³

Description	Deviation	Conventional	Expanded	Maximum	ID No.
	(mg)	Mass	Uncertainty	Permissible Error	
			(mg)	± (mg)	
50 g	-0.176	49.999824 g	0.10	0.30	LABE 10/4

The result expanded uncertainty of measurement U is stated as the standard uncertainty of measurement multiplied by the coverage factor $k = 2.0$, which for a normal distribution corresponds to a coverage probability of approximately 95%. The standard uncertainty of measurement has been determined in accordance with UKAS M3003

COPY

Certificate No. : 24-079773

Sample Code : 24-31841-003

Page 3 of 3

REPORT OF CALIBRATION

Condition of Calibration

1. Ambient Conditions : Temperature $20^{\circ}\text{C} \pm 1.5^{\circ}\text{C}$, Relative humidity $50\% \pm 10\%$ and air density 1.19 kg/m^3

2. Calibration Method : WI-CL-007 base on OIML R 111-1 : 2004(E)

3. Reference standard instrument

Instrument	Class	ID No.	Certificate No.	Due Date
1) Standard Weight 1 mg to 1 kg	E2	LB-WE-83	24-001894	11 January 2025

4. This certification is traceable to the International System of Unit maintained at : -

Asia Medical and Agricultural Laboratory and Research Center Public Company Limited

(Instrument number 1).

5. Condition of Calibration item: Normal

6. Description of Calibrated Item :

Type and Nominal Value :	Standard Weight 50 g
Shape :	Cylindrical weight with knob
Material :	Stainless steel
Case :	Wooden Box
Comments :	Recalibration

- End of Report -



COPY

ภาคผนวกที่ 5

เอกสาร Detection Limit ของรายการทดสอบ

Rev.3 วันที่ 21/6/2024 แก้ไข Detection Limit ของโลหะหนักโดยรายงานหน่วย mg/m3 ทุกพารามิเตอร์เพื่อให้สอดคล้อง กับมาตรฐาน

การตรวจวิเคราะห์คุณภาพอากาศ (Air Quality Analysis)

ประเภทตัวอย่าง : อากาศในปล่องระบาย - Stack Air Quality

ตารางที่ 1 สรุปข้อกำหนดการเก็บตัวอย่างและความสามารถในการทดสอบตัวอย่างของห้องปฏิบัติการ ตามที่ขึ้นทะเบียนกับกรมโรงงานอุตสาหกรรม
(ประเภทตัวอย่าง : อากาศในปล่องระบาย - Stack Air Quality)

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
แผนปฏิบัติการภาคสนาม									
1	Smoke density (Opacity)	Ringelmann' s method	U.S. EPA Method 9 / Ringelmann' s Chart	-	-	-	%	2	
2	Oxide of Nitrogen	Chemilluminescence Method	U.S. EPA Method 7E / Nitrogen dioxide Analyzer	-	-	0.1 - 100	ppm	1	ใช้ Dilution Probe ร่วมในการตรวจวัด
3	Sulfur Dioxide	UV Fluorescence Method	U.S. EPA Method 6C / Sulfur dioxide Analyzer	-	-	0.4 - 100	ppm	1	ใช้ Dilution Probe ร่วมในการตรวจวัด
4	Carbon Monoxide	Bag,Non-Dispersive Infrared Method	U.S. EPA method 10 / Carbon monoxide analyzer	-	-	0.1 - 100	ppm	1	ใช้ Dilution Probe ร่วมในการตรวจวัด
ส่วนงานทดสอบพื้นฐาน									
1	Hydrogen Sulfide (H ₂ S)	Absorption, Iodometric Method	U.S. EPA Method 11 / Iodometric			8.0 6.0	mg / m ³ ppm	1	
2	Sulfur Dioxide (SO ₂)	Absorption Barium Thorin Titrimetric Method	U.S. EPA Method 6 / Titration	0.03 m ³	Isokinetic (30 min)	1.3 0.5	mg / m ³ ppm	1	
3	Sulfuric acid (H ₂ SO ₄)	Isokinetic, Barium Thorin Titrimetric Method	U.S. EPA Method 8 / Titration	0.9 m ³	Isokinetic (30 min)	0.05 0.01	mg / m ³ ppm	2	
4	Total Particulate Matter (TSP)	Isokinetic, Sampling / Gravimetric Method	U.S. EPA Method 5 / Gravimetric Method	-	-	0.1	mg / m ³	1	
ส่วนงานเครื่องมือทดสอบ									
1	Oxide of Nitrogen (Nitrogen Dioxide ;	Chemical Absorption, Colorimetric Method	U.S. EPA Method 7 / Spectrophotometer	2.0 L	Non-Isokinetic (30 min)	2.0 1.0	mg / m ³ ppm	1	
2	Xylene	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	2.05 0.47	mg / m3 ppm	2	SKC Cat. No. 226-09
3	Vanadium (V)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-OES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
4	Tin (Sn)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-OES	0.9 m ³	Isokinetic (30 min)	0.010	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
5	Selenium (Se)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-OES	0.9 m ³	Isokinetic (30 min)	0.010	mg / m ³	3	Advantage MFS Cat No. GC5090 MM

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
6	Antimony (Sb)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.010	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
7	Arsenic (As)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.010	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
8	Cadmium (Cd)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
9	Chromium (Cr)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
10	Copper (Cu)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
11	Cobalt (Co)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
12	Lead and Inorganic Lead (Pb)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
13	Manganese (Mn)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
14	Nickel (Ni)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
15	Mercury (Hg)	Isokinetic, Sampling,Cold Vapor Technique-AAS Method	U.S. EPA Method 101 / AAS	0.053 m ³	Isokinetic (1.5 L/min)	0.0001	mg / m ³	4	Advantage MFS Cat No. GC5090 MM

Rev.3 วันที่ 21/6/2024 แก้ไข Detection Limit ของโลหะหนักโดยรายงานหน่วย mg/m3 ทุกพารามิเตอร์เพื่อให้สอดคล้อง กับมาตรฐาน

การตรวจวิเคราะห์คุณภาพอากาศ (Air Quality Analysis)

ประเภทตัวอย่าง : อากาศในปล่องระบาย - Stack Air Quality

ตารางที่ 2 สรุปข้อกำหนดการเก็บตัวอย่างและความสามารถในการทดสอบตัวอย่างของห้องปฏิบัติการ ที่ไม่ได้ขึ้นทะเบียนกับกรมโรงงานอุตสาหกรรม

(ประเภทตัวอย่าง : อากาศในปล่องระบาย - Stack Air Quality)

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
แผนปฏิบัติการภาคสนาม									
1	Sampling and Traverse point	U.S. EPA Recommend (Method 1)	U.S. EPA Method 1 / Calculation	-	-	-	-	-	
2	Velocity and Volumetric Flow rate		U.S. EPA Method 2 / Calculation	-	-	-	-	-	
3	Oxygen	Electrochemical Sensor	Modified U.S. EPA 3 / Electrochemical Sensor	-	-	0-20.9	%	1	
4	Moisture Content		U.S. EPA Method 4 / Calculation	-	-	-	-	2	
5	Carbon dioxide (CO ₂)	Electrochemical Sensor	Modified U.S. EPA 3 / Electrochemical Sensor	-	-	0-20.9	%	2	
ส่วนงานทดสอบพื้นฐาน									
1	PM10,PM2.5	Isokinetic, Sampling / Gravimetric Method	U.S. EPA Method 201A / Gravimetric Method	-	-	0.1	mg / m ³	1	
ส่วนงานเครื่องมือทดสอบ									
1	Aluminium (Al)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
2	Barium (Ba)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
3	Calcium (Ca)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.100	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
4	Iron (Fe)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
5	Magnesium (Mg)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.100	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
6	Beryllium (Be)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
7	Silver (Ag)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
8	Sodium (Na)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.100	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
9	Zinc (Zn)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
10	Acetone	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	1.88 0.79	mg / m ³ ppm	2	SKC Cat. No. 226-09
11	Benzene	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	1.68 0.52	mg / m ² ppm	2	SKC Cat. No. 226-09
12	Cyclohexanone	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	2.26 0.56	mg / m ² ppm	2	SKC Cat. No. 226-09
13	Ethanol (Ethyl alcohol)	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	1.88 1.00	mg / m ² ppm	2	SKC Cat. No. 226-09
14	Ethylbenzene	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	2.07 0.48	mg / m ² ppm	2	SKC Cat. No. 226-09
15	Ethylacetate	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	4.32 1.20	mg / m ² ppm	2	SKC Cat. No. 226-09
16	Hexane	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	4.23 1.20	mg / m ² ppm	2	SKC Cat. No. 226-09
17	Isopropanol (Isopropyl alcohol); IPA	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	1.87 0.76	mg / m ² ppm	2	SKC Cat. No. 226-09
18	Methanol (Methyl alcohol)	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	0.94 0.72	mg / m ² ppm	2	SKC Cat. No. 226-09
19	Methyl Ethyl Ketone (MEK)	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	1.92 0.65	mg / m ² ppm	2	SKC Cat. No. 226-09

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
20	Styrene	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	2.16 0.51	mg / m ² ppm	2	SKC Cat. No. 226-09
21	Toluene	Sorbent Adsorption, Gas Chromatography Method	US. EPA Method 18 / GC-FID	0.21 m ³	0.7 L/min (30 min)	2.07 0.55	mg / m ² ppm	2	SKC Cat. No. 226-09
22	Methylcyclohexane	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	2-23 L	0.10 L/min (1 hr)	4.02 1.00	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
23	Diethyl Ether or Ethyl Ether	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	0.25-3 L	0.01-0.20 L/min (1 hr)	11.88 3.92	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
24	Methyl tert-Butyl Ether (MTBE)	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	2-96 L	0.01-0.20 L/min (1 hr)	3.08 0.86	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
25	Dichloromethane	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	0.5-2.5 L	0.01-0.20 L/min (1 hr)	3.16 0.91	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
26	1-Butanol /n-butyl alcohol	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	2.31 0.76	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
27	2-Butanol /sec-butyl alcohol	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	2.31 0.76	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
28	Isobutyl alcohol (IBA)	Sorbent Adsorption, Gas Chromatography Method	U.S.EPA Method18/SKC.Guide/ GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	2.29 0.76	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
29	Thallium (Tl)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.010	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
30	Ketones	Sorbent Adsorption, Gas Chromatography Method	NIOSH2555 (P.1-5) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	1.88 0.79	mg / m ³ ppm	2	SKC Cat. No. 226-09
31	n-Heptane	Sorbent Adsorption, Gas Chromatography Method	NIOSH1500 (P.1-8) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	3.89 0.95	mg / m ³ ppm	2	SKC Cat. No. 226-09
32	n-Butyl acetate	Sorbent Adsorption, Gas Chromatography Method	NIOSH 1450(P.1-6) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	4.75 1.00	mg / m ³ ppm	2	SKC Cat. No. 226-09

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
33	n-Pentane	Sorbent Adsorption, Gas Chromatography Method	NIOSH 1500(P.1-8) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	1.50 0.51	mg / m ³ ppm	2	SKC Cat. No. 226-09
34	Chloroform	Sorbent Adsorption, Gas Chromatography Method	NIOSH1003 (P.1-7) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	2.82 0.58	mg / m ³ ppm	2	SKC Cat. No. 226-09
35	Chlorobenzene	Sorbent Adsorption, Gas Chromatography Method	NIOSH1003 (P.1-7) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	2.64 0.57	mg / m ³ ppm	2	SKC Cat. No. 226-09
36	Formaldehyde	Sorbent Adsorption, Gas Chromatography Method	NIOSH2541 (P.1-5) / PS pump / GC-FID	21 L	0.70 L/min (1 hr)	0.31 0.25	mg / m ³ ppm	2	SKC Cat. No. 226-118
37	Hydrogen chloride	Sorbent Adsorption, IC Method	U.S. EPA Method 26A /IC	0.12 m3	1 L/min (30 min)	0.015 0.010	mg / m ³ ppm	3	0.1 N H2SO4 / 0.1 N NaOH
38	Hydrogen fluoride	Sorbent Adsorption, IC Method	U.S. EPA Method 26A /IC	0.12 m3	1 L/min (30 min)	0.012 0.015	mg / m ³ ppm	3	0.1 N H2SO4 / 0.1 N NaOH
39	Nitric	Sorbent Adsorption, IC Method	U.S. EPA Method 26A /IC	0.029 m3	1 L/min (30 min)	0.026 0.010	mg / m ³ ppm	3	Milli-Q Water
40	Chlorine	Sorbent Adsorption, IC Method	U.S. EPA Method 26A /IC	0.12 m3	1 L/min (30 min)	0.029 0.010	mg / m ³ ppm	3	0.1 N H2SO4 / 0.1 N NaOH
41	Molybdenum (Mo)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
42	Titanium (Ti)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
43	Boron (B)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
44	Silicon (Si)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.005	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
45	Potassium (K)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.100	mg / m ³	3	Advantage MFS Cat No. GC5090 MM

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
46	Phosphorus (P)	Isokinetic, Sampling,Digestion,ICP-OES Method	U.S. EPA Method 29 / ICP-AES	0.9 m ³	Isokinetic (30 min)	0.100	mg / m ³	3	Advantage MFS Cat No. GC5090 MM
47	Phosphoric acid	Sorbent Adsorption, IC Method	U.S. EPA Method 26A /IC	0.12 m3	1 L/min (30 min)	0.040 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03

เอกสารอ้างอิง

1. Method of Air Sampling and Analysis, APHA Intersociety Committee, 2017
2. NIOSH Manual of Analytical Methods (NMAM)
3. Code of Federal Regulation, U.S. EPA. , 40 CFR Part 50, Part 60, 2000
4. Occupational Health and Safety Management System(OSHA) Analytical Methods Manuel
5. International Standard Organization, ISO 11204:1995
6. Compendium of Methods for Determination of Inorganic Compound in Ambient Air, U.S. EPA. , 1999
7. Annual Book of ASTM Standard, Section 11, 2001

[illegible]

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
2	Sulfur Dioxide (SO ₂)	Pararosaniline Method	U.S. EPA 40 CFR Part 50 Appendix A / Spectrophotometer	288 L	0.2 L/min (24 hrs)	0.01	mg / m ³	2	
3	Aluminium (Al)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
4	Antimony (Sb)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
5	Arsenic (As)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
6	Barium (Ba)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
7	Cadmium (Cd)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
8	Calcium (Ca)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
9	Chromium (Cr)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
10	Copper (Cu)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
11	Iron (Fe)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
12	Lead (Pb)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
13	Magnesium (Mg)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
14	Manganese (Mn)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
15	Mercury (Hg)	Filtration, AAS Method	U.S. EPA Method IO-3.4 / High Volume - AAS	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
16	Nickel (Ni)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
17	Potassium (K)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
18	Sodium (Na)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
19	Tin (Sn)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
20	Titanium (Ti)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
21	Vanadium (V)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
22	Zinc (Zn)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
23	Selenium (Se)	Filtration, ICP-OES Method	U.S. EPA Method IO-3.4 / High Volume - ICP-OES	1,590 – 2,447 m ³	39-60 ft ³ /min (24 hrs)	0.0001	mg / m ³	4	Advantage MFS Cat. No. GA55 8 x 10 "
24	Acetone	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.14 0.06	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
25	Benzene	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.12 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-02
26	Cyclohexanone	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.16 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-04
27	Ethanol (Ethyl alcohol)	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	288 L	0.10 L/min (24 hrs)	0.14 0.07	mg / m ³ ppm	2	SKC Cat. No. ST 226-05

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
28	Ethylacetate	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.32 0.09	mg / m ³ ppm	2	SKC Cat. No. ST 226-06
29	Ethylbenzene	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.15 0.03	mg / m ³ ppm	2	SKC Cat. No. ST 226-07
30	Hexane	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.32 0.09	mg / m ³ ppm	2	SKC Cat. No. ST 226-08
31	Isopropanol (Isopropyl alcohol) ; IPA	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	288 L	0.10 L/min (24 hrs)	0.14 0.06	mg / m ³ ppm	2	SKC Cat. No. ST 226-09
32	Methanol (Methyl alcohol)	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.07 0.05	mg / m ³ ppm	2	SKC Cat. No. ST 226-10
33	Methyl Ethyl Ketone (MEK)	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.14 0.05	mg / m ³ ppm	2	SKC Cat. No. ST 226-11
34	Styrene	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.16 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-12
35	Toluene	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.15 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-13
36	Xylene	Sorbent Adsorption, GC Method	ASTM D 3687-95 / GC-FID	144 L	0.10 L/min (24 hrs)	0.15 0.03	mg / m ³ ppm	2	SKC Cat. No. ST 226-14
37	Methylcyclohexane	Sorbent Adsorption, GC Method	NIOSH 1500 (P.1-8) / PS pump / GC-FID	2-23 L	0.10 L/min (1 hr)	0.32 0.08	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
38	Methyl acetate	Sorbent Adsorption, GC Method	NIOSH 1458 (P.1-8) / PS pump / GC-FID	0.2-10 L	0.10 L/min (1 hr)	0.61 0.20	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
39	Diethyl Ether or Ethyl Ether	Sorbent Adsorption, GC Method	NIOSH 1610 (P.1-4) / PS pump / GC-FID	0.25-3 L	0.01-0.20 L/min (1 hr)	0.12 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
40	Methyl tert-Butyl Ether (MTBE)	Sorbent Adsorption, GC Method	NIOSH 1615 (P.1-4) / PS pump / GC-FID	2-96 L	0.01-0.20 L/min (1 hr)	0.13 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-01

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
41	Dichloromethane	Sorbent Adsorption, GC Method	NIOSH 1005 (P.1-4) / PS pump / GC-FID	0.5-2.5 L	0.01-0.20 L/min (1 hr)	0.23 0.07	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
42	1-Butanol /n-butyl alcohol	Sorbent Adsorption, GC Method	NIOSH 1401 (P.1-4) / PS pump / GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	0.17 0.06	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
43	2-Butanol /sec-butyl alcohol	Sorbent Adsorption, GC Method	NIOSH 1401 (P.1-4) / PS pump / GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	0.17 0.06	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
44	Isobutyl alcohol (IBA)	Sorbent Adsorption, GC Method	NIOSH 1401 (P.1-4) / PS pump / GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	0.17 0.06	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
45	Methyl Isobutyl Ketone (MIBK)	Sorbent Adsorption, GC Method	OSHA 1004(P.1-27) / PS pump / GC-FID	0.25-12L	0.10 L/min (1 hr)	0.14 0.03	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
46	Ketones	Sorbent Adsorption, GC Method	NIOSH 2555 (P.1-5) / PS pump / GC-FID	0.5-10L	0.01-0.20 L/min (1 hr)	0.14 0.06	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
47	n-Butyl acetate	Sorbent Adsorption, GC Method	NIOSH 1450 (P.1-6) / PS pump / GC-FID	1-10L	0.01-0.20 L/min (1 hr)	0.38 0.08	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
48	n-Pentane	Sorbent Adsorption, GC Method	NIOSH 1500 (P.1-8) / PS pump / GC-FID	-	0.01-0.20 L/min (1 hr)	0.11 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
49	Chloroform	Sorbent Adsorption, GC Method	NIOSH 1003 (P.1-7) / PS pump / GC-FID	1-50L	0.01-0.20 L/min (1 hr)	0.21 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
50	Chlorobenzene	Sorbent Adsorption, GC Method	NIOSH 1003 (P.1-7) / PS pump / GC-FID	1.5-40L	0.01-0.20 L/min (1 hr)	0.19 0.04	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
51	Formaldehyde	Sorbent Adsorption, GC Method	NIOSH 2541 (P.1-5) / PS pump / GC-FID	1-36L	0.01-0.10 L/min (1 hr)	0.01 0.01	mg / m ³ ppm	2	SKC Cat. No. 226-118
52	Hydrogen chloric	Sorbent Adsorption, IC Method	OSHA ID-174SG / PS pump / IC	1-7.5 L	0.20 L/min (24 hr)	0.015 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
53	Hydrogen Bromide	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	1-96 L	0.20 L/min (24 hr)	0.033 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03

Items	Parameter	Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
54	Sulfuric Acid	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC NIOSH 7908 / PS pump / IC	1-96 L	0.20 L/min (24 hr)	0.040 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03 Fiter (PTFE)
55	Phosphoric Acid	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC NIOSH 7908 / PS pump / IC	1-96 L	0.20 L/min (24 hr)	0.040 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03 Fiter (PTFE)
56	Nitric	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	1-96 L	0.20 L/min (24 hr)	0.026 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
57	Chlorine	Sorbent Adsorption, IC Method	OSHA ID-202 / PS pump / IC	14 L	0.20 L/min (24 hr)	0.029 0.010	mg / m ³ ppm	3	0.02% KI in Buffer solution
58	Ammonia (NH ₃)	Sorbent Adsorption, IC Method	NIOSH 6016 / PS pump / IC	0.10 - 96 L	0.20 L/min (120min)	0.200 0.280	mg / m ³ ppm	3	SKC Cat. No. 226-10-06
59	Hydrogen fluoride	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	60 L	0.2 L/min (60min)	0.008 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03

เอกสารอ้างอิง

1. Method of Air Sampling and Analysis, APHA Intersociety Committee, 2017
2. NIOSH Manual of Analytical Methods (NMAM)
3. Code of Federal Regulation, U.S. EPA. , 40 CFR Part 50, Part 60, 2000
4. Occupational Health and Safety Management System(OSHA) Analytical Methods Manuel
5. International Standard Organization, ISO 11204:1995
6. Compendium of Methods for Determination of Inorganic Compound in Ambient Air, U.S. EPA. , 1999
7. Annual Book of ASTM Standard, Section 11, 2001

Rev.3 วันที่ 21/6/2024 แก้ไข Detection Limit ของโลหะหนักโดยรายงานหน่วย mg/m³ ทุกพารามิเตอร์เพื่อให้สอดคล้อง กับมาตรฐาน

การตรวจวิเคราะห์คุณภาพอากาศ (Air Quality Analysis)

(ประเภทตัวอย่าง : อากาศในบริเวณการทำงาน - Workplace Air Quality)									
Items	Parameter	Sampling/Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
แผนปฏิบัติการภาคสนาม									
1	Illumination	Lux Meter	JIS C 1906 / Lux meter		-	0-5000	lux	-	
2	Sound (Leq, Lmin, Lmax, Ldn, Lp)	Integrated Sound Level Method	ISO 11202 / Sound Level Meter		-	40 - 140	dB (A)	1	
3	Noise Octave band	Integrated Sound Level Method	AS/NZS 4476 1997 / Sound Level Meter		-	40 – 140	dB (A)	1	1/3 Octave band หรือ 1/1 Octave band
4	Noise dose	Integrated Sound Level Method	BS6402 / Noise Dosemeter		-	0 - 9999	% Dose	2	
5	Carbon Monoxide (CO)	Non-Dispersive Infrared Photometric Method	U.S. EPA 10 (P.1-5)/ Carbon Monoxide Analyzer		-	0.1 - 100	ppm	1	
6	Ozone (O ₃)	UV Fluorescence Method	U.S. EPA method / Ozone Analyzer		-	0.1 - 100	ppm	2	
7	Heat Stress	WBGT Method	ACGIH / Grove + DI + Thermometer / calculation	-	-	0 - 100	oC	2	
ส่วนงานทดสอบพื้นฐาน									
1	Total Dust (TD)	Filtration, Gravimetric Method	NIOSH 0500 (P.1-3) / PS pump / Gravimetric	7-133 L	2 L/min (1 hr)	0.8	mg / m ³	1	SKC Cat No. 225-8-01
2	Respirable Dust (RD)	Cyclone - Filtration, Gravimetric Method	NIOSH 0600 (P.1-3) / PS pump cyclone / Gravimetric	20-400 L	1.70 L/min (1 hr)	0.5	mg / m ³	1	SKC Cat No. 225-8-01
3	NaOH	Acid-Base Titrimetric Method	NIOSH 7401(P.1-4) / PS pump / Titration	70-1000 L	1-4 L/min	0.4	mg / m ³	1	SKC Cat No. 225-17-01
4	KOH	Acid-Base Titrimetric Method	NIOSH 7401(P.1-4) / PS pump / Titration	70-1000 L	1-4 L/min	0.6	mg / m ³	1	SKC Cat No. 225-17-01
5	LiOH	Acid-Base Titrimetric Method	NIOSH 7401(P.1-4) / PS pump / Titration	70-1000 L	1-4 L/min	0.2	mg / m ³	1	SKC Cat No. 225-17-01
ส่วนงานเครื่องมือทดสอบ									
1	Ammonia	Impingement Absorption - Colorimetric Method	Modified NIOSH 6015(P.1-7) / Spectrophotometer	0.1-96 L	1 L/min (1 hr)	0.01	mg / m ³	2	
2	Nitrogen Dioxide	Impingement Absorption, Spectrophotometer Method	APHA 817(P.1-3) / Spectrophotometer	7.5 – 10 L	0.5 L/min (15-20 min)	0.01	ppm	2	
3	Sulfur Dioxide	Impingement Absorption, Titrimetric Method	APHA 823(P.1-3) / Titration	26 L	0.21 L/min (2 hrs)	0.30 0.11	mg / m ³ ppm	2	
4	P,P'-diphenylmethane diisocyanate(MDI) (MDI)	Impingement Absorption, Spectrophotometer Method	APHA 831(P.1-3) / Spectrophotometer	20 L	1 L/min (20 min)	0.002	ppm	2	
5	Aluminum (Al)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-100 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
6	Antimony (Sb)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	50-2000 L	2 L/min (1 hr)	0.021	mg / m ³	3	SKC Cat No. 225-5

Items	Parameter	Sampling/Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
7	Arsenic & Compound (as As)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-2000 L	2 L/min (1 hr)	0.010	mg / m ³	3	SKC Cat No. 225-5
8	Barium (Ba)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	50-2000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
9	Cadmium & Compounds (as Cd)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	25-1500 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
10	Calcium & Compounds (as Ca)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	20-400 L	2 L/min (1 hr)	0.208	mg / m ³	3	SKC Cat No. 225-5
11	Chromium & Compounds (as Cr)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
12	Copper (Cu) (Dust & Fume)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	50-1500 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
13	Iron & Compounds (as Fe)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
14	Lead (Pb)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	50-2000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
15	Magnesium (Mg)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	6-67 L	2 L/min (1 hr)	0.208	mg / m ³	3	SKC Cat No. 225-5
16	Manganese (Mn)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-200 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
17	Mercury (Hg)	Filtration - AAS Method	NIOSH 6009(P.1-5) / PS pump / AAS	2 – 100 L	0.2 L/min (1 hr)	0.00002	mg / m ³	5	SKC Cat No. 225-5
18	Nickel & Compounds (as Ni)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
19	Selenium (Se)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	13-2000 L	2 L/min (1 hr)	0.021	mg / m ³	3	SKC Cat No. 225-5
20	Silver (Ag)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	250-2000 L	2 L/min (2-17 hr)	0.010	mg / m ³	3	SKC Cat No. 225-5
21	Sodium (Na)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	13-2000 L	2 L/min (1 hr)	0.208	mg / m ³	3	SKC Cat No. 225-5
22	Tin (Sn)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.021	mg / m ³	3	SKC Cat No. 225-5
23	Titanium (Ti)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
24	Vanadium (V)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-2000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5

Items	Parameter	Sampling/Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
25	Zinc & Compounds (Zn)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-2000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
26	Acetone	Sorbent Adsorption, GC Method	NIOSH 1300 (P.1-5)/ PS pump / GC-FID	0.5-3 L	0.10 L/min (30 min)	13.17 5.54	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
27	Benzene	Sorbent Adsorption, GC Method	NIOSH 1501(P.1-7) / PS pump / GC-FID	5-30 L	0.10 L/min (1 hr)	2.93 0.92	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
28	Cyclohexanone	Sorbent Adsorption, GC Method	NIOSH 1300(P.1-5) / PS pump / GC-FID	1-10 L	0.10 L/min (1 hr)	3.96 0.99	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
29	Ethanol (Ethyl alcohol)	Sorbent Adsorption, GC Method	NIOSH 1400(P.1-4) / PS pump / GC-FID	12 L	0.10 L/min (1 hr)	3.29 1.75	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
30	Ethylacetate	Sorbent Adsorption, GC Method	NIOSH 1457 (P.1-4) / PS pump / GC-FID	0.1-10 L	0.10 L/min (1 hr)	7.21 2.00	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
31	Ethylbenzene	Sorbent Adsorption, GC Method	NIOSH 1501 (P.1-7) / PS pump / GC-FID	1-24 L	0.10 L/min (1 hr)	3.63 0.83	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
32	Hexane	Sorbent Adsorption, GC Method	NIOSH 1500(P.1-8) / PS pump / GC-FID	4 L	0.10 L/min (1 hr)	7.05 2.00	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
33	Isopropanol (Isopropyl alcohol) ; IPA	Sorbent Adsorption, GC Method	NIOSH 1400(P.1-4) / PS pump / GC-FID	12 L	0.10 L/min (1 hr)	3.28 1.33	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
34	Methanol (Methyl alcohol)	Sorbent Adsorption, GC Method	OSHA 91(P.1-10) / PS pump / GC-FID	1-5 L	0.10 L/min (30 min)	3.96 3.02	mg / m ³ ppm	2	SKC Cat. No. ST 226-82
35	Methyl Ethyl Ketone (MEK)	Sorbent Adsorption, GC Method	OSHA 1004(P.1-27) / PS pump / GC-FID	0.25-12L	0.10 L/min (1 hr)	3.35 1.14	mg / m ³ ppm	2	SKC Cat. No. ST 226-81A
36	Methyl Isobutyl Ketone (MIBK)	Sorbent Adsorption, GC Method	OSHA 1004(P.1-27) / PS pump / GC-FID	0.25-12L	0.10 L/min (1 hr)	3.34 0.81	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
37	Styrene	Sorbent Adsorption, GC Method	NIOSH 1501 (P.1-7) / PS pump / GC-FID	1-24 L	0.10 L/min (1 hr)	3.78 0.89	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
38	Toluene	Sorbent Adsorption, GC Method	NIOSH 1501 (P.1-7) / PS pump / GC-FID	1-8 L	0.10 L/min (1 hr)	3.63 0.96	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
39	Xylene	Sorbent Adsorption, GC Method	NIOSH 1501 (P.1-7) / PS pump / GC-FID	2-23 L	0.10 L/min (1 hr)	3.58 0.83	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
40	Cumene	Sorbent Adsorption, GC Method	NIOSH 1501 (P.1-7) / PS pump / GC-FID	2-23 L	0.10 L/min (1 hr)	3.60 0.73	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
41	Methylcyclohexane	Sorbent Adsorption, GC Method	NIOSH 1500 (P.1-8) / PS pump / GC-FID	2-23 L	0.10 L/min (1 hr)	7.23 1.80	mg / m ³ ppm	2	SKC Cat. No. ST 226-01

Items	Parameter	Sampling/Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
42	Methyl acetate	Sorbent Adsorption, GC Method	NIOSH 1458 (P.1-8) / PS pump / GC-FID	0.2-10 L	0.10 L/min (1 hr)	9.09 3.00	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
43	Diethyl Ether or Ethyl Ether	Sorbent Adsorption, GC Method	NIOSH 1610 (P.1-4) / PS pump / GC-FID	0.25-3 L	0.01-0.20 L/min (1 hr)	11.88 3.92	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
44	Methyl tert-Butyl Ether (MTBE)	Sorbent Adsorption, GC Method	NIOSH 1615 (P.1-4) / PS pump / GC-FID	2-96 L	0.01-0.20 L/min (1 hr)	3.08 0.86	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
45	Dichloromethane or Methylene chloride	Sorbent Adsorption, GC Method	NIOSH 1005 (P.1-4) / PS pump / GC-FID	0.5-2.5 L	0.01-0.20 L/min (1 hr)	22.1 6.36	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
46	1-Butanol /n-butyl alcohol	Sorbent Adsorption, GC Method	NIOSH 1401 (P.1-4) / PS pump / GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	4.86 1.60	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
47	2-Butanol /sec-butyl alcohol	Sorbent Adsorption, GC Method	NIOSH 1401 (P.1-4) / PS pump / GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	4.86 1.60	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
48	Isobutyl alcohol (IBA)	Sorbent Adsorption, GC Method	NIOSH 1401 (P.1-4) / PS pump / GC-FID	2-10 L	0.01-0.20 L/min (1 hr)	4.81 1.59	mg / m ³ ppm	2	SKC Cat. No. ST 226-01
49	Beryllium (Be)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	1250-2000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
50	Cobalt (Co)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	25-2000 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
51	Molybdenum (Mo)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-67 L	2 L/min (1 hr)	0.004	mg / m ³	3	SKC Cat No. 225-5
52	Thallium (Tl)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	25-2000 L	2 L/min (1 hr)	0.021	mg / m ³	3	SKC Cat No. 225-5
53	Silicon (Si)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.010	mg / m ³	3	SKC Cat No. 225-5
54	Potassium (K)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.208	mg / m ³	3	SKC Cat No. 225-5
55	Ketones	Sorbent Adsorption, GC Method	NIOSH 2555 (P.1-5) / PS pump / GC-FID	0.5-3.0 L	0.01-0.20 L/min (1 hr)	13.17 5.54	mg / m ³ ppm	2	SKC Cat. No. 226-01
56	n-Heptane	Sorbent Adsorption, GC Method	NIOSH 1500 (P.1-8) / PS pump / GC-FID	-	0.01-0.20 L/min (1 hr)	6.97 1.70	mg / m ³ ppm	2	SKC Cat. No. 226-01
57	n-Butyl acetate	Sorbent Adsorption, GC Method	NIOSH 1450(P.1-6) / PS pump / GC-FID	1-10 L	0.01-0.20 L/min (1 hr)	8.55 1.80	mg / m ³ ppm	2	SKC Cat. No. 226-01
58	n-Pentane	Sorbent Adsorption, GC Method	NIOSH 1500(P.1-8) / PS pump / GC-FID	-	0.01-0.20 L/min (1 hr)	2.63 0.89	mg / m ³ ppm	2	SKC Cat. No. 226-01

Items	Parameter	Sampling/Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
59	Chloroform	Sorbent Adsorption, GC Method	NIOSH 1003 (P.1-7) / PS pump / GC-FID	1-50 L	0.01-0.20 L/min (1 hr)	4.93 1.01	mg / m ³ ppm	2	SKC Cat. No. 226-01
60	Chlorobenzene	Sorbent Adsorption, GC Method	NIOSH 1003 (P.1-7) / PS pump / GC-FID	1.5-40L	0.01-0.20 L/min (1 hr)	4.63 1.00	mg / m ³ ppm	2	SKC Cat. No. 226-01
61	Formaldehyde	Sorbent Adsorption, GC Method	NIOSH 2541 (P.1-5) / PS pump / GC-FID	1-36L	0.01-0.10 L/min (1 hr)	0.12 0.10	mg / m ³ ppm	2	SKC Cat. No. 226-118 เปลี่ยน DL:1/2/24
62	Hydrogen chloride	Sorbent Adsorption, IC Method	OSHA ID-174SG / PS pump / IC	100 L	0.5 L/min (15 min)	0.015 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
63	Hydrogen Bromide	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	96 L	0.2 L/min (60min)	0.033 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
64	Sulfuric Acid	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	96 L	0.2 L/min (60min)	0.040 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
65	Phosphoric Acid	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	96 L	0.2 L/min (60min)	0.040 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
66	Ammonia (NH ₃)	Sorbent Adsorption, IC Method	NIOSH 6016 / PS pump / IC	0.10 - 96 L	0.2 L/min (120min)	0.200 0.280	mg / m ³ ppm	3	SKC Cat. No. 226-10-06
67	Nitric	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	96 L	0.2 L/min (60min)	0.026 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
68	Chlorine	Sorbent Adsorption, IC Method	OSHA ID-202 / PS pump / IC	60 L	0.5 L/min (60min)	0.029 0.010	mg / m ³ ppm	3	0.02% KI in Buffer solution
69	Hydrogen fluoride	Sorbent Adsorption, IC Method	OSHA ID165SG / PS pump / IC	96 L	0.2 L/min (60min)	0.008 0.010	mg / m ³ ppm	3	SKC Cat. No. 226-10-03
70	Phosphorus (P)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.042	mg / m ³	3	SKC Cat No. 225-5
71	Boron (B)	Filtration, ICP-OES Method	NIOSH 7300(P.1-8) / PS pump / ICP-OES	5-1000 L	2 L/min (1 hr)	0.010	mg / m ³	3	SKC Cat No. 225-5
72	Sulfur dioxide	Filtration, IC Method	NIOSH 6004 / PS pump / IC	4-200 L	1 L/min (120min)	0.015 0.006	mg / m ³ ppm	3	Treated Filter
73	Sulfuric Acid	Filtration, IC Method	NIOSH 7908 / PS pump / IC	15-2000 L	1 L/min (120min)	0.040 0.010	mg / m ³ ppm	3	Fiter (PTFE)
74	Phosphoric Acid	Filtration, IC Method	NIOSH 7908 / PS pump / IC	15-2000 L	1 L/min (120min)	0.040 0.010	mg / m ³ ppm	3	Fiter (PTFE)
75	Ammonium NH ₄ ⁺	Sorbent Adsorption, IC Method	NIOSH 6016 / PS pump / IC	0.10 - 96 L	0.2 L/min (120min)	0.017 0.023	mg / m ³ ppm	3	SKC Cat. No. 226-10-06

Items	Parameter	Sampling/Method	Reference Method / Analytical Technique	Air Volume	Sampling Rate / Period	LOQ / Range	Unit	Decimal point	Remark
76	Ammonium Chloride (NH ₄ Cl) as NH ₄ ⁺	Sorbent Adsorption, IC Method	NIOSH 6016 / PS pump / IC	0.10 - 96 L	0.2 L/min (120min)	0.049 0.067	mg / m ³ ppm	3	SKC Cat. No. 226-10-06

เอกสารอ้างอิง

1. Method of Air Sampling and Analysis, APHA Intersociety Committee, 1997
2. NIOSH Manual of Analytical Method, 4th Edition, 1994
3. Code of Federal Regulation, U.S. EPA. , 40 CFR Part 50, Part 60, 2000
4. OSHA Analytical Methods Manual, 2nd Edition, U.S. Department of Labor, 1992
5. International Standard Organization, ISO 11204:1995
6. Compendium of Methods for Determination of Inorganic Compound in Ambient Air, U.S. EPA. , 1999
7. Annual Book of ASTM Standard, Section 11, 2001